

[Start Here](#)[Blog](#)[Training](#)[About](#)

Penalized Regression in R

by **Jason Brownlee** on July 25, 2014 in **Uncategorized**


3

2

13

In this post you will discover 3 recipes for penalized regression for the R platform.

You can copy and paste the recipes in this post to make a jump-start on your own problem or to learn and practice with linear regression in R.



Each example in this post uses the [longley](#) dataset provided in the [datasets](#) package that comes with R. The longley dataset describes 7 economic variables observed from 1947 to 1962 used to predict the number of people employed yearly.

Ridge Regression

Ridge Regression creates a linear regression model that is penalized with the L2-norm which is the

sum of the squared coefficients. This has the effect of shrinking the coefficient values (and the complexity of the model) allowing some coefficients with minor contribution to the response to get close to zero.

```

1 # load the package
2 library(glmnet)
3 # load data
4 data(longley)
5 x <- as.matrix(longley[,1:6])
6 y <- as.matrix(longley[,7])
7 # fit model
8 fit <- glmnet(x, y, family="gaussian", alpha=0, lambda=0.001)
9 # summarize the fit
10 summary(fit)
11 # make predictions
12 predictions <- predict(fit, x, type="link")
13 # summarize accuracy
14 rmse <- mean((y - predictions)^2)
15 print(rmse)

```

Learn about the **glmnet** function in the **glmnet** package.

Least Absolute Shrinkage and Selection Operator

Least Absolute Shrinkage and Selection Operator (LASSO) creates a regression model that is penalized with the L1-norm which is the sum of the absolute coefficients. This has the effect of shrinking coefficient values (and the complexity of the model), allowing some with a minor affect to the response to become zero.

```

1 # load the package
2 library(lars)
3 # load data
4 data(longley)
5 x <- as.matrix(longley[,1:6])
6 y <- as.matrix(longley[,7])
7 # fit model
8 fit <- lars(x, y, type="lasso")
9 # summarize the fit
10 summary(fit)
11 # select a step with a minimum error
12 best_step <- fit$df[which.min(fit$RSS)]
13 # make predictions
14 predictions <- predict(fit, x, s=best_step, type="fit")$fit
15 # summarize accuracy
16 rmse <- mean((y - predictions)^2)
17 print(rmse)

```

Learn about the **lars** function in the **lars** package.

Elastic Net

Elastic Net creates a regression model that has the effect of effectively shrinking coefficients to zero (as in LASSO).

```

1 # load the package

```

Machine Learning Crash Course


You can learn and apply Machine Learning even without a background in maths or a fancy degree. Find out how in this ridiculously practical (and totally free) email course.

```
2 library(glmnet)
3 # load data
4 data(longley)
5 x <- as.matrix(longley[,1:6])
6 y <- as.matrix(longley[,7])
7 # fit model
8 fit <- glmnet(x, y, family="gaussian")
9 # summarize the fit
10 summary(fit)
11 # make predictions
12 predictions <- predict(fit, x, type="link")
13 # summarize accuracy
14 rmse <- mean((y - predictions)^2)
15 print(rmse)
```

[SIGN ME UP](#)

Learn about the **glmnet** function in the [glmnet](#) package.

How to Get Started and Practice Machine Learning in R



R is the most popular platform among professional data scientists for applied machine learning.

Download your mini-course in Machine Learning with R.

[Start Your FREE Mini-Course >>](#)

FREE 14-Day Mini-Course in Machine Learning with R

Download your PDF containing all 14 lessons.

Get your daily lesson via email with tips and tricks.

Summary

In this post you discovered 3 recipes for penalized regression in R.

Penalization is a powerful method for attribute selection and improving the accuracy of predictive models. For more information see Chapter 6 of [Applied Predictive Modeling](#) by Kuhn and Johnson that provides an excellent introduction to linear regression with R for beginners.

About Jason Brownlee

The editor-in-chief at MachineLearningMastery.com. Jason is a husband, father, researcher, author, professional programmer and a machine learning practitioner. [Learn more about him.](#)

[View all posts by Jason Brownlee →](#)[< Linear Regression in R](#)[Non-Linear Regression in R >](#)

5 Responses to *Penalized Regression in R*

**Hrvoje** July 25, 2014 at 10:53 pm #

REPLY ↩

Nice article, but first and third code are the same 😊 What's the difference?

**jasonb** July 26, 2014 at 7:40 am #

REPLY ↩

Almost. Note the value of alpha (the elastic net mixing parameter).
A great thing about the glmnet function is that it can do ridge, lasso and a hybrid of both. In the first example, we have used glmnet with an alpha of 0 which results in ridge regression (only L2). If alpha was set to 1 it would be lasso (only L1). Note in the third example that alpha is set to 0.5, this is the elastic net mixture of L1 and L2 at a 50% mixing.
I hope that is clearer.

**Hrvoje** July 26, 2014 at 11:47 pm #

REPLY ↩

It's much clearer now. Tnx a lot 😊

**TropoSco** August 2, 2014 at 7:50 pm #

REPLY ↩

Thanks for the post,

I was wondering if you knew the differences (computational and statistical performances) between using the lars package and the glmnet one with alpha=1 for performing a LASSO regression ?

Thank you for your time and keep up the good work!

**JOY** May 12, 2015 at 10:04 pm #

REPLY ↩

nice article.I want to know how to use R for regression analysis.you are following the step by step method to do it to my e-mail.I have R package already on my Laptop

Leave a Reply

Name (required)

Email (will not be published) (required)

Website

SUBMIT COMMENT

Welcome!



Hi, my name is Jason and welcome to Machine Learning Mastery where we make programmers awesome at machine learning.

If you have any questions or you just want to chat about machine learning, [send me an email](#).

Free Guide to the Best Resources

Discover the best videos, books, courses and MUCH MORE in my Machine Learning Resource Guide.

Get your copy right now!


[Download For Free](#)

Are You a Developer?

Do You want to FINALLY get started with

Machine Learning in R?

Start Machine Learning in R NOW!



POPULAR




A Tour of Machine Learning Algorithms

NOVEMBER 25, 2013



How to Run Your First Classifier in Weka

FEBRUARY 17, 2014



Tutorial To Implement k-Nearest Neighbors in Python From Scratch

SEPTEMBER 12, 2014




How To Implement Naive Bayes From Scratch in Python

DECEMBER 8, 2014



Machine Learning for Programmers: Leap from developer to machine learning practitioner

AUGUST 17, 2015



Discover Feature Engineering, How to Engineer Features and How to Get Good at It

SEPTEMBER 26, 2014



Find Your Machine Learning Tribe: Get Started And Avoid Getting The Wrong Advice

AUGUST 31, 2015



Best Machine Learning Resources for Getting Started

NOVEMBER 27, 2013



4 Self-Study Machine Learning Projects

JANUARY 3, 2014



Feature Selection with the Caret R Package

SEPTEMBER 22, 2014

Looking for something? Search!



© 2016 Machine Learning Mastery. All Rights Reserved.

[Privacy](#) | [Contact](#) | [About](#)