

Computational Photography




Dr. Irfan Essa

Professor

School of Interactive Computing

Study the basics of computation and its impact on the entire workflow of photography, from capturing, manipulating and collaborating on, and sharing photographs.



Feature Detection and Matching



Dr. Irfan Essa

Professor


School of Interactive Computing

Methods for Detecting Features in Images
that can be Matched for Registration and
Alignment.

Lesson Objectives

- ★ Describe in your own words two (2) benefits of Feature Detection and Matching in images
- ★ Describe in your own words the four (4) Characteristics of Good Features.
- ★ Explain in your own words why corners are Good Features.
- ★ Outline the five (5) steps of Harris Corner Detector Algorithm
- ★ Outline the four (4) stages of a SIFT detector





REVIEW: Detection and Matching



Image Matching



Image Matching




Image Matching




Image Matching




Image Matching




Image Matching




Image Matching




Image Matching




Image Matching




Image Matching






Image Matching

Finding Features



Finding Features


- ★ Goal: Find points in an image that can be:
 - Found in other images
 - Found precisely – well localized
 - Found reliably – well matched



Finding Features

- ★ Goal: Find points in an image that can be:
 - Found in other images
 - Found precisely – well localized
 - Found reliably – well matched

- ★ Why?
 - Align Images
 - Build a Panorama,
 - Etc.



Characteristics of Good Features



Slide motivated by Aaron Bobick

Characteristics of Good Features

★ Repeatability/Precision

- The same feature can be found in several images despite geometric and photometric transformations



Slide motivated by Aaron Bobick

Characteristics of Good Features

★ Repeatability/Precision

- The same feature can be found in several images despite geometric and photometric transformations

★ Saliency/Matchability

- Each feature has a distinctive description



Characteristics of Good Features

★ Repeatability/Precision

- The same feature can be found in several images despite geometric and photometric transformations

★ Saliency/Matchability

- Each feature has a distinctive description

★ Compactness and efficiency

- Many fewer features than image pixels



Characteristics of Good Features

- ★ Repeatability/Precision
 - The same feature can be found in several images despite geometric and photometric transformations
- ★ Saliency/Matchability
 - Each feature has a distinctive description
- ★ Compactness and efficiency
 - Many fewer features than image pixels
- ★ Locality
 - A feature occupies a relatively small area of the image; robust to clutter and occlusion



Find Corners



Find Corners



- ★ Key property: in the region around a corner, image gradient has two or more dominant directions

Find Corners




- ★ Key property: in the region around a corner, image gradient has two or more dominant directions
- ★ Corners are repeatable and distinctive


Find Corners




- ★ Key property: in the region around a corner, image gradient has two or more dominant directions
- ★ Corners are repeatable and distinctive
- ★ Harris and Stephens (1988)



“flat”
No change in
any directions




“edge”
no change
along the edge
direction




“corner”
change in all
directions


Corner Detection: The Basics



“flat”
No change in
any directions




“edge”
no change
along the edge
direction




“corner”
change in all
directions

Corner Detection: The Basics




“flat”

No change in
any directions




“edge”
no change
along the edge
direction




“corner”
change in all
directions

Corner Detection: The Basics




“flat”

No change in
any directions




“edge”
no change
along the edge
direction




“corner”
change in all
directions

Corner Detection: The Basics




“flat”

No change in
any directions



“edge”
no change
along the edge
direction




“corner”
change in all
directions


- ★ Possible to recognize a point by looking through a small window
- ★ Shifting a window in any direction gives a large change in intensity

Corner Detection: The Basics


Corner Detection: The Basics




Slide motivated by Alyosha Efros




Corner Detection: The Basics




Slide motivated by Alyosha Efros



Corner Detection: The Basics




Slide motivated by Alyosha Efros





“flat”
No change in
any directions

Corner Detection: The Basics




Slide motivated by Alyosha Efros





Corner Detection: The Basics

"flat"

No change in
any directions




Slide motivated by Alyosha Efros




Corner Detection: The Basics

"flat"

No change in
any directions




Slide motivated by Alyosha Efros



“flat”


No change in
any directions




“edge”

no change
along the edge
direction

Corner Detection: The Basics




Slide motivated by Alyosha Efros




"flat"


No change in
any directions




"edge"
no change
along the edge
direction



Corner Detection: The Basics




Slide motivated by Alyosha Efros




"flat"


No change in
any directions




"edge"
no change
along the edge
direction



Corner Detection: The Basics




Slide motivated by Alyosha Efros




“flat”


No change in
any directions



“edge”
no change
along the edge
direction




“corner”
change in all
directions




Corner Detection: The Basics

Slide motivated by Alyosha Efros




“flat”

No change in
any directions




“edge”
no change
along the edge
direction



“corner”
change in all
directions

Corner Detection: The Basics

- ★ Harris Corners
(Harris and Stephens, 1988)




Slide motivated by Alyosha Efros

Computation of the change in appearance by shifting the window by u, v :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

$w(x, y)$ {


- box function
- a Gaussian
- 1 inside, 0 outside



Corner Detection: Mathematics

Computation of the change in appearance by shifting the window by u, v :


$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$



intensity

$w(x, y)$

{ box function
 a Gaussian
 1 inside, 0 outside



Corner Detection: Mathematics


Computation of the change in appearance by shifting the window by u, v :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

shifted intensity
intensity

$w(x, y)$ {

- box function



a Gaussian

1 inside, 0 outside

Corner Detection: Mathematics

Computation of the change in appearance by shifting the window by u, v :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

window
function

shifted
intensity

intensity


$w(x, y)$

box function



a Gaussian

1 inside, 0 outside



Corner Detection: Mathematics

Computation of the change in appearance by shifting the window by u, v :

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

change in appearance

window function


shifted intensity

intensity

$w(x, y)$

{ box function
 a Gaussian

1 inside, 0 outside



Corner Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

Corner Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

Corner Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix}$$

Corner

Detection:
Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix}$$

where M is a second moment matrix computed from image derivatives I_x and I_y :

Corner

Corner Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix}$$

where M is a second moment matrix computed from image derivatives I_x and I_y :

$$M = \sum_{x,y} \omega(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

Corner

Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix}$$

where M is a second moment matrix computed from image derivatives I_x and I_y :

$$M = \sum_{x,y} \omega(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

Corner

Detection: Mathematics

$$E(u, v) = \sum_{x,y} w(x, y) [I(x + u, y + v) - I(x, y)]^2$$

The quadratic approximation, following Taylor Expansion, simplifies to:

$$E(u, v) \approx \begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix}$$

where M is a second moment matrix computed from image derivatives I_x and I_y :

$$M = \sum_{x,y} \omega(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

The surface $E(u, v)$ is locally approximated by a quadratic form.

Corner Detection: Mathematics


The surface $E(u,v)$ is locally approximated by a quadratic form.

$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$



The surface $E(u,v)$ is locally approximated by a quadratic form.


$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$



The surface $E(u,v)$ is locally approximated by a quadratic form.

$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

consider a “slice”: $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$




The surface $E(u,v)$ is locally approximated by a quadratic form.

$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

consider a “slice”: $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$

which is an equation of an ellipse.




The surface $E(u,v)$ is locally approximated by a quadratic form.


$$E(u, v) = \sum_{x,y} \omega(x, y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

consider a “slice”: $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$

which is an equation of an ellipse.



direction of the
fastest change



direction of the
slowest change

Slide motivated by Aaron Bobick


The surface $E(u,v)$ is locally approximated by a quadratic form.

$$E(u,v) = \sum_{x,y} \omega(x,y) (u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2)$$

consider a “slice”: $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$


which is an equation of an ellipse.

direction of the
fastest change



Eigenvalue Analysis:

The axis lengths of the ellipse are determined by the eigenvalues and the orientation is determined by eigenvectors




Consider a "slice": $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$

which is an equation of an ellipse.

$$\begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix} = k$$

$$M = R^{-1} \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} R \quad M \text{ is a diagonal matrix}$$



Eigenvalue Analysis:

The axis lengths of the ellipse are determined by the eigenvalues and the orientation is determined by eigenvectors, R .

Consider a "slice": $u^2 I_x^2 + 2uv I_x I_y + v^2 I_y^2 = k$


which is an equation of an ellipse.

$$\begin{bmatrix} u & v \end{bmatrix} M \begin{bmatrix} u \\ v \end{bmatrix} = k$$

$$M = R^{-1} \begin{bmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{bmatrix} R$$

M is a diagonal matrix


direction of the
fastest change



direction of the
slowest change

Eigenvalue Analysis:


The axis lengths of the ellipse are determined by the eigenvalues and the orientation is determined by eigenvectors, R.



Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)




Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

- ★ R depends only on eigenvalues of M




Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

- ★ R depends only on eigenvalues of M
- ★ R is large for a corner




Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

- ★ R depends only on eigenvalues of M
- ★ R is large for a corner
- ★ R is negative with large magnitude for an edge




Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

- ★ R depends only on eigenvalues of M
- ★ R is large for a corner
- ★ R is negative with large magnitude for an edge
- ★ $|R|$ is small for a flat region




Eigenvalues

$$R = \det(M) - \alpha \operatorname{trace}(M)^2 = \lambda_1 \lambda_2 - \alpha (\lambda_1 + \lambda_2)^2$$

α : constant (0.04 to 0.06)

- ★ R depends only on eigenvalues of M
- ★ R is large for a corner
- ★ R is negative with large magnitude for an edge
- ★ $|R|$ is small for a flat region
- ★ Note: No explicit computation of eigenvalues required.



Harris Detector Algorithm



Harris Detector Algorithm

1. Compute Gaussian derivatives at each pixel



Harris Detector Algorithm

1. Compute Gaussian derivatives at each pixel
2. Compute second moment matrix M in a Gaussian window around each pixel



Harris Detector Algorithm

1. Compute Gaussian derivatives at each pixel
2. Compute second moment matrix M in a Gaussian window around each pixel
3. Compute corner response function R



Harris Detector Algorithm

1. Compute Gaussian derivatives at each pixel
2. Compute second moment matrix M in a Gaussian window around each pixel
3. Compute corner response function R
4. Threshold R



Harris Detector Algorithm

1. Compute Gaussian derivatives at each pixel
2. Compute second moment matrix M in a Gaussian window around each pixel
3. Compute corner response function R
4. Threshold R
5. Find local maxima of response function
(non-maximum suppression)



Properties of the Harris Detector



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant

★ Intensity Invariant?

- Partial invariance to additive and multiplicative intensity changes (threshold issue for multiplicative)
- Only Image derivatives are used



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant

★ Intensity Invariant?

- Partial invariance to additive and multiplicative intensity changes (threshold issue for multiplicative)
- Only Image derivatives are used



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant

★ Intensity Invariant?

- Partial invariance to additive and multiplicative intensity changes (threshold issue for multiplicative)
- Only Image derivatives are used



Properties of the Harris Detector

★ Rotation Invariant?

- Ellipses rotate, but shape (eigenvalues) remain same
- Corner Response R is invariant

★ Intensity Invariant?

- Partial invariance to additive and multiplicative intensity changes (threshold issue for multiplicative)
- Only Image derivatives are used

★ Scale Invariant

- NO! Dependent on Window Size!
- USE Pyramids (or Frequency Domain!)



Scale Invariant Detectors

Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:


- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale

Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
 - ★ Laplacian in scale
- ★ SIFT (Lowe, 2004)
- Find local maximum of:
- ★ Difference of Gaussians (DoG) in space and scale
 - ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave




Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)

Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
 - ★ Laplacian in scale
- ★ SIFT (Lowe, 2004)
- Find local maximum of:
- ★ Difference of Gaussians (DoG) in space and scale
 - ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave



Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)



Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale

- ★ SIFT (Lowe, 2004)

Find local maximum of:

- ★ Difference of Gaussians (DoG) in space and scale
- ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave



Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)



Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale

- ★ SIFT (Lowe, 2004)

Find local maximum of:

- ★ Difference of Gaussians (DoG) in space and scale
- ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave



Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)



Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale

- ★ SIFT (Lowe, 2004)

Find local maximum of:

- ★ Difference of Gaussians (DoG) in space and scale
- ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave



Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)



Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale

- ★ SIFT (Lowe, 2004)

Find local maximum of:

- ★ Difference of Gaussians (DoG) in space and scale
- ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave



Scale Invariant Detectors

- ★ Harris-Laplacian (Mikolajczyk and Schmid, 2001)



Find local maximum of:

- ★ Harris corner detector in space (image coordinates)
- ★ Laplacian in scale


- ★ SIFT (Lowe, 2004)

Find local maximum of:

- ★ Difference of Gaussians (DoG) in space and scale
- ★ Where DoG is simply a pyramid of the difference of Gaussians within each octave




SIFT (Scale-Invariant Feature Transform)



http://en.wikipedia.org/wiki/File:Sift_keypoints_filtering.jpg

SIFT (Scale-Invariant Feature Transform)


- ★ Scale-space extrema detection
 - Search over multiple scales and image locations



http://en.wikipedia.org/wiki/File:Sift_keypoints_filtering.jpg

SIFT (Scale-Invariant Feature Transform)


- ★ Scale-space extrema detection
 - Search over multiple scales and image locations
- ★ Keypoint localization (not just corners!)
 - Define a model to determine location and scale.
Select keypoints based on a measure of stability.



http://en.wikipedia.org/wiki/File:Sift_keypoints_filtering.jpg

SIFT (Scale-Invariant Feature Transform)


- ★ Scale-space extrema detection
 - Search over multiple scales and image locations
- ★ Keypoint localization (not just corners!)
 - Define a model to determine location and scale.
Select keypoints based on a measure of stability.
- ★ Orientation assignment
 - Compute best orientation(s) for each keypoint region.




http://en.wikipedia.org/wiki/File:Sift_keypoints_filtering.jpg

SIFT (Scale-Invariant Feature Transform)

- ★ Scale-space extrema detection
 - Search over multiple scales and image locations
- ★ Keypoint localization (not just corners!)
 - Define a model to determine location and scale.
Select keypoints based on a measure of stability.
- ★ Orientation assignment
 - Compute best orientation(s) for each keypoint region.
- ★ Keypoint description
 - Use local image gradients at selected scale and rotation to describe each keypoint region.



http://en.wikipedia.org/wiki/File:Sift_keypoints_filtering.jpg




Invariant Local Features

- ★ Image content is transformed into local feature coordinates that are invariant to translation, rotation, scale, and other imaging parameters
- ★ (Lowe, 2004)


Results

Detect




Results

Detect




Results

Detect
Match



Results

Detect
Match
Show



Results

Summary

- ★ Introduced Feature Detection and Matching for images
- ★ Discussed the four (4) Characteristics of Good Features.
- ★ Introduced the Harris Corner Detector Framework
- ★ Introduced the SIFT detector



Further Reading

- ★ Harris and Stephens (1988) "A Combined Corner and Edge Detector." Proceedings of the 4th Alvey Vision Conference, 1988, [PDF][DOI]
- ★ Mikolajczyk and Schmid (2001). "Indexing Based on Scale Invariant Interest Points". ICCV 2001
- ★ Lowe (2004) "Distinctive Image Features from Scale-Invariant Keypoints". IJCV 2004
- ★ Search for "Features" on OpenCV site



commons.wikimedia.org/


Next Class

- ★ How to do Alignment for Panoramas



Credits

- ★ For more information, see
 - Richard Szeliski (2010) Computer Vision: Algorithms and Applications, Springer.
- ★ Some concepts in slides motivated by similar slides by A. Efros and J. Hays.
- ★ Some images retrieved from
 - <http://commons.wikimedia.org/>.
 - List will be available on website.



www.flickr.com/photos/neneonline/231886965/


Computational Photography



Dr. Irfan Essa

Professor

School of Interactive Computing



Study the basics of computation and its impact on the entire workflow of photography, from capturing, manipulating and collaborating on, and sharing photographs.