



This lesson is for members only. **Join us and get access to hundreds of tutorials and a community of expert Pythonistas.**

 [Unlock This Lesson](#)

Course Contents



 Overview



38%

Getting Started With Requests

- ☐ [Requests Introduction & Overview 01:18](#)
- ☐ [The GET Request 01:59](#)
- ☐ [Responses: Status Codes 06:28](#)
- ☒ [Responses: Content and Headers 04:09](#)
- ☐ [Section 1 Recap & Review 00:40](#)

Fetching & Sending Data

- ☒ [Query String Parameters 03:54](#)
- ☒ [Request Headers 03:22](#)
- ☒ [Other HTTP Methods 02:44](#)
- ☒ [The Message Body 03:05](#)
- ☒ [Inspecting Requests 01:09](#)
- ☒ [Section 2 Recap & Review 00:45](#)

Advanced Usage

- ☒ [Making Authenticated Requests 05:48](#)
- ☒ [SSL Certificate Verification 01:18](#)
- ☒ [Request Timeouts 05:52](#)
- ☒ [The Session Object 03:20](#)
- ☒ [Limiting Retries 02:29](#)
- ☒ [Section 3 Recap & Course Conclusion 00:48](#)

Query String Parameters



Mark as Completed



Supporting Material ▾

Give Feedback

Description

📄 Transcript

💬 Comments & Discussion (14)

What are query strings? How do I use them? In this lesson you'll learn exactly that. The `get()` function accepts a `params` argument, which can be a dictionary. Let's use the [GitHub Search](#) API looking for the requests library

Python

```
>>> requests.get(
...     'https://api.github.com/search
...     params={'q': 'requests+language:python'}
... )
<Response [200]>
```

```
1 # How to merge two dicts
2 # in Python 3.5+
3
4 >>> x = {'a': 1, 'b': 2}
5 >>> y = {'b': 3, 'c': 4}
6
7 >>> z = {**x, **y}
8
9 >>> z
10 {'c': 4, 'a': 1, 'b': 3}
```

Improve Your Python



...with a fresh 🐍 **Python Trick** 📧
code snippet every couple of days:

Email Address

Send Python Tricks »