Back

Knowledge Check: Setting up NER as a Machine Learning Task
Practice Assignment • 10 min

Due Oct 21, 11:59 PM IST

Your grade: 100%

Your latest: **100%** • Your highest: **100%** • To pass you need at least 80%. We keep your highest score.

Next item

1. Which of the following are examples of sequence labeling models used in NER? 1 / 1 point

- [x] Hidden Markov Models

Nice work

Correct! HMMs are traditional models used for sequence labeling in NER.

- [ ] K-means clustering
- [ ] Decision trees
- [x] Conditional Random Fields

Nice work

Correct! CRFs are a common choice for NER sequence labeling.

2. Which of the following is an example of a domain where NER can be applied as a sequence labeling task? 1 / 1 point

- (•) Pharmacy directions
- ( ) Image classification
- ( ) Video scene segmentation
- ( ) Speech synthesis

Nice work

Correct! NER can be used to extract entities such as drug name, strength, and frequency in pharmacy directions.

3. How is NER formulated in a machine learning context? 1 / 1 point

- (•) As a sequence classification or sequence labeling task
- ( ) As a sentence reordering task
- ( ) As an entity translation task
- ( ) As a document summarization task

Nice work

Correct! NER is formulated as a sequence labeling task where each token is assigned a label.

4. In sequence labeling for NER, what does the "O" label represent? 1 / 1 point

- ( ) Opening token of a named entity
- ( ) Optional entity label
- (•) Outside any named entity category
- ( ) Overlapping entity types

Nice work

Correct! The "O" label marks tokens that do not belong to any named entity.

5. What is one purpose of using **BIO encoding** in NER? 1 / 1 point

- ( ) To improve document summarization
- ( ) To add punctuation labels
- (•) To distinguish the beginning and inside tokens of multiword named entities
- ( ) To convert text into audio

Nice work

Correct! BIO encoding helps distinguish the start (B) and inside (I) tokens within multiword entities.