# nltk.skipgrams()

**nltk.skipgrams**(*sequence, n, k, **kwargs*) [source]

Returns all possible skipgrams generated from a sequence of items, as an iterator. Skipgrams are ngrams that allows tokens to be skipped. Refer to
http://homepages.inf.ed.ac.uk/ballison/pdf/lrec_skipgrams.pdf

```
>>>
>>> sent = "Insurgents killed in ongoing fighting".split()
>>> list(skipgrams(sent, 2, 2))
[('Insurgents', 'killed'), ('Insurgents', 'in'), ('Insurgents', 'ongoing'), ('killed', 'in'),
('killed', 'ongoing'), ('killed', 'fighting'), ('in', 'ongoing'), ('in', 'fighting'), ('ongoing',
'fighting')]
>>> list(skipgrams(sent, 3, 2))
[('Insurgents', 'killed', 'in'), ('Insurgents', 'killed', 'ongoing'), ('Insurgents', 'killed',
'fighting'), ('Insurgents', 'in', 'ongoing'), ('Insurgents', 'in', 'fighting'), ('Insurgents',
'ongoing', 'fighting'), ('killed', 'in', 'ongoing'), ('killed', 'in', 'fighting'), ('killed',
'ongoing', 'fighting'), ('in', 'ongoing', 'fighting')]
```

**Parameters:**
- **sequence** (*sequence or iter*) – the source data to be converted into trigrams
- **n** (*int*) – the degree of the ngrams
- **k** (*int*) – the skip distance

**Return type:** iter(tuple)