

[< Previous](#)[Next >](#)

Notifications



In-Video Quiz

[🔖 Bookmark this page](#)

Q4

1/1 point (ungraded)

Consider table $R(A)$ containing $\{(1),(2)\}$. Suppose transaction T1 is "update T set $A=2*A$; insert into R values (6)" and transaction T2 is "select avg(A) from R; select avg(A) from R". If transaction T2 executes using "repeatable read", what are the possible values returned by its SECOND statement?

☒ 1.5, 4☐ 1.5, 2, 4☐ 1.4, 3, 4☐ 1.5, 2, 3, 4

Explanation

T2 must (appear to) execute entirely before or after T1. You might think T2 could (appear to) execute between T1's two statements since the second statement is an insert, but that would be allowing dirty reads.

Submit

You have used 1 of 4 attempts

[< Previous](#)[Next >](#)

Pursue a verified certificate

- ✓ Earn a **verified certificate** of completion to showcase on your resumé
- ✓ Support our **mission** at edX

Upgrade for \$50

**edX**[About](#)[Affiliates](#)[edX for Business](#)

Hide Notes

[Open edX](#)
[Careers](#)
[News](#)

Legal

[Terms of Service & Honor Code](#)
[Privacy Policy](#)
[Accessibility Policy](#)
[Trademark Policy](#)
[Sitemap](#)

Connect

[Blog](#)
[Contact Us](#)
[Help Center](#)
[Media Kit](#)



© 2022 edX Inc. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)