Introduction to Computational Science and Engineering

<u>Help</u>

Ď

sandipan_dey ~

<u>Course</u>

<u>Progress</u>

<u>Dates</u>

<u>Discussion</u>

MO Index





Previous























Next >

5.1.5 Exam: Implementing a Third-order Runge-Kutta Method

☐ Bookmark this page

Exams due Aug 30, 2023 05:00 IST Completed

In this problem, you are to implement the following third-order accurate Runge-Kutta method which we will refer to as RK3. The RK3 method can be written as:

RK3 Method

$$\underline{a} = \Delta t \underline{f}(\underline{v}^n, t^n) \tag{5.4}$$

$$\underline{b} = \Delta t \underline{f} (\underline{v}^n + \underline{a}, t^n + \Delta t)$$
 (5.5)

$$\underline{c} = \Delta t \underline{f} \left(\underline{v}^n + \frac{1}{4} \underline{a} + \frac{1}{4} \underline{b}, t^n + \frac{1}{2} \Delta t \right)$$
(5.6)

$$\underline{v}^{n+1} = \underline{v}^n + \frac{1}{6}(\underline{a} + \underline{b} + 4\underline{c}) \tag{5.7}$$

Here are some specifics on what you need to do:

- Your task is to implement the RK3 Method above in the function step_RK3 in the provided runge.py code which is available on the submission site (link given below).
- Please note that step_RK3 is to be written using NumPy ndarrays as described in the docstring of the provided runge.py code.

Problem: Third order Runge Kutta (External resource) (5.0 / 5.0 points)

This will launch an external site that will require forwarding of your username.

Launch external site for submission and grading of Python code 🗷

Previous

Next >

© All Rights Reserved



edX

About

<u>Affiliates</u>

edX for Business

Open edX

Careers

<u>News</u>

Legal

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

<u>Trademark Policy</u>

<u>Sitemap</u>

Cookie Policy

Your Privacy Choices

Connect

<u>Idea Hub</u>

Contact Us

Help Center

Security

Media Kit

















© 2023 edX LLC. All rights reserved.

深圳市恒宇博科技有限公司 <u>粤ICP备17044299号-2</u>