


EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Final exam \(1 week\)](#) > [Final Exam](#) > Problem 6

## Problem 6



Recurrent neural networks (RNN) can be used as classification models for time series data. Here we have a simple RNN as shown in the figure above, where

$$s_t = f_1(W^{s,s}s_{t-1} + W^{s,x}x_t), \quad t = 1, 2, \dots, T$$

and

$$y = f_2(W^{s,y}s_T + W_0)$$

We assume all offsets are 0 except  $W_0$  for the final output layer and we decide the two activation functions to be:

$$f_1(z) = \text{RELU}(z) = \max(0, z)$$

and

$$f_2(z) = \text{sign}(z) = \begin{cases} 1, & \text{if } z \geq 0 \\ 0, & \text{if } z < 0 \end{cases}$$

Note that the  $\text{RELU}(z)$  can be applied elementwise if  $z$  is a vector.

Suppose we want to apply this model to classify sentences into different categories (e.g. positive/negative sentiment), we need to encode each word in a sentence into a vector as the input  $x_t$  to the model. One way to do this is to represent the  $t$ th word as a column vector of length  $|V|$ , where  $V$  is the set of the entire vocabulary. The  $i$ th element of  $x_t$  is 1 if the word is the  $i$ th word in the vocabulary and all other elements are zero.

---

6. (1)

2.0/2 points (graded)

We first explore a simple scenario where our vocabulary contains only 2 words,  $V = \{A, B\}$ . Let  $s_t \in \mathbb{R}^2$  and we set the initial state  $s_0$  and the weights before the last layer as follows:

$$s_0 = \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \quad W^{s,s} = \begin{bmatrix} -1 & 0 \\ 0 & 1 \end{bmatrix}, \quad W^{s,x} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

Now given 3 training sentences:  $AA$ ,  $ABB$ ,  $BAA$

Encode each of them into a sequence of vectors. As an example, the sentence  $AA$  is encoded as  $x^{(1)} = (x_1^{(1)}, x_2^{(1)})$ , where  $x_1^{(1)} = x_2^{(1)} = [1, 0]^T$ .

(To enter the sequence above, type `[[1,0],[1,0]]`.)

Now encode the other 2 sentences into  $x^{(2)}$  and  $x^{(3)}$ .

$x^{(2)} =$   ✔ Answer: `[[1,0],[0,1],[0,1]]`

$x^{(3)} =$   ✔ Answer: `[[0,1],[1,0],[1,0]]`

**Solution:**

$A$  is encoded as  $[1, 0]^T$  and  $B$  is encoded as  $[0, 1]^T$ , so we have

$$x^{(2)} = (x_1^{(2)}, x_2^{(2)}, x_3^{(2)}) = ([1, 0]^T, [0, 1]^T, [0, 1]^T)$$

$$x^{(3)} = (x_1^{(3)}, x_2^{(3)}, x_3^{(3)}) = ([0, 1]^T, [1, 0]^T, [1, 0]^T)$$

Submit

You have used 1 of 5 attempts

**i** Answers are displayed within the problem

6. (2)

3.0/3 points (graded)

Now compute the final hidden state  $s_T^{(1)}, s_T^{(2)}, s_T^{(3)}$  for each of the three sentences  $AA, ABB, BAA$  in this RNN.

(Enter  $[0, 0]$  for  $S_T = [0, 0]^T$ .)

$s_T^{(1)} =$   ✓ Answer: [0,0]

$s_T^{(2)} =$   ✓ Answer: [0,2]

$s_T^{(3)} =$   ✓ Answer: [0,1]

**Solution:**

Using  $s_t = \text{RELU}(W^{s,s} s_{t-1} + W^{s,x} x_t)$ , we can compute

$$s_T^{(1)} = [0, 0]^T$$

$$s_T^{(2)} = [0, 2]^T$$

$$s_T^{(3)} = [0, 1]^T$$

Submit

You have used 1 of 5 attempts

**i** Answers are displayed within the problem

## 6. (3)

0/1 point (graded)

Fixing  $s_0$ ,  $W^{s,s}$ ,  $W^{s,x}$  and by only learning the linear classifier in the final layer, can this RNN separate the 3 examples regardless of how they were labeled?

☒ Yes **✗**☐ No **✓**

### Solution:

No. As the final layer is a linear classifier and  $s_T^{(1)}$ ,  $s_T^{(2)}$ ,  $s_T^{(3)}$  are collinear points, they are not linear separable in general. A concrete example is when  $y^{(1)} = y^{(2)} = 1$  and  $y^{(3)} = -1$ .

Submit

You have used 2 of 3 attempts

**i** Answers are displayed within the problem

## 6. (4)

1/1 point (graded)

A simpler model to classify sentences is to represent the entire sentence into a vector  $z$  and apply a linear model on  $z$ , i.e.

$$y = \text{sign}(W^{z,y} z)$$

The vector  $z$  has length  $|V|$  and the  $i$ th element of  $z$  is the count of how many times the  $i$ th word appears in the sentence. For example, the sentence  $ABA$  with  $V = \{A, B\}$  will be encoded as  $z = [2, 1]^T$ . If we want the RNN we described earlier to match the output of this linear model given any input sentences, Which of the following is a possible setting of the weights and initial state  $s_0$  of the RNN? Check all that apply.

Here  $c^{|V|}$  stands for a vector of length  $|V|$  in which every element is  $c$  (e.g.  $[1, 1, 1]^T$  if  $c = 1$  and  $|V| = 3$ ),  $I_{|V|}$  stands for the identity matrix of size  $|V|$ .

☐  $s_0 = 1^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = I_{|V|}, W^{s,y} = -W^{z,y}, W_0 = \sum_i W_i^{z,y}$

☒  $s_0 = 1^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = I_{|V|}, W^{s,y} = W^{z,y}, W_0 = -\sum_i W_i^{z,y}$  ✓

☐  $s_0 = 0^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = -I_{|V|}, W^{s,y} = -W^{z,y}, W_0 = 0$

☒  $s_0 = 0^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = I_{|V|}, W^{s,y} = W^{z,y}, W_0 = 0$  ✓



### Solution:

By setting  $W^{s,s} = I_{|V|}$  and  $W^{s,x} = I_{|V|}$ , we have  $s_t = \text{RELU}(s_{t-1} + x_t)$ .

If we initialize  $s_0 = 0^{|V|}$ , then  $s_T$  will be the same as  $z$ ,  
thus  $W^{s,y} = W^{z,y}$  and  $W_0 = 0$ .

If we initialize  $s_0 = 1^{|V|}$ ,

then  $s_T = z + 1^{|V|}$ .

To make  $W^{z,y}z = W^{s,y}(z + 1^{|V|}) + W_0$ ,

we have  $W^{s,y} = W^{z,y}$  and  $W_0 = -W^{s,y} \cdot 1^{|V|} = -\sum_i W_i^{z,y}$

Submit

You have used 1 of 3 attempts

**i** Answers are displayed within the problem

6. (5)

1/1 point (graded)

Now suppose we want to use indicators instead of counts for the vector  $z$ . That is the  $i$ th element of  $z$  will be 1 if the  $i$ th word appears anywhere in the sentence. Which of the following is a possible setting of the weights and initial state  $s_0$  of the RNN? Check all that apply.

**Note (Sept 8):** In the choices below,  $W_0$  is a scalar, and the summation  $\sum_i W_i^{z,y}$  over  $i$  is summing over the elements of the vector  $W^{z,y}$ .

☐  $s_0 = 1^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = -I_{|V|}, W^{s,y} = W^{z,y}, W_0 = -\sum_i W_i^{z,y}$

☒  $s_0 = 1^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = -I_{|V|}, W^{s,y} = -W^{z,y}, W_0 = \sum_i W_i^{z,y}$  ✓

☐  $s_0 = 0^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = -I_{|V|}, W^{s,y} = -W^{z,y}, W_0 = 0$

☐  $s_0 = 0^{|V|}, W^{s,s} = I_{|V|}, W^{s,x} = I_{|V|}, W^{s,y} = W^{z,y}, W_0 = 0$



### Solution:

As the RELU activation function will map all non-positive input to 0, so whenever a word appears, we can minus the corresponding state by 1. If we set the initial state to be 1, representing a word does not appear, then as long as a word appears, no matter how many times, the state will be 0.

With this idea, we choose  $s_0 = 1^{|V|}$ ,  $W^{s,s} = I_{|V|}$  and  $W^{s,x} = -I_{|V|}$ . By doing so, we have  $s_T = 1^{|V|} - z$ .

To make  $W^{z,y}z = W^{s,y}(1^{|V|} - z) + W_0$ ,

We have  $W^{s,y} = -W^{z,y}$  and  $W_0 = \sum_i W_i^{z,y}$ .



Submit

You have used 1 of 3 attempts

**i** Answers are displayed within the problem

## Error and Bug Reports/Technical Issues

[Hide Discussion](#)

**Topic:** Final exam (1 week):Final Exam / Problem 6

[Add a Post](#)

Show all posts ▼

by recent activity ▼

? [\[STAFF\] Is the extension for Everybody?](#)

8

[Hello staff, May I please ask if the 12-hour exam extension is for everybody? If yes would the timer be adjusted to reflect that? Seeing that I have ...](#)

? [I have been informed that there was a extension given but the timer on my page does not reflect that](#)

6

[I opened the exam page this morning \(i.e. approximately 10 hours ago\). Right now the timer on the upper right corner of the webpage shows tha...](#)

✓ [Could you please help me to reset the attempt for Q6\(4\)?](#)

4

[I accidentally double clicked submitted Q 6\(4\) which was a wrong answer. Could you please help me to reset the attempt? Thank you very much!!](#)

💬 [\[staff\] typo in intro description for Problem 6](#)

1

[1 of the word -> 1 if the word](#)

? [6.1 clarification.](#)

4 new\_

[Can you please clarify this statement. I am having a hard time understanding it as the grammar in the highlighted part is off: The  \$i\$  th element of ...](#)

💬 [Sign function](#)

3

[--- edited ---](#)

🗨	<u>NOT in course lectures</u> Most of the content in the exam was not presented in the course.	4
?	<u>[Staff] 6(4): need confirmation</u> as for the statement in 6(4), is $y = \text{sign}(W z, y z)$ correct? i'm wondering if $W_0$ is missing.	2
?	<u>6. (4) 6. (5) Need explanation in notation.</u>	4
?	<u>Fixing = to leave as was defined (e.g. Firmly fixed) or to correct/amend ?</u> Fixing = to leave as was defined (e.g. Firmly fixed) or to correct/amend ?	1
?	<u>[Edited to remove content]</u> [Edited to remove content. We have emailed you]	3
🗨	<u>Number of Attempts for 6.(3)</u> The question has only one attempt. Should there be three? Thanks.	2
🗨	<u>Number of attempts in 6.3</u> Right after I clicked submit on 6.3 I noticed I had clicked in the wrong answer (not the one I wanted). I know this is my mistake, but every questio...	3

© All Rights Reserved