

L9 PROBLEM 6 (5/5 points)

In the following examples, assume all graphs are undirected. That is, an edge from A to B is the same as an edge from B to A and counts as exactly one edge.

A **clique** is an unweighted graph where each node connects to all other nodes. We denote the clique with n nodes as **KN**. Answer the following questions in terms of n .

1. What is the asymptotic worst-case runtime of a Breadth First Search on KN? For simplicity, write $O(n)$ as just n , $O(n^2)$ as n^2 , etc.

Answer: n

EXPLANATION:

Answer: $O(n)$

BFS begins by checking all the paths of length 1. In its worst case, it must check the paths to every node from the source to find the destination. This is at most, $n - 1$ checks.

2. BFS will always run faster than DFS.

☐ True

☒ False

**EXPLANATION:**

Consider a graph of two nodes, A and B, connected by an edge. You wish to search for a path from A to B. As there is exactly one edge in the graph, and exactly one path from A to B, both run in an equal number of steps.

3. If a BFS and DFS prioritize the same nodes (e.g., both always choose to explore the lower numbered node first), BFS will always run at least as fast as DFS when run on two nodes in KN.


☒ True

☐ False

EXPLANATION:

As seen in our previous problems in this lecture sequence, BFS checks at most $n - 1$ paths in KN, and DFS always checks $O((n - 2)!)$ paths. If given the same node prioritization, both will first find the desired node in the same number of steps.


4. If a BFS and Shortest Path DFS prioritize the same nodes (e.g., both always choose to explore the lower numbered node first), BFS will always run at least as fast as Shortest Path DFS when run on two nodes in any connected unweighted graph.

- ☒ True 
- ☐ False

EXPLANATION:

While Shortest Path DFS may find the desired node first in this case, it still must explore all other paths before it has determined which path is the fastest. BFS will explore only a fraction of the paths.

5. Regardless of node priority, BFS will always run at least as fast as Shortest Path DFS on two nodes in any connected unweighted graph.

- ☒ True 
- ☐ False

EXPLANATION:

Shortest Path DFS must always explore every path from the source to the destination to ensure that it has found the shortest path. Once BFS has found a path, it knows that it is the shortest, and does not have to explore any other paths.

Check

Hide Answer

Show Discussion

 New Post






EdX offers interactive online classes and MOOCs from the world's best universities. Online courses from MITx, HarvardX, BerkeleyX, UTx and many other universities. Topics include biology, business, chemistry, computer science, economics, finance, electronics, engineering, food and nutrition, history, humanities,

About edX

About
News
Contact
FAQ

Follow Us

 Twitter
 Facebook
 Meetup

law, literature, math, medicine, music, philosophy, physics, science, statistics and more. EdX is a non-profit online initiative created by founding partners Harvard and MIT.

© 2014 edX, some rights reserved.

[Terms of Service and Honor Code](#)

[Privacy Policy \(Revised 4/16/2014\)](#)

[edX Blog](#)

[Donate to edX](#)

[Jobs at edX](#)

 [LinkedIn](#)

 [Google+](#)