



[Unit 4 Unsupervised Learning](#) (2
Course > [weeks](#))

[Project 4: Collaborative Filtering via](#)
> [Gaussian Mixtures](#)

> 2. K-means

2. K-means

K-means

1/1 point (graded)

For this part of the project you will compare clustering obtained via K-means to the (soft) clustering induced by EM. In order to do so, our K-means algorithm will differ a bit from the one you learned. Here, the means are estimated exactly as before but the algorithm returns additional information. More specifically, we use the resulting clusters of points to estimate a Gaussian model for each cluster. Thus, our K-means algorithm actually returns a mixture model where the means of the component Gaussians are the K centroids computed by the K-means algorithm. This is to make it such that we can now directly plot and compare solutions returned by the two algorithms as if they were both estimating mixtures.

Read a 2D toy dataset using `x = np.loadtxt('toy_data.txt')`. Your task is to run the K-means algorithm on this data using the implementation we have provided in `kmeans.py`. Initialize K-means using `common.init(X, K, seed)`, where K is the number of clusters and `seed` is the random seed used to randomly initialize the parameters.

Note that `init(X, K)` returns a K-component mixture model with means, variances and mixing proportions. The K-means algorithm will only care about the means, however, and returns a mixture that is retrofitted based on the K-means solution.

Try $K = [1, 2, 3, 4]$ on this data, plotting each solution using our `common.plot` function. Since the initialization is random, please use seeds 0, 1, 2, 3, 4 to and select the one that minimizes the total distortion cost. Save the associated plots (best solution for each K). The code for this task can be written in `main.py`.

Report the lowest cost for each K :

Cost $_{K=1}$ = ✓

Cost $_{K=2}$ = ✓

Cost $_{K=3}$ = ✓

Cost $_{K=4}$ = ✓

Submit

You have used 2 of 20 attempts

✓ Correct (1/1 point)

Discussion

Hide Discussion

Topic: Unit 4 Unsupervised Learning (2 weeks) :Project 4: Collaborative Filtering via Gaussian Mixtures / 2. K-means

[Add a Post](#)

Show all posts ▼

by recent activity ▼

[Stuck on this for hours](#)

1

[Well I do not understand how to walk ahead in this. Any hints please?](#)[Code implementation](#)

1 new_

[I opened the file named "kmeans.py", but I'm not sure I'm proceeding the right way. 1\) We're asked to initialize K-means using "common.init\(X, K, see...](#)

© All Rights Reserved