



< Previous



Next >

Notifications



In-Video Quiz

Bookmark this page

Pursue a verified certificate

- Earn a **verified certificate** of completion to showcase on your resumé
- Support our **mission** at edX

Upgrade for \$50



Hide Notes

Q2

1/1 point (ungraded)

Consider tables R(A) and S(B), both containing {(1),(2)}. Suppose transaction T1 is "update R set A = 2*A; update S set B = 2*B" and transaction T2 is "select avg(A) from R; select avg(B) from S". If transaction T2 executes using "read committed", is it possible for T2 to return two different values?

© All Rights Reserved



About

Affiliates

Explanation

T2 could return avg(A) computed before T1 and avg(B) computed after T1.

Open edX

Careers

News

Submit

You have used 1 of 4 attempts

Legal

Terms of Service & Honor Code

Answers are displayed within the problem

Privacy Policy

Accessibility Policy

Trademark Policy

Sitemap

1/1 point (ungraded)

Consider tables R(A) and S(B), both containing {(1),(2)}. Suppose transaction T1 is "update R set A = 2*A; update S set B = 2*B" and transaction T2 is "select avg(A) from R; select avg(B) from S". If transaction T2 executes using "read committed", is it possible for T2 to return a smaller avg(B) than avg(A)?

Blog

Contact Us

Help Center

Media Kit

Yes

No



avg(A) > avg(B) would require the two statements of T2 to execute between the two statements of T1, not permitted by "read committed".

© 2022 edX, Inc. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)

< Previous

Next >

Hide Notes