

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Unit 2 Foundation of Inference](#) > [Hypothesis Testing](#) > 5. P-Values Formulas

Currently enrolled in **Audit Track** (expires December 25, 2019) [Upgrade \(\\$300\)](#)

5. P-Values Formulas

In each of the following questions, you are given an i.i.d. sample and two hypotheses. For any $\alpha \in (0, 1)$, define a test with asymptotic level α , then give a formula for the asymptotic p -value of your test.

(a)

1/1 point (graded)

$X_1, \dots, X_n \stackrel{i.i.d.}{\sim} \text{Pois}(\lambda)$ for some unknown $\lambda > 0$;

$$H_0 : \lambda = \lambda_0 \quad \text{v.s.} \quad H_1 : \lambda \neq \lambda_0 \quad \text{where } \lambda_0 > 0.$$

(Type **barX_n** for \bar{X}_n , **lambda_0** for λ_0 . If applicable, type **abs(x)** for $|x|$, **Phi(x)** for $\Phi(x) = \mathbf{P}(Z \leq x)$ where $Z \sim \mathcal{N}(0, 1)$, and **q(alpha)** for q_α , the $1 - \alpha$ quantile of a standard normal variable, e.g. enter **q(0.01)** for $q_{0.01}$.)

Asymptotic p -value =

2-2*Phi(sqrt(n)*abs(barX_n-lambda_0)/sqrt(lambda_0))



Generating Speech Output [NOTATION](#)

Submit

You have used 2 of 3 attempts

✓ Correct (1/1 point)

(b)

1/1 point (graded)

 $X_1, \dots, X_n \stackrel{i.i.d.}{\sim} \text{Pois}(\lambda)$ for some unknown $\lambda > 0$;

$$H_0 : \lambda \geq \lambda_0 \quad \text{v.s.} \quad H_1 : \lambda < \lambda_0 \quad \text{where } \lambda_0 > 0.$$

(Type **barX_n** for \bar{X}_n , **lambda_0** for λ_0 . . If applicable, type **abs(x)** for $|x|$, **Phi(x)** for $\Phi(x) = \mathbf{P}(Z \leq x)$ where $Z \sim \mathcal{N}(0, 1)$, and **q(alpha)** for q_α , the $1 - \alpha$ quantile of a standard normal variable.)

Asymptotic p -value =

Phi(sqrt(n)*(barX_n-lambda_0)/sqrt(lambda_0))



STANDARD NOTATION

Submit

You have used 2 of 3 attempts

✓ Correct (1/1 point)

(c)

1/1 point (graded)

 $X_1, \dots, X_n \stackrel{i.i.d.}{\sim} \text{Exp}(\lambda)$ for some unknown $\lambda > 0$;

Generating Speech Output

$$H_0 : \lambda = \lambda_0 \quad \text{v.s.} \quad H_1 : \lambda \neq \lambda_0 \quad \text{where } \lambda_0 > 0.$$

(Type **barX_n** for \bar{X}_n , **lambda_0** for λ_0 . If applicable, type **abs(x)** for $|x|$, **Phi(x)** for $\Phi(x) = \mathbf{P}(Z \leq x)$ where $Z \sim \mathcal{N}(0, 1)$, and **q(alpha)** for q_α , the $1 - \alpha$ quantile of a standard normal variable.)

Asymptotic *p*-value =

2-2*Phi(sqrt(n)*lambda_0*abs(barX_n-1/lambda_0))

✓

STANDARD NOTATION

Submit

You have used 1 of 3 attempts

✓

Correct (1/1 point)

Discussion

Hide Discussion

Topic: Unit 2 Foundation of Inference:Homework 3: Introduction to Hypothesis Testing / 5. P-Values Formulas

Add a Post

◀ All Posts

[Staff] Could not format HTML for problem. Contact course staff in the discussion forum for assistance.

question posted 2 days ago by [NataliaBor](#)

After saving my answer in problem (a) and reloading the page I receive "Could not format HTML for problem. Contact course staff in the discussion forum for assistance." Description of the problem disappeared. The other problems are still there. Could you please help me?

This post is visible to everyone.

+

★

...

Generating Speech Output

NataliaBor

2 days ago - marked as answer a day ago by **karenechu** (Staff)



After one more reloading it started working.

Add a comment

Preview

Submit

Audit Access Expires Dec 24, 2019

You lose all access to this course, including your progress, on Dec 24, 2019.

Upgrade by Nov 4, 2019 to get unlimited access to the course as long as it exists on the site. **Upgrade now**

Learn About Verified Certificates

© All Rights Reserved

Generating Speech Output