

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Unit 3:...](#) > [Part B...](#) > 6. Opti...

6. Optimizing the design

The next step is to study the system's behavior at other forcing frequencies, as we want to minimize the largest amplitude of the building's oscillations that can occur in the range $\Omega \in [0.7, 1.3]$.

Problem 2 (External resource) (1.0 / 1.0 points)

Sweeping through input frequencies

The script below is designed to compute and plot the swaying amplitude of the building over a range of driving frequencies. The swaying amplitude of the building without a TMD will also be plotted for comparison. To complete the script, you must:

1. Define the variable **omSweep** to be a row vector containing 50 equally spaced points over the interval $[0.7, 1.3]$. (Hint: use MATLAB function linspace.)
2. Copy the relevant lines of code from the previous problem to solve the system using ODE45.

$$m_1 = 1, \quad m_2 = 0.05,$$

To test the script, use the parameters: $k_1 = 1, \quad k_2 = 0.02,$

$$b_1 = 0.001, \quad b_2 = 0.02.$$

Use the initial conditions $\mathbf{x}_0 = \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \end{bmatrix}$,

and solve the system for times t on the interval $[0, 500]$. If your script runs correctly, you will see how the TMD changes the swaying amplitude of the building for each forcing frequency Ω in the range $[0.7, 1.3]$.

Your Script

 Save  Reset  MATLAB Documentation (<https://www.mathworks.com/help/>)

```

1 load('Reference.mat')
2
3 %Define parameters
4 m1 = 1;
5 m2 = 0.05;
6 k1 = 1;
7 k2 = 0.02;
8 b1 = 0.001;
9 b2 = 0.02;
10 omSweep = linspace(0.7,1.3,50);
11
12 %Numerically solve DE at each forcing frequency
13 for i=1:length(omSweep)
14
15     om = omSweep(i);
16
17     %Copy code to solve DE here
18     x0 = [0;0;0;0];
19     tspan = [0,7000];
20     A = [0,0,1,0;0,0,0,1;-(k1+k2)/m1,k2/m1,-(b1+b2)/m1,b2/m1;k2/m2,-k2/m2,b2/m2,-b2/
21     m2;0,0,0,0];
22     [t,x] = ode45(@(t,x) A*x + [0;0;sin(om*t);0],tspan,x0);

```

```

21 [t,x] = ode45(@(t,x) A*x + [0;0;sin(om*t)/m1;0],tspan,x0);
22
23 %Compute steady state solution and extract building oscillation amplitude
24 lt = length(t);
25 per = 2*pi/om;
26 [~,idx] = min(abs(t-(t(end)-5*per)));
27 ampBuilding(i) = max(x(idx:lt,1));
28
29 end
30
31 %Plot
32 plot(omRef,ampRef,'r'); hold on;
33 plot(omSweep,ampBuilding,'k');
34 xlim([0.7,1.3]); ylabel('Max. Amp. of Building'); xlabel('$\Omega$');
35 legend('Without TMD','With TMD')
36

```

[▶ Run Script](#)


Previous Assessment: Correct

[Submit](#)


✓ Correct definition of OmSweep

✓ Correct numerical result

Optimization problem

The optimal values of k_2 and b_2 will minimize the maximum value of the black response curve. This is a two-dimensional minimization problem. However, in our example where the building has a small damping constant, b_1 , it can be shown that the parameters k_2 and b_2 can be optimized independently of each other. Therefore, let's first determine the optimal value, k_2^* , of the spring constant.

MATLAB exploration 1

1/1 point (graded)

Copy the script you used in problem 2 to MATLAB online or on your computer. You will also need to save and copy the file 'Reference.mat'. You can do this by typing

```
url = 'https://courses.edx.org/asset-  
v1:MITx+18.033x+1T2018+type@asset+block@Reference.mat';  
websave('Reference.mat', url);
```

into MATLAB command window.

While keeping all of the other parameters constant, change k_2 and see what effect it has on the response curve of the building. Based on your observations, enter the optimal value, k_2^* , that is accurate to three decimal places.

$k_2^* =$

0.0449

✓ Answer: 0.045

Solution:

$$k_2^* = 0.045$$


Submit

You have used 2 of 10 attempts

i Answers are displayed within the problem




Matching graphs 1

3/3 points (graded)

 Keyboard Help

PROBLEM

Match the three graphs to the corresponding inequalities based on your MATLAB exploration.



Submit

You have used 1 of 2 attempts.



Reset



Show Answer

FEEDBACK

✓ Correctly placed 3 items.

✓ Good work! You have completed this drag and drop problem.

✓ Your highest score is 3.0

MATLAB exploration 2

1/1 point (graded)

Now that you have found the optimal spring constant, k_2^* , the last step is to determine the optimal damping constant, b_2^* . Using your value of k_2^* and keeping all of the other parameters constant, vary b_2 and see what effect it has on the response curve of the building. Like in the previous problem, based on your observations, enter the optimal value, b_2^* , that is accurate to three decimal places.

$b_2^* =$

✓ Answer: 0.013

Solution:

$b_2^* = 0.013$


Submit

You have used 1 of 10 attempts

i Answers are displayed within the problem




Matching graphs 2

3/3 points (graded)

 Keyboard Help

PROBLEM

Match the three graphs to the corresponding inequalities based on your MATLAB exploration.



Submit

You have used 1 of 2 attempts.


Reset


Show Answer

FEEDBACK

✓ Correctly placed 3 items.

✓ Good work! You have completed this drag and drop problem.

✓ Your highest score is 3.0

We have achieved our goal and have determined the optimal spring and damping constants that minimize the swaying amplitude of the building over a range of forcing frequencies! You should double check that using the value of b_2 found in the previous step and then optimizing k_2 will give you the same result. (A general numerical approach to optimizing two parameters is to iteratively optimize each parameter independently, and using the new value to re-optimize the other parameter until no changes are detected.)

Note that this problem is a toy model. In reality, there are often many other factors that engineers must consider when designing a TMD for a building. For example:

- The building might sway in multiple dimensions and might also twist around its vertical axis.
- The building might need to withstand forcing from the ground due to seismic activity, which can produce a very different response compared to wind forcing.

6. Optimizing the design

[Hide Discussion](#)

Topic: Unit 3: Solving systems of first order ODEs using matrix methods
/ 6. Optimizing the design

[Add a Post](#)[◀ All Posts](#)

Problem 2

question posted 3 days ago by [Abanoub Mikhail](#)

I do not see how the code in problem 2 is connected to this problem (do not see a reason to copy it).

This post is visible to everyone.

[Add a Response](#)

1 response

[BlackColt](#) (Community TA)

3 days ago

Problem 2 is the "Sweeping through input frequencies" problem. The optimal value of k_2 has to be (or can be) found by changing the value of k_2 in the script of Problem 2 or by adding some code to that script.

The title/name of the problem should be changed to "Problem 2 (External resource)" from "LTI Consumer (External resource)", like the previous problem, "Problem 1 (External resource) Modeling the tuned mass damper, without the damper"

Add a comment

Showing all responses

Add a response:

Preview

Submit

[Learn About Verified Certificates](#)

© All Rights Reserved