



< Previous







Next >

9.2.1 Accuracy and Convergence

 Bookmark this page

MO2.4

MO2.6

As the timestep is decreased, i.e. $\Delta t \rightarrow 0$, we would like our numerical method to better approximate the exact solution to the model equations. Let's define the error in our approximation at timestep n to be:

$$\underline{e}^n \equiv \underline{v}^n - \underline{u}(t^n)$$

(9.1)

Since this is $\underline{u}(t^n)$ is in general an M -dimensional vector of states, then so are \underline{v}^n and \underline{e}^n . We can define the components of this error then,

$$e_m^n = v_m^n - u_m(t^n)$$

(9.2)

© All Rights Reserved

for each $m = 0$ to $M - 1$. Then, to measure the error for the entire simulation (i.e. over all timesteps), we'll take the maximum magnitude,

edX

About

Affiliates

edX for Business

Open edX

Careers

News

$$(e_m)_{\max} = \max_n |e_m^n|$$

(9.3)

Then, in terms of these error definitions, we desire that the maximum error in each state goes to zero as $\Delta t \rightarrow 0$. This concept is known as convergence and is stated mathematically as follows:

Legal

Definition 2 (Convergence).

Terms of Service & Honor Code

Privacy Policy

Accessibility Policy

Trademark Policy

Sitemap

Cookie Policy

Your Privacy Choices

While convergence is a clear requirement for a good numerical method, the rate at which the method converges is also important. This rate is known as the order of accuracy.

Connect

Blog

Contact Us

Help Center

Security

Media Kit

Definition 3 (Order of Accuracy).

A method has an order of accuracy of p if, for all m ,



$$(e_m)_{\max} = O(\Delta t^p)$$

as $\Delta t \rightarrow 0,$



Some important comments:

Discussions

All posts sorted by recent activity

$$(e_m)_{\max} = C\Delta t^p \quad \text{as} \quad \Delta t \rightarrow 0.$$

where C is depends on the method and the