

This website uses cookies to ensure you get the best experience on our website.

[Ok](#)[Learn more](#)

Statistical tools for high-throughput data analysis

Licence:

[Home](#)[Basics](#)[Data](#)[Visualize](#)[Analyze](#)[Resources](#)[Our Products](#)[Support](#)[About](#)

[Home](#) / [Easy Guides](#) / [R software](#) / [R Basic Statistics](#) / [Comparing Means in R](#) / [One-Way ANOVA Test in R](#)

Actions menu for module Wiki

## One-Way ANOVA Test in R

Tools

- [What is one-way ANOVA test?](#)
- [Assumptions of ANOVA test](#)
- [How one-way ANOVA test works?](#)
- [Visualize your data and compute one-way ANOVA in R](#)
  - [Import your data into R](#)
  - [Check your data](#)
  - [Visualize your data](#)
  - [Compute one-way ANOVA test](#)
  - [Interpret the result of one-way ANOVA tests](#)
  - [Multiple pairwise-comparison between the means of groups](#)
    - [Tukey multiple pairwise-comparisons](#)
    - [Multiple comparisons using multcomp package](#)
    - [Pairwise t-test](#)
  - [Check ANOVA assumptions: test validity?](#)
    - [Check the homogeneity of variance assumption](#)
    - [Relaxing the homogeneity of variance assumption](#)
    - [Check the normality assumption](#)
  - [Non-parametric alternative to one-way ANOVA test](#)
- [Summary](#)
- [See also](#)
- [Read more](#)
- [Infos](#)

### What is one-way ANOVA test?

The **one-way analysis of variance (ANOVA)**, also known as *one-factor ANOVA*, is an extension of [independent two-samples t-test](#) for comparing means in a situation where there are more than two groups. In **one-way ANOVA**, the data is organized into several groups base on one single grouping variable (also called *factor* variable). This tutorial describes the basic principle of the **one-way ANOVA test** and provides practical **anova test examples** in R software.



**aws** is how

**Build and train machine  
learning models fast.**

! Note that, if you have only two groups, you can use [t-test](#). In this case the F-test and the t-test are equivalent.


## One-Way ANOVA Test in R

Compare more than two groups

- + Definition
- + ANOVA Assumptions
- + Compute ANOVA in R
- + Interpret
- + Post Hoc Test
- + Check Assumptions
- + Non-Parametric Alternative

© sthda.com 2016

### Related Book:



Practical Statistics in R for Comparing Groups: Numerical Variables

## Assumptions of ANOVA test

Here we describe the requirement for **ANOVA test**. ANOVA test can be applied only when:

- ✗ The observations are obtained independently and randomly from the population defined by the factor levels
- ✗ The data of each factor level are normally distributed.
- ✗ These normal populations have a common variance. (**Levene's test** can be used to check this.)

## How one-way ANOVA test works?

Assume that we have 3 groups (A, B, C) to compare:

1. Compute the common variance, which is called **variance within samples** ( $S^2_{within}$ ) or **residual variance**.
2. Compute the variance between sample means as follow:
  - Compute the mean of each group
  - Compute the **variance between sample means** ( $S^2_{between}$ )
3. Produce F-statistic as the ratio of  $S^2_{between} / S^2_{within}$ .

! Note that, a lower ratio (ratio < 1) indicates that there are no significant difference between the means of the samples being compared. However, a higher ratio implies that the variation among group means are significant.

## Visualize your data and compute one-way ANOVA in R

aws is how

Build and train machine learning models fast.

2. **Save your data** in an external .txt tab or .csv files

3. **Import your data into R** as follow:

```
# If .txt tab file, use this
my_data <- read.delim(file.choose())
# Or, if .csv file, use this
my_data <- read.csv(file.choose())
```

Here, we'll use the built-in R data set named *PlantGrowth*. It contains the weight of plants obtained under a control and two different treatment conditions.

```
my_data <- PlantGrowth
```

## Check your data

To have an idea of what the data look like, we use the the function **sample\_n()**[in **dplyr** package]. The **sample\_n()** function randomly picks a few of the observations in the data frame to print out:

```
# Show a random sample
set.seed(1234)
dplyr::sample_n(my_data, 10)
```

```
  weight group
19  4.32  trt1
18  4.89  trt1
29  5.80  trt2
24  5.50  trt2
17  6.03  trt1
1  4.17  ctrl
6  4.61  ctrl
16  3.83  trt1
12  4.17  trt1
15  5.87  trt1
```

**!** In R terminology, the column "group" is called factor and the different categories ("ctr", "trt1", "trt2") are named factor levels. **The levels are ordered alphabetically.**

```
# Show the levels
levels(my_data$group)
```

```
[1] "ctrl" "trt1" "trt2"
```

If the levels are not automatically in the correct order, re-order them as follow:

```
my_data$group <- ordered(my_data$group,
  levels = c("ctrl", "trt1", "trt2"))
```

**!** It's possible to compute summary statistics (mean and sd) by groups using the **dplyr** package.

- Compute summary statistics by groups - count, mean, sd:

```
library(dplyr)
group_by(my_data, group) %>%
  summarise(
    count = n(),
    mean = mean(weight, na.rm = TRUE),
    sd = sd(weight, na.rm = TRUE)
  )
```

```
Source: local data frame [3 x 4]
  group count mean      sd
  (fctr) (int) (dbl)   (dbl)
1✓ ctrl    10 5.032 0.5830914
```



Build and train machine learning models fast.

- To use R base graphs read this: [R base graphs](#). Here, we'll use the **ggpubr** R package for an easy ggplot2-based data visualization.
- Install the latest version of ggpubr from GitHub as follow (recommended):


```
# Install
if(!require(devtools)) install.packages("devtools")
devtools::install_github("kassambara/ggpubr")
```

- Or, install from CRAN as follow:


```
install.packages("ggpubr")
```

- Visualize your data with ggpubr:

```
# Box plots
# ++++++
# Plot weight by group and color by group
library("ggpubr")
ggboxplot(my_data, x = "group", y = "weight",
  color = "group", palette = c("#00AFBB", "#E7B800", "#FC4E07"),
  order = c("ctrl", "trt1", "trt2"),
  ylab = "Weight", xlab = "Treatment")
```



```
# Mean plots
# ++++++
# Plot weight by group
# Add error bars: mean_se
# (other values include: mean_sd, mean_ci, median_iqr, ....)
library("ggpubr")
ggline(my_data, x = "group", y = "weight",
  add = c("mean_se", "jitter"),
  order = c("ctrl", "trt1", "trt2"),
  ylab = "Weight", xlab = "Treatment")
```



If you still want to use R base graphs, type the following scripts:

```
# Box plot
boxplot(weight ~ group, data = my_data,
        xlab = "Treatment", ylab = "Weight",
        frame = FALSE, col = c("#00AFBB", "#E7B800", "#FC4E07"))
# plotmeans
library("gplots")
plotmeans(weight ~ group, data = my_data, frame = FALSE,
          xlab = "Treatment", ylab = "Weight",
          main="Mean Plot with 95% CI")
```

## Compute one-way ANOVA test

? We want to know if there is any significant difference between the average weights of plants in the 3 experimental conditions.

The R function **aov()** can be used to answer to this question. The function **summary.aov()** is used to summarize the analysis of variance model.

```
# Compute the analysis of variance
res.aov <- aov(weight ~ group, data = my_data)
# Summary of the analysis
summary(res.aov)
```

```
      Df Sum Sq Mean Sq F value Pr(>F)
group    2  3.766   1.8832    4.846  0.0159 *
Residuals 27 10.492   0.3886
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

✓ The output includes the columns *F value* and *Pr(>F)* corresponding to the p-value of the test.

## Interpret the result of one-way ANOVA tests

As the p-value is less than the significance level 0.05, we can conclude that there are significant differences between the groups highlighted with "\*" in the model summary.

## Multiple pairwise-comparison between the means of groups

In one-way ANOVA test, a significant p-value indicates that some of the group means are different, but we don't know which pairs of groups are different. It's possible to perform multiple pairwise-comparison, to determine if the mean difference between specific pairs of group are statistically significant.

## Tukey multiple pairwise-comparisons

As the ANOVA test is significant, we can compute **Tukey HSD** (Tukey Honest Significant Differences, R function: **TukeyHSD()**) for performing multiple pairwise-comparison between the means of groups.

The function **TukeyHSD()** takes the fitted ANOVA as an argument.



**Build and train machine learning models fast.**

```
Tukey multiple comparisons of means
 95% family-wise confidence level
Fit: aov(formula = weight ~ group, data = my_data)
$group
      diff      lwr      upr      p adj
trt1-ctrl -0.371 -1.0622161 0.3202161 0.3908711
trt2-ctrl  0.494 -0.1972161 1.1852161 0.1979960
trt2-trt1  0.865  0.1737839 1.5562161 0.0120064
```

- **diff**: difference between means of the two groups
- **lwr, upr**: the lower and the upper end point of the confidence interval at 95% (default)
- **p adj**: p-value after adjustment for the multiple comparisons.

✔ It can be seen from the output, that only the difference between trt2 and trt1 is significant with an adjusted p-value of 0.012.

## Multiple comparisons using multcomp package

It's possible to use the function **glht()** [in **multcomp** package] to perform multiple comparison procedures for an ANOVA. **glht** stands for general linear hypothesis tests. The simplified format is as follow:

```
glht(model, lincft)
```

- **model**: a fitted model, for example an object returned by **aov()**.
- **lincft()**: a specification of the linear hypotheses to be tested. Multiple comparisons in ANOVA models are specified by objects returned from the function **mcp()**.

Use **glht()** to perform multiple pairwise-comparisons for a one-way ANOVA:

```
library(multcomp)
summary(glht(res.aov, lincft = mcp(group = "Tukey")))
```

```
Simultaneous Tests for General Linear Hypotheses
Multiple Comparisons of Means: Tukey Contrasts
Fit: aov(formula = weight ~ group, data = my_data)
Linear Hypotheses:
      Estimate Std. Error t value Pr(>|t|)
trt1 - ctrl == 0  -0.3710    0.2788  -1.331   0.391
trt2 - ctrl == 0   0.4940    0.2788   1.772   0.198
trt2 - trt1 == 0   0.8650    0.2788   3.103   0.012 *
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
(Adjusted p values reported -- single-step method)
```

## Pairwise t-test

The function **pairwise.t.test()** can be also used to calculate pairwise comparisons between group levels with corrections for multiple testing.

```
pairwise.t.test(my_data$weight, my_data$group,
               p.adjust.method = "BH")
```

```
Pairwise comparisons using t tests with pooled SD
data: my_data$weight and my_data$group
      ctrl trt1
trt1 0.194 -
trt2 0.132 0.013
P value adjustment method: BH
```

The result is a table of p-values for the pairwise comparisons. Here, the p-values have been adjusted by the Benjamini-Hochberg method.

## Check ANOVA assumptions: test validity?

The ANOVA test assumes that, the data are normally distributed and the variance across groups are homogeneous. We can check that with some diagnostic plots.


## Check the homogeneity of variance assumption

The **residuals versus fits plot** can be used to check the homogeneity of variances.

In the plot below, there is no evident relationships between residuals and fitted values (the mean of each groups), which is good. So, we can assume the homo-



**Build and train machine learning models fast.**



✗ Points 17, 15, 4 are detected as outliers, which can severely affect normality and homogeneity of variance. It can be useful to remove outliers to meet the test assumptions.

✓ It's also possible to use **Bartlett's test** or **Levene's test** to check the homogeneity of variances.

We recommend **Levene's test**, which is less sensitive to departures from normal distribution. The function `leveneTest()` [in `car` package] will be used:

```
library(car)
leveneTest(weight ~ group, data = my_data)
```

```
Levene's Test for Homogeneity of Variance (center = median)
Df F value Pr(>F)
group 2  1.1192 0.3412
27
```

✓ From the output above we can see that the p-value is not less than the significance level of 0.05. This means that there is no evidence to suggest that the variance across groups is statistically significantly different. Therefore, we can assume the homogeneity of variances in the different treatment groups.

## Relaxing the homogeneity of variance assumption

The classical one-way ANOVA test requires an assumption of equal variances for all groups. In our example, the homogeneity of variance assumption turned out to be fine: the Levene test is not significant.

? How do we save our ANOVA test, in a situation where the homogeneity of variance assumption is violated?

An alternative procedure (i.e.: **Welch one-way test**), that does not require that assumption have been implemented in the function `oneway.test()`.

- **ANOVA test with no assumption of equal variances**

```
oneway.test(weight ~ group, data = my_data)
```

- **Pairwise t-tests with no assumption of equal variances**

```
pairwise.t.test(my_data$weight, my_data$group,
  p.adjust.method = "BH", pool.sd = FALSE)
```

## Check the normality assumption


**Normality plot of residuals.** In the plot below, the quantiles of the residuals are plotted against the quantiles of the normal distribution. A 45-degree reference line is also plotted.

The normal probability plot of residuals is used to check the assumption that the residuals are normally distributed. It should approximately follow a straight line.

▼



Build and train machine learning models fast.



✓ As all the points fall approximately along this reference line, we can assume normality.

The conclusion above, is supported by the **Shapiro-Wilk test** on the ANOVA residuals ( $W = 0.96$ ,  $p = 0.6$ ) which finds no indication that normality is violated.

```
# Extract the residuals
aov_residuals <- residuals(object = res.aov )
# Run Shapiro-Wilk test
shapiro.test(x = aov_residuals )
```

```
Shapiro-Wilk normality test
data:  aov_residuals
W = 0.96607, p-value = 0.4379
```

## Non-parametric alternative to one-way ANOVA test

✓ Note that, a non-parametric alternative to one-way ANOVA is **Kruskal-Wallis rank sum test**, which can be used when ANOVA assumptions are not met.

```
kruskal.test(weight ~ group, data = my_data)
```

```
Kruskal-Wallis rank sum test
data:  weight by group
Kruskal-Wallis chi-squared = 7.9882, df = 2, p-value = 0.01842
```

## Summary

1. Import your data from a .txt tab file: `my_data <- read.delim(file.choose())`. Here, we used `my_data <- PlantGrowth`.
2. Visualize your data: `ggpubr::ggboxplot(my_data, x = "group", y = "weight", color = "group")`
3. Compute one-way ANOVA test: `summary(aov(weight ~ group, data = my_data))`
4. Tukey multiple pairwise-comparisons: `TukeyHSD(res.aov)`

## See also

- Analysis of variance (ANOVA, parametric):
  - [One-Way ANOVA Test in R](#)
  - [Two-Way ANOVA Test in R](#)
  - [MANOVA Test in R: Multivariate Analysis of Variance](#)
- [Kruskal-Wallis Test in R \(non parametric alternative to one-way ANOVA\)](#)

## Read more



**Build and train machine learning models fast.**



## Infos



This analysis has been performed using **R software** (ver. 3.2.4).

✓ Enjoyed this article? I'd be very grateful if you'd help it spread by emailing it to a friend, or sharing it on Twitter, Facebook or Linked In.

Show me some love with the like buttons below... Thank you and please don't forget to share and comment below!!

Tweet


Share

Save


Share

221


## Recommended for You!



Machine Learning Essentials: Practical Guide in R




Practical Guide to Cluster Analysis in R



Practical Guide to Principal Component Methods in R



R Graphics Essentials for Great Data Visualization



Network Analysis and Visualization in R



More books on R and data science

## Recommended for you

✓ This section contains best data science and self-development resources to help you on your path.

### Coursera - Online Courses and Specialization

#### Data science

- [Course: Machine Learning: Master the Fundamentals](#) by Standford
- [Specialization: Data Science](#) by Johns Hopkins University
- ✓ [Specialization: Python for Everybody](#) by University of Michigan

aws is how

Build and train machine learning models fast.

## Popular Courses Launched in 2020

- [Google IT Automation with Python](#) by Google
- [AI for Medicine](#) by deeplearning.ai
- [Epidemiology in Public Health Practice](#) by Johns Hopkins University
- [AWS Fundamentals](#) by Amazon Web Services

## Trending Courses

- [The Science of Well-Being](#) by Yale University
- [Google IT Support Professional](#) by Google
- [Python for Everybody](#) by University of Michigan
- [IBM Data Science Professional Certificate](#) by IBM
- [Business Foundations](#) by University of Pennsylvania
- [Introduction to Psychology](#) by Yale University
- [Excel Skills for Business](#) by Macquarie University
- [Psychological First Aid](#) by Johns Hopkins University
- [Graphic Design](#) by Cal Arts

## Books - Data Science

### Our Books

- [Practical Guide to Cluster Analysis in R](#) by A. Kassambara (Datanovia)
- [Practical Guide To Principal Component Methods in R](#) by A. Kassambara (Datanovia)
- [Machine Learning Essentials: Practical Guide in R](#) by A. Kassambara (Datanovia)
- [R Graphics Essentials for Great Data Visualization](#) by A. Kassambara (Datanovia)
- [GGPlot2 Essentials for Great Data Visualization in R](#) by A. Kassambara (Datanovia)
- [Network Analysis and Visualization in R](#) by A. Kassambara (Datanovia)
- [Practical Statistics in R for Comparing Groups: Numerical Variables](#) by A. Kassambara (Datanovia)
- [Inter-Rater Reliability Essentials: Practical Guide in R](#) by A. Kassambara (Datanovia)

### Others

- [R for Data Science: Import, Tidy, Transform, Visualize, and Model Data](#) by Hadley Wickham & Garrett Golemund
- [Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow: Concepts, Tools, and Techniques to Build Intelligent Systems](#) by Aurelien Géron
- [Practical Statistics for Data Scientists: 50 Essential Concepts](#) by Peter Bruce & Andrew Bruce
- [Hands-On Programming with R: Write Your Own Functions And Simulations](#) by Garrett Golemund & Hadley Wickham
- [An Introduction to Statistical Learning: with Applications in R](#) by Gareth James et al.
- [Deep Learning with R](#) by François Chollet & J.J. Allaire
- [Deep Learning with Python](#) by François Chollet

## Want to Learn More on R Programming and Data Science?

Follow us by Email

by [FeedBurner](#)

On Social Networks:  
on Social Networks



Get involved :



Click to **follow us** on [Facebook](#) and [Google+](#) :



**Comment this article** by clicking on "Discussion" button (top-right position of this page)

This page has been seen 1112906 times

## Sign in

### Login

### Password

### Auto connect





**aws** is how

**Build and train machine  
learning models fast.**

Welcome!

Want to Learn More on R Programming and Data Science?

Follow us by Email

Subscribe

by FeedBurner

on Social Networks


Click to see our collection of resources to help you on your path...

Course & Specialization

Recommended for You (on Coursera):

- Course: Machine Learning: Master the Fundamentals
- Specialization: Data Science
- Specialization: Python for Everybody
- Course: Build Skills for a Top Job in any Industry
- Specialization: Master Machine Learning Fundamentals
- Specialization: Statistics with R
- Specialization: Software Development in R
- Specialization: Genomic Data Science


See More Resources




 **aws** is how

**Build and train machine learning models fast.**

- factoextra
- survminer
- ggpubr
- ggcorrplot
- fastqcr




Our Books



R Graphics Essentials for Great Data Visualization: 200 Practical Examples You Want to Know for Data Science  
★ NEW!!

3  
D  
P  
l  
o  
t  
s  
i  
n  
R




Practical Guide to Cluster Analysis in R

 is how

Build and train machine learning models fast.




Practical Guide to Principal Component Methods in R



 **is how**

**Build and train machine learning models fast.**

-  [Datanovia: Online Data Science Courses](#)
-  [R-Bloggers](#)


Newsletter

Email




Boosted by PHPBoost


Recommended for you




ggplot2 title : main, axis and legend titles - Easy Guides - Wiki - STHDA  
[www.sthda.com](http://www.sthda.com)



Reading Data From Excel Files (xls |xlsx) into R - Easy Guides - Wiki...  
[www.sthda.com](http://www.sthda.com)



ggplot2 barplots : Quick start guide - R software and data visualization...  
[www.sthda.com](http://www.sthda.com)



ggplot2 colors : How to change colors automatically and manually? - E...  
[www.sthda.com](http://www.sthda.com)

AddThis



 **is how**

**Build and train machine learning models fast.**