

 Previous







Next 

Practice Questions: Min-heaps

 [Bookmark this page](#)

What have you learnt so far?

3/3 points (ungraded)

1. A min-heap contains the following (*key, value*) couples: $(A, 25)$, $(B, 37)$, $(C, 5)$ What is the next couple that will be removed?

- ☐ $(A, 25)$
- ☒ $(C, 5)$
- ☐ $(B, 37)$



2. A min-heap contains the following (*key, value*) couples: $(A, 55)$, $(B, 22)$, $(C, 32)$, $(D, 87)$ Consider each of the following items one by one, and select the correct ones:

- ☒ If performing add or replace with $(A, 32)$, the resulting status will be $(A, 32)$, $(B, 22)$, $(C, 32)$, $(D, 87)$
- ☐ If performing add or replace with $(B, 53)$, the resulting status will be $(A, 55)$, $(B, 53)$, $(C, 32)$, $(D, 87)$
- ☒ The next element to be removed is $(B, 22)$
- ☐ The next element to be removed is $(D, 87)$
- ☒ If performing add or replace with $(D, 86)$, the resulting status will be $(A, 55)$, $(B, 22)$, $(C, 32)$, $(D, 86)$



3. The Dijkstra algorithm can be implemented...

- ☒ using a min-heap, by storing vertices as keys, and distances to the starting position as values.
- ☐ using a min-heap, by storing edges as keys, and distances to the starting position as values.
- ☐ using two min-heaps, one for the edges, one for the vertices.



Submit

[< Previous](#)

[Next >](#)

© All Rights Reserved



edX

[About](#)

[Affiliates](#)

[edX for Business](#)

[Open edX](#)

[Careers](#)

[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

Connect

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Media Kit](#)

[Donate](#)



© 2020 edX Inc. All rights reserved.

深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)