



< Previous

 

 



Next >

10.4.3 Gaussian elimination implementation

 Bookmark this page

MO2.3

MO2.8

MO2.9

This construction of Gaussain elimination can be generalized to N -by- N matrices, and results in the code below. Note that the code below is not utilizing NumPy's vectorization capability. As a result, it will be significantly slower than it could, especially in comparison to `np.linalg.solver`.

```
"""
Solve Ku = f by Gaussian elimination (no
pivoting)
"""

import numpy as np

def mysolve(K, f):
    """
    Args:
        K (numpy ndarray): square matrix
        f (numpy ndarray): right-hand side
vector

    Returns:
        numpy ndarray: u, solution to Ku=f
    """
    m,n = K.shape
    assert m == n, "Non-square matrix"

    u = np.zeros(n)

    # Extended matrix with the right-hand side
as last column
    A = np.zeros((n,n+1))
    A[:,0:n] = K
    A[:,n] = f
```

```
edX# Elimination of nonzero elements below
the diagonal
for i in range(n):
    assert A[i,i] != 0.0, "Zero pivot
detected"
    for j in range(i+1,n):
        Lji = A[j,i] / A[i,i]
        for k in range(i+1,n+1):
            A[j,k] = A[j,k] - Lji * A[i,k]
```

```
Legal# Back substitution
u[n-1] = A[n-1,n]/A[n-1,n-1]
for i in range(n-2,-1,-1):
    u[i] = A[i,n]
    for j in range(i+1,n):
        u[i] = u[i] - A[i,j]*u[j]
```

Discussions

All posts sorted by recent activity

© All Rights Reserved



[About](#)

[Affiliates](#)

[edX for Business](#)

[Open edX](#)

[Careers](#)

[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

[Cookie Policy](#)
[Your Privacy Choices](#)

[← Previous](#)

[Next >](#)

Connect

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Security](#)

[Media Kit](#)



© 2023 edX LLC. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)



Now that we've
looked
at the simple 3-