



< Previous

Next >

12.3.1 Implementation of Implicit Methods for Linear Systems

Bookmark this page

MO2.7

MO2.8

Let's next look at the implementation of an implicit method for an IVP for which $\underline{f}(\underline{u}, t)$ involves a linear system as described in Section 10.1.2. Recall that for such an IVP that $\underline{f}(\underline{u}, t)$ has the following form,

$$\underline{f}(\underline{u}, t) = \underline{A}\underline{u} + \underline{b}(t)$$

(12.32)

where \underline{A} is an $M \times M$ matrix, M is the number of states, and \underline{b} is a vector of known functions of time (but do not depend on \underline{u}). Let's now compare the Forward Euler and Backward Euler implementations for this $\underline{f}(\underline{u}, t)$. For Forward Euler, an iteration is,

$$\underline{v}^{n+1} = \underline{v}^n + \Delta t [\underline{A}\underline{v}^n + \underline{b}(t^n)]$$

(12.33)

The computational cost of a Forward Euler iteration will be dominated by the matrix-vector multiplication $\underline{A}\underline{v}^n$ (unless $\underline{b}(t)$ is an extremely complex function to evaluate). The asymptotic computational complexity of a matrix-vector multiply is $2M^2$ (try deriving this yourself by determining the total number of mathematical operations, in particular multiplications and additions, required to multiply a matrix and

© All Rights Reserved



For Backward Euler we have the following iteration,

edX

[About](#)
$$\underline{v}^{n+1} = \underline{v}^n + \Delta t [\underline{A}\underline{v}^{n+1} + \underline{b}(t^{n+1})]$$

(12.34)

[Affiliates](#)

[edX for Business](#)

Now, re-arranging this iteration produces the following linear system of equations to be solved for

\underline{v}^{n+1} ,
[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

[Cookie Policy](#)

[Your Privacy Choices](#)

where \underline{I} is an $M \times M$ identity matrix. On the left-hand side of this equation, we have a matrix $(\underline{I} - \Delta t \underline{A})$ multiplying the vector \underline{v}^{n+1} . On the right-hand side, we have a known vector, $\underline{v}^n + \Delta t \underline{b}(t^{n+1})$. Thus, a Backward Euler iteration requires the solution of a linear $M \times M$ system of equations. If we use Gaussian elimination (see Section 10.4) to solve this system of equations, the asymptotic computational complexity is $\frac{2}{3}M^3$

Discussions

All posts sorted by recent activity

< Previous

Connect

Next >

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Security](#)

[Media Kit](#)



© 2023 edX LLC. All rights reserved.

深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)