

[Course](#)

[Progress](#)

[Dates](#)

[Discussion](#)

[Syllabus](#)

[Outline](#)

[laff routines](#)

[Community](#)

 [Course](#) / [Exam 1](#) / [E1.2 Sample Exam 1](#)



< Previous

 ✓

 ✓

 ✓

 ✓

 ✓

 ✓







Next >

E1.2.6 Sample Question 6

 Bookmark this page

6. Consider the MATLAB (M-script) code

```
function [ y_out ] = foo( A, x, y )

n = size( A, 1 );
for j = 1:n
    for i = 1:j
        y( i ) = A( j,i ) * x( j ) + y( i );
    end
    for i = j+1:n
        y( i ) = A( i,j ) * x( j ) + y( i );
    end
end

y_out = y;

return
end
```

(If you have a hard time interpreting this algorithm, you may want to consider the algorithm typeset with FLAME notation at the end of this exam.)

Mark which operation this implements (check all correct answers):

- ☐ $y := Lx + y$, where L is a lower triangular matrix, stored only in the lower triangular part of array A .
- ☐ $y := Ux + y$, where U is a upper triangular matrix, stored only in the lower triangular part of array A .
- ☐ $y := Ax + y$, where A is symmetric, stored only in the lower triangular part of array A .
- ☐ $y := Ax + y$, where A is symmetric, stored only in the upper triangular part of array A .
- ☐ The equivalent of $y = (\text{tril}(A) + \text{tril}(A, -1)') * x + y$ in MATLAB's M-script.
- ☐ The equivalent of $y = (\text{triu}(A) + \text{triu}(A, 1)') * x + y$ in MATLAB's M-script.

Algorithm typeset using FLAME Notation:

Algorithm: $y := \text{FOO}(A, x, y)$
<p>Partition $A \rightarrow \left(\begin{array}{c c} A_{TL} & A_{TR} \\ \hline A_{BL} & A_{BR} \end{array} \right)$,</p> <p>$x \rightarrow \left(\begin{array}{c} x_T \\ \hline x_B \end{array} \right)$, $y \rightarrow \left(\begin{array}{c} y_T \\ \hline y_B \end{array} \right)$</p> <p>where A_{TL} is 0×0, x_T, y_T are 0×1</p> <p>while $m(A_{TL}) < m(A)$ do</p> <p style="padding-left: 20px;">Repartition</p> $\left(\begin{array}{c c} A_{TL} & A_{TR} \\ \hline A_{BL} & A_{BR} \end{array} \right) \rightarrow \left(\begin{array}{c c c} A_{00} & a_{01} & A_{02} \\ \hline a_{10}^T & \alpha_{11} & a_{12}^T \\ \hline A_{20} & a_{21} & A_{22} \end{array} \right),$ $\left(\begin{array}{c} x_T \\ \hline x_B \end{array} \right) \rightarrow \left(\begin{array}{c} x_0 \\ \hline \chi_1 \end{array} \right), \quad \left(\begin{array}{c} y_T \\ \hline y_B \end{array} \right) \rightarrow \left(\begin{array}{c} y_0 \\ \hline \psi_1 \end{array} \right)$

where α_{11} , χ_1 , and ψ_1 are scalars

$$y_0 := \chi_1(a_{10}^T)^T + y_0$$

$$\psi_1 := \chi_1 \alpha_{11} + \psi_1$$

$$y_2 := \chi_1 a_{21} + y_2$$

Continue with

$$\left(\begin{array}{c|c} A_{TL} & A_{TR} \\ \hline A_{BL} & A_{BR} \end{array} \right) \leftarrow \left(\begin{array}{c|c|c} A_{00} & a_{01} & A_{02} \\ \hline a_{10}^T & \alpha_{11} & a_{12}^T \\ \hline A_{20} & a_{21} & A_{22} \end{array} \right),$$

$$\left(\begin{array}{c} x_T \\ \hline x_B \end{array} \right) \leftarrow \left(\begin{array}{c} \frac{x_0}{\chi_1} \\ \hline x_2 \end{array} \right), \quad \left(\begin{array}{c} y_T \\ \hline y_B \end{array} \right) \leftarrow \left(\begin{array}{c} \frac{y_0}{\psi_1} \\ \hline y_2 \end{array} \right)$$

endwhile

Answer Video

SampleExam1.pdf

75% Tools Sign Comment

```

y(i) = A(j,i) * x(j) + y(i);
end
for i = j+1:n
    y(i) = A(i,j) * x(j) + y(i);
end
end

y_out = y;

return
end

```

(If you have a hard time interpreting this algorithm, you may want to consider the algorithm typeset with FLAME notation at the end of this exam.)

Mark which operation this implements (check all correct answers):

- ☐ $y := Lx + y$, where L is a lower triangular matrix, stored only in the lower triangular part of array A .
- ☐ $y := Ux + y$, where U is an upper triangular matrix, stored only in the lower triangular part of array A .
- ☐ $y := Ax + y$, where A is symmetric, stored only in the lower triangular part of array A .
- ☐ $y := Ax + y$, where A is symmetric, stored only in the upper triangular part of array A .
- ☒ The equivalent of $y = (\text{tril}(A) + \text{tril}(A, -1)') * x + y$ in MATLAB's M-script.
- ☐ The equivalent of $y = (\text{triu}(A) + \text{triu}(A, 1)') * x + y$ in MATLAB's M-script.

h1Question6.pptx

Search in Presentation

Animations Slide Show Review

Paragraph Insert Format

Arrange Quick Styles Play

Slide 1 of 15 100%

3:55 / 4:02

► **2.0x**



Video

 [Download video file](#)

Transcripts

 [Download SubRip \(.srt\) file](#)

 [Download Text \(.txt\) file](#)

Discussion

Topic: Exam 1 / E1.2.6

Hide Discussion

 Calculator

Show all posts

by recent activity

Conventional gotcha! Why is n assigned the row size of A i.e., $n = \text{size}(A, 1)$?
On first blush From the get go, the algorithm seems to obfuscate the fact that we're dealing with a symmetric matrix (or submatrix in a fat m...

2

< Previous

Next >

© All Rights Reserved



edX

- About
- Affiliates
- edX for Business
- Open edX
- Careers
- News

Legal

- Terms of Service & Honor Code
- Privacy Policy
- Accessibility Policy
- Trademark Policy
- Sitemap
- Cookie Policy
- Your Privacy Choices

Connect

- Idea Hub
- Contact Us
- Help Center
- Security
- Media Kit



© 2023 edX LLC. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)

Calculator