sign up log in tour help

Dismiss

Announcing Stack Overflow Documentation

We started with Q&A. Technical documentation is next, and we need your help.

Whether you're a beginner or an experienced developer, you can contribute.

Sign up and start helping \rightarrow

Learn more about Documentation →

Count number of non-NaN entries in each column of Spark dataframe with Pyspark



I have a very large dataset that is loaded in Hive. It consists of about 1.9 million rows and 1450 columns. I need to determine the "coverage" of each of the columns, meaning, the fraction of rows that have non-NaN values for each column.

Here is my code:

```
.map(lambda x: (x, float(df.select(x).dropna().count()) / float(nrows_tot) *
100.))
```

Trying this out in the pyspark shell, if I then do covgs.take(10), it returns a rather large error stack. It says that there's a problem in save in the file /usr/lib64/python2.6/pickle.py . This is the final part of the error:

```
py4j.protocol.Py4JError: An error occurred while calling o37.__getnewargs__. Trace:
py4j.Py4JException: Method __getnewargs__([]) does not exist
    at py4j.reflection.ReflectionEngine.getMethod(ReflectionEngine.java:333)
    at py4j.reflection.ReflectionEngine.getMethod(ReflectionEngine.java:342)
    at py4j.Gateway.invoke(Gateway.java:252)
    at py4j.commands.AbstractCommand.invokeMethod(AbstractCommand.java:133)
    at py4j.commands.CallCommand.execute(CallCommand.java:79)
    at py4j.GatewayConnection.run(GatewayConnection.java:207)
    at java.lang.Thread.run(Thread.java:745)
```

If there is a better way to accomplish this than the way I'm trying, I'm open to suggestions. I can't use pandas, though, as it's not currently available on the cluster I work on and I don't have rights to install it.

```
python apache-spark apache-spark-sql pyspark
```

edited Nov 24 '15 at 23:31



zero323

69.1k 16 82 148

asked Nov 24 '15 at 18:03



1 Answer

Let's start with a dummy data:

```
from pyspark.sql import Row

row = Row("x", "y", "z")
df = sc.parallelize([
    row(0, 1, 2), row(None, 3, 4), row(None, None, 5)]).toDF()

## +---+--+
## | x| y| z|
## +---+---+
## | 0| 1| 2|
## | null| 3| 4|
```

```
## |null|null| 5|
## +---+
```

All you need is a simple aggregation:

```
from pyspark.sql.functions import col, count, sum
def count not null(c):
   """Use conversion between boolean and integer
   - False -> 0
   - True -> 1
   return sum(col(c).isNotNull().cast("integer")).alias(c)
exprs = [count not null(c) for c in df.columns]
df.agg(*exprs).show()
## +---+
## | x| y| z|
## +---+
## | 1| 2| 3|
## +---+
```

You can also leverage SQL NULL semantics to achieve the same result without creating a custom function:

```
df.agg(*[
                      # vertical (column-wise) operations in SQL ignore NULLs
    count(c).alias(c)
    for c in df.columns
]).show()
## +---+
## | x| y| z|
## +---+
## | 1| 2| 3|
## +---+
If you prefer fractions:
```

```
exprs = [(count not null(c) / count("*")).alias(c) for c in df.columns]
df.agg(*exprs).show()
## +----+
            хl
## +----+
```

```
## |0.333333333333333|0.66666666666666666|1.0|
## +-----
```

edited Jul 7 at 14:50



eliasah

9,173 3 21 48

answered Nov 24 '15 at 18:38



zero323

69.1k 16 82 148