

Pandoc a universal document converter

Demos

Try pandoc online

You can try pandoc online [here](http://johnmacfarlane.net/pandoc/try) (<http://johnmacfarlane.net/pandoc/try>).

Examples

To see the output created by each of the commands below, click on the name of the output file:

1. HTML fragment:

```
pandoc MANUAL.txt (demo/MANUAL.txt) -o example1.html (demo/example1.html)
```

2. Standalone HTML file:

```
pandoc -s MANUAL.txt (demo/MANUAL.txt) -o example2.html (demo/example2.html)
```

3. HTML with smart quotes, table of contents, CSS, and custom footer:

```
pandoc -s -S --toc -c pandoc.css (demo/pandoc.css) -A footer.html (demo/footer.html) MANUAL.txt (demo/MANUAL.txt) -o example3.html (demo/example3.html)
```

4. LaTeX:

```
pandoc -s MANUAL.txt (demo/MANUAL.txt) -o example4.tex (demo/example4.tex)
```

5. From LaTeX to markdown:

```
pandoc -s example4.tex (demo/example4.tex) -o example5.text (demo/example5.text)
```

6. reStructuredText:

```
pandoc -s -t rst --toc MANUAL.txt (demo/MANUAL.txt) -o example6.text (demo/example6.text)
```

7. Rich text format (RTF):

```
pandoc -s MANUAL.txt (demo/MANUAL.txt) -o example7.rtf (demo/example7.rtf)
```

8. Beamer slide show:

```
pandoc -t beamer SLIDES (demo/SLIDES) -o example8.pdf (demo/example8.pdf)
```

9. DocBook XML:

```
pandoc -s -S -t docbook MANUAL.txt (demo/MANUAL.txt) -o example9.db (demo/example9.db)
```

10. Man page:

```
pandoc -s -t man pandoc.1.md (demo/pandoc.1.md) -o example10.1 (demo/example10.1)
```

11. ConTeXt:

```
pandoc -s -t context MANUAL.txt (demo/MANUAL.txt) -o example11.tex (demo/example11.tex)
```

12. Converting a web page to markdown:

```
pandoc -s -r html http://www.gnu.org/software/make/ (http://www.gnu.org/software/make/) -o example12.text (demo/example12.text)
```

13. From markdown to PDF:

```
pandoc MANUAL.txt (demo/MANUAL.txt) --latex-engine=xelatex -o example13.pdf (demo/example13.pdf)
```

14. PDF with numbered sections and a custom LaTeX header:

```
pandoc -N --template=mytemplate.tex (demo/mytemplate.tex) --variable mainfont="Palatino" --variable sansfont="Helvetica" --variable monofont="Menlo" --variable fontsize=12pt --variable version=1.17.2 MANUAL.txt (demo/MANUAL.txt) --latex-engine=xelatex --toc -o example14.pdf (demo/example14.pdf)
```

15. A wiki program using Happstack (<http://happstack.com>) and pandoc: gitit (<http://gitit.net>)

16. HTML slide shows:

```
pandoc -s --mathml -i -t dzslides SLIDES (demo/SLIDES) -o example16a.html (demo/example16a.html)
```

```
pandoc -s --webtex -i -t slidy SLIDES (demo/SLIDES) -o example16b.html (demo/example16b.html)
```

```
pandoc -s --mathjax -i -t revealjs SLIDES (demo/SLIDES) -o example16d.html (demo/example16d.html)
```

17. TeX math in HTML:

```
pandoc math.text (demo/math.text) -s -o mathDefault.html (demo/mathDefault.html)
```

```
pandoc math.text (demo/math.text) -s --mathml -o mathMathML.html (demo/mathMathML.html)
```

```
pandoc math.text (demo/math.text) -s --webtex -o mathWebTeX.html (demo/mathWebTeX.html)
```

```
pandoc math.text (demo/math.text) -s --mathjax -o mathMathJax.html (demo/mathMathJax.html)
```

```
pandoc math.text (demo/math.text) -s --latexmathml -o mathLaTeXMathML.html (demo/mathLaTeXMathML.html)
```

18. Syntax highlighting of delimited code blocks:

```
pandoc code.text (demo/code.text) -s --highlight-style pygments -o example18a.html (demo/example18a.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style kate -o example18b.html (demo/example18b.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style monochrome -o example18c.html (demo/example18c.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style espresso -o example18d.html (demo/example18d.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style haddock -o example18e.html (demo/example18e.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style tango -o example18f.html (demo/example18f.html)
```

```
pandoc code.text (demo/code.text) -s --highlight-style zenburn -o example18g.html (demo/example18g.html)
```

19. GNU Texinfo, converted to info, HTML, and PDF formats:

```
pandoc MANUAL.txt (demo/MANUAL.txt) -s -o example19.texi (demo/example19.texi)
```

```
makeinfo --no-validate --force example19.texi (demo/example19.texi) -o example19.info (demo/example19.info)
```

```
makeinfo --no-validate --force example19.texi (demo/example19.texi) --html -o example19 (demo/example19)
```

```
texi2pdf example19.texi (demo/example19.texi) # produces example19.pdf (demo/example19.pdf)
```

20. OpenDocument XML:

```
pandoc MANUAL.txt (demo/MANUAL.txt) -s -t opendocument -o example20.xml (demo/example20.xml)
```

21. ODT (OpenDocument Text, readable by OpenOffice):

```
pandoc MANUAL.txt (demo/MANUAL.txt) -o example21.odt (demo/example21.odt)
```

22. MediaWiki markup:

```
pandoc -s -S -t mediawiki --toc MANUAL.txt (demo/MANUAL.txt) -o example22.wiki (demo/example22.wiki)
```

23. EPUB ebook:

```
pandoc -S MANUAL.txt (demo/MANUAL.txt) -o MANUAL.epub (demo/MANUAL.epub)
```

24. Markdown citations:

```
pandoc -s -S --bibliography biblio.bib (demo/biblio.bib) --filter pandoc-citeproc CITATIONS (demo/CITATIONS) -o example24a.html (demo/example24a.html)
```

```
pandoc -s -S --bibliography biblio.json (demo/biblio.json) --filter pandoc-citeproc --cs1 chicago-fullnote-bibliography.csl (demo/chicago-fullnote-bibliography.csl) CITATIONS (demo/CITATIONS) -o example24b.html (demo/example24b.html)
```

```
pandoc -s -S --bibliography biblio.yaml (demo/biblio.yaml) --filter pandoc-citeproc --cs1 ieee.csl (demo/ieee.csl) CITATIONS (demo/CITATIONS) -t man -o example24c.1 (demo/example24c.1)
```

25. Textile writer:

```
pandoc -s -S MANUAL.txt (demo/MANUAL.txt) -t textile -o example25.textile (demo/example25.textile)
```

26. Textile reader:

```
pandoc -s -S example25.textile (demo/example25.textile) -f textile -t html -o example26.html (demo/example26.html)
```

27. Org-mode:

```
pandoc -s -S MANUAL.txt (demo/MANUAL.txt) -o example27.org (demo/example27.org)
```

28. AsciiDoc:

```
pandoc -s -S MANUAL.txt (demo/MANUAL.txt) -t asciidoc -o example28.txt (demo/example28.txt)
```

29. Word docx:

```
pandoc -s -S MANUAL.txt (demo/MANUAL.txt) -o example29.docx (demo/example29.docx)
```

30. LaTeX math to docx:

```
pandoc -s math.tex (demo/math.tex) -o example30.docx (demo/example30.docx)
```

31. DocBook to markdown:

```
pandoc -f docbook -t markdown -s howto.xml (demo/howto.xml) -o example31.txt (demo/example31.txt)
```

32. MediaWiki to html5:

```
pandoc -f mediawiki -t html5 -s haskell.wiki (demo/haskell.wiki) -o example32.html (demo/example32.html)
```

33. Custom writer:

```
pandoc -t sample.lua (demo/sample.lua) example33.text (demo/example33.text) -o example33.html (demo/example33.html)
```

34. Docx with a reference docx:

```
pandoc -S --reference-docx twocolumns.docx (demo/twocolumns.docx) -o UsersGuide.docx (demo/UsersGuide.docx) MANUAL.txt (demo/MANUAL.txt)
```

35. Docx to markdown, including math:

```
pandoc -s example30.docx (demo/example30.docx) -t markdown -o example35.md (demo/example35.md)
```

36. EPUB to plain text:

```
pandoc MANUAL.epub (demo/MANUAL.epub) -t plain -o example36.text (demo/example36.text)
```

