

1. Which of the following is the correct method to enable the response to process HTML code and display the output in the browser?
 - a. AllowHTML
 - b. SetHTML
 - c. SetContentType**
 - d. GetContentType
2. Identify the methods of ServletContextListener?
 - a. ContextInit, ContextService, Contextdestroyed.
 - b. ContextInitialized, Contextdestroyed**
 - c. ContextService, Contextdestroyed
 - d. ContextInitialized, ContextService, Contextdestroyed
3. Select the correct options from the following.
[Select 2 options]
 - a. The default value of isThreadSafe attribute of page directive is true.**
 - b. If isThreadSafe attribute of page directive is set to true, then JSP container dispatches request for the page sequentially.
 - c. When isThreadSafe attribute of page directive is set to true, a thread is created for each request for this page.**
 - d. Setting isThreadSafe attribute to true for JSP pages, can lead to poor performance.
4. What gets printed when the following is compiled?


```
<%int y= 0;%>
<%int z=0;%>
<%for(int i=0;x<3;i++){%>
<%z++;++y;z+=--z+y++; %>
<%}%>
<%if(z<y){%>
<%=z%>
<%}else{%>
<%=z-1%>
<%}%>
```

 - a. 0
 - b. 21
 - c. 3
 - d. -1

e. Infiniteloop

5. `<html>`
`<body>`
`</body>`
`<pid="idi">Paragraph</p>`
`</html>`
- a. Red,redandbluerespectively
 - b. Red,blackandbluerespectively**
 - c. Red,blackandblackrespectively
 - d. Red,blueandbluerespectively
6. IdentifywhichofthefollowingPseudoclassescanbeappliedtohyperlinks.
- a. Cue
 - b. Clicked
 - c. Hover**
 - d. Visited**
 - e. Focus**
7. WhichofthefollowingstatementsAngularcomponentconsistsof?
- a. Acomponentclassthathandlesdataandfunctionality.**
 - b. AnHTMLtemplatethatdeterminestheUI.**
 - c. Component-specificstylesthatdefinethelookandfeel.**
 - d. AngularRoutingmodule
8. WhichofthefollowingarethefeaturesofHttpClientservice?
- a. Theabilitytorequesttypedresponseobjects.**
 - b. Streamlinederrorhandling.**
 - c. Requestandresponseinterception.**
 - d. Non-Testability
9. Whatwillbetheoutputofthefollowingcodesnippet?
- ```
<pagelanguage="java"
<html>
<head></head>
<body>
<java.util.Datenow=newjava.util.Date();
$><H1>
<=now.getHours():<=now.getMinutes():<=now.getSeconds()
%></l></body></html>>
```

- a. Itwilldisplaythedataasmm:dd:yy
- b. Itwilldisplaythedataandtime
- c. Itwilldisplaytimeashh/mm/ss
- d. Itwilldisplaythecurrenttimeashh:mm:ss**

10. In the below code snippet, what is the correct statement to be placed at line number 6 to display the course name?

Line1: import(Component) from '@angular/core': Line

2: Component ({

Line3:

Line4: template:

Line5: <h1>>

Line6:

Line7: </h1>

Line 8:

Line9:

Line10: export class AppComponent

Line 11: {

Line12: courseName: string = "Angular":

Line13: selector: 'my-app',

- a. {{courseName}}**
- b. this.courseName
- c. courseName
- d. AppComponent.courseName

11. Given the below code

```
@Component("user")
```

```
Public class User {
```

```
@value("100")
```

```
Private int id; //
```

```
@value("John")
```

```
@value("#{John'.toUpperCase()}")
```

```
Private String firstName;
```

```
@Value("Doe")
```

```
Private String lastName;
```

```
@Value("#{user.firstName.concat('').concat(user.lastName)}") private
string fullName;
```

```

@Value("#{hobbies['1']}")
Private String hobby;
@Value("#{400>300 || 150<100}")
Private Boolean flag; // Getter Setter methods}
Config.xml: <util:list class="java.util.ArrayList" id="hobbies">
<value>Singing</value>
<value>Dancing</value>
<value>Reading</value>
</util:list>

```

What will be the output of these fields when printed?

OPTIONS:

- a. id=100, fullName=JOHN DOE, hobby=Dancing, flag=false
- b. id=100, fullName=JOHN DOE, hobby=Singing, flag=true
- c. **id=100, fullName=JOHN DOE, hobby=Dancing, flag=true**
- d. id=100, fullName=JOHN DOE, hobby=Singing, flag=false

12. Refer the following code for a Java class?

```

Package com.mphasis;
Import javax.persistence.Entity;
Import javax.persistence.GeneratedValue;
Import javax.persistence.GenerationType;
Import javax.persistence.Id; // code goes here
Public class Customer { // code goes here
Private String firstName;
Private String lastName; // setters and getters}

```

Which of the following lines of code when added to Lines 6, 8, and 9 will enable mapping of the Java class with the database by JPA during generation of records? OPTIONS:

- a. @Table  
@Id  
@GeneratedValue(strategy=GenerationType.AUTO)
- b. **@Entity**  
**@Id**  
**@GeneratedValue(strategy=GenerationType.AUTO)**
- c. @Table  
@Identity

@GeneratedValue(strategy=GenerationType.AUTO)

d. @Table

@Id

@AutoGenerated(strategy=GenerationType.AUTO)

13. Given the below code (Assume necessary imports are included).

@RestController

@RequestMapping("/employee")

Public class EmployeeController {

@PostMapping("/create")

Public EmployeeDTO addEmployee(@RequestBody EmployeeDTO  
employeeDTO) { // code to add employee and return the same back }

Chose the correct statement. OPTIONS:

a. @PostMapping is not supported when the controller class is annotated with @RequestMapping.

b. @PostMapping is not allowed to hold path matching info ("/create")

c. CompilationError

**d. This controller is perfectly fine and will work as expected.**

14. which access modifier is used when you do not inherit the class by other and which keyword is used to create interface---

a. Private, class

**b. final, interface**

c. protected, abstract

d. public, enum

15. Which of the following decorators specifies that Angular can use this class in the DI system?

**a. @Injectable()**

b. @Component()

c. @Service()

d. @Inject()

16. Given the below code:

Class UseStatic {

static int a = 3;

static int b;

static void meth (int x) {

System.out.println("x=" + x);

```

System.out.println("a="+a);
System.out.println("b="+b);
}
Static{
b=a*4;
}
publicstaticvoidmain(Stringargs[]){ meth
(42);
}
}

```

Whatwillbetheoutputwhentheprecedingprogramiscompiledand executed?

a. **Theprogramwilldisplaytheoutputas:**

**static block initialized.**

**x=42**

**a=3**

**b=12**

b. Theprogramwillgeneratecompilationerror

c. Theprogramwilldisplaytheoutputas:

Static block initialized.

x=42

a=12

b=3

d. Theprogramwillthrowaruntimeexception.

17. AssumethattheEmployeeclassismappedwithanEMPLOYEEtable.

The entity class Employee is configured with the Identifier value. Assume thattheEMPLOYEEtableisempty,whatwillbetherow(empid,empname) inserted into the EMPLOYEE table when the following code is executed?

```

Employeeemp=newEmployee();
emp.setEmpName("Alex");
session.getTransaction().begin();
session.persist(emp);
session.getTransaction().commit();

```

Options:

a. `HibernateException` is thrown as the increment generator is not able to fetch maximum value from EMPID

**b. 1,Alex**

c. 0,Alex

d. NULL,Alex

18. Consider the following JSP page source: S

```
<%@page import="java.io.*"%>
```

```
<html>
```

```
<body>
```

```
<%
```

```
PrintWriter out=response.getWriter();
```

```
out.write("X");
```

```
%>
```

```
<%out.write("Y");%>
```

```
</body>
```

```
</html>
```

Which of the following are true statements about the above code?

a. "X" will be written to the response, followed by "Y".

b. Only "Y" will be written to the response.

**c. The page has a compilation error because of a directives syntax error.**

**d. In JSP technology it is a bad idea to get hold of the `PrintWriter` directly from the response.**

e. The page has a compilation error for other reasons.

19. Consider the following code:

```
<html>
```

```
<body>
```

```
<jsp:useBean id="address" class="AddressBean" scope="session" />
```

```
state=<jsp:getPropertyname="address" property="state"/></body>
```

```
</html>
```

Which of the following options are equivalent to the third line?

a. `<%state=address.getState();%>`

**b. `<%out.write("state=");out.print(address.getState());%>`**

c. `<%out.write("state=");out.print(address.getState());%>`

**d. `<%out.print("state="+address.getState());%>`**

e. `state=<%=address.getState()%>`

20. What will be the output for the following code?

Page.html;

<p>BuildingWebApplications</p>

Page2.html;

<p>BuildingEnterpriseApplications</p>

TestServlet: protected void doGet(HttpServletRequest request,  
HttpServletResponse response) throws ServletException, IOException

RequestDispatcher rd = request.getRequestDispatcher("Page.html");

rd.Include(request, response);

rd = request.getRequestDispatcher("Page2.html");

rd.Include(request, response); }

a. **BuildingWebApplications**

**BuildingEnterpriseApplications**

b. BuildingWebApplications

c. BuildingEnterpriseApplications

d. ServletException

21. Identify the different values which are scope attributes of a

<jsp:useBean> action can set

a. **page,request,session and application**

b. page and request only

c. page,request,response and application

d. page,response,session and application

22. Which of the following is true about AOP Advice?

a. A point during the execution of a program.

b. An aspect and a Pointcut.

c. **An action taken by an aspect at a particular Joinpoint.**

d. A predicate that matches Joinpoint.

23. To enable all actuator endpoints for monitoring, which of the following property should be enabled. Options

a. **management.endpoints.web.exposure.include=\***

b. management.endpoints.web.exposure.all=\*

c. management.endpoints.web.exposure.enable=\*

d. management.endpoints.enable.exposure=\*

24. Which command is used to create a new branch called "new-email"?
- a. gitbranchnew "new-email"
  - b. gitaddbranch "new-email"
  - c. **gitbranchnew-email**
  - d. gitcreatebranch "new-email"
25. Which statements regarding the PreparedStatement are true?
- a. **The performance of the application will be faster if you use PreparedStatement interface because query is compiled only once.**
  - b. The performance of the application will degrade if you use PreparedStatement interface.
  - c. **PreparedStatement object is preferred in case we fire repetitive kind of queries.**
  - d. PreparedStatement interface is a super interface of Statement.
26. Which of the following activated Route is used to access?  
(select 2 options) Options:
- a. **Route parameters**
  - b. Params
  - c. **Query parameters**
  - d. Route
27. Explicit dependency injection in constructors specified by using \_\_\_\_ decorator? options:
- a. **@Inject**
  - b. @Injectable
  - c. @Explicit
  - d. @Hostbinding
  - e. @Host