

Phase 4

Which of the following options are correct statements to apply the CSS class pick

☐ `<p [ngClass]='pink'> background is pink</p>`

`<p [ngClass]='{pink:true}'> background is pink</p>`

`<p [ngClass]='["pink"]'> background is pink</p>`

`<p ngClass ={pink:true}>background is pink</p>`

Please refer below

What will be the output of the below code?

let product Details: [string, number]: productDetails ["Samsung Galaxy J7", 16,8, Samsung Galaxy J5,321 for (let i=0;i< productDetails.length;i++ console.log(productDetails(11):

Samsung Galaxy J7 16 Samsung Galaxy J5 32

Samsung Galaxy J7 16 8 Samsung Galaxy J5 32

Samsung Galaxy J7 Samsung Galaxy J5 16 8

Compilation Error

What will be the output of the below code?

var line "Fundamentals of Javascript";

console.log("Slice (1, 12) ", line, slice (1, 12))) console.log("Slice (-20,-16) ",line.slice(-20,-16)); console.log("Slice (15)", line, alice (15))

option c

C)

Slice (2,5) : nda

Slice(-20,-16): enta

Slice (18) : vascript

that will be the color of Line1, Line, Line), and Lined when the above web page is rendered on the home

Line1 red, Line2 blue, Line3 cyan, Line4: green

Line1 red, Line2 blue, Line3 yellow, Line4: green

Line1 red, Line2 green, Line3 cyan, Line4: green

Line1 red, Line2 green, Line3: yellow, Line4: green

In order to create a custom impure pipe, you use _____ attribute in @Pipe decorator

pure true

pure false

impure true

impure false

In the below code snippet, what is the correct statement to be placed at line number 6 to display the coursehlame?

Line 1: import (Component) from '@angular/core':

Line 2: Component ({

Line 3:

Line 4: template:

Line 5: <h1>>

Line 6:

Line 7:</h1>

Line 8:

Line 91

Line 10: export class AppComponent

Line 11:1

Line 121 coursellane: string "Angular":

Line 13:) selector: 'my-app',

{{ courseName }}

this.courseName

courseName

AppComponent.courseName

Mr.Zeal has designed the following web page. Choose the correct option for Z-index

Catal

Chead>

catyle>

Lng

position: absolute;

left: Ops:

1top: Ops:

</style> </head>

Chody>

Cing srow image.jpg" width="100" height="140">

</body>

<p>E-index refers to the stacking order of the elementsx/p>

</html>

p (z-index:-1:3

p (z-index:1,)

p (position:absolute; z-index: 1;)

p(position absolute, z-index:-1.)

Which of the following are the valid HTML5 input types?

colors

time

datetime

number

Which of the following option describes the setTimeout() function in JavaScript?

It halts all code execution for the given amount of time

It delays the execution of a specified function by the given amount of time

It halts all code execution after the given amount of time

It freezes the browser for the given amount of time

Rank the elements of the CSS box model from most inner to outer layer

Padding Border Content Margin

Margin Border Padding Content

Content Padding Border Margin

Content Border Padding Margin

Mr Ra working on a web development project. According to the styling guidelines provided by the organization of spacing between paragraphs that appear immediately after the heading Which of the below requirement?

`margin-bottom: 20px`

`1 (margin-bottom: 40px)`

`h1 (margin: 0 0 40px 0)`

`margin-bottom: 0 20px 0 3`

Consider the code snippet given below and find out which line will result in an error.

```
class Person { constructor (name, age) { this.pname = name; this.page = age;
display() {
console.log("name:" + this.pname); console.log("age:" + this.page);
set pname (namePerson) { this.pname = namePerson; } get pname() { return this.pname; }
1st per new Person();
par.pname = "Rexha";
console.log(per.pname);
```

```
console.log(per1.pname);  
let pari new Person("Alex", 10);  
Type here to search
```

Line no 8 gives error as no arguments have been passed to the constructor.

Line no. 10 gives error as this is not the way to fetch the instand variable of a class.

Line 10 displays undefined and line 12 displays Alex

Line 10 displays Rexha and line 12 displays Alex

Which of the following options would correctly set the viewport to make your website look good on all devices

<meta name="port" content="width=device-width, initial-scale=0"/>

<meta name="viewport" content="width=device-width initial-scale=1" />

<meta name="port" content="width=device-width inity scale=1"/>

<meta name="viewport" content="width=devicewidth, initial-scale=1" />

Ryan is trying to create an email account. During the registration process, as soon as he focuses on the name held and enters the character to fill his name, he gets a message This name is taken

We understand that the website is using JavaScript Event-handling to respond to the data entered by Ryan Which event do you think is triggering the JavaScript code for the account to check the value entered by the user?

Onfocus

onblur

Onkeypress

Onkeyup

Which of the following are the valid syntax of using ng Class directive to apply CSS classes A,B in Angular?

`<h1 [ngClass]="A B"Hello World <h1>`

`<h1 [ngClass]="['A','B']" >Hello World <h1>`

`<h1 [ngClass]="('A':true,'B' true)" >Hello World <h1>`

`<h1 {ngClass}="A,B" >Hello World <h1>`

-----means that if we declare a variable (declared but not initialized) at the end of a function, the runtime will hoist it to the top and we will not have any error if we would have used that variable before being declared

Variable hoisting

Overloading

Inheritance

Static Typing

What will be the output of the below code?

`function sayli (person: string) { return "Hello, + person:`

`var customer :string[] document.body.innerHTML`

`["Tom", "Harry", "Jack"];`

`sayli (customer);`

Hello Tom

Hello

Hello Tom Harry Jack

Compilation Error

What is the correct statement to bind required and maxlength validators to name field in a reactive T

`name ['. Validators required, Validators maxlength(10)]`

name: [' Validators required, Validators maxlength(10)']

name: [Validators required, Validators.maxlength(10)]

name: Validators required, Validators.maxlength(10)

Predict the output of the below code snippet

```
class Demo {  
  n:number 9;  
  check () {  
    if(this.n==9) {  
      let n: number= 10; console.log(this.n);  
    }  
  }  
  let demoObject=new Demo (): demoobject.check();
```

9

10

11

Compilation Error

Select valid states of Promise Object.

pending

fulfilled

rejected

completed

Rahul has completed the development of a website. Rahul needs to add "note" keyword before each paragraph in one of his web pages and Rahul has forgotten to end headings with full-stop How can achieve these requirements?

Using before and after pseudo class

Using first-letter and after pseudo class

Using before for first requirement and "full-stop" can be added manually in webpage

Rahul cannot achieve this requirement.

`</body>`

`<p id="idi">Paragraph</p>`

`</html>`

Red, red and blue respectively

Red, black and blue respectively

Red, black and black respectively

Red, blue and blue respectively

_____ option of Angular CLI indicates to use inline templates for the project

-inline

-inline-templates

-inline-temp

-inline-template

Rest parameters are used when

datatypes of parameters are not known

number of parameters are not known

function needs to be called recursively

○ function needs to be called asynchronously

The purpose and function of the ADDRESS and CITE tags has changed since HTML 4.01 and are now syndication purposes. Identify the true statements that describes how the function of each tag has ch HTMLS

The Address tag now defines the contact information of the author or owner of a document allowing you to have one sulle par web page

The Cite tag now defines a citation or article footer

The Cite tag now defines the title of a work such as a song, book, or movie

The Address tag now defines the contact information of the author or owner of a document or an article allowing you to multiple authors for a single page

Which of the following are the valid attribute-directives in Angular?

ngStyle

ngClass

ngSwitch

ngif

Which of the following are the valid statements with respect to production builds?

Uses AOT compilation

Files are tree shaken

Source maps are generated

Cas are extracted to js files

Uses JIT compilation

Which of the following are the valid methods of an Array object?

reverse()

sort()

search()

filter

Which of these operations are permitted if you apply Object.freeze() on myObject?

Adding a property to a nested object in myObject

Adding a new top-level property to myObject

Modifying a top-level property of myObject

Modifying a property of a nested object in myObject

What will be the output of the below code?

```
let originalString="Digital!";
```

```
let updatedString1 originalString.substr(2,3); let updatedString2 originalString.substring  
(2,3). document.write(updatedStringie'br>'); document.write(updatedstring2)
```

git g

git git

ggit

gg

Which of the following is a valid command to create a component in Angular?

ng generate component <component-name>

ng create component <component-name>

Ong create <component-rame>

Ong generate <component-name>

Identify which of the following Pseudo classes can be applied to hyperlinks.

Cue

Clicked

Hover

Visited

Focus

You are creating a web page that requires some text to span across the width of the screen and other preos be emphasized within those text blocks. Which statements below correctly explain the rules about block and elements that will help you build your web page?

You should use block-level elements when you want text or content to go across the width of the browser window or to s on a new line.

You should use block-level elements when you want text or content to align horizontally with an image on a web page

You should use inline-level elements when you want to align or format text without having it start on another line or spen the width of a browser window.

You should use inline-level elements when using the <p> tag.

Which of the following is true about border property?

border short hand property will not work if border width is not specified.

border will not appear if border style is not specified.

border will not appear if border color is not specified.

border will not appear if border height is not specified.

This <article> </article> and <section></section> tags are new to HTML5, Identify the true statements that de ench is used in HTML5.

Article elements or tags in HTML5 can be used as CSS styles that group images on a web page that are separated by chunks of content

Article elements or tags in HTML5 can be used as RRS syndication and applied to dynamic content such as forum posts blog posts, comments, and news stories.

The Section tag in HTML5 defines and isolates tables and images that have text wrapped around them,

The Section tag in HTML5 defines and isolates sections or logical chunks of content in a document such as an Introduction, header, or footer.

Which of the following statements Angular component consists of?

A component class that handles data and functionality.

An HTML template that determines the UI.

Component-specific styles that define the look and feel.

Angular Routing module

Which of the following members can be included in the class?

constructor

properties

methods

modules

How do you add a background color for all <h1> elements?

all.h1 {background-color:#FFFFFF}

h1.all {background-color:#FFFFFF}

h1 {background-color:#FFFFFF}

h {background-color:#ffffff}

Which of the following are the valid methods of XMLHttpRequest object?

send()

open()

cancel()

abort()

When you hover your mouse over the host element (tag), the color of the tag should change. In addition, when the mouse is moved away, the color of the tag should change to its default color. To do this, you need to handle events raised on the host element in the directive class. Which decorator is used to implement this functionality?

@Host

HostBinding

HostListener

Attribute

Which of the following attributes controls the valid numeric boundaries of a range control?

min

minbound

count

max

Which are the built-in browser validation features?

max

minlength

conversion

currency

required

Which of the following will map the name of an input parameter "studentinfo" to a field named "students"

@Input('studentinfo') students

@Input() studentinfo: students

Input() students: studentinfo

Input('students') studentinfo

What will be the output for the following code?

```
// eas rest parameter
```

```
function fun(...input) {
```

```
  let sum 0;
```

```
  for(let i of input)
```

```
    return sum;
```

```
  console.log (fun (1,2)); console.log(" ", "+fun (1,2,3)); console.log(" ", "+fun (1,2,3,4,5));
```

3,6,15

3. undefined

3,error

3,6,error

What will be the output for the following code?

```
let employee = {empId: '11001',
```

```
  empName: (
```

firstName: 'John',

middleName: 'Thomson',

lastName: 'Mark'

empStatus: 'Active'

let (firstName: middleName, lastName) = employee.emplame; console.log (middleName);

John

Thomson

Mark

Compilation Error

Which of the following are the valid methods of an Array object?

reverse()

sort()

search()

filter()

Which of the following are the valid methods of XMLHttpRequest object?

send()

open()

cancel()

abort()

What is a proper syntax to construct a module?

Ovar variable_name = angular.module("app_name", []);

Ovar variable_name = angular.module("app_name");

Ovar variable_name = angular.module();

Ovar variable_name = new module();

The tag defines an alternate content to be displayed to users that have disabled scripts in the browser or have a browser that doesn't support script.

`<noscript>`

`<script>`

`<notscript>`

`<js>`

Which of the following statements Angular component consists of?

A component class that handles data and functionality.

AngularRouting module

An HTML template that determines the UI.

Component-specific styles that define

Typescript compiler configuration is stored in ___ file

package.json

Otsc.json

tsconfig.json

Olint.json

Select the new HTML5 layout containers,

`<aside>`

`<boxtitle>`

`<header>`

`<footnote>`

1:yellow, 2: yellow, 3: yellow, 4: yellow

1:green, 2 yellow, 3:green, 4: yellow

1:yellow, 2:green, 3:green, 4: yellow

1 yellow, 2: yellow, 3: green, 4: yellow

Kah wants to apply margin property to an element with top-margin value of 30px, bottom-margin value of 20px and of a margin value of 25px. Which among the following will help her in achieving the requirement?

margin: 25px 30px 20px;

margin: 20px 30px 25px;

Omargin: 20px 25px 30px

Omargin: 30px 25px 20px.

You are creating a web page that requires some text to span across the width of the screen and other pieces of text to be emphasized within those text blocks. Which statements below correctly explain the rules about block and inline elements that will help you build your web page?

You should use block-level elements when you want text or content to go across the width of the browser or to start on a new line

You should use block-level elements when you want text or content to align horizontally with an image on a page

You should use inline-level elements when you want to align or format text without having it start on another or span the width of a browser window.

You should use inline-level elements when using the <p> tag

What will be the output for the following code?

```
let prices = new Array(67,23,90,67,12,73); prices.push(110); prices.unshift(43); prices.pop(); prices.unshift(89); prices.shift(); console.log(prices);
```

[43, 67, 23, 90, 67, 12, 73]

[67, 23, 90, 67, 12, 89]

[67, 23, 90, 67, 12, 73, 89]

[110, 67, 23, 90, 67, 12, 89]

Which of the following are the features of HttpClient service?

The ability to request typed response objects.

Streamlined error handling.

Request and response interception.

Non Testability

What will be the output of the below code?

```
import PipeTransform from 'Bangalore/core'
```

```
class LengthPipe implements PipeTransform {  
  transform(value: string): string {  
    return value.length;  
  }  
}
```

Length method should be an no args method

The Length Pipe class has not implemented the transform() method of Pipe Transform Interface

Length Pipe class should be using @Component decorator to make it working

The length method should return an numeric value

Which of the following are the valid properties of Promise Object?

state

result

readyState

response