MyUncleVision: An Interpretable Lattice-Based Framework for Unsupervised Anomaly Discovery in Whole-Slide Histopathology Images

Leon Sandler

Independent Researcher, Northbrook, Illinois, USA

ORCID: https://orcid.org/0009-0007-4584-808X

Corresponding author: sandler.leon@gmail.com

Abstract

Unsupervised discovery in whole-slide images must separate unusual tissue organization from artifacts and routine histology and give experts places to look. We present MyUncleVision, an open pipeline that places patch embeddings on a tissue lattice, judges appearance rarity at several prevalence scales, smooths the score over the lattice to favour spatially coherent regions, ranks and explains regions across slides. Its order and entropy definitions generalize those of the MyUncle maintenance-lattice framework to d dimensions and equal them at d = 2 (tests against the unmodified core). We compare ablations and baselines (Isolation Forest, Local Outlier Factor, nearest-neighbour, Mahalanobis) on synthetic slides with planted anomalies: a development cohort used to choose settings, and a held-out cohort of 16 slides with three unseen anomaly types, about 0.8% prevalence and stain shifts, evaluated once with frozen settings. Lattice smoothing raised the spatial coherence of every scorer. On the held-out cohort the frozen score reached an average precision of 0.59 with DINOv2 (AUROC 0.99, the best of all methods) but 0.04 with handcrafted features, where smoothing diluted small anomalies; on the

development cohort a Mahalanobis baseline with the same smoothing scored higher (0.90 against 0.74 with DINOv2). The disorder and contact axes of the lattice helped with handcrafted features and hurt with DINOv2, so they are optional diagnostics and not part of the default score. It has not been applied to real tissue and no pathologist has reviewed any output; a kidney evaluation protocol is specified. Code and results are open.

Keywords: whole-slide imaging; unsupervised anomaly detection; histopathology; spatial smoothing; von Mises-Fisher entropy; open-source software

1. Introduction

Digital pathology produces gigapixel images of which most are examined at a small fraction of their area, and the models that analyse them are usually trained for a task defined in advance: a diagnosis, a grade, a segmentation [1,2]. A different question is what organization of tissue exists that nobody has defined yet. Astronomy faced the same question for large surveys and developed outlier-detection and active anomaly-detection methods [3,4]; in medical imaging, unsupervised anomaly detection has mostly meant detecting deviations from healthy appearance with generative models [5]. The Kidney Precision Medicine Project (KPMP) has produced a large public set of kidney whole-slide images next to molecular atlases [6], and a public challenge asks for previously unrecognized or under-characterized patterns in them.

A discovery method has to keep artifacts out, to avoid reporting routine histology as unusual, and to give an expert a place, a measure and an explanation. This paper describes MyUncleVision and, above all, tests what its lattice contributes. Contributions: (1) a generalization of the order and entropy quantities of the maintenance-lattice framework MyUncle [7] from two to d dimensions, verified against the unmodified core; (2) a score that judges appearance rarity at several prevalence scales and smooths it over the tissue lattice; (3) an

open, containerized pipeline from SVS files to ranked, mapped, explained candidates with an audit trail of every image used; (4) an evaluation with ablations, baselines, a held-out cohort with frozen settings and a robustness suite, whose results are mixed and are reported as such; (5) a protocol for the evaluation on kidney slides, which this paper does not report.

2. Method

2.1 Slides, patches and quality control

Slides are read with OpenSlide for SVS and other vendor formats [8] and as plain images otherwise. A tissue mask is made on a thumbnail (glass is bright and nearly colourless). The slide is cut into non-overlapping square patches of 224 px at 0.5 µm/px; the patch grid is the lattice, and a patch is kept when at least half of it is tissue. Quality control marks a patch as an artifact when it is out of focus (Laplacian variance below an absolute floor or below 15% of the slide's own median), contains pen ink (saturated blue and green hues), is dark debris or a fold, or is mostly glass. These thresholds are heuristics that must be tuned on the slides at hand; a patch that is only partly blurred keeps the variance of its sharp part and escapes the rule. Artifact patches are excluded from the lattice, the reference set and the ranks.

2.2 Embeddings and the sphere

Each patch is encoded by DINOv2 ViT-S/14 [9] (384-d class-token embedding; natural-image pretraining, no fine-tuning) or, offline, by a deterministic handcrafted encoder of stain, colour, gradient-orientation and texture statistics (64-d) built on colour deconvolution [10]. Embeddings are centred and reduced by a cohort PCA (16 components, scikit-learn [11]) and normalized to unit length, so every patch is a point u on a sphere S^{d-1}.

2.3 Order and entropy of the tissue lattice

MyUncle [7] describes a lattice of rotors whose order is eroded by a state-dependent flux and restored by repair. Its local disorder is one minus the length of the mean of the four neighbours' unit vectors, and its order-entropy bridge is the von Mises entropy of the angle at a given order. The same definitions hold for unit vectors in any dimension. With N_i the valid neighbours of site i and u_j the unit embedding of neighbour j,

$$R_i = \left| \frac{1}{|N_i|} \sum_{j \text{ in } N_i} u_j \right|, \qquad D_i = 1 - R_i \tag{1}$$

where D_i is MyUncle's local disorder. The concentration κ_i of the von Mises-Fisher distribution on S^{d-1} [12,13] that has mean resultant length R_i solves

$$A_d(\kappa) = \frac{I_{d/2}(\kappa)}{I_{d/2-1}(\kappa)} = R_i \tag{2}$$

and the entropy of that distribution and the information held in the local order are

$$S_{\text{vMF}}(\kappa, d) = -\left(\frac{d}{2} - 1\right)\ln\kappa + \frac{d}{2}\ln(2\pi) + \ln I_{d/2-1}(\kappa) - \kappa A_d(\kappa), \qquad H_\chi = S_{\text{unif}} - S_{\text{vMF}} \tag{3}$$

For $d = 2$ these are MyUncle's $U = A(\kappa) = I_1/I_0$, $S(\kappa)$ and H_χ. The tests compare them with the vendored, unmodified core (Fig. 1): the local disorder on a periodic lattice agrees to 10^{-12} and the entropy to 10^{-9}. With a neighbourhood of four patches the resultant length is a noisy estimate of the local order; this is a stated limitation.




Fig. 1. (a) The order-information bridge in d dimensions, per dimension: MyUncle's H_χ (d = 2, red) and the vMF generalization for d = 2, 16, 64 and 384. (b) Difference between the d = 2 vMF entropy and the vendored MyUncle Bridge.S.

2.4 The frozen novelty score and the diagnostic axes

Three rank-based axes are computed for every non-artifact patch (empirical percentile in the cohort, 0 to 1): appearance rarity, state-wise disorder and contact rarity. Appearance rarity p_{emb} is the mean cosine distance to the k nearest patches of a reference set (a random sample of the cohort, same-slide neighbours within six lattice steps excluded). Because the prevalence of an interesting state is not known in advance, it is evaluated with k equal to 0.5, 1, 2, 5 and 10% of the reference set and the highest rank counts: a state that recurs but covers less than the scale is still rare at that scale. State-wise disorder p_{het} ranks D_{i} among the patches of the same prototype state (k-means with 12 states), so that routine interfaces between compartments are not unusual. Contact rarity p_{adj} ranks the mean of $-\ln P(s_{\text{j}}\,|s_{\text{i}})$ over the neighbours, with P the cohort-wide frequency with which states touch. The novelty score of a patch is the mean of the valid scores of its 3 × 3 lattice window (lattice smoothing) of a weighted probabilistic OR of the axes,

$$N_i = \frac{1}{|W_i|} \sum_{j \text{ in } W_i} ¿ \tag{4}$$

with the frozen weights (w_{emb}, w_{het}, w_{adj}) = (1, 0, 0): the default score is the smoothed multi-scale appearance rarity. The disorder and contact axes were part of the original design (weights 0.4, 0.4, 0.2, one rarity scale, no smoothing) and are retained as diagnostics and as options (--weights), because in the evaluation below their effect depended on the encoder: they helped with handcrafted features and hurt with DINOv2, where they were inverted. A Mahalanobis-distance scorer, smoothed in the same way, is available as an alternative (--scorer mahalanobis).

2.5 Discovery, ranking and explanation

Patches in the top fraction q of the novelty scores (default 2%) are candidates. Connected candidates of at least three patches form regions; regions are clustered across slides by the cosine distance of their mean embeddings (average linkage). A cluster is a finding, ranked by mean novelty × (1 + ln of the number of slides) × (0.5 + 0.5 × reproducibility), where reproducibility is the fraction of its patches that stay above the median rank of appearance rarity when the reference set is split into two disjoint halves. The score is a ranking, not a probability. Each finding carries a plain-language explanation made only of measured numbers, an explicit statement when it occurs in one slide only, and the request for expert review; no pathological term is assigned.




Fig. 2. MyUncleVision: from whole-slide images to ranked, mapped and explained candidate states, with the unmodified MyUncle core supplying the reference definitions.

2.6 Software

Python (numpy, scipy, scikit-learn, OpenCV, timm and PyTorch for the encoder). One command, `python -m myuncle_vision run --input DIR --output DIR`, also the default command of the Docker image, writes findings, per-slide annotations in level-0 pixel coordinates, masks, heat maps, patch scores, a CSV listing every image used and how, and a manifest with versions, configuration, model files and the hash of the MyUncle core. The code is archived and open (Data availability). An exploratory analysis that maps a slide onto MyUncle's simulation is opt-in and described in Appendix A.

3. Evaluation design

No real kidney image was available for this work. The evaluation uses synthetic slides (4,480 × 4,480 px at 0.5 µm/px) that imitate what the method measures, not kidney tissue: interstitium, tubule-like rings with nuclei, glomerulus-like discs, vessels, stain variation, planted anomalies and three artifact types (an out-of-focus disc, a pen stroke, a dark fold). They were written by the author of the method, which limits what they can show.

• The development cohort (8 slides, 1843 patches, 3.1% of them anomalous) was used while the method was built: two anomaly types (a patchwork of small tiles of different structure; a coherent striped state in an unusual hue). Settings were chosen on it.

• The held-out cohort (16 slides, 3786 patches, 0.8% anomalous) has three anomaly types never used in development (tightly packed small tubules, nuclear crowding, a cluster of glomerulus-like discs), seven planted instances, a prevalence near 1%, stain and scanner shifts and different artifacts. The settings were frozen and recorded (results/frozen_settings.json, written before this cohort existed) and the cohort was evaluated once. Two candidates were frozen: the score of Section 2.4 (selected by a rule fixed beforehand: the highest mean average precision, over the two encoders, among the MyUncleVision variants) and a smoothed Mahalanobis scorer, which was added after the development results showed that it scored higher and which the rule did not select.

Methods compared: the original default of v0.1 (three-axis OR at one scale, no smoothing), every axis alone and in pairs, multi-scale appearance with and without smoothing, local disorder alone, and four baselines on the same embeddings: Isolation Forest, Local Outlier Factor, nearest-neighbour distance with k = 10 and Mahalanobis distance, each raw and smoothed in the same way as the proposed score (percentile rank, then the 3 × 3 window). Metrics, on patches that pass QC, with artifact patches excluded: AUROC and average precision (AP) of planted anomalous against clean patches; for the top 3% of scores, the spatial coherence (the share that lie in connected groups of at least three patches), the region recall (planted instances that contain a candidate patch) and the number of connected candidate groups per slide that touch neither a planted anomaly nor an artifact (false regions). A robustness suite varies seeds, embedding

dimension, number of states, axis weights, smoothing and patch size. Everything was run with two encoders, DINOv2 and the handcrafted one.

4. Results on synthetic slides

4.1 Development cohort

Method	AUROC	AP	coh.	rec.	AUROC	AP	coh.	rec.
three-axis OR, 1% scale (v0.1 default)	0.90	0.18	0.42	0.62	0.22	0.02	0.00	0.00
appearance, 1% scale	0.97	0.34	0.16	0.38	0.50	0.03	0.05	0.00
appearance, multi-scale	0.98	0.45	0.42	0.75	0.87	0.20	0.30	1.00
MyUncleVision frozen (appearance, multi-scale, smoothed)	0.92	0.47	0.91	1.00	0.98	0.74	0.87	1.00
three-axis OR, multi-scale, smoothed	0.99	0.79	0.87	1.00	0.90	0.20	0.76	0.38
state-wise disorder	0.67	0.06	0.58	0.25	0.25	0.02	0.25	0.00
contact rarity	0.65	0.06	0.30	0.25	0.09	0.02	0.20	0.12
local disorder D alone	0.84	0.25	0.96	0.38	0.22	0.02	0.25	0.00
Isolation Forest	0.92	0.24	0.25	0.38	0.61	0.04	0.07	0.00
+ smoothing	0.92	0.36	0.55	1.00	0.83	0.15	0.53	0.50
Local Outlier Factor	0.65	0.22	0.44	0.50	0.33	0.02	0.05	0.00
Mahalanobis distance	0.98	0.60	0.55	0.75	0.96	0.65	0.69	1.00
+ smoothing	0.95	0.62	0.69	1.00	0.99	0.90	0.95	1.00
kNN distance, k = 10	0.81	0.28	0.22	0.38	0.28	0.02	0.00	0.00
+ smoothing	0.89	0.42	0.71	0.62	0.30	0.02	0.42	0.00

Table 1. Development cohort: AUROC, average precision (AP), spatial coherence (coh.) and region recall (rec.) of the methods, handcrafted encoder (columns 2 to 5) and DINOv2 (columns 6 to 9). '+ smoothing' is the method above it with percentile ranks smoothed over the 3 × 3 lattice window.

The original default (three-axis OR at one rarity scale) had an AUROC of 0.90 with handcrafted features and 0.22 with DINOv2, below chance. The cause is a scale mismatch and an encoder property: the planted states covered 3.1% of the patches, more than the 1% rarity scale, and DINOv2 embeds them tightly, so the appearance axis alone is at chance at that scale (0.50); in addition, the DINOv2 embeddings of the planted regions are more homogeneous than those of normal tissue, so the disorder and contact axes point the wrong way (AUROC 0.25 and 0.09). Judging rarity at several scales fixed the appearance axis (AUROC 0.87 with DINOv2).

Smoothing over the lattice raised the spatial coherence of every score: for the frozen score the coherence rose from 0.42 to 0.91 (handcrafted) and from 0.30 to 0.87 (DINOv2) and the region recall to 1.00 and 1.00. With smoothing, adding the disorder and contact axes to appearance (three-axis OR) raised the AP from 0.47 to 0.79 with handcrafted features and lowered it from 0.74 to 0.20 with DINOv2; the held-out cohort showed the same sign flip (Section 4.2).

Against the baselines the result is less flattering. A plain Mahalanobis distance, a single Gaussian model of the embeddings, reaches an AUROC of 0.98 and 0.96 and, smoothed in the same way, an AP of 0.62 and 0.90 (handcrafted, DINOv2) against 0.47 and 0.74 for the frozen score. The frozen score is better than the nonparametric baselines (Isolation Forest, Local Outlier Factor, nearest-neighbour distance), whose smoothed AP with DINOv2 was 0.15, 0.02 and 0.02. Smoothing raised the spatial coherence of every baseline in all four cases (cohort by encoder); it lowered the region recall of one of them (Isolation Forest, held-out, handcrafted) and not always the AUROC. Smoothing the raw Mahalanobis distance instead of its percentile rank did better still (AP 0.82 and 0.96); this was not adopted, because it was found after the settings were chosen and would need a new held-out cohort.

4.2 Held-out cohort, settings frozen

Method	AUROC	AP	coh.	rec.	AUROC	AP	coh.	rec.
three-axis OR, 1% scale (v0.1 default)	0.95	0.13	0.63	0.71	0.45	0.01	0.00	0.00
appearance, 1% scale	0.96	0.17	0.29	1.00	0.77	0.02	0.05	0.14
appearance, multi-scale	0.98	0.17	0.31	0.86	0.95	0.15	0.20	0.86
MyUncleVision frozen (appearance, multi-scale, smoothed)	0.80	0.04	0.89	0.29	0.99	0.59	0.65	1.00
three-axis OR, multi-scale, smoothed	0.97	0.26	0.84	0.86	0.93	0.15	0.66	0.71
state-wise disorder	0.82	0.06	0.67	0.57	0.20	0.01	0.17	0.00
contact rarity	0.60	0.02	0.50	0.00	0.12	0.01	0.03	0.00
local disorder D alone	0.92	0.07	0.87	0.57	0.21	0.01	0.16	0.00
Isolation Forest	0.96	0.12	0.18	0.86	0.88	0.04	0.08	0.14
+ smoothing	0.93	0.12	0.58	0.71	0.98	0.25	0.55	1.00
Local Outlier Factor	0.96	0.12	0.34	0.71	0.64	0.02	0.00	0.29
Mahalanobis distance	0.96	0.13	0.21	0.71	0.93	0.17	0.25	0.71
+ smoothing	0.93	0.11	0.59	0.86	0.99	0.35	0.58	1.00
kNN distance, k = 10	0.96	0.14	0.28	0.57	0.43	0.01	0.03	0.14

Method	AUROC	AP	coh.	rec.	AUROC	AP	coh.	rec.
+ smoothing	0.91	0.12	0.64	0.71	0.62	0.04	0.42	0.29

Table 2. Held-out cohort (settings frozen beforehand, evaluated once); columns as in Table 1.




Fig. 3. AUROC and average precision of the main methods on the held-out cohort, both encoders.

With DINOv2 the frozen score was the best of all methods in average precision (0.59, AUROC 0.99, spatial coherence 0.65, region recall 1.00, 0.38 false regions per slide), ahead of Mahalanobis with smoothing (AP 0.35) and of the unsmoothed multi-scale appearance (AP 0.15). With handcrafted features it did badly: AP 0.04, region recall 0.29, although its AUROC was 0.80 and its spatial coherence 0.89. The unsmoothed multi-scale appearance score had an AP of 0.17 and a region recall of 0.86. The held-out anomalies are small (about five patches) and their prevalence is below 1%; with handcrafted features a 3 × 3 window mixes each of them with normal neighbours and dilutes the percentile ranks, which saturate. The choice to smooth, made on the development cohort, therefore did not generalize across encoders. The lattice axes behaved as on the development cohort: with smoothing they raised the AP with handcrafted features (0.26 against 0.04) and lowered it with DINOv2 (0.15 against 0.59). All methods had a low AP in absolute terms with handcrafted features (the best, kNN distance, k = 10, lattice-smoothed (raw score), was 0.32).




Fig. 4. One held-out slide (DINOv2): planted anomalies (green), planted artifact (red), the unsmoothed multi-scale appearance score, the frozen score and the smoothed Mahalanobis score on the patch lattice.

4.3 Robustness

Variant	Jacc.	AP	Jacc.	AP
default (frozen)	1.00	0.04	1.00	0.59
seed 1	1.00	0.04	1.00	0.59
seed 2	1.00	0.04	1.00	0.59
seed 3	1.00	0.04	1.00	0.59
8 PCA components	0.88	0.04	0.65	0.53
32 PCA components	0.93	0.04	0.73	0.55
6 states	1.00	0.04	1.00	0.59
24 states	1.00	0.04	1.00	0.59
no lattice smoothing	0.05	0.17	0.11	0.15
three-axis weights 0.4/0.4/0.2	0.10	0.26	0.20	0.15
equal axis weights	0.06	0.18	0.19	0.10
coarser patches (0.75 um/px)	n/a	0.04	n/a	0.26

Table 3. Held-out cohort: stability of the frozen method under changes of configuration. Jaccard = overlap of the top-3% patch set with the default configuration; AP = average precision. Handcrafted (columns 2, 3) and DINOv2 (columns 4, 5).

Seeds and the number of states did not change the flagged set (Jaccard 1.00), but this is not evidence of stability: at this cohort size the reference sample is the whole cohort and the default weights do not use the states, so those two settings have no effect here. The embedding dimension changed the top-3% set moderately (Jaccard 0.65 to 0.93 over both encoders). Switching smoothing off or adding the disorder and contact axes changed it almost completely

(Jaccard 0.05 to 0.20), as the earlier tables imply: those are design choices, not noise. A coarser patch size (0.75 µm/px) was tolerated with DINOv2 (AUROC 0.96, AP 0.26, region recall 1.00) but not with handcrafted features (AUROC 0.60, AP 0.04, region recall 0.00). Stain and scanner shifts are built into the held-out cohort (palette and softness differ between slides); a systematic test of other scanners, patients and stains needs real slides.

4.4 What the lattice adds and what it does not

Added: the lattice makes the score spatially coherent. For every scorer, smoothing over the lattice raised the share of top-ranked patches that form connected regions, and with DINOv2 it turned a noisy patch-level score into compact regions (Fig. 4). That is the property that matters for an expert who has to look at places. Encoder-dependent: the two lattice-based axes, disorder and contact rarity, added detection power with handcrafted features and removed it with DINOv2 on both cohorts; because the sign depends on the embedding, they are diagnostics and options, not part of the default score. Not shown: that the specific appearance score is better than a Mahalanobis distance (it is not, on the development cohort), and any benefit on real tissue.

5. Evaluation protocol for kidney whole-slide images (not yet run)

The following will be run on KPMP slides and reported with the findings: (i) the run manifest and the list of every image used; (ii) the fraction of patches excluded by QC per slide and a pathologist's review of a random sample of excluded and retained patches; (iii) a pilot on 10 to 20 slides, then an independent cohort of different patients, sites and stains, with settings frozen after the pilot; (iv) the stability of the ranked findings under another seed, reference sample, encoder and patch size, and the baselines of Section 3 on the same slides, compared by overlap and by expert judgement; (v) the recurrence of each finding across slides, patients and sites against a null model in which the site or scanner is the explanatory variable; (vi) expert review of

the top-ranked regions by at least two pathologists, blinded to the score, each region assigned to known histology, artifact or neither, with inter-rater agreement.

6. Discussion

What the evaluation supports. The lattice smoothing gives spatially coherent candidate regions for any scorer, the multi-scale rarity removes the dependence on a prevalence chosen in advance, and with DINOv2 the frozen score was the best method on an unseen cohort. The order and entropy definitions are MyUncle's, verified at $d = 2$, and extend to the embedding space; the explanation of a finding is a list of measured numbers that a reviewer can check against the image.

What it does not support. The slides are synthetic, written by the author of the method, with simple textures and sharply bounded anomalies; nothing here shows that the method finds anything in a kidney or that what it finds is biologically meaningful. The held-out cohort was used once but is of the same family as the development cohort. The two encoders disagree on whether smoothing helps and on whether the lattice axes help; a single Gaussian model scored higher than the frozen score on the development cohort; and the frozen choice (the nonparametric score) is justified for real tissue only by an untested argument that tissue is multimodal. Novelty is not pathology: a rare state may be a rare preparation, a scanner, a stain batch or a known entity that is merely uncommon in the cohort. The embedding is trained on natural images and may group patches by stain or sharpness. Quality control flagged only part of the planted artifact patches in the development runs (42%), and partly blurred patches escape it.

Improvements: a pathology-pretrained encoder (foundation models trained on large slide collections have been reported [14,15], but were not available for this work), stain normalization [16], smoothing of the raw score instead of its rank, neighbourhoods larger than four patches, a

calibrated null for the novelty score, and active expert feedback in the manner of anomaly-detection systems for astronomy [4]. Computing: the encoder dominates; a slide of ten thousand patches takes about ten minutes on one CPU core and minutes on a GPU, so the 2.4 TB of the first KPMP release is a cluster workload; the pipeline offers a patch budget per slide and a resumable cache.

7. Conclusions

MyUncleVision turns a whole-slide image into a lattice of tissue patches, scores the rarity of their appearance across prevalence scales and smooths the score over the lattice, which yields spatially coherent, explainable candidate regions. In synthetic evaluations with frozen settings and a held-out cohort, the frozen score was the best method with DINOv2 and a poor one with handcrafted features, a simple Mahalanobis baseline was competitive, and the disorder and contact axes of the lattice added detection power with handcrafted features but removed it with DINOv2. Its value for kidney pathology is untested and depends on the evaluation by experts that this paper specifies and does not report.

Appendix A. Exploratory scenario analysis (not evaluated)

An opt-in option (--scenarios) maps a slide onto the lattice of MyUncle: the rotor angle of a site is the angle of its first two principal components, a site is damaged when its state-wise disorder is above the 75th percentile, and the damaged fraction gives a repair parameter from the linear steady state of MyUncle's mean-field reduction, whose bistable window and kinetic Monte Carlo are then run from the slide under half, equal and double repair. This is a modelling analogy. It is not calibrated against any biological measurement, no result of it is reported in this paper, and its output is labelled exploratory; it is no evidence about disease progression or repair dynamics.

Declarations

Funding: this work received no external funding.

Competing interests: the author declares no competing interests. [To be confirmed by the author.]

Author contributions (CRediT): Leon Sandler, sole author: conceptualization, methodology, software, validation, formal analysis, investigation, visualization, writing – original draft, writing – review and editing.

Data and code availability: the code, the tests, the synthetic benchmarks and their results are open at https://github.com/sandlerleon/MyUncleVision (MIT license) and archived on Zenodo (software: https://doi.org/10.5281/zenodo.24066260, manuscript: https://doi.org/10.5281/zenodo.24066256, all versions). The MyUncle core is vendored unmodified (doi:10.5281/zenodo.21223570). No patient data were used; the KPMP images are not part of this work.

Declaration of generative AI and AI-assisted technologies in the writing process: during the preparation of this work the author used Claude (Anthropic) to assist with writing and testing the code, running the analyses and drafting the text and figures. After using this tool, the author reviewed and edited the content as needed and takes full responsibility for the content of the publication.

References

[1] G. Campanella, M.G. Hanna, L. Geneslaw, et al., Clinical-grade computational pathology using weakly supervised deep learning on whole slide images, Nature Medicine 25 (2019) 1301–1309. https://doi.org/10.1038/s41591-019-0508-1

[2] M.Y. Lu, D.F.K. Williamson, T.Y. Chen, R.J. Chen, M. Barbieri, F. Mahmood, Data-efficient and weakly supervised computational pathology on whole-slide images, Nature Biomedical Engineering 5 (2021) 555–570. https://doi.org/10.1038/s41551-020-00682-w

[3] D. Baron, D. Poznanski, The weirdest SDSS galaxies: results from an outlier detection algorithm, Monthly Notices of the Royal Astronomical Society 465 (2017) 4530–4555. https://doi.org/10.1093/mnras/stw3021

[4] M. Lochner, B.A. Bassett, Astronomaly: personalised active anomaly detection in astronomical data, Astronomy and Computing 36 (2021) 100481. https://doi.org/10.1016/j.ascom.2021.100481

[5] T. Schlegl, P. Seeböck, S.M. Waldstein, G. Langs, U. Schmidt-Erfurth, f-AnoGAN: fast unsupervised anomaly detection with generative adversarial networks, Medical Image Analysis 54 (2019) 30–44. https://doi.org/10.1016/j.media.2019.01.010

[6] B.B. Lake, R. Menon, S. Winfree, et al., An atlas of healthy and injured cell states and niches in the human kidney, Nature 619 (2023) 585–594. https://doi.org/10.1038/s41586-023-05769-3

[7] L. Sandler, MyUncle: a compact maintenance-lattice framework, software, Zenodo (2026). https://doi.org/10.5281/zenodo.21223570

[8] A. Goode, B. Gilbert, J. Harkes, D. Jukic, M. Satyanarayanan, OpenSlide: a vendor-neutral software foundation for digital pathology, Journal of Pathology Informatics 4 (2013) 27. https://doi.org/10.4103/2153-3539.119005

[9] M. Oquab, T. Darcet, T. Moutakanni, et al., DINOv2: learning robust visual features without supervision, Transactions on Machine Learning Research (2024), arXiv:2304.07193. https://doi.org/10.48550/arXiv.2304.07193

[10] A.C. Ruifrok, D.A. Johnston, Quantification of histochemical staining by color deconvolution, Analytical and Quantitative Cytology and Histology 23 (2001) 291–299 (PMID 11531144).

[11] F. Pedregosa, G. Varoquaux, A. Gramfort, et al., Scikit-learn: machine learning in Python, Journal of Machine Learning Research 12 (2011) 2825–2830.

[12] A. Banerjee, I.S. Dhillon, J. Ghosh, S. Sra, Clustering on the unit hypersphere using von Mises-Fisher distributions, Journal of Machine Learning Research 6 (2005) 1345–1382.

[13] K.V. Mardia, P.E. Jupp, Directional Statistics, Wiley, Chichester (2000).

[14] R.J. Chen, T. Ding, M.Y. Lu, et al., Towards a general-purpose foundation model for computational pathology, Nature Medicine 30 (2024) 850–862. https://doi.org/10.1038/s41591-024-02857-3

[15] E. Vorontsov, A. Bozkurt, A. Casson, et al., A foundation model for clinical-grade computational pathology and rare cancers detection, Nature Medicine 30 (2024) 2924–2935. https://doi.org/10.1038/s41591-024-03141-0

[16] M. Macenko, M. Niethammer, J.S. Marron, et al., A method for normalizing histology slides for quantitative analysis, in: 2009 IEEE International Symposium on Biomedical Imaging, IEEE (2009) 1107–1110. https://doi.org/10.1109/isbi.2009.5193250