

HOW-TO GUIDE

Configure an End User in the Legacy OpenScape Voice Platform

Technical Procedure / Standard Operating Procedure

Document Type	Technical Procedure / SOP
Platform	Legacy Siemens / Unify OpenScape Voice
Management Interface	Common Management Portal (CMP)
Device Provisioning	Deployment Service (DLS), where applicable
Audience	Unified Communications Engineers, Voice Engineers, System Administrators
Prepared By	Sandrina Mosley
Version	1.0
Status	Technical Reference
Intended Use	Training, documentation, and professional portfolio sample

Prepared by: Sandrina Mosley

Professional IT / Unified Communications Portfolio Sample

1. Purpose

This procedure provides a standardized process for configuring a new end user/subscriber within a legacy OpenScape Voice environment.

The procedure covers subscriber creation, directory-number assignment, subscriber identity, numbering plan and Class of Service assignment, Feature Profile assignment, SIP authentication, DLS/device association, phone registration, functional testing, and troubleshooting.

2. Scope

This procedure applies to environments using legacy Siemens / Unify OpenScape Voice with administration performed through the Common Management Portal (CMP) and, where applicable, Deployment Service (DLS). Exact screens and available fields may vary by software release, licensing, and customer deployment.

3. Prerequisites

Before creating the user, obtain the following information from the approved service request or change ticket.

Item	Example
Employee Name	Jane Smith
User ID	jsmith
Directory Number	4521
Business Group	Corporate
Office Code / Extension	45 / 21
Display ID	Jane Smith
Department / Location	Information Technology / Baltimore
Phone Type	OpenStage/OpenScape SIP Phone
Phone MAC Address	XX:XX:XX:XX:XX:XX
Feature Profile	Standard Employee
Class of Service	Standard User
DLS Profile	Standard SIP Phone
Voicemail	Required

4. Pre-Configuration Validation

- Confirm the correct Business Group and, if applicable, Branch Office.
- Verify the requested Directory Number (DN) is available.
- Confirm the required Feature Profile and Class of Service exist.
- Verify the appropriate DLS server and device profile are available.
- Confirm required OpenScape licenses are available.

- Verify the user's telephone model and MAC address.
- Confirm the request has the appropriate authorization and change record.

5. Access the Common Management Portal

1. Open the organization's Common Management Portal (CMP).
2. Sign in using an authorized administrator account.
3. Select the configuration area for OpenScape Voice.
4. Navigate to the appropriate Business Group.

6. Select the Business Group

Navigate to the appropriate Business Group and verify that it represents the correct organizational and numbering environment before creating the subscriber.

7. Open Subscriber Administration

Navigate to:

Business Group → Members → Subscribers

Select Add to create the new subscriber.

8. Create the Subscriber

8.1 Directory Number

Enter the assigned Directory Number (DN), for example 4521. Verify that the DN is available and consistent with the organization's numbering plan.

8.2 Display ID

Enter the user's display identity, such as Jane Smith. Depending on the deployment, this may be presented on internal phones and caller-ID displays.

8.3 Subscriber / User Name

Enter the user's name according to the organization's naming convention.

9. Configure the Numbering Plan

Select the approved Numbering Plan for the user. Confirm that it supports the assigned extension and required dialing behavior. Do not alter a numbering plan simply to resolve an unavailable extension; escalate the conflict through the change process.

10. Configure Rate Area / Class of Service

Assign the appropriate Rate Area and Class of Service (COS). The COS should reflect the user's authorized calling capabilities.

- Standard employee
- Executive
- Receptionist

- Contact Center Agent
 - International calling
 - Restricted calling
- Only assign elevated calling privileges when they are authorized.

11. Configure SIP Authentication

If required by the endpoint and deployment, configure the subscriber's SIP authentication information, such as the authentication realm, authentication ID, SIP username, and required credentials.

Security: Never place actual passwords in a ticket, portfolio document, screenshot, or general configuration guide.

12. Assign the Feature Profile

Open the subscriber's feature configuration and assign the appropriate Feature Profile, such as Standard Employee.

Feature Profiles provide reusable collections of feature permissions/settings, allowing administrators to maintain consistent configurations across groups of subscribers.

- Call Hold
- Call Transfer
- Call Forwarding
- Call Waiting
- Caller ID
- Voicemail access
- Conference calling
- Do Not Disturb

13. Configure Individual Subscriber Features

If the user requires features not inherited from the Feature Profile, configure them individually at the subscriber level.

- Call Forwarding
- Hunt Group membership
- Pickup Group membership
- Keyset functionality
- Executive/Assistant features
- Additional lines
- Contact-center functionality

Best practice: use the organization's standard Feature Profile whenever possible and document approved exceptions.

14. Configure DLS / Device Provisioning

If the user has a managed IP phone, associate the subscriber with the appropriate Deployment Service (DLS) configuration.

Typical workflow:

Business Group → Members → Subscribers → Select Subscriber → Device Management

Add or associate the endpoint using the verified device identifier/MAC address and the approved device profile.

Device Information

- Device ID: Enter the verified phone MAC address.
- Device Family: Select the appropriate phone/device category.
- Device Profile: Select the organization's approved profile.

15. Verify the Device Profile

- Correct phone model
- Correct MAC address
- Correct device family
- Correct DLS profile
- Correct firmware/profile requirements
- Correct subscriber/DN association

Do not associate a phone with the wrong subscriber. A MAC-address mismatch can prevent correct provisioning or registration.

16. Save the Configuration

Before committing the change, review the complete configuration. Verify the Business Group, DN, numbering plan, COS, Feature Profile, authentication requirements, DLS information, device profile, and MAC address. Select Save/Apply as appropriate for the installed release.

17. Verify DLS Provisioning

- Confirm the device appears in DLS.
- Verify the device is associated with the correct subscriber.
- Verify the MAC address.
- Verify the assigned device profile.
- Check provisioning/job status.
- Confirm the configuration has been delivered to the phone.

18. Verify Subscriber Registration

Return to subscriber administration and verify the endpoint registration status. Confirm that the phone is Registered / Online rather than Unregistered / Offline.

19. Perform Functional Testing

Internal Calling

Test user-to-user calling. Confirm call setup, caller ID, signaling, and two-way audio.

External Calling

Test an authorized outbound call. Confirm route selection, caller ID, two-way audio, and calling permissions.

Inbound Calling

Call the new DN from another phone. Verify ringing, display information, call setup, and two-way audio.

Transfer and Hold

Place a call on hold and retrieve it. Perform a transfer to another authorized endpoint.

Voicemail

Allow a test call to reach voicemail, leave a message, retrieve the message, and verify notification.

Call Forwarding

If authorized, test the applicable forwarding configuration.

Additional Features

Test all features specifically assigned to the user.

20. Contact Center User Configuration

If the user is also a contact-center agent, completing the OpenScope Voice subscriber configuration may not complete the entire provisioning process. The user may additionally require contact-center agent identity, group/queue membership, skills, ACD configuration, agent login, or supervisor configuration.

Important: Voice subscriber creation does not necessarily equal complete contact-center agent provisioning.

21. Troubleshooting

Phone Does Not Register

- Verify MAC address.
- Verify DLS association and device profile.
- Verify subscriber DN.
- Verify SIP authentication.
- Check network connectivity, VLAN, DHCP, and DNS.
- Check SIP signaling and licensing.
- Check endpoint firmware compatibility.

Internal Calls Work but External Calls Fail

- Check Class of Service.
- Check Rate Area and numbering plan.
- Check external dialing permissions.
- Check route selection, trunk availability, and digit translation.

Phone Registers but Features Are Incorrect

- Verify the assigned Feature Profile.
- Check individual subscriber features.
- Verify the DLS device profile.
- Confirm that updated configuration has been applied to the endpoint.

Incorrect Caller ID

- Verify Display ID.
- Verify subscriber DN.
- Check calling-party presentation settings.
- Check route/trunk configuration.

22. Change Validation Checklist

✓	Subscriber created
✓	Correct DN assigned
✓	Correct Business Group
✓	Correct numbering plan
✓	Correct COS/Rate Area
✓	Correct Feature Profile
✓	SIP authentication configured where required
✓	DLS/device association correct
✓	Device provisioned
✓	Phone registered
✓	Internal calling tested
✓	External calling tested
✓	Inbound calling tested
✓	Hold tested
✓	Transfer tested
✓	Voicemail tested
✓	Call forwarding tested if applicable
✓	Additional requested features tested
✓	Ticket updated
✓	Test results documented

23. Example Completed Provisioning

Configuration	Assigned Value
User	Jane Smith
DN	4521
Business Group	Corporate
Office Code / Extension	45 / 21
Display ID	Jane Smith
Numbering Plan	Corporate
COS	Standard Employee
Rate Area	Baltimore
Feature Profile	Standard Employee
DLS	Corporate DLS
Device Family	SIP Phone
Device Profile	Standard SIP Phone
MAC Address	XX:XX:XX:XX:XX:XX
Voicemail	Enabled
Validation	Registered; functional call testing passed

24. Standard Engineer Workflow

Service Request → Validate Requirements → Verify DN Availability → Select Business Group → Create Subscriber → Assign DN/Display ID → Assign Numbering Plan → Assign COS/Rate Area → Configure SIP Authentication → Assign Feature Profile → Configure Individual Features → Associate DLS/Device Profile → Provision Phone → Verify Registration → Perform Call Testing → Document Results → Close Change/Service Request

25. Engineering Best Practices

- Use standardized Feature Profiles whenever possible.
- Never assign an extension without verifying availability.
- Verify the MAC address before associating a device.
- Do not document passwords in tickets or general documentation.
- Use least-privilege Class of Service assignments.
- Test both signaling and media.
- Verify registration before troubleshooting call features.
- Document configuration changes and test results.
- Follow the organization's change-management process.
- Do not assume a registered phone means the user is fully provisioned; voice, UC, voicemail, and contact-center services may require additional configuration.

26. Reference Architecture

End User
↓
OpenScape Subscriber / DN
↓
Business Group
↓
Numbering Plan + COS + Feature Profile
↓
DLS / Device Profile
↓
IP Phone / SIP Endpoint
↓
OpenScape Voice
↓
Enterprise Network / PSTN / Contact Center

This layered view is useful for troubleshooting because a service issue can originate at the subscriber, feature, device-provisioning, network, or endpoint layer.

27. Key Terminology

Term	Definition
Subscriber	The OpenScape Voice user/line object associated with a directory number.
DN — Directory Number	The telephone number or extension assigned to the subscriber.
Business Group (BG)	An organizational grouping containing related subscribers and configuration.
Feature Profile	A reusable collection of subscriber feature permissions/settings.
COS — Class of Service	Defines calling/service permissions assigned to the subscriber.
DLS — Deployment Service	The component used to manage/provision supported devices and configurations.
Device Profile	The configuration profile applied to a supported endpoint.
CMP — Common Management Portal	The administrative management interface used to configure OpenScape components.

28. Version / Environment Note

This procedure is a legacy OpenScape Voice administration reference. Exact screen names, fields, available options, and provisioning behavior can differ between OpenScape Voice releases and customer deployments. Validate the procedure against the specific release and approved customer configuration before performing production changes.

29. Completion Criteria

- Subscriber exists.
- Correct DN is assigned.
- Correct Business Group is assigned.

- Numbering plan is correct.
- COS/Rate Area is correct.
- Feature Profile is assigned.
- SIP authentication is configured when required.
- DLS/device association is correct.
- Phone is provisioned.
- Phone is registered.
- Required calling features have been tested.
- Configuration and test results are documented.

Prepared by Sandrina Mosley

Legacy OpenScape Voice End User Configuration — Technical SOP