



POLITECNICO DI TORINO

Electronics for Embedded Systems

Project of the course

Professor: Claudio Passerone

Data: November 16, 2019

Author: Alessandro Salvato



Contents

1	Introduction	4
2	Analog to digital conversion	7
3	Peripheral programming	9
4	Power management	12



1 Introduction

I'm very glad to present by this report, my own project for Electronics for Embedded Systems course. The main idea consists in realizing a camera able to capture photos to be transferred to an host computer for further processing. Before describing in details the environmental structure, I guess it's fundamental to highlight that all the topics of the course have been covered in the following manner:

- **Memory:** memory controller as FSM
- **Programmable logic device:** acts as remote to send the user command
- **Interconnection protocol:** I2C, SCCB and UART
- **Peripheral management:** programming of camera peripheral
- **AD and DA converters:** usage of AD converter to sample the luminance of the environment
- **Power management:** Step-down converter to drive a LED

Each of them owns a proper section below. Let's have a look on the general architecture, listing the main parts of the system. The camera is connected to an ST microcontroller: a STM32F446ZET. The choice on this MCU has due to the fact that it integrates a very useful and widespread engaged peripheral in the video-capturing field: the Digital CaMera Interface (**DCMI**). All images are sent to the host computer by UART protocol, exploiting another embedded peripheral of the microcontroller. Computer reads UART's data plugging a USB-UART adapter. Then a small Python script converts those data into a BMP image. The command is generated by the user pushing a specific button. An 8 buttons keyboard is tied up to the FPGA: an Altera Cyclone IV on DE0-Nano board. The implemented VHDL is composed of the keyboard driver and a fully structural UART peripheral. When a button has clicked, an encoded 8-bit data is sent to the microcontroller, which, by an interrupt, recognizes that the user pushed something. A breadboard has been used to build circuits for AD and Bulk converters. I used STM32 CubeIDE to program the microcontroller, a software Eclipse based. To program the FPGA I exploited both Quartus II when uploading the *sof* file and Xilinx ISE Design Suite when simulating (just for my high familiarity with that). Moreover, as classical laboratory instruments I relied on an oscilloscope provided by GW Instek and a multimeter for resistor measurements. Moreover, I exploited the functionalities offered by GitHub, more specifically the desktop version that I found very easy and immediate to use.



For sure, the following image is more clarifying for the reader.




Figure 1: General block schema

Camera has been set to capture images in format QVGA (320x240) RGB 565 for an amount of 153600 bytes. However due to the poorness of memory availability, I capture the half of them. Then the Python script generates on the host a picture 640x120 without colors.




Figure 2: Apple logo captured by camera and then processed by software



Figure 3: Original Apple logo



What actually the system appears. . . . It's a little bit messy due to the high number of flying wires. Only the camera requires 18 links.




Figure 4: Real system

I'll proceed in the description in the same order I implemented each part of the project.

2 Analog to digital conversion

The analog to digital conversion aims at reading the luminance of the room, sending the sample to microcontroller. The input channel is feed by the voltage passing through a photoresistor. After having measured that voltage in condition of both full and absence of light, the dynamics has approximated at range [0.5 - 3.0] Volt.

The chip is ultra-small, low-Power, 16-Bit analog-to-digital converter with internal reference, provided by Texas Instrument at 3.50\$. The microcontroller drives it by means of an I2C interface.




Figure 5: A2D internal architecture, from datasheet

The chip operates either in continuous conversion mode or a single-shot mode that automatically powers down after a conversion and greatly reduces current consumption during idle periods. I decided to work in the single shot one, sending the command directly from the microcontroller.

In general, to write and read 4 bytes must be sent, the string is composed of the **slave address** (0x48), the **register address**, and then in the big-endian format 2 bytes of data. Due to the fact I choose to operate in single shot mode, I have to send every time the command, so the protocol gets as follows: write 4 bytes (including the command), write the slave address and the register address containing the converted data and read 2 byte from it.

Bit(s) name	Description
Command	Begin conversion (automatically cleared when completed)
Input multiplexer configuration	Channel P: In0, Channel N: In1 (physically grounded on breadboard)
Programmable gain amplifier configuration	$\pm 2.048V$
Device operating mode	Power-down single shot mode
Data rate	8 sample per second
Comparator mode	not used
Comparator polarity	not used
Latching comparator	not used

Table 1: A2D configuration




Figure 6: Connection between MCU and A2D

GPIO	Morpho Connector	Description
PB8	D15	I2C1_SCL
PB9	D14	I2C1_SDA

Table 2: A2D: GPIOs involved




Figure 7: Starting an interrogation sending as first byte the slave address of A2D (0x48)

3 Peripheral programming

The camera is composed of 18 pins, where 2 are dedicated to Vdd and Gnd, 2 are part of the serial protocol called **Serial Camera Control Bus**, 11 are connected to MCU's DCMI peripheral for image acquiring and synchronization, 1 pin is an input for the clock source and the last 2 are for resetting and enabling. Before describing what I did, I would like to spend few words about SCCB and DCMI.

Substantially, SCCB is almost identical to I2C. The only difference regards the role of the ACK bit. This protocol doesn't care it, anyway it's generated low as well. However, from the microcontroller side, I enabled another I2C peripheral, another one than whose interfaces with A2D.

DCMI is a kind of protocol widespread used in multimedia processing. Although it allows also an higher parallelism, in terms of data bits, the camera chip, provided by OmniVision, has constrained at 8, labeled from *D0* to *D7*. After having configured, the acquisition of the image works as follows. PXCLK is used as internal synchronizator derived from the XCLK, i.e. the system clock generated by a GPIO of the STM32F446. VSYNC and HREF pins are part of DCMI interface as well. VSYNC triggers the start and the stop of frame capturing, HREF signal indicates the start/end of a line.




Figure 8: Start of frame capturing (top) and sampling line by line (bottom)

I guess that another relevant aspect of DCMI is how data are then transferred within microcontroller. This peripheral embeds and works as default by DMA. In fact, when setting DCMI, any option related to DMA's disable cannot be modified. So, in the firmware, I had to declare an array 76800 bytes long, to satisfy image sizing. If I hadn't been constrained by RAM capacity (128Kbyte), I would have used a 153000 long one.

I programmed the camera in order to work in single snap shot. The command is user generated on the FPGA side, which sends the command via UART to microcontroller. That UART generates an interrupt when start working; the interrupt launches the start capturing function. When the image transfer has done, I turn the camera off and then I drive the array to the host computer via another UART peripheral of the microcontroller.

The camera embeds a register configuration file of 200 locations around. Not all of them are required to be written to make it work. However I found an example online, where the main ones are highlighted with values to be loaded in them. I modified some of them to make the application compliant with my system. I'm going to list some important configuration settings.

Bit(s) name	Description
(COM7) Color Bar	Enable
(COM7) Output format	RGB and QVGA
(MVFP) Mirror	Normal Image Acquisition (No mirroring)
(CLKRC) Clock prescaler	Prescaler disabled for PXCLK
(COM16) Threshold and de-noise auto adjustment	Both enabled

Table 3: Camera configuration




Figure 9: Connection between MCU and camera




Figure 10: Camera's bottom side

GPIO	Morpho Connector	Description
PF0	D68	I2C2_SDA
PF1	D69	I2C2_SCK
PA8		RCC_MCO1 (25 Mhz) -> XCLK
PA4	D24	DCMI_HSYNC
PG9	D0	DCMI_VSYNC
PA6	D12	DCMI_PXCLK
PC6	D16	DCMI_D0
PC7	D21	DCMI_D1
PC8	D43	DCMI_D2
PC9	D44	DCMI_D3
PE4	D57	DCMI_D4
PD3	D55	DCMI_D5
PE5	D58	DCMI_D6
PE6	D59	DCMI_D7

Table 4: Camera: GPIOs involved

4 Power management

Any commercial camera integrates a flash light, which is turned on in leakage of adequate luminance. I have tried to emulate that behaviour using an high emittance LED. I choose a component able to emit a very cold light: it should be fed with 100 mA at 3V. Having defined the load, then I had to chose the input voltage between two possibilities: 3.3 and 5 volts, both of them directly generated by microcontroller and accessible by means of its own morpho connectors. I thought that the former was too close to the desired output, making the implementation of a converter totally useless. So I decided for 5V as input. Due to the fact that I need of a lower voltage, the straightforward architecture is the Bulk one, whose characteristic is

$$V_{out} = \frac{T_{on}V_{in}}{T_{on} + T_{off}} = \delta V_{in}$$

Another, maybe the most important, feature of a switching regulator is the duty cycle used to drive the NPN transistor's base terminal. First of all I adopted a reasonable period $T = T_{on} + T_{off}$. One of the timer on microcontroller is involved in generating the square wave. It's connected to the Advanced Peripheral Bus (APB) which is synchronized with a clock of 16 Mhz. The timer prescaler has been choosen at 160, so each tick is sensed each $10 \mu s$. Selecting a period of 100 ticks, the overall period T gets $1ms$, making any consideration about duty cycle easier. However setting duty cycle isn't so simple, something cannot be taken out from a simple equation.






Figure 11: Connection between MCU and Buck circuit

GPIO	Morpho Connector	Description
PF9	D63	TIM14_CH1 (PWM)

Table 5: Buck: GPIOs involved

Before showing measurements captured by oscilloscope, I need to state a couple of things. I put a $1K\Omega$ serially the 5V pin in order to avoid overfeeding. It's useless but I was afraid of burning some component: MCU, A2D, camera, resistors, inductor...since all of them were connected somehow. Then, few words about the inductor: in the circuit I put $470\mu H$. But, due to the length of T_{on} ($750\mu s$) I would need a much higher one to do not enter in Discontinuous Current Mode. I choose that because it is the biggest I own and have immediate availability. However, everything works and waveforms among the nodes of the circuit seems to have a compliant shape.


Figure 12: From top to bottom: V_{in} , PWM signal, V_{out}

Figure 13: From top to bottom: V_{in} , V_A of the node where are emitter, diode's cathode and one inductor pin, V_{out} , $V_{in} - V_A$