

Cryptography and Network Security

Third Edition
by William Stallings

Lecture slides by Lawrie Brown

Chapter 19 – Malicious Software


What is the concept of defense: The parrying of a blow. What is its characteristic feature: Awaiting the blow.

—On War, Carl Von Clausewitz

Viruses and Other Malicious Content

- computer viruses have got a lot of publicity
- one of a family of **malicious software**
- effects usually obvious
- have figured in news reports, fiction, movies (often exaggerated)
- getting more attention than deserve
- are a concern though

Malicious Software



Trapdoors

- secret entry point into a program
- allows those who know access bypassing usual security procedures
- have been commonly used by developers
- a threat when left in production programs allowing exploited by attackers
- very hard to block in O/S
- requires good s/w development & update

Logic Bomb

- one of oldest types of malicious software
- code embedded in legitimate program
- activated when specified conditions met
 - eg presence/absence of some file
 - particular date/time
 - particular user
- when triggered typically damage system
 - modify/delete files/disks

Trojan Horse

- program with hidden side-effects
- which is usually superficially attractive
 - eg game, s/w upgrade etc
- when run performs some additional tasks
 - allows attacker to indirectly gain access they do not have directly
- often used to propagate a virus/worm or install a backdoor
- or simply to destroy data

Zombie

- program which secretly takes over another networked computer
- then uses it to indirectly launch attacks
- often used to launch distributed denial of service (DDoS) attacks
- exploits known flaws in network systems

Viruses

- a piece of self-replicating code attached to some other code
 - cf biological virus
- both propagates itself & carries a payload
 - carries code to make copies of itself
 - as well as code to perform some covert task

Virus Operation

- virus phases:
 - dormant – waiting on trigger event
 - propagation – replicating to programs/disks
 - triggering – by event to execute payload
 - execution – of payload
- details usually machine/OS specific
 - exploiting features/weaknesses

Virus Structure

```
program V :=  
  {goto main;  
  1234567;  
  subroutine infect-executable := {loop:  
    file := get-random-executable-file;  
    if (first-line-of-file = 1234567) then goto loop  
    else prepend V to file; }  
  subroutine do-damage := {whatever damage is to be done}  
  subroutine trigger-pulled := {return true if some condition holds}  
  main: main-program := {infect-executable;  
    if trigger-pulled then do-damage;  
    goto next;}  
  next:  
}
```

Types of Viruses

- can classify on basis of how they attack
- parasitic virus
- memory-resident virus
- boot sector virus
- stealth
- polymorphic virus
- macro virus

Macro Virus

- **macro code** attached to some **data file**
- interpreted by program using file
 - eg Word/Excel macros
 - esp. using auto command & command macros
- code is now platform independent
- is a major source of new viral infections
- blurs distinction between data and program files making task of detection much harder
- classic trade-off: "ease of use" vs "security"

Email Virus

- spread using email with attachment containing a macro virus
 - cf Melissa
- triggered when user opens attachment
- or worse even when mail viewed by using scripting features in mail agent
- usually targeted at Microsoft Outlook mail agent & Word/Excel documents

Worms

- replicating but not infecting program
- typically spreads over a network
 - cf Morris Internet Worm in 1988
 - led to creation of CERTs
- using users distributed privileges or by exploiting system vulnerabilities
- widely used by hackers to create **zombie PC's**, subsequently used for further attacks, esp DoS
- major issue is lack of security of permanently connected systems, esp PC's

Worm Operation

- worm phases like those of viruses:
 - dormant
 - propagation
 - search for other systems to infect
 - establish connection to target remote system
 - replicate self onto remote system
 - triggering
 - execution

Morris Worm

- best known classic worm
- released by Robert Morris in 1988
- targeted Unix systems
- using several propagation techniques
 - simple password cracking of local pw file
 - exploit bug in finger daemon
 - exploit debug trapdoor in sendmail daemon
- if any attack succeeds then replicated self

Recent Worm Attacks

- new spate of attacks from mid-2001
- **Code Red**
 - exploited bug in MS IIS to penetrate & spread
 - probes random IPs for systems running IIS
 - had trigger time for denial-of-service attack
 - 2nd wave infected 360000 servers in 14 hours
- **Code Red 2**
 - had backdoor installed to allow remote control
- **Nimda**
 - used multiple infection mechanisms
 - email, shares, web client, IIS, Code Red 2 backdoor

Virus Countermeasures

- viral attacks exploit lack of integrity control on systems
- to defend need to add such controls
- typically by one or more of:
 - **prevention** - block virus infection mechanism
 - **detection** - of viruses in infected system
 - **reaction** - restoring system to clean state

Anti-Virus Software

- **first-generation**
 - scanner uses virus signature to identify virus
 - or change in length of programs
- **second-generation**
 - uses heuristic rules to spot viral infection
 - or uses program checksums to spot changes
- **third-generation**
 - memory-resident programs identify virus by actions
- **fourth-generation**
 - packages with a variety of antivirus techniques
 - eg scanning & activity traps, access-controls

Advanced Anti-Virus Techniques

- generic decryption
 - use CPU simulator to check program signature & behavior before actually running it
- digital immune system (IBM)
 - general purpose emulation & virus detection
 - any virus entering org is captured, analyzed, detection/shielding created for it, removed

Behavior-Blocking Software

- integrated with host O/S
- monitors program behavior in real-time
 - eg file access, disk format, executable mods, system settings changes, network access
- for possibly malicious actions
 - if detected can block, terminate, or seek ok
- has advantage over scanners
- but malicious code runs before detection

Summary

- have considered:
 - various malicious programs
 - trapdoor, logic bomb, trojan horse, zombie
 - viruses
 - worms
 - countermeasures