

DOCUMENTATION

Payment Method Integration (Developer Preview)

API Documentation

V1.05

Introduction

This is the API reference for Koko's APIs. The checkout API is used to create a payment request for a Koko user.

This is a developer preview of Koko's Platforms APIs. This documentation will be updated as we introduce new features.

How it works

The following diagram illustrates how a payment flow works between the Koko and the merchant's eCommerce site:

Authentication

You will receive the following,

- Merchant ID
- API Key
- RSA Public Key for the Koko environment
- RSA Private Key for merchant-specific API signing

Note: The API credentials are separate from your Merchant ID, and it is possible to have several API credentials associated with the same Merchant ID but different Cashier accounts.

The credentials should be sent as an authorization header for every request with the username and password.

You receive both your live and test credentials by contacting the Koko Merchant Success team for your country.

If the credentials are missing or wrong, Koko will respond with **401 Unauthorized**.

Note: Below endpoints examples are shown using production urls, Please found relevant QA and Dev endpoints

Dev: devapi.paykoko.com

QA: qaapi.paykoko.com

PROD: prodapi.paykoko.com

Initiate Payment Request

Use this API to start initiating the payment process. The user needs to be **redirected** to the below URL with the mentioned request parameters.

POST	https://prodapi.paykoko.com/api/merchants/orderCreate
------	---

Parameter	Example	Description
_mld	508213dec440c1009d d17dd914aaf8ed1	Merchant Id. Note: Encrypted value needs to be passed
api_key	zqSYURUTOdf1xoDpga F1mNTARXSAqdtU	A string that is associated with your Merchant ID and is used to authorize the use of Koko's APIs
_responseUrl	http://eComm.com/orders/66/response/3	Response URL on the eCommerce site to do the POST implementation after processing of the payment on Koko's side See below for the detailed description
_cancelUrl	http://eComm.com/orders/66/cancel/3	If the Order is Cancelled Here needs to pass the Url of the page that needs to redirect . See below for the detailed description
_returnUrl	http://eComm.com/orders/66/returned/3	If the Order is Successful/Unsuccessful Here needs to pass the Url of the page that needs to redirect. See below for the detailed description
_amount	300.00	The total amount of the order including tax and any available discounts. The value should be non-negative
_currency	LKR	The purchased currency of the merchant's store. The format to be used is ISO 4217. Eg: USD, EUR, SEK, GBP, etc. Note: purchase country and currency need to match the defined merchant configuration.
_reference	53	Reference id.
_orderId	53	Specific order id.

_pluginName	customapi	Name of the Plugin
_pluginVersion	1.0.1	Plugin Version
_description	2 products	Products Description
_firstName	John	First name of the Customer
_lastName	Doe	Last Name of the Customer
_email	john@gmail.com	Email address of the Customer
dataString	(Please view the section for dataString creation)	All other Data will Needed to Encode with the signature. (Please view the section for dataString creation)
signature	JnK2CcsQCDvjSCIGkcr H1bVsQDIF3hLXIh3aE Y53hLXwsov6Lt/0pvFf XHljBhxaXp0iuKNtqtjLI 9lj9JXSn44gbO93/kAU Hj3HvW62KHt/Tw23 WCDuFuF9cYfKfjI3UPj hQYezw4z/v+BddduUS RaT745bFja7Pjwgmsga 2c=	RSA Signing of request parameters

Example

Example request body is given below.

```
{
  "_mId": "5082323ec440c1009dd17dd914aaf8ed1",
  "api_key": "zqSYURUT0df1xoDpgaF1mNTARXSAqdtU",
  "_returnUrl": "http://eComm.com/orders/66/returned/3",
  "_cancelUrl": "http://eComm.com/orders/66/cancel/3",
  "_responseUrl": "http://eComm.com/orders/66/response/3",
  "_amount": "300.00",
  "_currency": "LKR",
  "_reference": "53",
  "_orderId": "53",
  "_pluginName": "customapi",
  "_pluginVersion": "5.5.1",
  "_description": "2 products",
  "_firstName": "John",
  "_lastName": "Doe",
  "_email": "john@gmail.com",
  "dataString":
    "5082323ec440c1009dd17dd914aaf8ed1300.00LKRcustomapi5.5.1http://eComm.com/o
    rders/66/returned/3http://eComm.com/orders/66/cancel/35353JohnDoejohn@gmail
    .com2
    productszqSYURUT0df1xoDpgaF1mNTARXSAqdtUhttp://eComm.com/orders/66/response
    /3"
  "signature":
    "JnK2CcsQCDvjSCIGkcrH1bVsQDIF3hLXlIh3aEY53hLXwsov6Lt/0pvFfXHljBhxaXp0iuKNtq
    tjLI9lj9JXSn44gb093/kAUHj3HvW62Kht/Tw23WCDuFuF9cYfKfjl3UPjhQYezw4z/v+BddduU
    SRaT745bFja7Pjwgmsga2c= "
}
```

Sample curl request is given below

```
curl --location --request POST 'https://prodapi.paykoko.com/api/merchants/orderCreate' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--header 'Cookie: acw_tc=0bc1a14616605528271427652ee15f2b1523859fdab83fcf75e7764ce80041' \
--data-urlencode '_mId=08cad12000cefd69d6de20e1abcd36' \
--data-urlencode 'api_key=CEQBfz88LXwGxespepwMYCaOGu0wdoLE' \
--data-urlencode '_returnUrl=http://localhost:3001/returnSuccess?orderId=62esjsjkfksjse8abcd&signature=xyz' \
--data-urlencode '_cancelUrl=http://localhost:3001/returnCanceled?orderId=62esjsjkfksjse8abcd' \
```

```
--data-urlencode '_responseUrl=http://localhost:3001/returnSuccess?orderId=62esjsjkfkfsjse8abcd' \
--data-urlencode '_amount=100' \
--data-urlencode '_currency=LKR' \
--data-urlencode '_reference=62esjsjkfkfsjse8abcd' \
--data-urlencode '_orderId=62esjsjkfkfsjse8abcd' \
--data-urlencode '_pluginName=customapi' \
--data-urlencode '_pluginVersion=1.0.1' \
--data-urlencode '_description=2 records' \
--data-urlencode '_firstName=firstName' \
--data-urlencode '_lastName=lastName' \
--data-urlencode '_email=example@hotmail.com' \
--data-urlencode 'dataString=testDataString' \
--data-urlencode 'signature=testSignature'
```

Data String Creation

Note: Please follow the below data string creation order. It is **not in alphabetical** order.

In Java

```
String dataString = request.getMId() + request.getAmount() +
request.getCurrency() + request.getPluginName() +
request.getPluginVersion() + request.getReturnUrl() +
request.getCancelUrl()+ request.getOrderId() + request.getReference() +
request.getFirstName() + request.getLastName() + request.getEmail() +
request.getDescription() + request.getApiKey() + request.getResponseUrl();

byte[] data = dataString.getBytes();
byte[] signature = Base64.decodeBase64(request.getSignature());
Bool comply = RsaVerify.verify(data, signature,
merchantPluginDetail.getMerchantPublicKey());
```

Return URL (_returnUrl)

If the payment made is successful or fails, the user will be redirected to the eCommerce site using the _returnUrl set when the createOrder api is called.

eg: <http://eComm.com/orders/66/returned/3>

Parameter	Example	Description
orderId	40070	Specific order id
trnId	f7ec3q588eq435zfc8c396d3ecd3306a	Koko transaction id
status	SUCCESS FAILURE	Payment status

Cancel Url (_cancelUrl)

If the payment is cancelled, the user will be redirected to the '_cancelUrl' which is entered when the 'createOrder' api is called.

eg: <http://eComm.com/orders/66/cancel/3>

Parameter	Example	Description
orderId	400702	Specific order id
trnId	f7ec3q588eq435zfc8c396d3ecd3306a	Koko transaction id
status	CANCELED	Payment status

Response Url (_responseUrl)

If the payment is successful, Koko backend will send an api request to the url specified in '_responseUrl' parameter. Example given below.

It will be a HTTP POST api call. Using the '_responseUrl' parameter. Content type will be "application/x-www-form-urlencoded".

Therefore it is the eCommerce responsibility to set up an endpoint supporting this for the url given in '_responseUrl'. Otherwise eCommerce will not have any way to verify if the payment has been successfully done or not from the backend. Else eCommerce will have to rely on front end redirection only, which is not 100% secure.

Parameter	Example	Description
orderId	400702	Specific order id
trnId	f7ec3q588eq435zfc8c396d3ecd3306a	Koko transaction id
status	SUCCESS	Payment status
desc	2 orders	This value is "" as of now. In future it might return the description which sent in 'createOrder' api
signature	NgMKIcu0MEZ5Zkbbc/2aFFz7zHw5IE+bjr39HoBu9ehaGKWK5Gv8LjzLj4m+9QT11la7t9X8Z211Qbwgmq4dCBXKMmRHwpUFAZdZQXlvL++MLiA0Gb0AcsOGERhRHSBbMN7Q0qKBV1XrGQ2HwOd++O6s1oXB36NV8xmioT0Oh6s=	String to encrypted - 400702f7ec3q588eq435zfc8c396d3ecd3306aSUCCESS Above data string will be encrypted using Koko private key, eCommerce need to decrypt and validate it with Koko public key which is already shared.