

The Regolith Forge Crawler

An Autonomous In-Situ Construction Machine for Sintered Habitats on the Moon and Mars

Concept Study RFC-CS-006 · Off-World Civilisation Toolkit · July 2026

Classification: Speculative engineering, constrained to known physics

Wijerathne Arachchilage Sandun Priyankara Wijerathne

sandunwijerathne51@gmail.com · linkedin.com/in/sandun-wijerathne · github.com/sandunwijerathne

Abstract

The costliest way to build a house on the Moon is to ship the house. Every brick, panel, and beam launched from Earth pays the full toll of the gravity well, which is why the mass of a lunar or Martian base has always been the wall between us and living there. The Regolith Forge Crawler dissolves that wall by making the base out of the ground it stands on. The RFC-1 'Terramother' is a 26-tonne autonomous machine that ingests raw planetary soil, sorts it, sinters it at high temperature into a strong ceramic, and prints the result — through a gantry arm — into habitat domes, roads, landing pads, and thick radiation shielding, with no imported binder and no human within a hundred million kilometres. We describe the intake, separation, and plasma-sintering chain, the extrusion and print architecture, the fission power and thermal systems, and the autonomy that lets a base build itself before its occupants arrive. In-situ resource utilisation is no longer hypothetical — a NASA instrument has already made oxygen from Martian air — and sintered-regolith construction is an active laboratory field. The Terramother is what those results become when given wheels and a purpose.

1. Introduction: Ship the Factory, Not the House

There is an iron rule in spaceflight economics: mass is destiny. A permanent base needs pressurised shells, radiation shielding metres thick, level pads, and dust-free roads — and if every gram of that must be manufactured on Earth and flown across cislunar space, the base will forever remain a sketch. The escape is a principle NASA calls in-situ resource utilisation, or ISRU: stop importing the product and import the factory instead, then feed it on local material. Build with what is already there.

What is there, everywhere on the Moon and Mars, is regolith — the loose, broken, glassy soil that blankets airless and near-airless worlds. It is abrasive, awkward, and, crucially, rich in exactly the silicate and metal-oxide minerals that fuse into strong ceramics when heated. The insight behind the Terramother is that this dust is not an obstacle to construction but its feedstock. The idea of building lunar structures by sintering regolith has been studied for decades and demonstrated at laboratory scale with simulant soils and even solar and microwave heating (Taylor and Meek, 2005; Khoshnevis et al., 2005), and additive-manufacturing approaches to regolith habitats have since been explored under agency programmes (Cesaretti et al., 2014). The machine described here integrates that chain into a single mobile factory.

2. Concept Description

The RFC-1 'Terramother' is an 18-metre tracked crawler that reads, from front to back, as a small mobile foundry. At the leading end, a rotary intake maw grinds and lifts surface regolith. Above it, an electrostatic and magnetic separator stack sorts the raw feed into useful mineral streams — the ilmenite and metal oxides that will one day also yield oxygen and metals, and the silicates that become structural

ceramic. The heart of the machine is a microwave-plasma sinter kiln that fuses the sorted silicate at around 1,600 degrees Celsius into a dense, binder-free ceramic; behind it, a fission power module supplies the tens of kilowatts the kiln and drives demand, its waste heat rejected through deployable radiators. A three-axis extrusion gantry, reaching some nine metres, lays the sintered material down in courses to print the finished structure. An instrument mast carries the autonomy: terrain LIDAR, cameras, and the build-plan solver that turns a site into a settlement.

The output is not a kit to be assembled but a structure grown in place. Given a level patch of ground, the Terramother can raise an eight-metre habitat dome with a radiation-shielding wall over half a metre thick in roughly three weeks of unattended operation, then move on to the next foundation. Cities, in this vision, arrive before their citizens.

3. From Dust to Ceramic

The physical basis of the machine is sintering: heat a powder to just below its melting point and its grains weld together at their contacts into a solid mass, without ever becoming fully liquid. Regolith is unusually well suited to this. Lunar soil in particular contains nanophase iron and other constituents that couple strongly to microwave energy, so it can be heated volumetrically and efficiently rather than only from its surface — a property demonstrated with lunar simulant, which sinters readily under ordinary microwave energy (Taylor and Meek, 2005). The Terramother exploits this with a plasma-assisted microwave kiln that reaches sintering temperature quickly and cleanly, requiring no water, no cement, and no imported binder of any kind — a decisive advantage where every imported kilogram is precious.

Turning sintered ceramic into buildings is the province of additive manufacturing. Terrestrial 'contour crafting' has shown that structures can be printed by extruding material in stacked courses under robotic control (Khoshnevis et al., 2005), and the European Space Agency's collaboration with architects demonstrated that a lunar regolith simulant can be built up, layer by layer, into a load-bearing shell (Cesaretti et al., 2014). The Terramother fuses these two proven strands — sinter the local dust, print the local structure — into one continuous process running off a single feedstock: the ground.

4. The Machine Itself

Power is the first constraint. Sintering is energy-hungry, and sunlight on the Moon vanishes for fourteen days at a stretch, so the Terramother carries its own sun: a compact fission reactor of the kind NASA has already ground-tested, delivering tens of kilowatts continuously through the long night (Gibson et al., 2017). This choice cascades through the design — the reactor's waste heat demands large radiators, and its steady output lets the kiln run around the clock, which is what makes a three-week dome possible.

Dust is the second constraint, and on the Moon it is merciless: jagged, electrostatically clinging, and abrasive to every bearing and seal. The intake, separator, and drive systems are therefore designed as a dust-handling machine first and a foundry second, with sealed drives, sacrificial wear surfaces, and an architecture that expects grit everywhere. Autonomy is the third pillar: operating with minutes of light-lag on the Moon and far more at Mars, the Terramother cannot be joysticked, so its build-plan solver surveys the site, lays out the structure, monitors each printed course, and adapts to the inevitable irregularities of real terrain and real feedstock — the same class of autonomy now emerging in terrestrial mining and construction equipment.

5. Operations Concept

Phase one is a technology lander: a stationary sinter-and-print demonstrator that proves the full chain — intake, separation, sintering, extrusion — on real regolith at small scale, producing a paving slab or a low wall. Phase two gives the factory wheels and autonomy, fielding a single Terramother to build the first true infrastructure ahead of a crew: a landing pad to suppress the rocket-blown dust that endangers every landing, then roads, then the first shielded shell. Phase three deploys crawlers in coordinated teams, each specialising — pads, habitats, roads — so that a base of meaningful size stands finished, pressurisable, and radiation-safe before the first human steps out of the lander.

Parameter	Phase 1 (Lander demo)	Phase 2 (Terramother)
Form	stationary printer	18 m tracked crawler
Feedstock	local regolith (small)	local regolith (bulk)
Sintering	microwave/plasma, lab-scale	plasma kiln, ~1,600 °C
Power	solar + battery	fission, tens of kWe
Product	slab / test wall	8 m dome / 21 sols
Autonomy	supervised	fully autonomous

Table 1. Representative parameters for the staged programme.

6. Honest Difficulties

The obstacles are practical and stubborn. Dust is the first and worst: lunar regolith destroys mechanisms, and a machine that eats it for a living must survive years of the most abrasive material humans have engineered around (Taylor and Meek, 2005). The mechanical properties of sintered regolith vary with local mineralogy and with the sintering process, so a structure printed on one site may behave differently from one printed on another, demanding adaptive quality control rather than a fixed recipe (Cesaretti et al., 2014). Fission power in a mobile, autonomous, uncrewed machine raises real questions of safety, shielding, and control (Gibson et al., 2017). And full autonomy in unstructured terrain — surveying, planning, and building without human intervention for weeks — remains at the frontier of robotics, even if it is a frontier advancing quickly on Earth. None of these is a barrier of physics; each is a hard, fundable engineering problem.

7. Pathway to Reality

The building blocks are unusually mature for so ambitious a machine. ISRU has crossed from theory to flight: NASA's MOXIE experiment produced oxygen from the Martian atmosphere aboard the Perseverance rover, proving that a machine can manufacture a consumable from local material on another world. Regolith sintering and additive construction have been demonstrated with simulants and agency partners (Taylor and Meek, 2005; Cesaretti et al., 2014); compact space-fission power has been ground-tested (Gibson et al., 2017); and autonomous heavy equipment is an active terrestrial industry. A coordinated programme could field a stationary demonstrator this decade and a first mobile Terramother on the Moon within roughly two decades — early enough that the structures it prints could shelter some of the first long-duration lunar crews.

8. Conclusion

Humanity has always built its shelters from the ground beneath it — mud, stone, timber, brick — and only briefly, in the improvised early decades of spaceflight, imagined carrying its buildings with it. The Regolith Forge Crawler returns us to the older, wiser habit on a new world. It promises that the first cities beyond Earth will not be unpacked from crates but grown from the regolith, dome by dome, by patient machines that arrive first and prepare the way. When the settlers land, the walls will already be standing, made of the very dust their footprints press into.

References

Harvard referencing style (Cite Them Right).

- Cesaretti, G., Dini, E., De Kestelier, X., Colla, V. and Pambaguian, L. (2014) 'Building components for an outpost on the lunar soil by means of a novel 3D printing technology', *Acta Astronautica*, 93, pp. 430-450.
- Gibson, M.A., Oleson, S.R., Poston, D.I. and McClure, P. (2017) 'NASA's Kilopower reactor development and the path to higher power missions', in *2017 IEEE Aerospace Conference*. Big Sky, MT: IEEE, pp. 1-14.
- Khoshnevis, B., Bodiford, M.P., Burks, K.H., Ethridge, E., Tucker, D., Kim, W., Toutanji, H. and Fiske, M.R. (2005) 'Lunar contour crafting - a novel technique for ISRU-based habitat development', in *43rd AIAA Aerospace Sciences Meeting and Exhibit*, AIAA 2005-538. Reno, NV: American Institute of Aeronautics and Astronautics.
- Taylor, L.A. and Meek, T.T. (2005) 'Microwave sintering of lunar soil: properties, theory, and practice', *Journal of Aerospace Engineering*, 18(3), pp. 188-196.