

AJAX介紹

```
<form action="" method="get">
  <input type="text" name="name">
  <input type="text" name="mobile">
</form>
```



```
// ajax
```

```
$.ajax({
  type: "method",
  url: "url",
  data: "data",
  dataType: "dataType",
  success: function (response) {

  }
});
```

```
<form action="" method="get">
  <input type="text" name="name">
  <input type="text" name="mobile">
</form>
```

送回來的格式

text 少用

json 類似array

```
// ajax
```

```
$.ajax({
  type: "method",
  url: "url",
  data: "data",
  dataType: "dataType",
  success: function (response) {

  }
});
```

```
<form action="" method="get">
  <input type="text" name="name">
  <input type="text" name="mobile">
</form>
```

```
// ajax
```

```
$.ajax({
  type: "method",
  url: "url",
  data: "data",
  dataType: "dataType",
  success: function (response) {
  }
});
```

送回來的格式

text 少用

json 類似array

成功 ...後續處理

外送 自己分類

num1

num2



php

num1, num2

sum

data = [

num1

num2

sum

jQuery Event Methods

[< Previous](#)[Next >](#)

jQuery Event Methods

Event methods trigger or attach a function to an event handler for the selected elements.

The following table lists all the jQuery methods used to handle events.

Method / Property	Description
<u>bind()</u>	Deprecated in version 3.0. Use the <u>on()</u> method instead. Attaches event handlers to elements
<u>blur()</u>	Attaches/Triggers the blur event
<u>change()</u>	Attaches/Triggers the change event
<u>click()</u>	Attaches/Triggers the click event
<u>dblclick()</u>	Attaches/Triggers the double click event
<u>delegate()</u>	Deprecated in version 3.0. Use the <u>on()</u> method instead. Attaches a handler to current, or future, specified child elements of the matching elements

jQuery method 只能用在jQuery Object

```
console.log('this', this);  
console.log('$$(this)', $$(this));
```

```
const myP = $$('.p');  
const myInput = $$('.input');
```

this <p> Lorem ipsum dolor sit amet. </p>
\$\$(this) ▶ ce.fn.init {0: p, length: 1}