# Fertilizer for Gower's Bamboo Growing Company

Contract Consultants: Matthew Knorr, Nels Blair, and Sandy Auttelet

November 28, 2023

## Executive Summary

## Business Parameters

From the initial parameters, our reference numbers are that one meter of bamboo weighs about 10kg and each kg is worth 12 dollars. We can begin selling bamboo once it has grown up to 3 meters. These numbers were used in the calculations throughout this report and can be changed if the market shifts.

## Growth Data

These plots compare the growth of plants in x-grow brand fertilizer and y-grow brand fertilizer. The third plot containing both sets of data marks where plants are eligible to be sold.

If you choose to grow with x fertilizer, your plants will grow faster in the beginning of a 60 day cycle, but the growth rate will begin to decline below the growth rate of y at about 26 days. The plants grown in x or y will come to the same average growth rate and thus same height at 53 days. After 53 days, plants grown with y fertilizer have a higher growth rate for the rest of the duration of the trial experiment. We conclude that there are significant differences in bamboo growth when using the fertilizers from brands x-grow versus y-grow.

## Growth Rates

Table 1: Comparing Fertilizers

| Characteristic | Fertilizer x | Fertilizer y |
|---|---|---|
| Days to 3m | 12.7 | 25.42 |
| Rate of Growth at 3m | 0.46 | 0.232 |
| Optimal Growth Cycle (days) | 20.3 | 48.81 |
| Optimal Choice | Yes | No |

The plants grown in x-grow brand fertilizer are eligible for harvest on the 18 hours into the 13th day after planting. Plants grown in y-grow brand fertilizer are eligible for harvest 13 hours into the 26th day after planting. When the plants reach a height of 3 meters, the growth rates of bamboo with fertilizers x and y are, respectively, 0.46 and 0.232 meters per day.

Generally, it is sub-optimal to harvest a plant which is in the middle of a relatively high-growth period, but may be optimal to harvest directly after such a period. The optimal growth cycles are 20.3 and 48.81 days for x and y, respectively. These cycles will yield a profit of 730 and 1,030 dollars for fertilizer x and y, respectively. It is important to note that these cycles are of different duration. For direct comparison, x yields 34 dollars per day and y yields 21 dollars per day on average in an optimal cycle.

# 1 Decision

| Characteristics | x-grow Fertilizer | y-grow Fertilizer |
|---|---|---|
| Cost per Plant | 1 dollar | 1.25 dollar |
| Profit per Plant in Optimal Cycle of Growth | 690 dollars | 1,030 dollars |

Based on our analysis of the data, we have concluded that x-grow brand fertilizer is the optimal choice if you can harvest repeatedly in 60 days. The cost per plant of fertilizer y (1.25) is negligible compared with the revenue earned from the same plant (1,200). So, we simply disregard this cost of fertilizer without loss of any margin of comparison. The same applies for the cost per plant of fertilizer x (1.00), which in three (optimal) cycles becomes 3 compared with the revenue earned from the same individual physical growth slot (1950). Even though at the end of the full 60 day trial, y is favored, when we include factors like cost of fertilizer (negligible), and length of optimal growing cycle (significantly shorter for x) the clear winner, yielding more dollars per day is fertilizer x.

# 2 Profits of Scale

We assume the company operates at full capacity to produce 20,000 plants in the 60 day time frame, and has the corresponding turnover of product. We seek to use profit per plant, then scale up to 20,000 plants to get a number that represents profits per 60 days at full capacity.

The one dollar or one dollar twenty-five cents cost is actually quite negligible when compared with the revenue generated by each shoot cycle ($1950 and 1200$ for x and y respectively). Therefore, we effectively disregard the cost of each brand of fertilizer and focus on the difference in revenue generated by each optimal cycle.

The output of the above code indicates that fertilizers x and y will grow plants that generate revenue of 39 million and 24 million respectively. The 15 million difference between them is the difference of the total marginal benefit from employing fertilizer x as opposed to fertilizer

y.

# 3 Appendix

```
#Main File
import numpy as np
import pandas as pd
import Build_data_report as BDR
import Plot_data_figures as PDF


#User input business perameters
x_cost = 1.0
y_cost = 1.25
dollar_per_kg = 12
kg_per_m = 10
dollar_per_m = dollar_per_kg*kg_per_m
num_plants = 20000

#x_data = np.loadtxt("x_grow.csv", delimiter=",")
#y_data = np.loadtxt("y_grow.csv", delimiter=",")
x_data = pd.read_csv("C:/Users/sandy/OneDrive/Documents/Summer 2023/Computing - 300/Final/x_grow.csv", delimiter=",")
y_data = pd.read_csv("C:/Users/sandy/OneDrive/Documents/Summer 2023/Computing - 300/Final/y_grow.csv", delimiter=",")
x_data = np.array(x_data)
y_data = np.array(y_data)

x_data_list_0,x_data_list_1 = BDR.build_data_list(x_data)
y_data_list_0,y_data_list_1 = BDR.build_data_list(y_data)

sell_day_x = BDR.find_sell_day(x_data)
sell_day_y = BDR.find_sell_day(y_data)
sell_mom_x = BDR.find_sell_moment(x_data,sell_day_x)
sell_mom_y = BDR.find_sell_moment(y_data,sell_day_y)

x_growth_rate = BDR.find_growth_rate(x_data, sell_day_x)
y_growth_rate = BDR.find_growth_rate(y_data, sell_day_y)
x_growth_rates = BDR.find_growth_rates(x_data)
y_growth_rates = BDR.find_growth_rates(y_data)
x_max_rate, x_max_rate_day = BDR.find_peak_growth(x_data, x_growth_rates)
y_max_rate, y_max_rate_day = BDR.find_peak_growth(y_data, y_growth_rates)

x_optimal_cycle, x_max_profit_per_day = BDR.find_optimal_duration\
    (x_data,x_cost,dollar_per_m,sell_day_x)
y_optimal_cycle, y_max_profit_per_day = BDR.find_optimal_duration\
    (y_data,y_cost,dollar_per_m,sell_day_y)


```

```
44      profit_data_x, cycles_x = BDR.find_profit_data(x_data,sell_day_x,
    dollar_per_m,x_cost)
45      profit_data_y, cycles_y = BDR.find_profit_data(y_data,sell_day_y,
    dollar_per_m,y_cost)
46
47      x_max_profit, x_optimal_cycles = BDR.find_actual_profit(x_data, \
48          sell_day_x, dollar_per_m, x_cost)
49      y_max_profit, y_optimal_cycles = BDR.find_actual_profit(y_data, \
50          sell_day_y, dollar_per_m, y_cost)
51      x_total_profit = x_max_profit*num_plants
52      y_total_profit = y_max_profit*num_plants
53
54      if x_total_profit > y_total_profit:
55          total_saved_money = round((x_total_profit - y_total_profit),2)
56      if y_total_profit > x_total_profit:
57          total_saved_money = round((y_total_profit - x_total_profit),2)
58      if y_total_profit == x_total_profit:
59          total_saved_money = 0
60
61      x_profit_data,x_cycles = BDR.find_profit_data(x_data,sell_day_x,
    dollar_per_m,x_cost)
62      y_profit_data,y_cycles = BDR.find_profit_data(y_data,sell_day_y,
    dollar_per_m,y_cost)
63
64      report_x_profit = BDR.report_million(BDR.find_mantissa(
    x_total_profit))
65      report_y_profit = BDR.report_million(BDR.find_mantissa(
    y_total_profit))
66      report_total_profit = BDR.report_million(BDR.find_mantissa(
    total_saved_money))
67
68      #Plotting data report:
69
70      #Plots curve fit for data
71      PDF.plot_curve_fit_x(x_data_list_0,x_data_list_1)
72      PDF.plot_curve_fit_y(y_data_list_0,y_data_list_1)
73
74      #Plots data as line segment seperately
75      PDF.plot_x_data(x_data_list_0,x_data_list_1)
76      PDF.plot_y_data(y_data_list_0,y_data_list_1)
77
78      #Plots both sets together
79      PDF.plot_x_y_data(x_data_list_0,x_data_list_1,y_data_list_0,
    y_data_list_1)
80      #Plots together with 3m mark
81      PDF.plot_sell_day(x_data_list_0,x_data_list_1,y_data_list_0,
    y_data_list_1)
82
83      #Plots growth rates by day
84      PDF.plot_growth_rate(x_data_list_0,x_data_list_1,y_data_list_0,
    y_data_list_1,x_growth_rates,y_growth_rates)
85
86      #Plots growth per cycle
87      PDF.make_barchart_x(x_profit_data,x_cycles)
```

```
88      PDF.make_barchart_y(y_profit_data,y_cycles)
89
90
91      #Printing report set up for x and y grow brand fertilizer
92
93      #Prints sell day information
94      print(f'We can sell bamboo shoots grown with x fertilizer after \
95      {int(sell_day_x)} days and roughly {int(sell_mom_x)} hours after
    planting.')
96      print(f'\nWe can sell bamboo shoots grown with y fertilizer after \
97      {int(sell_day_y)} days and roughly {int(sell_mom_y)} hours after
    planting.')
98
99      #Prints groth rates
100     print(f'\n\nThe growth rate of bamboo grown with x fertilizer at \
101     point of sell is {BDR.find_mantissa(x_growth_rate)} meters per day.'
    )
102     print(f'\nThe growth rate of bamboo grown with y fertilizer at \
103     point of sell is {BDR.find_mantissa(y_growth_rate)} meters per day.'
    )
104
105     #Printing max rates and analysis of optimal cycles
106     print(f'\n\nFertilizer x results in a peak growth rate of {BDR.
    find_mantissa(x_max_rate)} meters per day on day {round(x_max_rate_day)
    }')
107     print(f'\nFertilizer y results in a peak growth rate of {BDR.
    find_mantissa(y_max_rate)} meters per day on day {round(y_max_rate_day)
    }.')
108
109     #Paragraph specific to this data and visual analysis. Not valid for
    new data.
110     print('\nIf you choose to grow with x fertilizer, your plants will \
111     grow faster in the beginning of a 60 day cycle, but the growth \
112     rate will begin to decline at about 26 days. After about 30 days, \
113     both sets will be growing at roughly the same rate. At this \
114     point, plants grown with y fertilizer will begin to grow faster. \
115     Both plant sets will come to the same average growth rate and \
116     thus same height at 53 days, after which y fertilizer grown \
117     plants have a faster average growth rate.')
118
119     #Prints optimal cycle days and max profit in that cycle
120     print(f'\n\nThe maximum profit per {BDR.find_mantissa(
    x_optimal_cycle)} days, the optimal cycle, per plant \
121     grown in x fertilizer will be {BDR.find_mantissa(
    x_max_profit_per_day*x_optimal_cycle)} dollars.')
122
123     print(f'\nThe maximum profit per {BDR.find_mantissa(y_optimal_cycle)
    } days, the optimal cycle, per plant \
124     grown in y fertilizer will be {BDR.find_mantissa(
    y_max_profit_per_day*y_optimal_cycle)} dollars.')
125
126     #Prints the optimal choice
127     print(f'\n\nThe maximum profit per {BDR.find_mantissa(
    y_optimal_cycle)} \
```

```
        days, the optimal cycle, per plant grown in y fertilizer will be \
        {BDR.find_mantissa(y_max_profit_per_day*y_optimal_cycle)} dollars.')
        if x_max_profit_per_day > y_max_profit_per_day:
            print("\nOptimal fertilizer choice is x because it yields more \
        dollars per day and in the long run pays off.")
        if y_max_profit_per_day > x_max_profit_per_day:
            print("\nOptimal fertilizer choice is y because it yields more \
        dollars per day and in the long run pays off.")
        if x_max_profit_per_day == y_max_profit_per_day:
            print("\nBoth fertilizers are equavalent in optimal profit.")

        #Notes irrelevent cost
        print('\nNote that the cost per plant is negligible because the
    profit is roughly one thousand times larger than the cost.')

        #Prints final data analysis
        print(f'\n\nAfter {len(x_data)} days as {int(BDR.find_mantissa(
    x_optimal_cycles))} \
        cycle(s) of {int(BDR.find_mantissa(len(x_data)/x_optimal_cycles))}
    days in \
        fertilizer x, the profit per plant is {BDR.find_mantissa(
    x_max_profit)}. \
        Therefore, the total profit for all {num_plants} plants at a time \
        is {report_x_profit}.')

        print(f'\nAfter {len(y_data)} days as {int(BDR.find_mantissa(
    y_optimal_cycles))} \
        cycle(s) of {int(BDR.find_mantissa(len(y_data)/y_optimal_cycles))}
    days in \
        fertilizer y, the profit per plant is {BDR.find_mantissa(
    y_max_profit)}. \
        Therefore, the total profit for all {num_plants} plants at a time \
        is {report_y_profit}.')

        print(f'\nFinally, the total profit saved from using the optimal \
        fertilizer is {report_total_profit}')

```

```
1
2       #Build_data_report File for functions
3       import numpy as np
4       import math
5
6       #For rounding later on:
7       def find_mantissa(num):
8           scale = int(round(np.log10(num),0))-3
9           mantissa = int(round(num/10**scale,0))
10          rounded_num = mantissa*10**scale
11          rounded_num = round(rounded_num,3)
12          return rounded_num
13
14      def report_million(num):
15          if num >= 1000000:
16              num = int(num/1000000)
17              return f'{num} Million'
18          if num < 1000000:
19              return num
20
21      #Build data report
22      def build_data_list(data):
23          data_list_0 = []
24          data_list_1 = []
25          for i in range(len(data)):
26              data_list_0.append(data[i][0])
27              data_list_1.append(data[i][1])
28          return data_list_0,data_list_1
29
30      #Finds day eligible for selling
31      def find_sell_day(data):
32          for i in range(len(data)):
33              if data[i][1] >= 3.0:
34                  max_day = data[i][0]
35                  min_day = data[i-1][0]
36                  grow_max = data[i][1]
37                  grow_min = data[i-1][1]
38                  mom_at_3 = ((grow_max-3)*max_day+(3-grow_min)*min_day)/(
    grow_max-grow_min)
39                  return mom_at_3
40          raise Exception("Did not reach 3 meters in observed duration.
    Expand duration or adjust expected height.")
41
42      def find_sell_moment(data,sell_day):
43          extra = sell_day - int(sell_day)
44          extra = 24*extra
45          extra = round(extra,0)
46          return extra
47
48      def find_growth_rate(data, sell_day):
49          for i in range(len(data)):
50              if data[i][0] >= sell_day:
51                  dh = data[i+1][1] - data[i-1][1]
```

```
                dt = data[i+1][0] - data[i-1][0]
                rate = dh/dt
                return rate

    def find_growth_rates(data):
        growth_rates = []
        dh0 = data[1][1] - data[0][1]
        dt0 = data[1][0] - data[0][0]
        growth_rates.append(dh0/dt0)
        dh1 = data[2][1] - data[0][1]
        dt1 = data[2][0] - data[0][0]
        growth_rates.append(dh1/dt1)
        dh2 = data[4][1] - data[0][1]
        dt2 = data[4][0] - data[0][0]
        growth_rates.append(dh2/dt2)
        for i in range(3,len(data)-3):
            dh = data[i+3][1] - data[i-3][1]
            dt = data[i+3][0] - data[i-3][0]
            growth_rates.append(dh/dt)
        dhe = data[len(data)-1][1] - data[len(data)-5][1]
        dte = data[len(data)-1][0] - data[len(data)-5][0]
        growth_rates.append(dhe/dte)
        dhe = data[len(data)-1][1] - data[len(data)-3][1]
        dte = data[len(data)-1][0] - data[len(data)-3][0]
        growth_rates.append(dhe/dte)
        dhe = data[len(data)-1][1] - data[len(data)-2][1]
        dte = data[len(data)-1][0] - data[len(data)-2][0]
        growth_rates.append(dhe/dte)
        return growth_rates

    def find_peak_growth(data,growth_rates):
        new_max_rate = 0
        for i in range(len(growth_rates)):
            max_rate = new_max_rate
            if growth_rates[i] > max_rate:
                max_rate = growth_rates[i]
                max_day = data[i][0]
            new_max_rate = max_rate
        return max_rate, max_day

    def find_optimal_duration(data,cost,dollar_per_m,sell_day):
        t_max = len(data)
        profit = []
        max_day = 0
        new_max = 0
        for i in range(int(round(sell_day,0)),t_max):
            max_profit = new_max
            profit.append((data[i][1]*dollar_per_m-cost)/data[i][0])
            new_max = max(profit)
            if new_max > max_profit:
                max_day = data[i][0]
        return max_day,max_profit

    def find_actual_profit(data,sell_day,dollar_per_m,cost):
```

```
106             cycles = int(math.trunc(len(data)/int(round(sell_day,0))))
107             max_profit = 0
108             for i in range(1,cycles+1):
109                 days = int(math.trunc(len(data)/i))
110                 height = data[days-1][1]
111                 profit = height*dollar_per_m - cost
112                 if profit*i >= max_profit:
113                     max_profit = profit*i
114                     optimal_cycles = i
115             return max_profit, optimal_cycles
116 
117         #For building a histogram
118         def find_actual_profit_cycles(data,sell_day,dollar_per_m,cost,days):
119             if sell_day > days:
120                 raise Exception("The requested duration is shorter than the
    eligible sell day. Choose a longer duration or different fertilizer.")
121             cycles = int(math.trunc(len(data)/int(round(days,0))))
122             height = data[int(round(days,0))-1][1]
123             profit = cycles*(height*dollar_per_m - cost)
124             return find_mantissa(profit)
125 
126         def find_profit_data(data,sell_day,dollar_per_m,cost):
127             num = len(data)
128             nums = [num]
129             profits = []
130             for i in range(2,len(data)):
131                 if num/i < sell_day:
132                     break
133                 nums.append(num/i)
134             for i in range(len(nums)):
135                 profits.append(2*find_actual_profit_cycles(data,sell_day,
    dollar_per_m,cost,nums[i]))
136             return profits, nums
137 
```

```
    #Plot_data_figures file for plotting
    import numpy as np
    import matplotlib.pyplot as plt

    #Functions made for curve fit.
    #Will need to change for different data.
    #constants = sc.optimize.curve_fit(f_y,y_data_list_0,y_data_list_1)

    def f_y(t,x0,x1,x2,x3):
        f = x0/(1+np.exp(-x1*t+x2))+x3
        return f

    def f_x(t,x0,x1,x2,x3,x4,x5,x6,x7,x8):
        f = x0*t**2 + x1*t**3 + x2*t**4 + x3*t + x4 + x5*t**5 + x6*t**6
+ x7*t**7 + x8*t**8
        return f

    def plot_curve_fit_x(x_data_list_0,x_data_list_1):
        tx = np.linspace(min(x_data_list_0),max(x_data_list_0),1000)
        fig1 = plt.figure(1)
        fig1.suptitle("Measured and Fit Data for x-grow", fontsize=16)
        plt.plot(x_data_list_0,x_data_list_1)
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')
        plt.scatter(x_data_list_0,x_data_list_1,color='red')
        plt.plot(tx,f_x(tx,-6.51968382e-02,  1.05973801e-02, -6.73468343
e-04,  2.59080135e-01,
                3.55047909e-01,  2.16533793e-05, -3.77703269e-07,
3.41898145e-09,
               -1.26162606e-11))
        labels = ('Measurements','Polynomial Curve Fit')
        plt.legend(labels)

    def plot_curve_fit_y(y_data_list_0,y_data_list_1):
        ty = np.linspace(min(y_data_list_0),max(y_data_list_0),1000)
        fig2= plt.figure(2)
        fig2.suptitle("Measured and Fit Data for y-grow", fontsize=16)
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')
        plt.scatter(y_data_list_0,y_data_list_1,color='red')
        plt.plot(ty,f_y(ty,10.70286051,  0.09901738,  3.46901829,
0.09466854))
        labels = ('Measurements','Logistic Curve Fit')
        plt.legend(labels)

    #Plot 1 of just x data
    def plot_x_data(x_data_list_0,x_data_list_1):
        fig3 = plt.figure(3)
        fig3.suptitle("Growth with Fertilizer x", fontsize=16)
        plt.plot(x_data_list_0,x_data_list_1)
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')

```

```
    #Plot 2 of just y data
    def plot_y_data(y_data_list_0,y_data_list_1):
        fig4 = plt.figure(4)
        fig4.suptitle("Growth with Fertilizer y", fontsize=16)
        plt.plot(y_data_list_0,y_data_list_1)
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')

    #Plot 3 of x and y data
    def plot_x_y_data(x_data_list_0,x_data_list_1,y_data_list_0,
y_data_list_1):
        fig5 = plt.figure(5)
        fig5.suptitle("Growth with Fertilizer x and y", fontsize=16)
        plt.plot(x_data_list_0,x_data_list_1)
        plt.plot(y_data_list_0,y_data_list_1)
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')
        labels = ('x Fertilizer','y Fertilizer')
        plt.legend(labels)

    #Plot 4 marks where 3m exists to find when we can sell
    def plot_sell_day(x_data_list_0,x_data_list_1,y_data_list_0,
y_data_list_1):
        fig6 = plt.figure(6)
        fig6.suptitle("When We Can Sell", fontsize=16)
        plt.plot(x_data_list_0,x_data_list_1)
        plt.plot(y_data_list_0,y_data_list_1)
        plt.axhline(3,linestyle='--')
        plt.xlabel('Days of Growth')
        plt.ylabel('Height (m)')
        labels = ('x Fertilizer','y Fertilizer','3m Achievement')
        plt.legend(labels)

    #Plot 5 Growth Rate
    def plot_growth_rate(x_data_list_0,x_data_list_1,y_data_list_0,
y_data_list_1,x_growth_rates,y_growth_rates):
        fig7 = plt.figure(7)
        fig7.suptitle("Growth Rates", fontsize=16)
        plt.plot(x_data_list_0,x_growth_rates)
        plt.plot(y_data_list_0,y_growth_rates)
        plt.xlabel('Days of Growth')
        plt.ylabel('Rate of Growth')
        labels = ('x Fertilizer','y Fertilizer')
        plt.legend(labels)

    def make_barchart_x(profit_data,cycles):
        fig8 = plt.figure(8)
        fig8.suptitle("60-Day Profit for Each Cycle Duration in x
Fertilizer", fontsize=16)
        plt.bar(cycles,profit_data)
        plt.xlabel('Cycle Duration in Days')
        plt.ylabel('Profit per Plant in Ten Thousand Dollars')

    def make_barchart_y(profit_data,cycles):
```

```
100           fig9 = plt.figure(9)
101           fig9.suptitle("60-Day Profit for Each Cycle Duration in y
    Fertilizer", fontsize=16)
102           plt.bar(cycles,profit_data)
103           plt.xlabel('Cycle Duration in Days')
104           plt.ylabel('Profit per Plant in Ten Thousand Dollars')
105
```