prodone.ai — Design & Code Styleguide

> ***Stack:*** *React 19 · Vite · Framer Motion · GSAP · Three.js · Lenis smooth scroll · React Router v7*

Table of Contents

1. Design Philosophy
2. Design Tokens
3. Typography
4. Color & Glassmorphism
5. Spacing & Radius
6. Components
7. Animation Conventions
8. Layout System
9. Responsive Breakpoints
10. Code Conventions

---

1. Design Philosophy

The site uses a **"Liquid Glass Dark"** aesthetic — a premium, high-contrast dark theme built around:

- ⬛ **Deep black backgrounds** (`#000` , `#050508`) with a subtle violet-tinted radial glow at the top
- 🔲 **Frosted glass cards** using `backdrop-filter: blur()` with thin white borders
- ✨ **Monochrome + glow** color language — white typography, colored glow orbs (purple / blue / teal / pink)
- 🎞️ **Cinematic motion** — every element enters with a smooth Framer Motion fade + slide
- 📐 **Tight typographic grid** — `letter-spacing: -0.03em` on headings, ultra-high `font-weight: 800–900`

> ⚠️ ***Rule:*** *Never use flat/solid backgrounds for cards — always use translucent glass layers. Never use saturated primary colors (red, blue, green) — use the glow palette instead.*

---

2. Design Tokens

All tokens live in `src/index.css` inside `:root { }` . Reference them via `var(--token-name)` .

2.1 Backgrounds

Token	Value	Usage
`--bg`	`#000`	Page body
`--bg-deep`	`#050508`	Loader, deep overlays
`--bg-card`	`rgba(255,255,255,0.04)`	Default card surface

2.2 Glass Layers

Token	Value	Usage
`--glass-1`	`rgba(255,255,255,0.04)`	Default card bg

`--glass-2`	`rgba(255,255,255,0.07)`	Hover state card bg
`--glass-3`	`rgba(255,255,255,0.11)`	Active / pressed state
`--glass-border`	`rgba(255,255,255,0.10)`	Default card border
`--glass-border-bright`	`rgba(255,255,255,0.22)`	Hover state border
`--glass-shine`	`rgba(255,255,255,0.18)`	`inset 0 1px 0` top sheen

2.3 Glow Palette

Token	Value	Best used for
`--glow-purple`	`rgba(110,60,240,0.55)`	Hero / primary feature orbs
`--glow-blue`	`rgba(40,120,255,0.45)`	Data / stats orbs
`--glow-teal`	`rgba(0,200,180,0.35)`	Success / positive metrics
`--glow-pink`	`rgba(220,60,160,0.35)`	Accent / creative elements

2.4 Text

Token	Value	Usage
`--text-bright`	`#ffffff`	Headings, key numbers
`--text-mid`	`rgba(255,255,255,0.55)`	Body copy, sub-labels
`--text-dim`	`rgba(255,255,255,0.28)`	Captions, metadata

---

3. Typography

3.1 Font Families

```
--font:      'Space Grotesk', sans-serif;  /* Headings, UI labels, buttons */
--font-body: 'Inter', sans-serif;          /* Body paragraphs only */
```

Both are loaded from Google Fonts at the top of `src/index.css`:

```
@import url('https://fonts.googleapis.com/css2?
family=Space+Grotesk:wght@300;400;500;600;700;800&family=Inter:wght@300;400;500;600;700&display
```

3.2 Type Scale

Element	Font-size	Weight	Letter-spacing	Family
`h1` — Hero	`clamp(38px, 4.8vw, 72px)`	800–900	`-0.03em`	Space Grotesk
`h2` — Section	`clamp(36px, 5vw, 64px)`	800	`-0.03em`	Space Grotesk

`h3` — Card title	`20px`	700	`-0.02em`	Space Grotesk
`p` — Body	`15–17px`	400	normal	Inter
`.section-label`	`10px`	700	`0.14em`	Space Grotesk
Captions / meta	`9–11px`	600	`0.06–0.12em`	Space Grotesk
Stat number (large)	`clamp(60px, 8vw, 96px)`	900	`-0.04em`	Space Grotesk

3.3 Gradient Text

Use the `.gradient-text` utility class, or this inline JSX pattern:

```
<span style={{
  background: 'linear-gradient(135deg, #fff 0%, rgba(255,255,255,0.45) 100%)',
  WebkitBackgroundClip: 'text',
  WebkitTextFillColor: 'transparent',
}}>
  Highlighted Word
</span>
```

---

4. Color & Glassmorphism

4.1 The Liquid Glass Formula

Every card / panel follows this exact recipe:

```
background:       rgba(255,255,255,0.04);        /* --glass-1 */
border:           1px solid rgba(255,255,255,0.10); /* --glass-border */
border-radius:    22px–28px;
backdrop-filter:  blur(12px–22px);
-webkit-backdrop-filter: blur(12px–22px);
box-shadow:
  0 8px 40px rgba(0,0,0,0.4),
  inset 0 1px 0 rgba(255,255,255,0.10);          /* top sheen */
```

Always add the 1px top-shine pseudo-element on prominent cards:

```
.my-card::before {
  content: '';
  position: absolute;
  top: 0; left: 20%; right: 20%; height: 1px;
  background: linear-gradient(90deg, transparent, rgba(255,255,255,0.25), transparent);
}
```

4.2 Glow Orbs

Place 1–2 blurred radial-gradient divs behind every major section or card:

```
<div style={{
  position: 'absolute',
  width: '50%', height: '50%',
  background: 'rgba(110,60,240,0.35)',   /* pick from glow palette */
  borderRadius: '50%',
  filter: 'blur(60px)',
  opacity: 0.55,
  pointerEvents: 'none',
  zIndex: 0,
  animation: 'orbPulse 6s ease-in-out infinite',
}} />
```

4.3 Body Background Texture

The global `body` combines:

1. A top-center violet radial gradient (ambient page glow)
2. A subtle `80×80px` grid of 1px lines at `opacity: 0.022`
3. A fixed SVG fractal-noise grain overlay at `opacity: 0.018`

Do not override or remove these on new pages.

---

5. Spacing & Radius

5.1 Border Radius Tokens

Token	Value	Used on
`--r-sm`	`14px`	Chips, tags, small badges
`--r-md`	`22px`	Standard glass cards
`--r-lg`	`32px`	Large panels
`--r-xl`	`48px`	Hero-scale feature cards
`50px` (hardcoded)	—	All pill buttons

> *Video card uses `28px`; CTA blocks use `24px` — these are per-component decisions.*

5.2 Section & Container

```
.section    { padding: 80px 0; }   /* ≤768px → 72px · ≤480px → 56px */
.container  {
  max-width: 1440px;
  margin: 0 auto;
  padding: 0 64px;                 /* ≤1200px → 40px · ≤768px → 20px · ≤480px → 16px */
}
```

5.3 Common Component Padding

Component	Padding
Glass card (default)	`40px 36px`
`.btn-primary`	`14px 30px` (hero CTA: `16px 34px`)
`.btn-ghost`	`13px 26px`
`.btn-outline`	`13px 28px`
`.section-label`	`7px 18px`
`.tool-chip`	`12px 20px`
Hero stat chip	`16px 22px`

---

6. Components

6.1 Buttons

`.btn-primary` — Primary CTA

Solid white pill, black text.

```
<button class="btn-primary">Get Started</button>
```

- Background: `#fff` · Color: `#000` · Border-radius: `50px`
- Hover: `translateY(-3px) scale(1.04)` + white glow shadow
- Has a shimmer `::after` overlay that fades in on hover

`.btn-ghost` — Secondary Action

Frosted glass pill.

```
<button class="btn-ghost">See Examples</button>
```

- Background: `--glass-1` · Border: `1px solid --glass-border`
- `backdrop-filter: blur(12px)`
- Hover: bg → `--glass-2`, border → bright, `translateY(-2px)`

`.btn-outline` — Tertiary Action

Transparent with a white border.

```
<button class="btn-outline">Learn More →</button>
```

- Border-radius: `50px`
- Hover: slight white tint fill + brighter border + subtle glow

> *On screens `≤ 400px` all three button variants go full-width automatically.*

6.2 `.glass-card` — Card Container

```
<div class="glass-card">...</div>
```

- Hover: `translateY(-6px)` lift + brighter border + deeper shadow
- The `::before` top-shine is already included globally
- Add `.glass-card-gpu` when the card contains heavy backdrop-filter content

---

6.3 `.section-label` — Badge Above Headings

```
<div className="section-label">CASE STUDIES</div>
```

- Animated pulsing dot via `::before` + `@keyframes pulse-dot`
- Font: 10px, weight 700, `letter-spacing: 0.14em`, `uppercase`
- Always placed directly above the section `h2`, with `margin-bottom: 24px–32px`

6.4 `.tool-chip` — Integration Logo Chip

```
<div class="tool-chip">
  <img src="tool-logo.svg" alt="Tool Name" />
  <span>Notion</span>
</div>
```

- Min-width: `150px` (mobile: `120px`)
- Hover: `translateY(-3px) scale(1.02)` + brighter border

6.5 `.stat-number` — Metric Highlight

```
<span class="stat-number">98%</span>
```

- `font-size: 3rem`, `font-weight: 900`
- White gradient fill via `--grad-white`

6.6 `.section-divider` — Horizontal Rule

```
<div class="section-divider"></div>
```

- `height: 1px`
- Fades in and out at the edges: `linear-gradient(90deg, transparent, rgba(255,255,255,0.08), transparent)`

6.7 `.grid-overlay` — Subtle Grid

```
<div class="grid-overlay"></div>
```

- Absolute-positioned inside a `position: relative` section
- `80×80px` grid lines at `rgba(255,255,255,0.025)`
- `pointer-events: none; z-index: 0`

6.8 Loader (`App.jsx`)

- Full-screen fixed overlay: `background: #050508`
- Central glass panel: logo + brand name + 2px progress bar
- Exit: Framer Motion `AnimatePresence` with `exit={{ opacity:0, scale:1.05 }}`
- Progress bar glow: `boxShadow: '0 0 10px rgba(255,255,255,0.8)'`

6.9 Marquee (Integration section)

```
<div class="marquee-track">
  <div class="marquee-content marquee-forward">...</div>
</div>
<div class="marquee-track">
  <div class="marquee-content marquee-reverse">...</div>
</div>
```

- Pauses on hover via `animation-play-state: paused`
- Forward row: 32s duration · Reverse row: 26s duration

---

7. Animation Conventions

7.1 Standard Entry Pattern (Framer Motion)

```
const ref = useRef(null)
const inView = useInView(ref, { once: true, margin: '-80px' })

// Label badge
<motion.div
  ref={ref}
  initial={{ opacity: 0, y: 16 }}
  animate={inView ? { opacity: 1, y: 0 } : {}}
  transition={{ duration: 0.7 }}
  className="section-label"
/>

// Section heading
<motion.h2
  initial={{ opacity: 0, y: 32 }}
  animate={inView ? { opacity: 1, y: 0 } : {}}
  transition={{ delay: 0.1, duration: 0.8 }}
/>
```

```
// Body copy
<motion.p
  initial={{ opacity: 0, y: 18 }}
  animate={inView ? { opacity: 1, y: 0 } : {}}
  transition={{ delay: 0.2 }}
/>
```

Always use `once: true` — never re-trigger enter animations on scroll-back.

7.2 Hero / Mount Animations

For above-the-fold elements that animate immediately (no scroll trigger):

```
<motion.h1
  initial={{ opacity: 0, y: 40 }}
  animate={{ opacity: 1, y: 0 }}
  transition={{ duration: 1, delay: 0.3, ease: [0.23, 1, 0.32, 1] }}
/>
```

7.3 Project-wide Easing

```
ease: [0.23, 1, 0.32, 1]   // custom cubic-bezier — fast start, silky landing
```

Transition durations: `0.7s – 1.1s` for major elements, `0.3–0.5s` for hover states.

7.4 CSS Keyframes (for decorative loops)

Defined globally in `src/index.css` — use CSS, not Framer Motion, for looping ambient elements:

```
/* Glow orb pulse */
@keyframes orbPulse {
  0%, 100% { transform: scale(1);    opacity: 0.5;  }
  50%      { transform: scale(1.14); opacity: 0.75; }
}

/* Hero video card orbs */
@keyframes heroGlowFloat {
  0%, 100% { transform: translateY(0) scale(1);    opacity: 0.55; }
  50%      { transform: translateY(-18px) scale(1.12); opacity: 0.8; }
}

/* Section label dot */
@keyframes pulse-dot {
  0%, 100% { opacity: 1;   transform: scale(1);   }
  50%      { opacity: 0.3; transform: scale(0.6); }
}
```

7.5 Hover Transforms — Standard Values

Component	Transform on hover

Large card (CaseCard)	`translateY(-8px) scale(1.02)`
Standard glass card	`translateY(-6px)`
`.btn-primary`	`translateY(-3px) scale(1.04)`
`.btn-ghost` / `.btn-outline`	`translateY(-2px)`
`.tool-chip`	`translateY(-3px) scale(1.02)`

7.6 Delay Stagger Pattern

For sequential sibling elements, stagger `delay` by index:

```
// Section header sequence
// label:  delay 0
// h2:     delay 0.1
// p:      delay 0.2
// CTA:    delay 0.3–0.4

// Array of cards / items
transition={{ duration: 0.5, delay: 1.0 + index * 0.1 }}
```

7.7 Spring Animations (Floating Badges)

```
<motion.div
  initial={{ opacity: 0, scale: 0.6 }}
  animate={{ opacity: 1, scale: 1 }}
  transition={{ duration: 0.6, delay: 1.3, type: 'spring', bounce: 0.45 }}
/>
```

7.8 Scroll Indicator

```
<motion.div
  animate={{ y: [0, 8, 0] }}
  transition={{ repeat: Infinity, duration: 1.6, ease: 'easeInOut' }}
>
  {/* mouse / chevron icon */}
</motion.div>
```

---

8. Layout System

8.1 Page Shell (`App.jsx`)

```
Router
 └─ AnimatePresence
     └─ Loader (until mounted, then fades out)
 └─ motion.div (page fade in)
```

```
    ├─ GlobalParticles   ← full-screen canvas, behind everything
    ├─ Navbar            ← fixed top
    ├─ Suspense fallback=<PageSkeleton>
    │   └─ Routes: Home | Pilot
    ├─ Footer
    └─ Chatbot           ← fixed bottom-right
```

8.2 Section Template

```
<section id="section-id" style={{ position: 'relative', padding: '72px 0', overflow:
'hidden' }}>

  {/* 1. Ambient glow (absolute, behind content) */}
  <div style={{ position: 'absolute', ... }} />

  {/* 2. Content wrapper */}
  <div className="container" style={{ position: 'relative', zIndex: 1 }}>

    {/* 3. Section header: label → h2 → p (centered, maxWidth: 700) */}
    <div style={{ textAlign: 'center', maxWidth: 700, margin: '0 auto 72px' }}>
      <div className="section-label">LABEL</div>
      <h2>Title <span style={{ ...gradientText }}>Accent</span></h2>
      <p>Supporting description.</p>
    </div>

    {/* 4. Content grid */}
    <div style={{ display: 'grid', gridTemplateColumns: 'repeat(2, 1fr)', gap: 28 }}>
      {items.map(...)}
    </div>

  </div>
</section>
```

8.3 Common Grid Templates

Section	Grid	Gap
Hero	`1fr 1fr` (copy + visual)	`80px`
CaseStudies	`repeat(2, 1fr)`	`28px`
Pilot — Results	`repeat(4, 1fr)`	(auto)
Pilot — Deliverables	`repeat(3, 1fr)`	(auto)
HowItWorks	`repeat(3, 1fr)`	(auto)

8.4 Z-index Layers

z-index	What lives here
`0`	Background glow orbs, grid overlay

`1–2`	Section content
`3–4`	In-card overlays (top bar, badges inside a card)
`10`	Hero content (above all backgrounds)
`9999`	Noise grain (fixed, always on top of content)
`99999`	Loader (topmost)

---

9. Responsive Breakpoints

Breakpoint	Target	Key layout changes
`≤ 1200px`	Large laptop	Container padding → `40px`
`≤ 900px`	Tablet landscape	Hero / Pilot grids → 1 col; Compare → 1 col; Results → 2 col
`≤ 768px`	Tablet portrait	Container → `20px`; `h1`/`h2` clamp smaller; footer stacks; cases → 1 col
`≤ 600px`	Large phone	Container → `16px`; Hero padding-top → `100px`; video card → `360px`
`≤ 480px`	Phone	Sections → `56px` vertical; Pilot results → 1 col; buttons stack
`≤ 400px`	Small phone	Results → 1 col; all buttons → `width: 100%`

> *Typography uses `clamp()` throughout, so font sizes scale fluidly — media query overrides are only needed for layout structure.*

---

10. Code Conventions

10.1 Component File Structure

```
// ── 1. Imports (React hooks → Framer Motion → local) ──────────────────
import { useRef, useState } from 'react'
import { motion, useInView } from 'framer-motion'
import { useLanguage } from '../context/LanguageContext'

// ── 2. Sub-components (before main export) ────────────────────────────
function SubCard({ prop }) {
  // ...
}

// ── 3. Main default export ────────────────────────────────────────────
export default function SectionName() {
  const { t } = useLanguage()
  const ref = useRef(null)
  const inView = useInView(ref, { once: true, margin: '-80px' })

  const data = [ /* static data arrays defined inside component */ ]
```

```
  return ( /* JSX */ )
}
```

10.2 Global CSS Class vs Inline Style

Use `.class` (global CSS) for	Use `style={{}}` (inline) for
Reusable primitives: `.btn-primary`, `.glass-card`, `.section-label`, `.tool-chip`	One-off per-component layout: grid columns, specific padding values
Responsive overrides	Framer Motion animated values
Scrollbar, selection, body background	Dynamic values derived from state or props
`@keyframes` animations on decorative elements	Component-specific hover (via Framer Motion `whileHover`)

10.3 i18n — Language Context

All user-visible strings go through the `useLanguage()` context hook:

```
const { t, lang, translations } = useLanguage()

// Single translated string
t('hero.badge')
t('hero.cta')

// Full array from the translation object
const cases = translations[lang].caseStudies.cases
```

Never hardcode English strings directly in JSX. Every text node must use `t()`.

10.4 Performance Rules

Rule	How
GPU-promote animated elements	`willChange: 'transform, opacity'` on hero cards and orbs
Off-screen sections	`content-visibility: auto` (already set globally via `section + section`)
Disable heavy blur on low-end / mobile	Global CSS handles `@media (prefers-reduced-motion), (max-width: 480px)`
Prefer CSS for decorative loops	Use `@keyframes orbPulse` instead of Framer Motion repeating animations
Code-split pages	Use `lazy()` + `Suspense` for all page components
Particle canvas	`ParticleCanvas` is disabled automatically on mobile viewports

10.5 Naming Conventions

Thing	Convention	Example

Component files	PascalCase	`CaseStudies.jsx`, `HowItWorks.jsx`
CSS classes	kebab-case	`.glass-card`, `.section-label`, `.hero-stat-chips`
Section IDs	kebab-case	`id="cases"`, `id="offer"`, `id="integration"`
Translation keys	dot-notation camelCase	`hero.videoCard.title`, `caseStudies.label`
Animation keyframe names	camelCase	`orbPulse`, `heroGlowFloat`, `pulseDot`

Quick Reference

```
── Backgrounds ──────────────────────────────────────────────────────
  Page body:    #000
  Deep surface: #050508
  Card surface: rgba(255,255,255,0.04)

── Glass Card Recipe ────────────────────────────────────────────────
  Default:  bg 0.04 · border 0.10 · blur(12px) · shadow 0 8px 40px rgba(0,0,0,0.4)
  Hover:    bg 0.07 · border 0.22 · translateY(-6px)

── Glow Orbs ────────────────────────────────────────────────────────
  Purple:  rgba(110,60,240,0.35)   Blue:  rgba(30,100,255,0.28)
  Teal:    rgba(0,200,180,0.35)    Pink:  rgba(220,60,160,0.35)

── Text ─────────────────────────────────────────────────────────────
  Bright:  #fff    Mid: rgba(255,255,255,0.55)    Dim: rgba(255,255,255,0.28)

── Fonts ────────────────────────────────────────────────────────────
  Headings / UI: Space Grotesk (wt 300–800)
  Body copy:     Inter (wt 300–700)

── Motion ───────────────────────────────────────────────────────────
  Easing:   cubic-bezier(0.23, 1, 0.32, 1)
  Duration: 0.7s – 1.1s (entries),  0.3s – 0.5s (hovers)

── Layout ───────────────────────────────────────────────────────────
  Container: max-width 1440px · 64px side padding
  Section:   80px vertical padding

── Radius ───────────────────────────────────────────────────────────
  sm 14px · md 22px · lg 32px · xl 48px · pill 50px
```

Last updated: February 2026 — prodone.ai (Fast Forward Artificial Intelligence)