

AePS API

Authentication, catalogs, merchant onboarding, transaction OTP, sale, and lookup. Request fields, status values, and error messages match the current FinPay API.

Client integration guide for the AePS APIs implemented on FinPay.

Base path: `/api/v1`

Every path below is relative to the FinPay API host issued to your company. Send JSON with `Accept: application/json`. POST and other bodies also use `Content-Type: application/json`. The raw body bytes you hash must be the same bytes you send.

This guide describes the current FinPay request and response contract. Catalog list items are returned as received. FinPay does not rename those item fields. Examples use placeholder values. Do not send the placeholders as live customer data.

Sequence

1	HMAC Every request
2	Banks GET <code>/api/v1/aeps/banks</code>
3	Bank IIN GET <code>/api/v1/aeps/bank-iin</code>
4	States GET <code>/api/v1/aeps/states</code>
5	Districts GET <code>/api/v1/aeps/districts</code>
6	Register merchant POST <code>/api/v1/aeps/merchants</code>
7–9	OTP Send, resend, then verify
10	eKYC POST <code>/api/v1/aeps/merchants/{merchant}/ekyc</code>
11	2FA POST <code>/api/v1/aeps/merchants/{merchant}/2fa</code>
12	Transaction OTP Only when CW or AP amount is above 5000

13 Transaction
POST /api/v1/aeps/transactions

14 Lookup
GET /api/v1/aeps/transactions/{reference}

Step	Call	Use the result for
1	HMAC authentication	Every later call
2	Bank catalog	Knowing which banks are available
3	Bank IIN	bank_iin on transaction OTP and sale
4	States	state and shop_state on registration
5	Districts	district and shop_district on registration
6	Register merchant	merchant code on every later merchant and transaction call
7	Send OTP	OTP delivery to the merchant
8	Resend OTP	A replacement OTP, only when required
9	Verify OTP	Confirm the OTP
10	eKYC	Biometric merchant KYC
11	2FA	Biometric merchant two-factor
12	Transaction OTP	Only CW or AP above 5000. Save provider_txn_ref
13	Transaction	The AePS sale or enquiry
14	Transaction lookup	Read that sale again by FinPay reference

Registration must return a merchant that FinPay has registered before OTP, eKYC, 2FA, transaction OTP, or sale. If it has not, those calls return HTTP 422 with Merchant is not registered with the AePS provider.

The sale API does not itself check that OTP, eKYC, or 2FA already succeeded. Complete those steps before a live sale. A merchant code can be used only by the partner that registered it.

Shared rules

Service codes

Code	Meaning	Where it is accepted
CW	Cash withdrawal	Bank IIN lookup and sale
BE	Balance enquiry	Bank IIN lookup and sale
MS	Mini statement	Bank IIN lookup and sale
CD	Cash deposit	Bank IIN lookup and sale
AP	Aadhaar Pay	Bank IIN lookup and sale
CWTFA	Cash withdrawal transaction OTP	Transaction OTP only
APTFA	Aadhaar Pay transaction OTP	Transaction OTP only

Bank IIN auth_type accepts only BA or FA.

Amount rules

Service	Amount
BE , MS	Must be 0
CW , AP , CD	100 to 10000 , inclusive
CWTFA , APTFA	Greater than 5000 and at most 10000 . Validation minimum is 5000.01

CW and AP amounts of 5000 or less do not use transaction OTP. Amounts above 5000 must call transaction OTP first.

Transaction OTP

Call `POST /api/v1/aeps/transaction-otp` only when all of these are true:

- the sale service is CW or AP
- the amount is greater than 5000

Use service CWTFA before a CW sale, and APTFA before an AP sale. Send the OTP response field `provider_txn_ref` as `cw_auth_txn_id` on the sale. It must belong to a successful OTP (`provider_status_code` 000) for the same merchant. BE , MS , and CD do not use this call. A `cw_auth_txn_id` sent below the threshold is accepted and forwarded; it is not required.

client_reference and idempotency

`client_reference` is your identifier, maximum 80 characters.

- Merchant registration: the same `client_reference` for the same partner and the same registration details returns the original merchant and does not register again. HTTP status remains 201 . Different details for that reference return HTTP 409 and This reference was already used with different merchant details.
- Sale and transaction OTP: the same `client_reference` for the same partner and the same transaction details returns the original transaction and does not create another one. HTTP status remains 201 . Different details return HTTP 409 and This reference was already used with different transaction details.
- OTP send, resend, verify, eKYC, and 2FA still require `client_reference` , but they are not idempotent. Each call is processed again. The merchant response field `client_reference` stays the value stored at registration.

Comparison of a repeated sale includes the merchant, service, amount, bank IIN, Aadhaar, mobile, device, coordinates, transaction OTP reference, and biometric payload. Aadhaar, PAN, account number, and biometric data are not returned.

Transaction status

`success: true` means FinPay accepted and stored the outcome. Read `data.status` for the transaction result.

Transaction status code	Transaction status
000	success
001	failed
002	pending
003	validation_failed
Any other or missing code	provider_error

`initiated` and `processing` exist only while a sale is in flight. A completed HTTP response uses one of the five values above. `failure_reason` is set for `failed` and `validation_failed` .

`wallet_effect` and `charge_effect` are `BUSINESS_RULE_PENDING` . These AePS APIs do not debit a wallet, post a charge, settle, or reverse funds.

Merchant ownership

`{merchant}` in the URL and `merchant` in a transaction body are the `merchant` code from registration, shaped like `MCH-` plus 10 characters. FinPay resolves it only for the authenticated partner. Another partner's merchant, or an unknown code, returns HTTP 404 and `Merchant not found`. Transaction lookup is the same: only that partner's `reference` is visible.

Aadhaar in responses

Responses include `aadhaar_masked` only. The form is `x` characters plus the last four digits, for example `xxxxxxx0738`. Full Aadhaar, PID data, OTP, PAN, and account numbers are not returned.

HTTP status summary

HTTP	When
200	Catalog, merchant OTP, resend, verify, eKYC, 2FA, and transaction lookup succeeded at the HTTP layer
201	Merchant registration, transaction OTP, and sale were stored, including an identical replay
400	The API secret was sent in the request
401	HMAC authentication failed
403	The caller IP is not allowed, or API access is not enabled
404	Merchant or transaction was not found for this partner
409	<code>client_reference</code> was reused with different details, or the transaction could not be stored
413	Body larger than 65536 bytes
422	Validation failed, or a business rule failed
429	More than 60 requests per minute for the API key, or too many failed authentication attempts
500 , 502	FinPay could not complete the provider call

Business-rule and not-found bodies:

```
{
  "success": false,
  "message": "Merchant not found."
}
```

Validation bodies use HTTP 422 when `Accept: application/json` is set:

```
{
  "message": "The aadhaar field is required.",
  "errors": {
    "aadhaar": [
      "The aadhaar field is required."
    ]
  }
}
```

Authentication failures:

```
{
  "success": false,
  "message": "Authentication failed."
}
```

Provider-call failures use `success: false` and `message`. A failed provider call after a sale row is created does not return the transaction object. The stored status becomes `provider_error`.

1. Authentication / HMAC

Purpose. Prove that the call comes from your company, from an allowed IP, without sending the API secret.

HTTP method. Applied to every method in this guide.

URL. Every `/api/v1/aeps/...` URL.

Required headers.

Header	Required	Rule
X-API-Key	Yes	Public API key issued by FinPay
X-Timestamp	Yes	Unix time in seconds. Digits only. Within 300 seconds of FinPay time
X-Nonce	Yes	16 to 64 characters. Allowed characters: letters, digits, <code>.</code> , <code>_</code> , <code>-</code> . One use per key inside the 300 second window
X-Signature	Yes	Lowercase hex HMAC-SHA256 of the canonical string, keyed with the API secret
Accept	Yes	<code>application/json</code>
Content-Type	Yes for bodies	<code>application/json</code>

Do not send `X-API-Secret`, `secret_key`, or `api_secret`. That request is rejected with HTTP 400 and `Do not send the API secret`. Sign the request with HMAC-SHA256 instead.

The caller IP must match the whitelist on the credential. An empty whitelist is denied. A single IP or a CIDR range is allowed. The partner account must be active and API access must be enabled. Otherwise HTTP 403 and `API access denied`.

Twenty failed authentication attempts from one IP return HTTP 429 and `Too many failed authentication attempts`. Try again later.

Canonical string. Five lines, separated by `\n` (LF). No trailing newline.

```
timestamp
nonce
METHOD
/path?query
sha256_hex(raw_body)
```

- `METHOD` is uppercase.
- Path starts with `/` and includes the query string exactly as sent. Parameter order is part of the signature. No query string means no `?`.
- Hash the raw body. An empty body hashes to `e3b0c44298fc1c149afb4c8996fb92427ae41e4649b934ca495991b7852b855`.

Example, not a live credential.

```
1711929600
a1b2c3d4e5f67890
GET
/api/v1/aeps/banks
e3b0c44298fc1c149afb4c8996fb92427ae41e4649b934ca495991b7852b855
```

HMAC-SHA256 with secret `example-secret-do-not-use`:

```
a7abc0384352ac10271e5ca3e33e1e417e5f944a7d732137b590b68e38ee82b7
```

Request parameters. None for authentication itself.

Success. Authentication has no body of its own. The next API returns its own success status.

Error example.

```
{
  "success": false,
  "message": "Authentication failed."
}
```

Next. `GET /api/v1/aeps/banks`.

2. GET `/api/v1/aeps/banks`

Purpose. List banks available for AePS.

HTTP method. `GET`

URL. `/api/v1/aeps/banks`

Required headers. Authentication headers. No body.

Request parameters. None.

JSON request example. No body. Sign the empty-string hash.

Success HTTP status. `200`

Success JSON example. `data` is the catalog list. If the result is not a list, `data` is the redacted object.

```
{
  "success": true,
  "data": []
}
```

Error example.

```
{
  "success": false,
  "message": "Authentication failed."
}
```

Validation. No request fields.

Next. `GET /api/v1/aeps/bank-iiin` with the service you will transact.

3. GET /api/v1/aeps/bank-iin

Purpose. List bank IIN records for one AePS service and authentication type.

HTTP method. GET

URL. /api/v1/aeps/bank-iin

Required headers. Authentication headers. No body. Put parameters in the query string and include that exact query string in the signed path.

Request parameters.

Field	In	Type	Required	Validation
txn_code	Query	string	Required	CW , BE , MS , AP , or CD
auth_type	Query	string	Required	BA or FA

JSON request example. There is no JSON body.

```
GET /api/v1/aeps/bank-iin?txn_code=BE&auth_type=BA
```

Success HTTP status. 200

Success JSON example.

```
{
  "success": true,
  "data": []
}
```

Use the IIN value from a returned record as `bank_iin` later. FinPay does not rename catalog fields.

Error example.

```
{
  "message": "The txn code field is required.",
  "errors": {
    "txn_code": [
      "The txn code field is required."
    ]
  }
}
```

Next. GET /api/v1/aeps/states when you still need to register a merchant. If the merchant already exists, continue at transaction OTP only when the amount rule requires it, otherwise POST /api/v1/aeps/transactions .

4. GET /api/v1/aeps/states

Purpose. List states for merchant and shop addresses.

HTTP method. GET

URL. /api/v1/aeps/states

Required headers. Authentication headers. No body.

Request parameters. None.

JSON request example. No body.

Success HTTP status. 200

Success JSON example.

```
{
  "success": true,
  "data": []
}
```

Error example.

```
{
  "success": false,
  "message": "API access denied."
}
```

Validation. No request fields.

Next. GET /api/v1/aeps/districts with a state_code from this list.

5. GET /api/v1/aeps/districts

Purpose. List districts for one state.

HTTP method. GET

URL. /api/v1/aeps/districts

Required headers. Authentication headers. No body. Sign the path including the query string.

Request parameters.

Field	In	Type	Required	Validation
state_code	Query	string	Required	Maximum 10 characters

JSON request example. No body.

```
GET /api/v1/aeps/districts?state_code=24
```

24 is an example code, not a guaranteed state code. Use a code from the states API.

Success HTTP status. 200

Success JSON example.

```
{
  "success": true,
  "data": []
}
```

Error example.

```
{
  "message": "The state code field is required.",
  "errors": {
    "state_code": [
      "The state code field is required."
    ]
  }
}
```

Next. `POST /api/v1/aeps/merchants`.

6. POST `/api/v1/aeps/merchants`

Purpose. Register an AePS merchant for the authenticated partner.

HTTP method. `POST`

URL. `/api/v1/aeps/merchants`

Required headers. Authentication headers plus `Content-Type: application/json`.

Request parameters.

Field	Type	Required	Validation
client_reference	string	Required	Maximum 80. Idempotency key for this registration
pipe	string	Required	Maximum 10
first_name	string	Required	Maximum 80
middle_name	string	Optional	Maximum 80
last_name	string	Required	Maximum 80
dob	string	Required	Date d-m-Y
email	string	Required	Email, maximum 120
phone	string	Required	Maximum 15
address1	string	Required	Maximum 255
address2	string	Optional	Maximum 255
state	string	Required	Maximum 10. Use a state code
district	string	Required	Maximum 10. Use a district code
gender	string	Required	M , F , or O
shop_name	string	Required	Maximum 120
mother_name	string	Required	Maximum 120
father_name	string	Required	Maximum 120
marital_status	string	Required	SINGLE or MARRIED
mcc	string	Required	Maximum 10
device_ip	string	Required	IP address
pin_code	string	Required	Maximum 10
pan	string	Required	Maximum 10
aadhaar	string	Required	Maximum 16
shop_pan	string	Required	Maximum 10
bank_account	string	Required	Maximum 30
bank_ifsc	string	Required	Maximum 20
bank_name	string	Required	Maximum 20
account_type	string	Optional	Maximum 40
shop_address	string	Required	Maximum 255
shop_district	string	Required	Maximum 10
shop_state	string	Required	Maximum 10
shop_pin	string	Required	Maximum 10
shop_lat	string	Required	Maximum 20
shop_long	string	Required	Maximum 20
lat	string	Required	Maximum 20
long	string	Required	Maximum 20
ip_address	string	Required	IP address

JSON request example. Identity numbers below are placeholders.

```
{
  "client_reference": "MERCHANT-1001",
  "pipe": "1",
  "first_name": "Asha",
  "middle_name": "",
  "last_name": "Shah",
  "dob": "01-01-1990",
  "email": "merchant@example.com",
  "phone": "98XXXXXX10",
  "address1": "Shop 1, Example Road",
  "address2": "",
  "state": "24",
  "district": "476",
  "gender": "F",
  "shop_name": "Example Stores",
  "mother_name": "Example Mother",
  "father_name": "Example Father",
  "marital_status": "MARRIED",
  "mcc": "5411",
  "device_ip": "203.0.113.10",
  "pin_code": "380001",
  "pan": "ABCDE1234F",
  "aadhaar": "XXXXXXXX0738",
  "shop_pan": "ABCDE1234F",
  "bank_account": "000000000000",
  "bank_ifsc": "SBIN0000001",
  "bank_name": "Example Bank",
  "account_type": "SAVINGS",
  "shop_address": "Shop 1, Example Road",
  "shop_district": "476",
  "shop_state": "24",
  "shop_pin": "380001",
  "shop_lat": "23.0722",
  "shop_long": "72.6269",
  "lat": "23.0722",
  "long": "72.6269",
  "ip_address": "203.0.113.10"
}
```

On a live call, `aadhaar` is the customer Aadhaar number. The response never echoes it.

Success HTTP status. `201`

Success JSON example.

```
{
  "success": true,
  "data": {
    "merchant": "MCH-EXAMPLE01",
    "client_reference": "MERCHANT-1001",
    "onboarding_status": "success",
    "provider_status_code": "000",
    "provider_status_description": "Success",
    "provider_ref": "example-provider-ref",
    "aadhaar_masked": "XXXXXXXX0738",
    "two_fa_at": null
  }
}
```

`onboarding_status` follows the transaction status mapping when a three-digit provider code is present. `two_fa_at` is `null` until 2FA returns `000`. Description and reference strings come from the provider result and may be `null`.

An identical registration replay also returns HTTP `201` and this same object. A provider failure that throws returns `success: false` and can leave `onboarding_status` as `provider_error`. Repeating the same reference then returns that stored merchant and does not register again.

Error example.

```
{
  "success": false,
  "message": "This reference was already used with different merchant details."
}
```

Next. POST `/api/v1/aeps/merchants/{merchant}/otp` using `data.merchant`.

7. POST `/api/v1/aeps/merchants/{merchant}/otp`

Purpose. Send the merchant onboarding OTP.

HTTP method. POST

URL. `/api/v1/aeps/merchants/{merchant}/otp`

`{merchant}` is the registration `merchant` code. Allowed characters: letters, digits, and `-`.

Required headers. Authentication headers plus `Content-Type: application/json`.

Request parameters.

Field	Type	Required	Validation
<code>client_reference</code>	string	Required	Maximum 80

JSON request example.

```
{
  "client_reference": "MERCHANT-1001-OTP"
}
```

Success HTTP status. `200`

Success JSON example. Same object shape as registration. `client_reference` in the response remains the registration reference. `onboarding_status` and `provider_status_code` reflect this OTP call.

```
{
  "success": true,
  "data": {
    "merchant": "MCH-EXAMPLE01",
    "client_reference": "MERCHANT-1001",
    "onboarding_status": "success",
    "provider_status_code": "000",
    "provider_status_description": "OTP sent",
    "provider_ref": "example-provider-ref",
    "aadhaar_masked": "XXXXXXXX0738",
    "two_fa_at": null
  }
}
```

Error example.

```
{
  "success": false,
  "message": "Merchant not found."
}
```

Next. POST `/api/v1/aeps/merchants/{merchant}/otp/verify` after the merchant receives the OTP. If another OTP is required, call resend first.

8. POST `/api/v1/aeps/merchants/{merchant}/otp/resend`

Purpose. Send another onboarding OTP.

HTTP method. POST

URL. `/api/v1/aeps/merchants/{merchant}/otp/resend`

Required headers. Authentication headers plus `Content-Type: application/json`.

Request parameters.

Field	Type	Required	Validation
<code>client_reference</code>	string	Required	Maximum 80

JSON request example.

```
{
  "client_reference": "MERCHANT-1001-OTP-2"
}
```

Success HTTP status. 200

Success JSON example. Same merchant object as the send OTP response.

Error example.

```
{
  "success": false,
  "message": "Merchant is not registered with the AePS provider."
}
```

Next. POST /api/v1/aeps/merchants/{merchant}/otp/verify.

9. POST /api/v1/aeps/merchants/{merchant}/otp/verify

Purpose. Verify the onboarding OTP.

HTTP method. POST

URL. /api/v1/aeps/merchants/{merchant}/otp/verify

Required headers. Authentication headers plus Content-Type: application/json.

Request parameters.

Field	Type	Required	Validation
client_reference	string	Required	Maximum 80
otp	string	Required	Maximum 10. The OTP the merchant received

JSON request example.

```
{
  "client_reference": "MERCHANT-1001-VERIFY",
  "otp": "000000"
}
```

000000 is a placeholder. Send the OTP that was delivered. FinPay does not return the OTP.

Success HTTP status. 200

Success JSON example. Same merchant object. Treat provider_status_code 000 as verified.

Error example.

```
{
  "message": "The otp field is required.",
  "errors": {
    "otp": [
      "The otp field is required."
    ]
  }
}
```

Next. POST /api/v1/aeps/merchants/{merchant}/ekyc.

10. POST /api/v1/aeps/merchants/{merchant}/ekyc

Purpose. Submit merchant biometric eKYC.

HTTP method. POST

URL. /api/v1/aeps/merchants/{merchant}/ekyc

Required headers. Authentication headers plus Content-Type: application/json.

Request parameters.

Field	Type	Required	Validation
client_reference	string	Required	Maximum 80
pid_data	string	Required	Maximum 20000 characters. Biometric capture payload

JSON request example.

```
{
  "client_reference": "MERCHANT-1001-EKYC",
  "pid_data": "<PidData>BIOMETRIC_CAPTURE</PidData>"
}
```

Replace `pid_data` with the capture from the biometric device. Do not log it. FinPay does not return it.

Success HTTP status. `200`

Success JSON example. Same merchant object. `provider_status_code 000` means eKYC succeeded.

Error example.

```
{
  "message": "The pid data field is required.",
  "errors": {
    "pid_data": [
      "The pid data field is required."
    ]
  }
}
```

Next. `POST /api/v1/aeps/merchants/{merchant}/2fa`.

11. POST /api/v1/aeps/merchants/{merchant}/2fa

Purpose. Complete merchant biometric two-factor authentication.

HTTP method. `POST`

URL. `/api/v1/aeps/merchants/{merchant}/2fa`

Required headers. Authentication headers plus `Content-Type: application/json`.

Request parameters.

Field	Type	Required	Validation
<code>client_reference</code>	string	Required	Maximum 80
<code>aadhaar</code>	string	Required	Maximum 16
<code>device_type</code>	string	Required	Maximum 40. Biometric device name
<code>pid_data</code>	string	Required	Maximum 20000 characters
<code>lat</code>	string	Required	Maximum 20
<code>long</code>	string	Required	Maximum 20

JSON request example.

```
{
  "client_reference": "MERCHANT-1001-2FA",
  "aadhaar": "XXXXXXXX0738",
  "device_type": "mantra",
  "pid_data": "<PidData>BIOMETRIC_CAPTURE</PidData>",
  "lat": "23.0722",
  "long": "72.6269"
}
```

Success HTTP status. 200

Success JSON example. When the provider code is 000, two_fa_at is an ISO-8601 timestamp. FinPay does not expire that timestamp.

```
{
  "success": true,
  "data": {
    "merchant": "MCH-EXAMPLE01",
    "client_reference": "MERCHANT-1001",
    "onboarding_status": "success",
    "provider_status_code": "000",
    "provider_status_description": "Two FA done",
    "provider_ref": "example-provider-ref",
    "aadhaar_masked": "XXXXXXXX0738",
    "two_fa_at": "2026-10-01T07:30:00+00:00"
  }
}
```

Error example.

```
{
  "success": false,
  "message": "Merchant not found."
}
```

Next. For BE, MS, CD, or for CW/AP of 5000 or less, call POST /api/v1/aeps/transactions. For CW or AP above 5000, call POST /api/v1/aeps/transaction-otp first.

12. POST /api/v1/aeps/transaction-otp

Purpose. Request the transaction OTP required before a high-value cash withdrawal or Aadhaar Pay.

HTTP method. POST

URL. /api/v1/aeps/transaction-otp

When to call. Only for a following CW sale (service CWTFA) or AP sale (service APTFA) whose amount is greater than 5000. Do not call it for BE, MS, or CD.

Required headers. Authentication headers plus Content-Type: application/json.

Request parameters.

Field	Type	Required	Validation
client_reference	string	Required	Maximum 80. Idempotency key for this OTP transaction
merchant	string	Required	Maximum 40. Merchant code you own
aadhaar	string	Required	Maximum 16
mobile	string	Required	Maximum 15
bank_iin	string	Required	Maximum 10
lat	string	Required	Maximum 20
long	string	Required	Maximum 20
ip_address	string	Required	IP address
service	string	Required	CWTFA or APTFA
amount	number	Required	Greater than 5000 and at most 10000
app_platform	string	Required	Maximum 30
app_version	string	Required	Maximum 20
customer_mobile	string	Optional	Maximum 15

JSON request example.

```
{
  "client_reference": "TXN-OTP-1001",
  "merchant": "MCH-EXAMPLE01",
  "aadhaar": "XXXXXXXX0738",
  "mobile": "98XXXXXX10",
  "bank_iin": "000000",
  "lat": "23.0722",
  "long": "72.6269",
  "ip_address": "203.0.113.10",
  "service": "CWTFA",
  "amount": 5001,
  "app_platform": "android",
  "app_version": "1.0.0",
  "customer_mobile": "98XXXXXX10"
}
```

Success HTTP status. 201

Success JSON example. Save provider_txn_ref when provider_status_code is 000.

```
{
  "success": true,
  "data": {
    "reference": "AEP-EXAMPLE0TP1",
    "client_reference": "TXN-OTP-1001",
    "merchant": "MCH-EXAMPLE01",
    "service": "CWTFa",
    "amount": 5001,
    "status": "success",
    "provider_status_code": "000",
    "provider_txn_ref": "example-otp-txn-ref",
    "rrn": null,
    "npci_code": null,
    "npci_message": null,
    "provider_status_description": null,
    "provider_available_balance": null,
    "transaction_list": null,
    "aadhaar_masked": "XXXXXXXX0738",
    "bank_iin": "000000",
    "wallet_effect": "BUSINESS_RULE_PENDING",
    "charge_effect": "BUSINESS_RULE_PENDING",
    "failure_reason": null,
    "created_at": "2026-10-01T07:30:00+00:00"
  }
}
```

`transaction_list` is a string when present, otherwise `null`. `amount` is a JSON number.

Error example.

```
{
  "success": false,
  "message": "Transaction OTP type must be CWTFa or APTFa."
}
```

An amount of `5000` or less fails validation (`min:5000.01`) before that business check.

Next. POST `/api/v1/aeps/transactions` with `cw_auth_txn_id` set to `provider_txn_ref`, service `CW` or `AP`, and the same merchant.

13. POST `/api/v1/aeps/transactions`

Purpose. Run a balance enquiry, mini statement, cash withdrawal, cash deposit, or Aadhaar Pay.

HTTP method. POST

URL. `/api/v1/aeps/transactions`

Required headers. Authentication headers plus `Content-Type: application/json`.

Request parameters.

Field	Type	Required	Validation
client_reference	string	Required	Maximum 80. Idempotency key
merchant	string	Required	Maximum 40. Merchant code you own
aadhaar	string	Required	Maximum 16
mobile	string	Required	Maximum 15
bank_iin	string	Required	Maximum 10. From the bank IIN catalog
lat	string	Required	Maximum 20
long	string	Required	Maximum 20
ip_address	string	Required	IP address
service	string	Required	CW, BE, MS, AP, or CD
amount	number	Required	0 to 10000, then the service amount rule
device_type	string	Required	Maximum 40
pid_data	string	Required	Maximum 20000 characters
cw_auth_txn_id	string	Conditional	Maximum 120. Required for CW and AP when amount is greater than 5000
udf1	string	Optional	Maximum 100
udf2	string	Optional	Maximum 100
udf3	string	Optional	Maximum 100

Additional business rules after validation:

- BE and MS amount must be 0, or HTTP 422 and Balance enquiry and mini statement amount must be 0.
- CW, AP, and CD amount must be from 100 to 10000, or HTTP 422 and Transaction amount must be between 100 and 10000.
- CW or AP above 5000 without cw_auth_txn_id returns HTTP 422 and cw_auth_txn_id is required for CW and AP amounts above 5000. Use the txnRefId returned by the transaction OTP API.
- A value that is not a successful OTP provider_txn_ref for this merchant returns HTTP 422 and cw_auth_txn_id does not match a successful transaction OTP reference for this merchant.

The txnRefId named in that error is returned to you as provider_txn_ref.

JSON request example, balance enquiry.

```
{
  "client_reference": "TXN-BE-1001",
  "merchant": "MCH-EXAMPLE01",
  "aadhaar": "XXXXXXXX0738",
  "mobile": "98XXXXXX10",
  "bank_iin": "000000",
  "lat": "23.0722",
  "long": "72.6269",
  "ip_address": "203.0.113.10",
  "service": "BE",
  "amount": 0,
  "device_type": "mantra",
  "pid_data": "<PidData>BIOMETRIC_CAPTURE</PidData>"
}
```

JSON request example, cash withdrawal above 5000.

```
{
  "client_reference": "TXN-CW-1001",
  "merchant": "MCH-EXAMPLE01",
  "aadhaar": "XXXXXXXX0738",
  "mobile": "98XXXXXX10",
  "bank_iin": "000000",
  "lat": "23.0722",
  "long": "72.6269",
  "ip_address": "203.0.113.10",
  "service": "CW",
  "amount": 5001,
  "device_type": "mantra",
  "pid_data": "<PidData>BIOMETRIC_CAPTURE</PidData>",
  "cw_auth_txn_id": "example-otp-txn-ref"
}
```

Success HTTP status. 201

HTTP 201 with `success: true` is also returned when the stored `status` is `failed`, `pending`, `validation_failed`, or `provider_error`. Read `data.status`.

Success JSON example.

```
{
  "success": true,
  "data": {
    "reference": "AEP-EXAMPLE1234",
    "client_reference": "TXN-BE-1001",
    "merchant": "MCH-EXAMPLE01",
    "service": "BE",
    "amount": 0,
    "status": "success",
    "provider_status_code": "000",
    "provider_txn_ref": "example-txn-ref",
    "rrn": "000000000000",
    "npci_code": null,
    "npci_message": null,
    "provider_status_description": null,
    "provider_available_balance": null,
    "transaction_list": null,
    "aadhaar_masked": "XXXXXXXX0738",
    "bank_iin": "000000",
    "wallet_effect": "BUSINESS_RULE_PENDING",
    "charge_effect": "BUSINESS_RULE_PENDING",
    "failure_reason": null,
    "created_at": "2026-10-01T07:30:00+00:00"
  }
}
```

`reference` is the FinPay id, shaped like `AEP-` plus 12 characters. Use it for lookup. `provider_txn_ref` and `rrn` may be `null` when the provider does not return them. `provider_available_balance` is a string when present.

Error example.

```
{
  "success": false,
  "message": "cw_auth_txn_id is required for CW and AP amounts above 5000. Use the txnRefId returned by the transaction OTP API."
}
```

Next. GET `/api/v1/aeps/transactions/{reference}` to read the stored result.

14. GET `/api/v1/aeps/transactions/{reference}`

Purpose. Read one AePS transaction for the authenticated partner.

HTTP method. GET

URL. `/api/v1/aeps/transactions/{reference}`

`{reference}` is `data.reference` from the sale or transaction OTP response. Allowed characters: letters, digits, and `-`. This is not `client_reference`.

Required headers. Authentication headers. No body.

Request parameters. None beyond the URL reference.

JSON request example. No body.

```
GET /api/v1/aeps/transactions/AEP-EXAMPLE1234
```

Success HTTP status. 200

Success JSON example. The same transaction object returned when the sale was created, including `status`, `provider_txn_ref`, `rrn`, `aadhaar_masked`, `wallet_effect`, and `charge_effect`.

```
{
  "success": true,
  "data": {
    "reference": "AEP-EXAMPLE1234",
    "client_reference": "TXN-BE-1001",
    "merchant": "MCH-EXAMPLE01",
    "service": "BE",
    "amount": 0,
    "status": "success",
    "provider_status_code": "000",
    "provider_txn_ref": "example-txn-ref",
    "rrn": "0000000000000",
    "npci_code": null,
    "npci_message": null,
    "provider_status_description": null,
    "provider_available_balance": null,
    "transaction_list": null,
    "aadhaar_masked": "XXXXXXXXX0738",
    "bank_iin": "000000",
    "wallet_effect": "BUSINESS_RULE_PENDING",
    "charge_effect": "BUSINESS_RULE_PENDING",
    "failure_reason": null,
    "created_at": "2026-10-01T07:30:00+00:00"
  }
}
```

Error example.

```
{
  "success": false,
  "message": "Transaction not found."
}
```

Validation. Unknown characters in the reference do not match this route.

Next. None. This is a read of a transaction you already created.

Response fields

Merchant object

Returned by registration, OTP, resend, verify, eKYC, and 2FA.

Field	Type	Meaning
merchant	string	FinPay merchant code
client_reference	string	Reference stored at registration
onboarding_status	string	Latest mapped onboarding status
provider_status_code	string or null	Three-digit provider code when present
provider_status_description	string or null	Provider description of this call
provider_ref	string or null	Provider reference when present
aadhaar_masked	string or null	Masked Aadhaar
two_fa_at	string or null	ISO-8601 time after 2FA code 000

Transaction object

Returned by transaction OTP, sale, and lookup.

Field	Type	Meaning
reference	string	FinPay transaction id
client_reference	string	Your idempotency key
merchant	string or null	Merchant code
service	string	Service code stored for the call
amount	number	Amount
status	string	FinPay status
provider_status_code	string or null	Provider code
provider_txn_ref	string or null	Provider transaction reference. This is the OTP value to send as cw_auth_txn_id
rrn	string or null	RRN when returned
npci_code	string or null	NPCI code when returned
npci_message	string or null	NPCI message when returned
provider_status_description	string or null	Provider description
provider_available_balance	string or null	Balance string when returned
transaction_list	string or null	Mini-statement text when returned
aadhaar_masked	string or null	Masked Aadhaar
bank_iin	string or null	Bank IIN sent on the call
wallet_effect	string	BUSINESS_RULE_PENDING
charge_effect	string	BUSINESS_RULE_PENDING
failure_reason	string or null	Set for failed and validation-failed outcomes
created_at	string or null	ISO-8601 creation time