ALLIANCEPE

API Integration Documentation

Payments • Wallet • Payouts • Webhooks

API Base URL
https://alliancepe.com/api

Structured reference prepared from the API text supplied in this conversation. Examples and behavior below are source-derived; the live API has not been independently tested.

Authentication: send `Authorization: Bearer YOUR_API_KEY` on requests.

Important: The source gives two different pay-in maximums: ■9,999 in the limits section and ■50,000 in an example error. Confirm the effective merchant limit before production use.

Prepared 24 October 2026

Contents & endpoint quick reference

Method	Endpoint	Purpose
POST	/payments/intents	Create payment intent
GET	/payments/intents/{transactionId}	Get intent status/details
GET	/payments/transactions/{transactionId}	Get payment by transaction ID
GET	/wallet/balance	Get available wallet balance
POST	/payouts	Create payout
GET	/payouts/{payoutId}	Get payout details/status
GET	/api/payouts/payout/{payoutId}	Alternative payout lookup
GET	/payouts	List payouts with filters/pagination

1. Overview, authentication & limits

All requests use the base URL https://alliancepe.com/api. Include the API key in the Authorization Bearer header; JSON requests use Content-Type: application/json.

```
Authorization: Bearer YOUR_API_KEY
Content-Type: application/json
```

Rate limits

Item	Documented behavior
Default limit	1,000 requests/hour per API key across /payments, /payouts and /wallet
Window	Fixed window; allowance resets when the window rolls over
HTTP 429	Retry-After gives seconds until reset. Wait, then retry with exponential backoff; avoid tight loops.
Payment effect	A 429 means request was not processed; no payment was created.
Safe retry	Reuse the same clientTransactionId to retrieve the original intent rather than creating another charge.

Default limits & fees

Operation	Minimum	Maximum / fee	Applies to
Pay-in	■100	■9,999	Payment intents, hosted checkout, public payment page
Payout	■100	■1,00,000	API, dashboard and batch payouts
Refund	—	■500 / transaction	Refund fee
Chargeback	—	■1,000 / transaction	Chargeback fee

Ranges are inclusive. Account-level and gateway limits may narrow the effective range. Out-of-range requests are rejected with HTTP 400 AMOUNT_OUT_OF_RANGE before creation/debit; error.details.source identifies the applicable bound.

Source inconsistency: a later sample error says “Maximum payin amount is ■50,000,” conflicting with the ■9,999 default above. See final section.

2. Create a payment intent

Endpoint: POST /payments/intents

Creates a pay-in intent for UPI integration. callbackUrl is an optional HTTPS URL for transaction-specific webhook delivery.

```
POST https://alliancepe.com/api/payments/intents
Authorization: Bearer YOUR_API_KEY
Content-Type: application/json

{
  "amount": 1500,
  "currency": "INR",
  "description": "Payment for Order #12345",
  "customerEmail": "customer@example.com",
  "customerPhone": "9876543210",
  "customerName": "John Doe",
  "paymentMethod": "upi",
  "callbackUrl": "https://yourapp.com/webhooks/payment-callback",
  "includeQrImage": false,
  "metadata": {"orderId": "12345", "userId": "user_123"}
}
```

Idempotency / duplicate-payment protection

- Use clientTransactionId in the request body OR the Idempotency-Key header. If both are present, clientTransactionId takes precedence.
- Keys are scoped to the merchant account. metadata.orderId, description and customer details do not themselves provide idempotency.
- The source says comparison uses amount, currency, paymentMethod and callbackUrl; changing description/customer/metadata does not make a request different.

Case	Expected result
No key	Each request creates a new transaction; identical requests may create multiple payments.
Same key + same request	HTTP 200; original intent returned with idempotent: true.
Same key + different request	HTTP 422, IDEMPOTENCY_CONFLICT; response includes existing transaction ID/details.

Success response (representative fields)

```
{
  "success": true,
  "message": "Payment intent created successfully",
  "data": {
    "paymentIntentId": "550e8400-e29b-41d4-a716-446655440000",
    "transactionId": "PG1759098589901F16172B8",
    "amount": 1500, "currency": "INR", "status": "pending",
    "createdAt": "2025-09-28T22:29:50.559Z",
    "expiresAt": "2025-09-28T22:34:50.559Z", "ttlSeconds": 300,
    "intentUrl": "upi://pay?... ", "qrString": "upi://pay?... ",
    "qrCode": "https://rzp.io/i/BWcUVrLp",
    "qrImageUrl": "https://rzp.io/i/BWcUVrLp"
  }
}
```

Response rendering and expiry

- **intentUrl:** primary UPI deep link on the payer device; it opens a UPI app with amount pre-filled.
- **qrString:** raw UPI payload; recommended for client-side QR rendering. qrCode / qrImageUrl are hosted image URLs, not image data.
- **upiApps:** GPay, PhonePe and Paytm deep links may be returned; null-check optional QR/UPI fields.
- **checkoutUrl:** if present, redirect to hosted checkout. intentUrl may be null and QR fields absent. Branch on the response field, not gateway identity.
- includeQrImage=true may add qrImage as a 256px PNG data URI, only when qrString exists.
- Use ttlSeconds as authoritative; do not rely on the payer device clock. At expiry, create a new intent with a new clientTransactionId; do not reuse expired links/IDs.
- Unpaid pay-ins become expired, not failed. The source says late successes can still be recovered through final/repeated status checks and webhooks.

Gateway unavailable

The API may return success=true while status remains pending and payment fields are absent. In that case, retry only as documented or check the status endpoint; do not assume payment succeeded.

3. Payment lookup & wallet balance

GET /payments/intents/{transactionId} retrieves current intent status/details using the human-readable transaction ID.

```
GET https://alliancepe.com/api/payments/intents/PG1759098589901F16172B8
Authorization: Bearer YOUR_API_KEY
```

Documented fields include paymentIntentId, transactionId, amount, currency, status, paymentMethod, customer details, description, metadata, createdAt, processedAt, failureReason and retryCount.

GET /payments/transactions/{transactionId} is an alternative lookup by transaction ID; its example includes payment details, status, timestamps and failureReason.

```
GET https://alliancepe.com/api/payments/transactions/PG1759098589901F16172B8
Authorization: Bearer YOUR_API_KEY
```

Get wallet balance

```
curl --location 'https://alliancepe.com/api/wallet/balance' \\
  --header 'Authorization: Bearer YOUR_API_KEY' \\
  --header 'Content-Type: application/json'
```

```
{
  "available": 12500.50,
  "currency": "INR"
}
```

Invalid/missing API key returns HTTP 401 Unauthorized, according to the supplied source.

Payment status meanings

Status	Meaning
pending	Payment created; awaiting customer action
processing	Payment is being processed
success	Payment completed successfully
failed	Payment failed
cancelled	Cancelled by user
refunded	Payment refunded
expired	Unpaid pay-in expired; distinct from failed

Confirmation rule: confirm payment using a verified webhook or the status API. A return/redirect URL is navigation only, not proof of payment.

4. Payouts

POST /payouts creates a bank payout request.

```
POST https://alliancepe.com/api/payouts
Authorization: Bearer YOUR_API_KEY
Content-Type: application/json

{
  "amount": 5000,
  "beneficiaryName": "John Doe",
  "beneficiaryAccountNumber": "1234567890123",
  "beneficiaryBankName": "State Bank of India",
  "beneficiaryIfscCode": "SBIN0001234",
  "beneficiaryPhoneNumber": "9876543210",
  "beneficiaryEmail": "beneficiary@example.com",
  "callbackUrl": "https://yourapp.com/webhooks/payout-callback",
  "merchantOrderId": "ORDER-12345",
  "remarks": "Payment for services rendered"
}
```

The source says all fields except merchantOrderId, remarks, type and method are required. Default payout range is ■100–■1,00,000, subject to narrower account/gateway limits.

Beneficiary validation & recommended fields

Field / rule	Details from source
IFSC	4 letters + 0 + 6 letters/digits; lowercase accepted and uppercased
Account number	9–18 digits; spaces/hyphens stripped
Beneficiary name	Required, non-empty, max 100 characters
Bank transfer	When method=bank_transfer, IFSC, account number and bank name are required
beneficiaryMobile	Recommended; uses beneficiaryPhoneNumber then registered account phone as fallback; if all missing, BENEFICIARY_MOBILE_REQUIRED
branchName / branchCode	Optional branch details
beneficiaryCity / beneficiaryAddress / beneficiaryState / beneficiaryPincode	Optional beneficiary address fields
purpose / narration	Optional purpose and bank-statement narration
transferMode	imps, neft, rtgs or a2a; omitted value uses account default (normally imps)

Payout lifecycle

Status	Meaning	Terminal
pending	Accepted; payout wallet debited; waiting for approval	No
processing	Accepted by bank rail; not settled; no UTR yet	No
completed	Money has left; UTR is bank reference; payout.completed fires	Yes
failed	Transfer failed or returned; wallet credited back exactly once	Yes
cancelled	Cancelled while pending; wallet credited back	Yes
on_hold	Held by operator for manual review	No

HTTP 201 means accepted and wallet debited, not proof of settlement. Settlement arrives via payout.completed or payout.failed. Payouts have no QR/UPI payer page; create and await callback/status.

4.1 Payout lookup, listing & errors

Lookup endpoints

- **GET /payouts/{payoutId}** retrieves a specific payout.
- **GET /api/payouts/payout/{payoutId}** is listed as an alternative lookup by human-readable payout ID.

List payouts: GET /payouts

Parameter	Rule
page	Page number, default 1
limit	1–100, default 20
status	pending, processing, completed, failed, cancelled or on_hold
fromDate / toDate	ISO 8601 date range filters

```
GET "https://alliancepe.com/api/payouts?page=1&limit=10&status=completed"
Authorization: Bearer YOUR_API_KEY
```

Payout error handling

HTTP / code	Meaning & action
400 AMOUNT_OUT_OF_RANGE	No payout created and wallet not debited; retry only with a different amount.
400 INVALID_BANK_DETAILS	Correct IFSC/account/name; details.errors lists invalid fields.
400 without code	Insufficient payout wallet balance or account limits; top up or resolve limit.
409	Duplicate merchantOrderId; inspect existing payout ID/status. Do not create a new ID.
502 GATEWAY_REJECTED	Bank rail rejected request; details.providerMessage contains provider wording; wallet hold released. Do not retry unchanged.
503 GATEWAY_UNAVAILABLE	Outcome unknown. Retry using the same merchantOrderId; a 409 can identify the original request.

Payout callback / UTR

- Completed payout callbacks include payoutId, amount, status, UTR (utrNumber / utrId), provider and processedAt.
- A returned payout may emit payout.failed with failureReason = reversed; the payout wallet is credited back once.
- merchantOrderId is echoed on callbacks and must be unique per account; repeats return HTTP 409.

Callback URL notes

callbackUrl is optional and must use HTTPS, be publicly accessible and return HTTP 200 OK. It complements registered webhooks, is immutable after transaction creation, and has a maximum length of 2,000 characters.

5. Webhooks & callbacks

Base payload

```
{
  "event": "event.type",
  "data": { /* event-specific data */ },
  "timestamp": "2025-11-03T12:00:00.000Z",
  "webhook_id": "webhook-uuid"
}
```

Headers

```
Content-Type: application/json
User-Agent: AlliancePe-Webhook/1.0
X-Webhook-Signature: <hmac-sha256-signature>
X-Webhook-Event: <event-type>
X-Webhook-ID: <webhook-uuid>
X-Webhook-Timestamp: <ISO-8601-timestamp>
X-API-Version: <api-version>
```

Signature verification

The source specifies HMAC-SHA256 using the webhook secret and X-Webhook-Signature. Verify signatures before trusting event data. The supplied example uses JSON.stringify(payload); in production, verify against the provider's exact raw-body signing convention.

```
const crypto = require('crypto');
const signature = crypto
  .createHmac('sha256', webhookSecret)
  .update(payloadString)
  .digest('hex');
// Compare with X-Webhook-Signature
```

Delivery, retries & idempotency

- Failed webhooks are automatically retried with exponential backoff: 1s, 2s, 4s, 8s, up to 5 minutes max.
- Respond with HTTP 2xx within the default 30-second timeout.
- Deduplicate using payoutId or transactionId; store webhook_id/event identity where appropriate.
- Payout status is documented as automatically polled every 5 minutes until completion/failure.
- Custom callback URLs are signed when at least one active webhook with a secret exists. If no active webhook exists, custom callbacks may be unsigned.

Pay-in webhook event example

```
{
  "event": "transaction.success",
  "data": {
    "transactionId": "TXN_20251103_ABC123",
    "id": "uuid-of-transaction",
    "amount": 1000.00, "currency": "INR", "status": "success",
    "paymentMethod": "UPI",
    "gatewayTransactionId": "PAYU_TXN_ID",
    "gatewayReferenceNumber": "REF_12345",
    "bankReferenceNumber": "BNK_67890",
    "upiTransactionId": "UPI_TXN_123",
    "processedAt": "2025-11-03T12:00:00.000Z"
  },
  "timestamp": "2025-11-03T12:00:01.000Z",
  "webhook_id": "webhook-uuid"
}
```

5.1 Payout webhooks & integration checklist

Payout completion event (representative payload)


```
{
  "event": "payout.completed",
  "data": {
    "payoutId": "PAYOUT_20251103_XYZ789",
    "id": "uuid-of-payout",
    "merchantOrderId": "ORDER-12345",
    "amount": 5000.00, "currency": "INR", "status": "completed",
    "utrNumber": "UTR1234567890", "utrId": "UTR1234567890",
    "providerPayoutId": "bf66316b-4620-4ec9-a3b5-4b7e222fa6c8",
    "provider": "rapidpays24",
    "processedAt": "2025-11-03T12:15:00.000Z",
    "failureReason": null, "failedAt": null
  },
  "timestamp": "2025-11-03T12:15:01.000Z",
  "webhook_id": "webhook-uuid"
}
```


Other events listed

- payout.pending, payout.processing, payout.completed, payout.failed.
- Additional events: payout.cancelled (cancelled by merchant) and payout.rejected (rejected by admin).

Implementation checklist

- Store API keys and webhook secrets securely; never expose them in client-side code.
- Use pay-in idempotency keys and preserve the same key for retries.
- Respect Retry-After on 429 and use backoff.
- Handle IDEMPOTENCY_CONFLICT (422) by inspecting the existing transaction.
- Support both UPI intent/QR responses and hosted checkoutUrl responses.
- Confirm pay-in status via webhook or status endpoint; never trust a redirect alone.
- On payout 503, retry with the same merchantOrderId; on 409, inspect the existing payout.
- Verify webhook signatures, acknowledge quickly, and make processing idempotent.
- Reconcile completed payouts using UTR/UTR ID; treat terminal payout statuses as final.

Source caveats & items to confirm

1. Pay-in maximum conflict. The source states ■100–■9,999 as default pay-in range but later includes an error example saying maximum ■50,000. Confirm the actual effective limit for the merchant and gateway.

2. Endpoint prefix. Base URL is https://alliancepe.com/api. Some endpoint headings omit /api (e.g. /payments/intents and /payouts), while full examples include /api. Join base URL and path once; confirm exact live routing and avoid duplicating /api.

3. Examples are illustrative. Sample IDs, customer data, bank details, URLs and deep links must not be reused. Some long deep links are abbreviated here for readability; use actual API response values.

4. Scope. This PDF is a structured, formatted reference from the supplied text. It does not claim live endpoint testing or independent verification of server behavior.

End of document