



SECURE CODE


WARRIOR

WEAK SESSION TOKEN GENERATION


We'll go through

some preventions steps for
vulnerabilities in this category

Here, an attacker logs into a site.



The site uses a simple increment to generate session IDs.



The site uses a simple increment to generate session IDs.

Cookie:
SessionID:1235




The attacker, noticing the predictability of the ID generation,




deduces new IDs , which he uses to browse back to the site.



After a few attempts, the attacker finds a session ID that is associated with another authenticated user.




After a few attempts, the attacker finds a session ID that is associated with another authenticated user.



By being able to predict session IDs he is able to impersonate the authenticated user and is allowed full access to the user's account.






By being able to predict session IDs he is able to impersonate the authenticated user and is allowed full access to the user's account.



**POOR SESSION MANAGEMENT
CAN BE PREVENTED**

using built-in session management functionality provided by your development framework, instead of inventing your own.



「To Prevent Poor Session Management」

- ⑤ Store the session ID in a cookie and then, protect session cookies.
- ⑤ This can be done by setting an expiry timestamp, path, "secure" and "HTTPOnly" flag and invalidate on logout.

- ⑤ Additionally, Session ID properties must be secure.
Always make them unpredictable, time limited and single session.
- ⑤ Finally, always use a secure communication channel.
For more details on this, see the “Insufficient Transport Layer Protection” module.

Congratulations, you have now completed this module!



SECURE CODE

WARRIOR

www.securecodewarrior.com