Table of Contents

Bulk Create Item-Driven Cycle Count Tasks 2
Prerequisites 2
URL 2
Authentication 2
Request Body Parameters 2
Parameters 2
Options 2
Request Body 3
Sample Success Response (200 OK) 3
Error Codes 3
Sample Error Response 3

Bulk Create Item-Driven Cycle Count Tasks

Use this API to create item-driven cycle count tasks in bulk, without executing a cycle count task creation template.

This API creates item-driven cycle count tasks for specified items across one or more locations, or across all eligible locations if no locations are provided.

Prerequisites

- Valid user credentials (username and password).
- Required access permission: lgfapi / lgfapi Create Access.
- Valid item, facility, and company identifiers.

URL

```
POST .../wms/lgfapi/v10/entity/location/cc_item_task/bulk_create
```

Authentication

This API uses Basic Authentication with username and password credentials.

Request Body Parameters

Parameters

Parameter	Type	Required	Description
`item_id_list`	Array (Integer)	Yes	Valid item IDs to create item-driven cycle count tasks. You can pass a single or multiple item IDs.
`facility_id`	Integer	Conditional	Facility context by id.
`facility_id__code`	String	Conditional	Facility context by code.
`company_id`	Integer	Conditional	Company context by id.
`company_id__code`	String	Conditional	Company context by code.

Options

Parameter	Type	Required	Description
`location_id_list`	Array (Integer)	No	Valid active or reserve location IDs. You can pass a single or multiple location IDs. If location IDs are not provided, the API creates item-driven cycle count tasks for the specified items at all active and reserve locations where they exist.
`priority`	Integer	Yes	Task Priority.
`description`	String	Yes	Valid item-driven cycle count task type description.
`commit_frequency`	Integer	No	Frequency at which the changes are applied to each resource or group of resources being processed. Supported values:

			• **0 (Default)** = Roll back on first error. • **1 / Any integer > 0** = Commit per number of objects passed.
`max_num_of_tasks`	Integer	No	Maximum number of tasks to create. This parameter is ignored when location_id_list is specified.

Note:

- Provide either `facility_id` or `facility_id__code`.
- Provide either `company_id` or `company_id__code`.

Request Body

```
{
    "parameters":
    {
        "item_id_list": [227989,227990,227988],
        "facility_id": 648,
        "company_id": 369
    },
    "options":
    {
        "location_id_list": [132873,136818,136798],
        "priority": 20,
        "description": "CC-LOCN-BY-ITEM",
        "commit_frequency": 1,
        "max_num_of_tasks": 1
    }
}
```

Sample Success Response (200 OK)

The system returns the successful and failed task creation count.

```
{
    "record_count": 3,
    "success_count": 3,
    "failure_count": 0,
    "data": null,
    "details": null
}
```

Error Codes

Status Code	Description
400	Invalid request
401	Authentication failed (invalid username or password)
403	Forbidden (insufficient permissions)
404	Resource not found
500	Internal server error

Sample Error Response

If a specific item in the list fails, the `details` array identifies the specific ID and error reason.

```
{
  "record_count": 3,
  "success_count": 2,
  "failure_count": 1,
  "details": [
    {
      "item_id": 227990,
      "error": "Invalid location ID"
    }
  ]
}
```