Problem-Solution Fit

Date	29 September 2026
Team ID	SWTID-2026-9550
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	5 Marks

Problem-Solution Fit Canvas:
Use the framework below to show how the proposed Script-Controlled ACL addresses the root cause, user behavior, limitations, and the security needs of ServiceNow record access.

<table>
<tr>
<td>1. CUSTOMER SEGMENT(S) [CS]
ServiceNow administrators, security teams, and organizations managing sensitive student/institution records.</td>
<td>6. CUSTOMER LIMITATIONS [CL]
Large user groups, multiple roles, sensitive records, and need for field-based restrictions.</td>
<td>5. AVAILABLE SOLUTIONS [AS]
Standard role-based ACLs, manual access configuration, and custom scripts.</td>
</tr>
<tr>
<td>2. PROBLEMS / PAINS + ITS FREQUENCY [PR]
Unauthorized users may view, create, edit, or delete records. Access mistakes can occur repeatedly as users and roles increase.</td>
<td>9. PROBLEM ROOT / CAUSE [RC]
Access is not sufficiently controlled by both user role and record field value; broad permissions can expose sensitive records.</td>
<td>7. BEHAVIOR + ITS INTENSITY [BE]
Users frequently access student/institution records. Higher-risk actions include viewing and modifying restricted branch records.</td>
</tr>
<tr>
<td>3. TRIGGERS TO ACT [TR]
Need to protect branch-specific records, prevent unauthorized changes, and enforce security rules automatically.</td>
<td rowspan="2">10. YOUR SOLUTION [SL]
Script-Controlled ACLs evaluate roles and field values to allow or deny READ, CREATE, WRITE, and DELETE operations.</td>
<td rowspan="2">8. CHANNELS OF BEHAVIOR [CH]
ONLINE
ServiceNow forms, lists, and Service Portal.

OFFLINE
Admin/security configuration and access-policy planning.</td>
</tr>
<tr>
<td>4. EMOTIONS BEFORE / AFTER [EM]
Before: concern about unauthorized access.
After: greater confidence that records are protected by defined ACL rules.</td>
</tr>
</table>

Project basis: The canvas is prepared from the project document describing a ServiceNow script-controlled ACL that restricts record access based on field value and user roles, with READ, CREATE, WRITE, and DELETE controls.