Computational Linguistics

Assignment 3 Context-free grammars and CKY parsing

Sangeet Sagar sasa00001@stud.uni-saarland.de

January 4, 2021

1 Introduction

This assignment implements the CKY algorithm for bottom-up CFG parsing and applies it to the word and the parsing problem of English. Developed in 1960, the CKY algorithm is the most used chart parser for CFGs (context-free grammars) in CNF (Chomsky normal-form). It uses a dynamic programming algorithm to tell whether a string is in the language of grammar.

2 Description

The script has been integrated with multiple functionalities:

- For a given test sentence, check if it is in the language of CFG or not. Return True for the same.
- For a given test sentence compute all possible CYK parse trees and CYK chart
- For a given test sentence compute counts of all possible parse trees in two ways:
 - Using back-pointer extract set of all parse trees and get their total count
 - Extra-credit Just using back-pointer, maintain a count variable that increments itself recursively
 every time the back-pointer is called for a node. This generates all possible counts of CYK parsed
 trees without actually computing the parse trees.
 - Print a summary table for all test sentences and display if it's in the language of CFG and total counts of all possible trees computed in two ways discussed above.

3 Requirements

- Python: 3.8.3
 NLTK: 3.5
- 3. Texttable: 1.6.3. Install: pip install texttable

4 Project file structure

```
atis
    atis-grammar-cnf.cfg
    atis-grammar-original.cfg
    atis-test-sentences.txt
    other_bad_sentences.txt

cky.py
README.md
results
```

```
summary_bad_sentences.txt
summary_tree_counts.txt
ten_sents_cyk_chart.txt
ten_sents_parsed_trees.txt
```

5 Usage

• **Help**: for instructions on how to run the script with appropriate arguments. python cky.py -help

Cocke-Kasami-Younger (CKY) algorithm for bottom-up CFG parsing Goals:

- > Write CKY algorithm and use it as a recognizer of CFG.
- > Extend it to a parser by adding back pointers
- > Get counts of all possible CKY parse trees for each sentence that is in the language of CFG

Functionalities:

- > Create CKY chart
- > Create CKY parsed trees
- > Get runtimes

```
positional arguments: grammar f
```

```
grammar_f path to grammar file path test sentences file
```

optional arguments:

```
-h, —help show this help message and exit

-show_chart SHOW_CHART display CYK parsed chart

-show_tree SHOW_TREE display CYK parsed tree

-show_summary SHOW_SUMMARY
```

• Run CYK parser: Given CNF grammar and set of test sentences, check if these sentences are in the language of grammar and also display counts of all possible CKY parsed tress. python cky.py atis/atis-grammar-cnf.cfg atis/atis-test-sentences.txt

• Run and test the parser on some self-made sentences that are ungrammatical (i.e. not in the language of given CFG)

```
python cky.py atis/atis-grammar-cnf.cfg atis/other_bad_sentences.txt
```

6 Runtime

• **Total** runtime: 20.51 s

• CYK parser runtime: 17.76 s

 \bullet Backpointer runtime: 0.015 s

However, if you use optional arguments -show_chart or -show_tree, the total runtime is as follows:

• Total runtime: -show_chart: 23.67 s

• Total runtime: -show_tree: 285.27 s

7 Results Contents


- summary_tree_counts.txt: Summary table of given ATIS test set with 98 sentences. Display if the sentence is in the language of CFG and counts of all possible CYK parse trees.
- ten_sents_parsed_trees.txt: Shows CYK parsed trees of the first 10 sentences from the ATIS test-set
- ten_sents_cyk_chart.txt: Shows CYK chart of first 10 sentences from the ATIS test-set
- summary_bad_sentences.txt: (Summary table of some self-made sentences) Shows if the sentences are in the language of CFG and counts of the parse tree for each.

8 Glimpse of results

• CKY tree of the sentence show availability ... A total of 3 trees are observed and they are:

(1) show availability.

Given sentence is in the language of ${\tt CFG}$



• Summary table for first 10 sentences.

S.No.	<u> </u>	CFG	parse tree counts
1	+=====================================	True	1 2
2		True	3
3		True	2
	milwaukee to detroit .	True	

++	_
	١
++	
7	١
8	I
9	١
10	١