

Fundamentals of Java

Created by :

Sangeeta Joshi

Agenda

- Types of variables in Java
 - static
- Memory Layout
- Packages
- Static Imports
- Arrays

Variables

- A variable is a name given to memory location.
- That memory is associated to a data type and can be assigned a value.

```
int n;  
float f1;  
char ch;  
double d;
```

Variables conti...

- Assigning a value to a variable
- Initialization of a variable with a primary value

```
1. int n1;  
2. n1 = 21 ;           // assignment  
3. int i2 = 18;        // initialization  
4. char ch = 'S';      // initialization  
5. double d = 21.8;    // initialization  
6. d = n1;              // assignment  
7. float f1 = 16.13F;
```

Types of variables in java

- Instance Variables : Copy exists per instance
- Static Variables : Class level variable i.e. copy exists per class
- Local Variables : Variables declared within methods or blocks. They are local to the block where they are declared

static

- class Date

{


static int ctr;

int dd;

int mm;

int yy;

}



More on static

Static members are associated with the class as a whole rather than with a particular instance

static variable : It's a class level variable.

static method : If a method is declared as static ,it becomes a class level method & thus can be invoked using class name. (where as non static methods require an instance of a class for invocation.)

`this' is never passed to any static data member or function

WHY main() is static ?

Static blocks can be used for initialization of static variables


Static blocks get executed even before main() method

Memory Layout

- Local variables



- Dynamically allocated Area



*Movable
boundary*

Memory

Local variables are created on stack where as objects are created on heap.

```
class Demo {  
    public static void main (String args[])  
    {  
        Date d = new Date ();  
    }  
}
```



Packages

- A *package* is a grouping of related classes & interfaces providing access protection and name space management
- Programmers bundle groups of related types into packages to make it easier to find & use related classes & interfaces
- Packages help to avoid naming conflicts
- There can be only one package declaration per source file
- In case if no package is declared, then the class is placed into the default package i.e., the current folder

Packagescontinued

- If you want to create a package ,the package statement should be the first statement.
- The fully qualified name of a class is :
packageName.className
- Fully qualified name of class Date in java is

java.util.Date

package name subpackage name class name

Packagescontinued

```
package p1;
```

```
import java.util.Date;
import java.sql.*;
```

```
class MyClass
{
```

}

Basic Structure Of Java File

- Package statement.....optional
- Import statementsoptional
- Standard class writing

Packagescontinued

- Import statement imports public classes within the package
It does not import sub packages.
- Classes from java.lang package are by default imported.

How Compiler locates classes?

- first checks current directory
- all directories in the class path for
the actual class file
or
the subdirectory that has same name of imported package
- then looks for the file in one of the imported packages
- then finally looks for file in java.lang package
- if still unable to locate then raises error

		same class	subclass same pkg	diff class same pkg	subclass diffpkg	diff class diffpkg
public		Y	Y	Y	Y	Y
protected		y	y	Y	y	N
default		Y	Y	Y	N	N
private		Y	N	N	N	N

Static Imports

- There are situations where you need frequent access to static final fields (constants) and static methods from one or two classes.
- Prefixing the name of these classes over and over can result in cluttered code.
- The *static import* statement gives you a way to import the constants and static methods that you want to use so that you do not need to prefix the name of their class.

Static Imports

- The static import declaration is analogous to the normal import declaration
- Normal import declaration: imports classes from packages.
- Advantage : classes can be used without package qualification
- static import declaration : imports static members from classes
- Advantage: static members can be used without class qualification

Static Imports

- Before Java 5.0

Required to fully qualify every static member referenced from external classes

```
Math.sin(x)
```

- Now :

```
import static TypeName.Identifier;  
import static Typename.*;
```

Also works for static methods and enums

```
sin(x)
```

Static Imports

- Caution : Use Static import Very sparingly!
- If you overuse the static import feature, it can make your program unreadable and unmaintainable
- Importing *all* of the static members from a class : Not a good idea
- use it when you require frequent access to static members from one or two classes
- Used appropriately, static import can make your program *more* readable

Array(contd)

- An *array* is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed.
- An array is contiguous block of memory locations referred by a common name.
- Each item in an array is called an *element*, and each element is accessed by its numerical *index*.

Declaring Arrays

- Collection of values of a single type
- Declare arrays of primitive or class types.
 - `char s[];` or `char [] s;`
 - `Point p[];` or `Point [] p;`
- An array is an object in java
- Array reference is stored on stack whereas actual
- array is created on heap

Creating Arrays

Arrays can be created either using new keyword or without using new keyword

```
int arr [] = { 1,2,3,4,5,6 }          .....primitive data type
```

OR

```
int arr[] =new int[6];  
arr[0]=1;
```

```
Date d[]= new Date[4];          .....Date type
```

```
d[0]=new Date();  
d[1]=new Date();
```

Initializing Arrays

- Initialize an array element

- Create an array with initial values

```
String names[] = new String[3];
```


```
names [0] = "Jack";
```

```
names [1] = "Jill";
```

```
names [2] = "Tom";
```

```
MyClass array[] = {new MyClass(), new MyClass() };
```

Initializing Arrays (contd)




One-dimensional Arrays

- One-dimensional array is a list of variables of the same data type.
- Syntax to declare a one-dimensional array type
-
- `array_name []; //type is the datatype of the array.`
- For Example:
- `String designations []; // designations is name of the array.`

One-dimensional Arrays (contd)

- `int [] a = {1, 2, 4, 8, 16};`



Two-dimensional Arrays

- In additions to one-dimensional arrays, you can create two-dimensional arrays. To declare two-dimensional arrays, you need to specify multiple square brackets after the array name.
- Syntax to declare a two dimensional array
- `type array_name = new type[rows][cols];`
- For Example:
- `int multidim[] = new int[3][5];`

Multi-dimensional Arrays

To store data in more dimensions a multi-dimensional array is used. A multi-dimensional array of dimension n is a collection of items. These items are accessed via n subscript expressions.

Multi-dimensional Arrays (contd)

Example

```
int [][][] x = new int [2] [3] [4];
    for(int i = 0;i <2 ;i++)
    {
        for(int j = 0;j <3 ;j++)
        {
            for(int k = 0;k <4 ;k++)


                {System.out.print(x[i][j][k]);}
                System.out.println(" ");
        }
    }
```

Creating Reference Arrays

Example:

```
public class MClass{
    public MClass(int x , int y){
        System.out.println("constr" + x + y );
    }
    public static void main(String [] a){
        MClass[] p;
        p = new MClass[10];
        for ( int i=0; i<10; i++ ) {
            p[i] = new MClass(i, i+1);
        }
    }
}
```

Creating Reference Arrays (contd)



Array Bounds

All array index begin at 0:

```
public void disp()  
{  
  
    Int [] x = new int[5];  
    for (int i = 0; i < x.length; i++)  
    {  
        System.out.println(x[i]);  
    }  
}
```

Enhanced for Loop

Enhanced for loop can be used for iterating over arrays:

```
public void disp()  
{  
    int x = new int[5];  
    for ( int i : x )  
    {  
        System.out.println(i);  
    }  
}
```

The for loop can be read as *for each x in i*.

Array Resizing

You cannot resize an array as it is a static data structure.

You can use the same reference variable to refer to an

entirely new array, such as:

```
int [] x = new int [5];  
x = new int[8];
```

Any Questions?