# Accurate on Average, Blind at the Fork

**Anonymous Author(s)**
Affiliation
Address
email

**Abstract:** A world model that predicts well on average can still be wrong exactly where it matters for safety: at forks, where small, realistic deviations send a manipulation task into different outcomes. We measure this *branching fidelity* with a goal-free fork probe modelled on the human intuitive physics engine [1]: sample the robot's measured execution and perception error, roll the intended action chunk forward 64 times, and flag the chunk if the futures split into distinct outcomes. With exact physics and a real camera-based perception model, the probe matches ground-truth fragility on unseen Jenga layouts ($\kappa$ up to 0.84 against a ceiling of 0.92), also when outcomes are read from images. Replacing the simulator by a stochastic token-space world model that predicts futures $3\times$ better than a no-motion baseline drops agreement to $\kappa$ 0.18: its sampled spread has the right size but ignores where futures branch. Robots that check actions before executing them need world models with branching fidelity, and average-error benchmarks do not measure it.

**Keywords:** World models, intuitive physics, runtime safety

## 1 Introduction

Modern manipulation policies, from diffusion policies to vision-language-action models, act by committing to short *action chunks* [2, 3, 4]. Before a chunk runs, a monitor can ask whether it is safe. In contact-rich tasks such as Jenga extraction the answer hinges on millimetres: the same command can slide the block out or tip a neighbour, depending on small errors in execution and perception. Such a chunk is precarious even if its nominal outcome is fine, because uncertainty the robot cannot control decides what happens.

People judge precariousness by running a few noisy mental simulations over an uncertain scene and checking whether the outcomes disagree, the *intuitive physics engine* (IPE) [1, 5, 6]. A robot can do the same, but it needs a model to simulate with. Outside simulation that model must be learned, and the debate on whether robots need world models then becomes concrete: a world model is useful for this check only if its rollouts *branch where the real dynamics branch*. Prediction error does not measure this.

**Contributions.** (1) A *fork probe* that checks an action chunk before execution without task labels, failure data or fitted thresholds, by sampling the robot's own measured execution and perception error (Sec. 2). (2) Validation of the probe with exact physics and real camera perception on unseen layouts, including reading outcomes from images, which sets the reference a world model should reach (Sec. 3.1). (3) *Branching fidelity* as a world-model evaluation: a token-space world model with low prediction error still loses the forks, and a diagnosis shows why (Sec. 3.2).

Submitted to the 10th Conference on Robot Learning (CoRL 2026). Do not distribute.

## 2 Setup and the fork probe

**Task.** A simulated Franka Panda (MuJoCo) extracts blocks from Jenga-like stacks. At every chunk start a policy commits to an 8-step action chunk. Our chunks come from recorded extraction episodes, but the probe treats the policy as a black box and sees only the commanded chunk, one camera image and proprioception, so it applies to any chunked policy.

**What counts as unsafe.** A chunk is *fragile* if deviations the robot cannot control, its execution error and the error in its perception of the scene, can send the outcome into qualitatively different regimes. This definition needs no goal predicate or failure label, which a monitor around a generalist policy cannot assume; it isolates cases where the robot's intent no longer determines the outcome; and in contact-rich manipulation damage typically happens at such boundaries. A chunk that fails every time is not fragile in this sense and needs a task-level check.

**The fork probe.** The probe imagines 64 versions of the chunk. Version $j$ subtracts an execution-error snippet from the commanded positions, drawn from the robot's measured tracking residuals (median chunk maximum 3.2 mm), and starts from a perturbed version of the perceived scene. The scene is perceived by a frozen DINOv2 encoder [7] on one close-camera image with a keypoint head that regresses the poses of the three blocks in play (2.5 mm held-out error). The perception error model is measured once, offline: we run the perception model on held-out validation images with known poses and fit a zero-mean Gaussian to its errors (a full $9 \times 9$ covariance over block positions, which captures correlated errors, plus a rotation covariance per block). Each rollout starts from the estimate plus one draw from this model, as in the IPE. The probe extends each imagined rollout by holding the chunk's last command for 30 steps, so that the outcome settles (the hold exists only in the monitor's imagination, not in the policy's execution). It then reads the 64 endings (object positions, or image tokens) at hold steps 10 and 30 and flags the chunk if, at both times, the endings projected on their first principal axis prefer two Gaussians to one by BIC, are well separated (Ashman's $D > 2$ [8]), have at least 2 rollouts in the smaller group, and keep the same grouping. These are fixed statistical conventions, not fitted to labels. A variant hedges against an unlucky estimate by drawing 5 scene hypotheses and running the probe around each ("5 hypotheses", flag if at least 3 split).

**Ground truth.** One real outcome cannot grade a monitor: a fragile chunk may succeed by luck. Fragility is a property of the spread of possible outcomes, so we compute it with privileged access. *Fragility truth* runs the probe from the *true* scene in exact physics, with the same execution and perception error draws: the answer an oracle that knows the scene would give at the robot's own uncertainty. Two independent oracle runs agree at Cohen's $\kappa$ 0.85–0.92, the ceiling any monitor can reach. Because this truth uses the same split test, we add a purely physical label: a *topple fork* is a state where some but not all oracle rollouts (2–62 of 64) knock over a neighbouring block. Each evaluation uses an unseen test set of stack layouts (up to 60 topple forks plus 100 safe states), under a protocol frozen before the data existed.

## 3 Results

### 3.1 Validating the probe with exact physics

On 112 development states with exact physics and the true scene, the split test flags all 23 topple forks and 10% of the 89 quiet states. With real perception, sampling the perception error is essential: perception errors of 2–4 mm are comparable to execution noise, and a probe that trusts the estimate ("no perception sampling") reaches only 38–55% of the ceiling $\kappa$, while the probe reaches 76–91% (Table 1). Reading outcomes from DINOv2 tokens of rendered endings instead of object positions changes few decisions ($\kappa$ 0.86–0.90 between the two), so the probe works from images alone: on test set C it agrees with fragility truth at $\kappa$ 0.83 and catches 88% of topple forks (95% CI 0.77–0.94) with 7% false alarms on other states. This is the reference a world model should reach. Most





Figure 1: (a) Two of 64 endings of one chunk under execution error: the neighbour stays or topples. (b) A held-out fork: real latent futures (colour = outcome) on their principal axes, with the token world models' futures for the same inputs; the deterministic model spreads along the branch axis, the stochastic one stays near one outcome. (c) Agreement with fragility truth on three unseen test sets (A–C); lines mark the ceiling.

Table 1: Probe with exact physics and real perception on unseen test sets. $\kappa$: agreement with fragility truth; topple: recall on topple forks.

| | Set A (153 states) | | Set B (160) | | Set C (156) | |
|---|---|---|---|---|---|---|
| outcomes read from object positions | $\kappa$ | topple | $\kappa$ | topple | $\kappa$ | topple |
| ceiling (two oracle runs) | 0.85 | – | 0.92 | – | 0.92 | – |
| no perception sampling | 0.32 | – | 0.51 | 0.65 | 0.42 | 0.67 |
| fork probe | 0.76 | – | 0.70 | 0.77 | 0.84 | 0.91 |
| fork probe, 5 hypotheses | 0.73 | 0.90 | 0.74 | 0.90 | 0.82 | 0.89 |
| outcomes read from images: fork probe | – | – | 0.70 | 0.77 | 0.77 | 0.88 |
| 5 hypotheses | – | – | – | – | **0.83** | **0.88** |

remaining misses arise when the estimate puts every rollout on the safe side of the edge (12 of 14 on test set B).

### 3.2 Branching fidelity of a learned world model

So far, rollouts ran in MuJoCo with the true geometry; only the block poses came from the camera. Outside simulation a learned model must take that role, and the probe becomes its test: given one image and the 64 perturbed chunks, do its rollouts branch where physics branches? Since outcomes can be read from image tokens, a world model in token space can be probed exactly like the simulator. Our candidate encodes the image with DINOv2, compressed by a fixed per-patch PCA to a $28 \times 28 \times 8$ latent; the split test on this latent agrees with the position-based test at $\kappa$ 0.93 on held-out real futures. A flow-matching transition predicts the next latent from the current one and the action, with fresh noise at every step, so repeated rollouts can differ. It is trained on 8 futures per image whose start scenes were sampled within the measured perception error, so the spread of its targets is the robot's own uncertainty. A deterministic version of the same network is the control. Both predict well on average, beating a no-motion baseline on 19-step latent error by 3–4×. Yet on test set C the stochastic model reaches $\kappa$ 0.18 and catches 18% of topple forks, below its deterministic control ($\kappa$ 0.42) and far below the simulator reference ($\kappa$ 0.83; Table 2).

**Why the stochastic model fails.** Table 2 compares, with real futures, the total spread of the 64 endings, the share of that spread on its main axis, and how much larger it is on fork states than on others. The stochastic model reproduces the *amount* of spread but not its *shape* or *placement*: its spread is isotropic and nearly the same on forks and non-forks, the average uncertainty of futures rather than where they branch; other samplers are worse. The deterministic model's spread is tiny but

Table 2: World models on test set C, and diagnostics on 60 held-out states with 64 real futures each.

| rollouts from | $\kappa$ | topple | spread | main axis | fork ratio |
|---|---|---|---|---|---|
| reference (MuJoCo; real futures) | 0.83 | 0.88 | 1.00 | 0.57 | 4.8 |
| token world model, stochastic | 0.18 | 0.18 | 0.98 | 0.15 | 1.3 |
| token world model, deterministic | 0.42 | 0.60 | 0.04 | 0.69 | 32 |
| [TODO: iteration 2] | | | | | |

aligned with the branch axis and 32× larger on forks (Fig. 1b), and started from rendered perturbed scenes it doubles agreement with real futures ($\kappa$ 0.17→0.37). Per-step noise is not wrong in general (diffusion weather ensembles stay well dispersed [9]); here it was misplaced. As in the IPE, the uncertainty that matters is in the initial conditions, and roughly right dynamics amplify it along the branch. A second iteration (a learned operator perturbing the start latent by physical perception error, then deterministic dynamics) is under evaluation [TODO: result].

## 4 Related work

**Simulation under uncertainty.** Beyond the IPE and counterfactual accounts of physical support [10], robotics runs Monte Carlo rollouts over pose, friction or model parameters to score grasps and pushes [11, 12] or to build safety filters [13, 14]. Closest to our setup, Cannizzaro et al. [15] sample measured perception and placement noise through a simulator to predict whether a block tower stands, and Goyal [16] perturbs action chunks with policy-scale noise to measure, offline, how fast deviations grow. These score a task predicate, labels [17] or a growth rate; Zapolsky and Drumwright [18] proposed goal-free detection of divergent particle traces but evaluated task failure. We judge only whether the outcome set splits, a Monte Carlo test of proximity to a basin boundary [19].

**Runtime monitors.** Latent safety filters use learned failure classifiers, also on Jenga [20, 21]; failure detectors use policy uncertainty calibrated on successes [22, 23]. Both measure what a model does not know, not whether the physics is at a branch.

**World models and their uncertainty.** Learned simulators and latent world models [24, 25, 26, 27, 28] struggle with stiff contact [29], and audits find poor physical grounding and optimism under failure-inducing actions [30, 31, 32]. Yu et al. [33] propose evaluating world models on interventional action branches by per-branch error; our model has low error yet loses the forks. Stochastic and ensemble models [34, 35] are judged by likelihood or return, not by where their spread falls.

## 5 Conclusion and limitations

A robot can judge fragility the way people do, by sampling its own perception and execution uncertainty through a rough simulator. For the question this workshop poses, our results suggest that such pre-execution checks need a queryable world model with branching fidelity, which the world model we trained lacks despite low average error, and that in this setting the uncertainty that matters enters through the initial conditions. Average-error benchmarks would rank this model well; branching fidelity is a needed additional axis.

**Limitations.** Simulation, one task family, three tracked blocks; MuJoCo rollouts use privileged geometry beyond the perceived poses; the perception error model is the same for every image; fragility truth shares the split test (topple forks are the independent check); test sets vary in difficulty; single world-model training runs; chunks that fail every time are not flagged.

# References


[1] P. W. Battaglia, J. B. Hamrick, and J. B. Tenenbaum. Simulation as an engine of physical scene understanding. *Proceedings of the National Academy of Sciences*, 110(45):18327–18332, 2013.

[2] C. Chi, S. Feng, Y. Du, Z. Xu, E. Cousineau, B. Burchfiel, and S. Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Robotics: Science and Systems*, 2023.

[3] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn. Learning fine-grained bimanual manipulation with low-cost hardware. In *Robotics: Science and Systems*, 2023.

[4] K. Black, N. Brown, D. Driess, et al. $\pi_0$: A vision-language-action flow model for general robot control. *arXiv:2410.24164*, 2024.

[5] K. A. Smith and E. Vul. Sources of uncertainty in intuitive physics. *Topics in Cognitive Science*, 5(1):185–199, 2013.

[6] A. N. Sanborn, V. K. Mansinghka, and T. L. Griffiths. Reconciling intuitive physics and Newtonian mechanics for colliding objects. *Psychological Review*, 120(2):411–437, 2013.

[7] M. Oquab et al. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024.

[8] K. M. Ashman, C. M. Bird, and S. E. Zepf. Detecting bimodality in astronomical datasets. *The Astronomical Journal*, 108:2348–2361, 1994.

[9] I. Price, A. Sanchez-Gonzalez, et al. Probabilistic weather forecasting with machine learning. *Nature*, 637:84–90, 2025.

[10] L. Zhou, K. A. Smith, J. B. Tenenbaum, and T. Gerstenberg. Mental Jenga: A counterfactual simulation model of causal judgments about physical support. *Journal of Experimental Psychology: General*, 2023.

[11] J. Mahler et al. Dex-Net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. In *Robotics: Science and Systems*, 2017.

[12] W. C. Agboh and M. R. Dogar. Pushing fast and slow: Task-adaptive planning for non-prehensile manipulation under uncertainty. In *Workshop on the Algorithmic Foundations of Robotics (WAFR)*, 2018.

[13] Johansson, Lindmark, Wiberg, and Servin. Safety filtering of robotic manipulation under environment uncertainty: a computational approach. *arXiv:2509.12674*, 2025.

[14] Wang, Ren, Morgan, and Hang. ManiDreams: An open-source library for robust object manipulation via uncertainty-aware task-specific intuitive physics. *arXiv:2603.18336*, 2026.

[15] R. Cannizzaro, M. Groom, J. Routley, R. Ness, and L. Kunze. COBRA-PPM: A causal Bayesian reasoning architecture using probabilistic programming for robot manipulation under uncertainty. *arXiv:2403.14488*, 2024.

[16] A. Goyal. Measuring the stability assumption behind action chunking. *arXiv:2610.01626*, 2026.

[17] A. Lerer, S. Gross, and R. Fergus. Learning physical intuition of block towers by example. In *International Conference on Machine Learning*, 2016.

[18] S. Zapolsky and E. Drumwright. Particle traces for detecting divergent robot behavior. *arXiv:1608.01606*, 2016.

[19] P. J. Menck, J. Heitzig, N. Marwan, and J. Kurths. How basin stability complements the linear-stability paradigm. *Nature Physics*, 9:89–92, 2013.

[20] K. Nakamura, L. Peters, and A. Bajcsy. Generalizing safety beyond collision-avoidance via latent-space reachability analysis. In *Robotics: Science and Systems*, 2025.

[21] J. Seo, K. Nakamura, and A. Bajcsy. Uncertainty-aware latent safety filters for avoiding out-of-distribution failures. In *Conference on Robot Learning*, 2025.

[22] Xu et al. Can we detect failures without failure data? Uncertainty-aware runtime failure detection for imitation learning policies. In *Robotics: Science and Systems*, 2025.

[23] C. Agia, R. Sinha, J. Yang, Z. Cao, R. Antonova, M. Pavone, and J. Bohg. Unpacking failure modes of generative policies: Runtime monitoring of consistency and progress. In *Conference on Robot Learning*, 2024.

[24] A. Sanchez-Gonzalez, J. Godwin, T. Pfaff, R. Ying, J. Leskovec, and P. W. Battaglia. Learning to simulate complex physics with graph networks. In *International Conference on Machine Learning*, 2020.

[25] K. R. Allen, Y. Rubanova, T. Lopez-Guevara, W. Whitney, A. Sanchez-Gonzalez, P. Battaglia, and T. Pfaff. Learning rigid dynamics with face interaction graph networks. In *International Conference on Learning Representations*, 2023.

[26] G. Zhou, H. Pan, Y. LeCun, and L. Pinto. DINO-WM: World models on pre-trained visual features enable zero-shot planning. In *International Conference on Machine Learning*, 2025.

[27] M. Assran et al. V-JEPA 2: Self-supervised video models enable understanding, prediction and planning. *arXiv:2506.09985*, 2025.

[28] D. Hafner, J. Pasukonis, J. Ba, and T. Lillicrap. Mastering diverse control tasks through world models. *Nature*, 640, 2025.

[29] M. Parmar, M. Halm, and M. Posa. Fundamental challenges in deep learning for stiff contact dynamics. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2021.

[30] D. M. Bear, E. Wang, D. Mrowca, F. J. Binder, H.-Y. Tung, et al. Physion: Evaluating physical prediction from vision in humans and machines. In *NeurIPS Datasets and Benchmarks*, 2021.

[31] S. Motamed, L. Culp, K. Swersky, P. Jaini, and R. Geirhos. Do generative video models understand physical principles? In *IEEE/CVF Winter Conference on Applications of Computer Vision*, 2026.

[32] Yang, Shen, Mi, et al. MiraBench: Evaluating action-conditioned reliability in robotic world models. *arXiv:2605.29360*, 2026.

[33] Y. Yu, S. Zhang, Y. Sheng, H. Ren, and H. Lin. How should world models be evaluated for embodied decision-making? A decision-making-centric position. *arXiv:2606.15032*, 2026.

[34] K. Chua, R. Calandra, R. McAllister, and S. Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems*, 2018.

[35] B. Lakshminarayanan, A. Pritzel, and C. Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, 2017.