

Mask R-CNN

Kaiming He | 24 Jan 2018

논문 구현


CloseAI팀 이상헌 박준혁 김유철 이정훈

목차


- Object Detection
- R-CNN
- Fast R-CNN
- Faster R-CNN
- Mask R-CNN
- 코드 구현
- Reference
- QnA

Object Detection

Object Detection





Object Detection 방식




R-CNN

R-CNN Process





Region proposal(영역 제안)



- 물체가 있을 법한 영역
- 기존 모델 sliding window
- Selective Search

Sliding window



- 고정된 크기의 window
- 각 window 위치에서 CNN
- 느리다는 단점

Selective search



- 초기 분할
- 유사 영역 병합
- 지역 제안
- 객체 검출

R-CNN의 한계

cpu 기반 Selective search 많은 시간 소요


Selective search로 추출한 RoI마다 개별 CNN연산(약 2000 * CNN)

SVM, Bounding Box Regressor가 CNN과 분리


CNN이 고정되므로, SVM, Bounding Box Regressor의 결과로 CNN을 업데이트할 수 없어서 end-to-end 방식으로 학습 불가

Fast R-CNN

Fast R-CNN



Rol pooling



SPP (Spatial Pyramid Pooling)


- Rol Pooling에 사용되는 알고리즘
- 4x4 , 2x2, 1x1의 bin들을 가진 각각의 SPP Layer를 통과 후 Concatenate(1차원 특성 벡터)

R-CNN과의 차이 및 한계










- 약 2000번의 CNN 연산을 한 번의 CNN 연산으로 바꿔 속도 향상
- 단일 손실 함수를 사용. Classification과 Bounding Box Regressor 을 동시에 최적화
- 위의 이유로 end-to-end로 학습 가능
- 여전히 cpu 기반 selective search를 사용.


Faster R-CNN

Faster R-CNN



Faster R-CNN


| | 128 | 256 | 512 |
|-----|--|--|--|
| 1:1 |  |  |  |
| 1:2 |  |  |  |
| 2:1 |  |  |  |



3가지 scale, ratio

각 그리드마다 9개의
anchor box 생성

Faster R-CNN




Fast R-CNN 차이점

- Selective Search 대신 RPN을 사용하여 region proposals 생성 속도 개선
- 동일한 CNN 특징 맵을 공유하여 연산 자원 효율 극대화



Mask R-CNN

Mask R-CNN



RoI Pooling에서 RoI Align으로 변경
Mask branch 추가

Roi Pooling의 문제점




Quantization(양자화) 문제

실수를 정수로 바꾸는 과정에서
데이터 소실 발생

픽셀 단위로 진행하는
segmentation에서는 부정적인
영향을 준다

RoI Align




$$1 \times 1 = \text{MAX}(0.14, 0.21, 0.51, 0.43) = 0.51$$

3x3 RoIAlign

| | | |
|------|--|--|
| 0.51 | | |
| | | |
| | | |

하나의 cell에 있는 4개의 sampling point에 대하여 max pooling

Mask branch



각각의 RoI에 작은 크기의 FCN이 추가된 형태

클래스 단위로 mask를 생성한 후 픽셀이 해당 클래스에 해당되는지 여부를 표시

Base




Binary Mask



Binary mask

FPN(Feature Pyramid Network)



다중 스케일 특성(Multi-scale Features)

정확한 객체 검출 및 분할

성능 향상


Mask R-CNN 결과

결과

| | backbone | AP | AP ₅₀ | AP ₇₅ | AP _S | AP _M | AP _L |
|--------------------|-----------------------|-------------|------------------|------------------|-----------------|-----------------|-----------------|
| MNC [10] | ResNet-101-C4 | 24.6 | 44.3 | 24.8 | 4.7 | 25.9 | 43.6 |
| FCIS [26] +OHEM | ResNet-101-C5-dilated | 29.2 | 49.5 | - | 7.1 | 31.3 | 50.0 |
| FCIS+++ [26] +OHEM | ResNet-101-C5-dilated | 33.6 | 54.5 | - | - | - | - |
| Mask R-CNN | ResNet-101-C4 | 33.1 | 54.9 | 34.8 | 12.1 | 35.6 | 51.1 |
| Mask R-CNN | ResNet-101-FPN | 35.7 | 58.0 | 37.8 | 15.5 | 38.1 | 52.4 |
| Mask R-CNN | ResNeXt-101-FPN | 37.1 | 60.0 | 39.4 | 16.9 | 39.9 | 53.5 |

Table 1. **Instance segmentation mask AP** on COCO test-dev. MNC [10] and FCIS [26] are the winners of the COCO 2015 and 2016 segmentation challenges, respectively. Without bells and whistles, Mask R-CNN outperforms the more complex FCIS+++, which includes multi-scale train/test, horizontal flip test, and OHEM [38]. All entries are *single-model* results.

평가 지표



16 May 2024

AP는 Precision-Recall 곡선 아래의 면적을 계산한 값

모델이 다양한 임계 값에서 얼마나 일관되게 높은 Precision과 Recall을 유지하는지를 평가합니다

코드 구현

```
92
93 def get_instance_segmentation_model(num_classes):
94     # load an instance segmentation model pre-trained on COCO
95     model = torchvision.models.detection.maskrcnn_resnet50_fpn(pretrained=True)
96
97     # get the number of input features for the classifier
98     in_features = model.roi_heads.box_predictor.cls_score.in_features
99     # replace the pre-trained head with a new one
100    model.roi_heads.box_predictor = FastRCNNPredictor(in_features, num_classes)
101
102    # now get the number of input features for the mask classifier
103    in_features_mask = model.roi_heads.mask_predictor.conv5_mask.in_channels
104    hidden_layer = 256
105    # and replace the mask predictor with a new one
106    model.roi_heads.mask_predictor = MaskRCNNPredictor(in_features_mask,
107                                                         hidden_layer,
108                                                         num_classes)
109
110    return model
111
```




Reference

Rich feature hierarchies for accurate object detection and semantic segmentation, Ross B. Girshick, 2014
(<https://arxiv.org/pdf/1311.2524.pdf>)

Fast R-CNN, Ross B. Girshick, 2015
(<https://arxiv.org/pdf/1504.08083.pdf>)

Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks, Shaoqing Ren, 2015
(<https://arxiv.org/pdf/1506.01497.pdf>)

Mask R-CNN, Kaiming He, 2017
(<https://arxiv.org/pdf/1703.06870.pdf>)

Q&A
