# Debugging in RStudio

Amanda Gadrow June 20, 2018



https://thumbs.dreamstime.com/b/lousing-monkeys-6160793.jpg



## Base R debug functions

```
debugonce()

debug(), undebug()

browser()

traceback()

options(error = browser), options(error = NULL)
```

## RStudio IDE debugging tools

- Editor breakpoint
- Browser breakpoint
- Debug mode
  - Source pane highlighting
  - Context-specific Environment pane, including a Traceback panel
  - o Browser prompt in Console pane
- "Show traceback" shortcut
- "Rerun with debug" shortcut
- Debug menu

# Shiny debugging


```
options(shiny.fullstacktrace = TRUE)
options(shiny.error = browser)
browser()
```

# Shiny tracing


```
runApp(appDir = "myApp", display.mode = "showcase")
options(shiny.reactlog=TRUE)
runApp(...)
showReactLog()
cat(file=stderr(), ...)
```

### shinyapps.io debugging

rsconnect::showLogs(streaming = TRUE)



### RStudio Connect debugging



#### Useful commands in base R

```
debug(), undebug()
debugonce()
browser()
traceback()
options(error = browser), options(error = NULL)
```

#### **Debugging Shiny applications**

Automatic traceback() in error output, in RStudio and application log Can set a breakpoint in the server function

Use  ${\tt browser}$  () everywhere else (ui, sourced file, etc.)

Open traceback to examine

the functions that R called

before the error occurred

options(shiny.error = browser)

Continue


Tracing: cat(file=stderr(),...), options(shiny.reactlog=TRUE)

#### **Debug mode in RStudio (from the IDE cheat sheet)**

Open with **debug()**, **browser()**, or a breakpoint. RStudio will open the debugger mode when it encounters a breakpoint while executing code.

Click next to ... line number to add/remove a breakpoint.

Highlighted line shows where execution has paused



Run commands in environment where execution has paused

Examine variables in executing environment

Select function in traceback to debug

Step through code one line at a time

Step into and out of functions to run

Console ~/IDEcheatsheet/ 🗇

Launch debugger

mode from origin

Console ~/IDEcheatsheet/ <

of error

> foo()

Error!

Resume Quit debug execution mode

Stop

Resources

Debugging with RStudio https://support.rstudio.com/hc/en-us/articles/205612627-Debugging-with-RStudio

Debugging Shiny applications <a href="https://shiny.rstudio.com/articles/debugging.html">https://shiny.rstudio.com/articles/debugging.html</a>

"Debugging, condition handling, and defensive programming" in Advanced R

http://adv-r.had.co.nz/Exception s-Debugging.html



https://github.com/rstudio/cheatsheets/raw/master/rstudio-ide.pdf