

[Courses](#)[Challenges](#)[Reviews](#)[Community](#)[FAQ](#)[Roadmap](#)[Boile](#)

플러터 챌린지

신청자 72명

기간 2주

Day 3 of 14

챌린지 사용방법

슬랙 이용방법

플러터 챌린지 진도표

Today's Assignment

Progress Report

Q&A

We Dart!

Keep pushing!

- 오늘의 강의: [Dart 시작하기: From #3.0 to #3.5](#)
- 오늘의 과제: 위의 강의를 시청하신 후, 아래 퀴즈를 풀면 됩니다.
- 제출기간: 익일 오전 6시까지

[Courses](#)[Challenges](#)[Reviews](#)[Community](#)[FAQ](#)[Roadmap](#)[Boile](#)

Your score is: 12/12

QUESTION 1 OF 12

CORRECT

This is how we declare a function correctly in Dart:

```
calculateTotal(items: List<int>) void {}
```

✓ False

QUESTION 2 OF 12

CORRECT

When do we use `void` on a function that does not return anything?

✓ Before the function name

QUESTION 3 OF 12

CORRECT

This is how we declare a function correctly in Dart:

```
void calculateTotal(List<int> items){}
```

✓ True

QUESTION 4 OF 12

CORRECT

These two functions are the same:



```
int calculate(int a, int b) {  
  return a + b;  
}
```

✓ True

QUESTION 5 OF 12

CORRECT

This function is using positional parameters:

```
calculateTotal(  
  items:5,  
  discount:10,  
  username:'nico',  
);
```

✓ False

QUESTION 6 OF 12

CORRECT

This function is using named parameters:

```
calculateTotal(  
  5,  
  10,  
  'nico',  
);
```

✓ False

[Courses](#)[Challenges](#)[Reviews](#)[Community](#)[FAQ](#)[Roadmap](#)[Boile](#)

How should we call this function?

```
int plus(int a, int b, int c) => a + b + c;
```

✓ plus(1, 2, 3)

QUESTION 8 OF 12

CORRECT

How should we call this function?

```
int plus({required int a, required int b, required int c}) => a + b + c;
```

✓ plus(a:1, b:2, c:3)

QUESTION 9 OF 12

CORRECT

With this code:

```
int plus(int a, int b, [int? c = 1]) => a + b + (c ?? 0);
```

What will the return value of plus(1,2) be?

✓ 4

QUESTION 10 OF 12

CORRECT

With this code:

```
var a = null;  
var b = a ?? 0;
```

[Courses](#)[Challenges](#)[Reviews](#)[Community](#)[FAQ](#)[Roadmap](#)[Boile](#)

0

QUESTION 11 OF 12

CORRECT

With this code:

```
var a = 1;  
a ??= 0;
```

What is the value of `a` ?

1

QUESTION 12 OF 12

CORRECT

When do we use `typedef` ?

When we want to create an alias for a type

[Courses](#)[Challenges](#)[Reviews](#)[Community](#)[FAQ](#)[Roadmap](#)[Boile](#)

유한회사 노마드컴퍼니

대표: 박인

개인정보책임관리자: 박인

사업자번호: 301-88-01666

주소: 서울시 마포구 백범로 8, 532호

-

원격평생교육원: 서울시 서부교육지원청(제2020-13호)

통신판매업 신고번호: 2020-서울마포-1987

이메일: help [at] nomadcoders.co

전화번호: 02-6487-1130

NAVIGATION

[Courses](#)[Challenges](#)[Reviews](#) [Community](#)[FAQ](#)[Roadmap](#)[Boilerplates](#)

LEGAL

[이용약관](#)[개인정보취급방침](#)[취소 및 환불정책](#)

COURSES

[Langchain 강의](#)[Supabase 강의](#)[NextJS 무료 강의](#)[React Native 무료 강의](#)[Flutter 무료 강의](#)[Python 무료 강의](#)

© 2017-2025 Nomad Company. All rights reserved.

