

MySQL Note Part 1 for student References Software corporate trainer : Chandrasekhar

MySQL Is a RDBMS

=====

=====

=====

=====

Example of RDBMS.

MySQL :- Open source

MariaDB :- Open source
Oracle SQL(Legacy Software)
SQL Server(Legacy Software)
PostgreSQL : Open source
DB2 (Legacy software)
Sybase : (SAP)
Pardox
INgres
Integra
Ibm-SQL

=====

=====

=====

=====

Oracle PL/SQL, (procedures,

Technical Support

email (\$10)

chat (\$15)

telephonic(\$1000)

=====

=====

=====

=====

datatypes

variables

attributes

database :

constraints :

primary key

foreign key

null

not null

default

check

table :

create table

insert records.

commit /rollback ;

update,

delete

truncate

like, not like
in, not in
between

20 functions.
aggregate functions /group
by functions

sum, max, min , average,
count()
string function/text
functions
date functions

group by
having clause

where clause

joins

sub query

Views

=====

=

Important Imp points of

MySQL

MySQL is a RDBMS.

MySQL is a Open Source.

MySQL is database.

What is a Database ?

Database is a secure software where you store the data in the format of rows and columns.

=====

=====

RDBMS

Employee File

Empno, Name, Designation
Salary city

233	John	Manger
494949.44	London	
949	Lucy	Office
39392.22	New York	.

In the above example empno
is called a cell/column in
Excel.

Excel is a spread sheet.
group of columns/cells make
a row

group of rows make a file/
spreadsheet file.

=====

=====

DBMS (Access, FoxPro,
clipper, dbase IV, Visual
FoxPro)

*

in the above example cell is
also called a field in dbms.

group of fields make a
records.

and group of records make a
table.

Employee file is called a
table.

and group of table make a

database.

=====

=====

=====

=====

RDBMS(relational database
management system)

field is called as an
attribute.

group of attributes make a
tuple.

group of tuple make a table.

and group of tables make a database.

and every database is connected to a project.

=====

=====

=

tables in an entity,
every attribute is called a key.

every key tries to become a super key.

one table can have only super key.

super key is called as

primary key in sql table.

=====

=====

=

=====

=====

=

Important points in MySQL

MySQL is structured
database.

every command in MySQL is a
query.

Dual is logical table.

it is a inbuilt table
can be used for date queries
if required for testing
purpose.

```
=====
=====
=
=====
=====
=
```

Important queries.

to see the list of
databases.

```
mysql>show databases()  :
```

```
mysql> select sysdate();
```

```
+-----+
| sysdate() |
+-----+
| 2026-07-11 14:37:49 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> select sysdate()
from dual;
```

```
+-----+
| sysdate() |
+-----+
| 2026-07-11 14:38:02 |
+-----+
```


if 1 records
qualified from the table in
the query.
then that record will get
displayed.

where clause is not case
sensitive in MySQL.

waq to fetch all salespeople
posted in London >
mysql> select * from
salespeople
 where city =
'London';

```
mysql> select * from  
salespeople  
      -> where city =  
'London' or city =  
'Bengaluru';
```

```
select * from salespeople  
      -> where comm <=  
7500;
```

=====

=====

waq to display the detail of
employee no 3434 and only,
snum, sname and city.

```
p select snum, sname, city
    ->    from salespeople
    ->    where snum =
3434;
```

=====

=====

SELECT CLAUSE Hierarchy

```
Select attribute1,
attribute2, attribute3,
    from table1, table2
    where
        group by
            having
                order by;
```

=====

=====

function in MySQL are
divided in to different
categories

string functions
numeric function
date functions
group by functions /
aggregate functions. (5
functions)

aggregate functions.

1) sum() : - it is used for doing the totaling of the numeric

values in the table as per the business requirement in the MySQL query.

wAQ TO print the total incentive paid to the sales team.

```
mysql> select sum(comm)
->      from salespeople;
```

=====

=====

=====

```
=====
=====
=====
```

Distinct

```
*****
```

This command is used to
remove duplicate values from
the output
of sql query.

distinct will not remove
duplicate values physically
from the
sql table.
distinct clause should not

be used on a primary key.

=====

=====

WAQ TO display all the
unique city the salesteam is
in operation.

```
mysql> select distinct city  
        from salespeople;
```

waq to display all the
unique incentives earned by
the sales team.

```
select distinct comm  
->    from salespeople;
```

=====

=====

