

MySQL Note Part 2 for student References Software corporate trainer : Chandrasekhar

```
select count(snum),  
sum(comm), avg(comm)  
      from salespeople;
```

constraints

1) primary key : -

2) null : - in MySQL null values represent blank values.

primary key attribute/field can never be null value as it cannot be left blank.

waq to display all the salespeople who are yet to get a city posting.

```
select * from salespeople
        where city is null;
```

```
=====
=====
=
```

```
select * from salespeople  
       where comm is null;
```

3) Not null : - not null is a constraint of MySQL.
not null mean the column in the MySQL table will not be or should not be left blank.

waq to display all salespeople who got a city posting.

```
select * from salespeople
    where city is not null;
```

```
=====
```

```
=====
```

```
=====
```

```
    insert into salespeople
values
```

```
    ->      (6664, 'James
Patel', null, null);
```

```
=====
```

```
=====
```

Group by clause

group by is used to group the records based on a column which is repeated many time.

grouping should be done based on non primary key.

group by functions can be used with group by clause if required.

waq to display city wise total incentive paid to the sales team.

```
select city, sum(comm)
      from salespeople
      group by city;
```

=====

=====

waq to display city wise
total incentive and highest
incentive.

```
select city, sum(comm),
max(comm)
      from salespeople
      group by city;
```

```
+-----+-----+--
-----
```

IN clause

In clause is used for
fetching the records faster.

and it will work on all the
datatypes in MySQL.

In clause is not case
sensitive in MySQL.

```
select snum, sname, city
      from salespeople
      where snum in
(1001,1008, 1004, 1090);
```

```
+-----+-----+-----
-+
```

```
| snum | sname          | city  
|
```

```
select snum, sname, city  
from salespeople  
where city in  
('London', 'New York',  
'Chichago', 'Mumbai');
```

```
=====
```

```
=====
```

waq to display all
salespeople
but salesperson posted in
bengalur, London, Chicago,

Chennai, Sydney should be discarded from the report.

```
select snum, sname, city
      from salespeople
     where city Not In
        ('Bengaluru',
 'London', 'Chicago',
 'Chennai', 'Sydney');
```

```
=====
=====
=====
```

Like operator :

it is used for fetch records
based on partial information
from the sql table.

wild cards/meta characters.

1)%

2)_

waq to display all
salespeople who are posted
in city
where the city name starts
with L

select * from salespeople

where city like 'l%';

+-----+-----+-----
--+-