

Important Notes Of MySQL Part 1

Software Corporate Trainer

:Chandrasekhar N

MySQL is a RDBMS.

RDBMS means Relational Database
Management System

Dr. E.F codd is the father of
RDBMS.

Examples of RDBMS

Oracle, MySQL, SQL Server,
Access, IBM-SQL, Paradox, ingres,
integra, Informatica, Posgre
SQL, Marina,

Latest versions of MySQL

MySQL 5, 5.5, 5.6. 5.7 & MySQL 8.

SQL (structured query language)

Important queries are as follows

Double click on mysql and it
will ask for password.
Give it accordingly.

2)mysql> show databases;

It is used to see the list of
current databases in the MySQL
user.

Date in mysql is always in the format of Yy-mm-dd

To check today current the query is as follows.

```
mysql> select sysdate() ;
```

```
+-----+
| sysdate()          |
+-----+
| 2022-11-20 18:47:26 |
+-----+
1 row in set (0.00 sec)
```

```
*****
*****
*****
```

```
mysql> select sysdate()
->    from dual;
```

```
+-----+
```

```
| sysdate() |
+-----+
| 2022-11-20 18:47:34 |
+-----+
1 row in set (0.00 sec)
```

```
*****
*****
*****
*****
```

To create a table called
salespeople query is as follows.

```
mysql> create table salespeople
      (snum numeric(5) primary key,
       sname char(25),
       city varchar(20),
       comm decimal(11,2));
```

Table created.

Creating a basic table involves naming the table and defining its columns and each column's data type.

The SQL CREATE TABLE statement is used to create a new table.

Primary key

Primary key is used to give uniqueness to that table through the attribute which will be declared as primary key.

Is short primary key is allowed only once in a table.

ONLY one columns in a table can have primary key. Primary key is by default not null.

Normally in a database world rollno, empno, ticketno, hotel room no, customer no, bank accnt no and in railway pnr no are primary keys.

Null has a special values in MySQL.

It is used for keeping the attributes blank, but the MySQL database engine does not count it as blank.

It is one type of constraint in MySQL.

```
*****  
*****  
*****
```

To see the structure of the table.


```
mysql> desc salespeople;
```

```
+-----+-----+-----+-----+
----+-----+-----+
| Field | Type                | Null |
Key | Default | Extra |
+-----+-----+-----+-----+
----+-----+-----+
| snum  | decimal(5,0)        | NO   |
PRI | NULL      |      |
| sname | char(20)             | YES  |
    | NULL      |      |
| city  | varchar(20)          | YES  |
    | NULL      |      |
| comm  | decimal(18,2)        | YES  |
    | NULL      |      |
+-----+-----+-----+-----+
----+-----+-----+

```

4 rows in set (0.00 sec)

mysql> describe salespeople;

+-----+-----+-----+-----+				
-----+-----+-----+-----+				
Field	Type		Null	
Key	Default	Extra		
+-----+-----+-----+-----+				
-----+-----+-----+-----+				
snum	decimal(5,0)		NO	
PRI	NULL			
sname	char(20)		YES	
	NULL			
city	varchar(20)		YES	
	NULL			
comm	decimal(18,2)		YES	
	NULL			
+-----+-----+-----+-----+				
-----+-----+-----+-----+				

To insert or add a record to the table. The query will be as follows.


```
mysql> INSERT INTO salespeople  
values(1001, 'James Bond', 'New  
York', 7788.55);
```

The above query will add 1 record to the table;

In case you want leave certain fields or attributes blank in case that field does not have any constraint or any keys associated with it in that case the query will be as follows.

```
mysql> INSERT INTO tsalespeople
```

```
values(1234, 'Dr. Dinesh', 'New  
York', Null);
```

in the above queries you will use
null value to leave a particular
attribute blank.

```
*****  
*****  
*****
```

commit is fired automatically.

```
-----  
-----
```

To see the number of records or
tuples in the table the query is

```
SQL> select * from salespeople;
```

```
*****  
*****
```

```
sql> select snum, sname, city
from
        salespeople;
```

The above query will display only particular attributes from the table (in short the above query is for display particular attributes).

```
*****
*****
*****
```

```
12)DROP TABLE table_name;
sql> DROP TABLE tempindia;
```

The table will be dropped or delted provided you have the right to delete the table.

The SQL DROP TABLE statement is used to remove a table definition and all data, indexes, triggers,

constraints, and permission specifications for that table.

```
*****  
*****  
*****
```

Where clause

```
*****
```

It is used for giving conditions and fetching the records you want.

The SQL WHERE clause is used to specify a condition while fetching the data from single table or joining with multiple table.

If the given condition is satisfied then only it returns specific value from the table.

The WHERE clause not only used in

SELECT statement, but it is also used in UPDATE, DELETE statement

write a query to display the salespeople who reside in london.

```
SQL> select * from salespeople
2     where city = 'London';
```

SNUM	SNAME	CITY	COMM
1001	Karan	London	
1090	Dr. Jun Jun Wala	London	

1810.14

1400 Dr. Rahul

London

9579

SNUM SNAME

CITY

COMM

COUNTRY

8977 Shri amit

London

Waq to print particular attributes for salesperson residing in london.

```
mysql> select snum, sname, city
from salespeople
2 where city = 'London';
```

SNUM	SNAME	CITY
1001	Kalia	London
1090	Dr. Jun Jun Wala	London
1400	Dr. Rahul	London
8977	Shri amit	London

Write a query where you will
print snum, sname, city for a
person whose salesman no is 1400;

```
mysql> select snum, sname, city  
        from salespeople  
        where snum =1400;
```

SNUM	SNAME	CITY
------	-------	------

1400	Dr. Rahul	London
------	-----------	--------

Write a query where you will
print all salesperson
residing in london or mumbai.

```
mysql> select snum, sname, city  
2   from salespeople  
3   where city = 'London' or  
city = 'Mumbai';
```

```
      SNUM SNAME  
      CITY
```

```
      1001 Kalia  
      London  
      1090 Dr. Jun Jun Wala  
      London  
      1400 Dr. Rahul  
      London
```

8977 Shri amit
London

Write a query where you will
print all salespeople whose name
is
"Dr. Rahul"

```
mysql> select * from salespeople  
2     where sname ='Dr. Rahul';
```

SNUM SNAME
CITY
COMM

COUNTRY

1400 Dr. Rahul

London

9579
