

Sanila.T.S

1) WAQ to print all sales persons who live in London (don't use in clause)

```
mysql> select * from salespeople
```

```
→ where city='London';
```

```
+-----+-----+-----+-----+-----+
| snum  | sname    | city   | comm      | country |
+-----+-----+-----+-----+-----+
| 1002  | Alex     | London | 5877453.21 | NULL    |
| 1011  | Simran   | London | 70374.21   | NULL    |
| 1012  | Peel     | London | 5962.01    | NULL    |
| 1016  | alexander | London | 99245.01   | NULL    |
| 1018  | Rixon    | London | 99245.21   | NULL    |
| 10067 | James    | London | 540.00     | UK      |
+-----+-----+-----+-----+-----+
```

6 rows in set (0.23 sec)

2) WAQ to print all customers who live in London, New York, Chicago, Johannesburg, Seoul, Tokyo, Mumbai and Punjab

(use in only)

```
mysql> SELECT *
```

```
→ FROM customers
```

```
→ WHERE city IN (
```

```
→ 'London',
```

```
→ 'NewYork',
```

```
→ 'Chicago',
```

```
→ 'Johannesburg',
```

```
→ 'Seoul',
```

```
→ 'Tokyo',
```

```
→ 'Mumbai',  
→ 'Punjab'  
→ );
```

```
+-----+-----+-----+-----+  
| cnum | cname   | city       | snum |  
+-----+-----+-----+-----+  
| 5001 | abi     | Mumbai     | 1004 |  
| 5003 | alex    | London     | 1016 |  
| 5004 | Rahul   | London     | 1002 |  
| 5005 | Sneha   | NewYork    | 1005 |  
| 5006 | Arjun   | Chicago    | 1009 |  
| 5007 | Meera   | Johannesburg | 1013 |  
| 5008 | Kiran   | Seoul      | 1011 |  
| 5009 | Priya   | Tokyo      | 1016 |  
| 5010 | Vivek   | Mumbai     | 1014 |  
| 5011 | Anita   | Punjab     | 1001 |  
| 5012 | John    | London     | 1012 |  
| 5013 | Sara    | NewYork    | 1005 |  
| 5014 | David   | Chicago    | 1018 |  
| 5015 | Grace   | Johannesburg | 1017 |  
| 5016 | Kevin   | Seoul      | 1011 |  
| 5017 | Yuki    | Tokyo      | 1002 |  
| 5018 | Harpreet | Punjab     | 1021 |  
+-----+-----+-----+-----+  
17 rows in set (0.01 sec)
```

3) WAQ where you update all sales persons commission by 100 pounds

```
mysql> update salespeople
```

```
→ set comm=comm+100;
```

```
Query OK, 22 rows affected (0.04 sec)
```

```
Rows matched: 23  Changed: 22  Warnings: 0
```

4) WAQ to update all ratings with null

5) WAQ to print cnum, cname, and city they live in London,

Hyderabad,Bengaluru and Chennai. cname should be printed in

upper case, city in lower case

```
mysql> select cnum,UPPER(cname) Customer_Name,LOWER(city) City
```

```
→ from customers
```

```
→ where city In
```

```
→ ('London','Hyderabad','Bengaluru','Chennai');
```

```
+-----+-----+-----+
```

```
| cnum | Customer_Name | City      |
```

```
+-----+-----+-----+
```

```
| 5003 | ALEX          | london    |
```

```
| 5004 | RAHUL         | london    |
```

```
| 5012 | JOHN          | london    |
```

```
| 5019 | AKHIL         | chennai   |
```

```
| 5020 | DIVYA         | chennai   |
```

```
| 5021 | RAMESH        | bengaluru |
```

```
| 5022 | KARTHIK       | bengaluru |
```

```
| 5023 | NISHA         | chennai   |
```

```
| 5024 | POOJA         | bengaluru |
```

```
| 5025 | SURESH        | chennai   |
```

```
| 5026 | ANJALI        | bengaluru |
```

+-----+-----+-----+

11 rows in set (0.00 sec)6) WAQ to print all those orders

where order amount is in range

of 2000 to 10000 pounds(use

between operator only)

7) WAQ where we only use order table to print number of orders

for each customer (use group by)

```
SELECT cnum, COUNT(*) AS number_of_orders
```

```
→ FROM orders
```

```
→ GROUP BY cnum;
```

+-----+-----+-----+

cnum	number_of_orders
------	------------------

+-----+-----+-----+

5001	1
------	---

5002	1
------	---

5003	2
------	---

5004	1
------	---

5006	1
------	---

5008	1
------	---

5012	1
------	---

5013	1
------	---

5015	1
------	---

5018	1
------	---

5019	1
------	---

5021	1
------	---

5022	1
------	---

5029	1
------	---

```
+-----+-----+-----+
```

14 rows in set (0.01 sec)

8) WAQ where you will print all orders in range 1000 to 5000

pounds but salesnumber(snum) 1002 should be disqualified

```
mysql> SELECT *
```

```
→ FROM orders
```

```
→ WHERE oamount BETWEEN 1000 AND 5000
```

```
→ AND snum NOT IN (1002);
```

```
+-----+-----+-----+-----+-----+
```

```
| onum | odate      | oamount | snum | cnum |
```

```
+-----+-----+-----+-----+-----+
```

```
| 3002 | 2026-01-12 | 4500.75 | 1004 | 5001 |
```

```
| 3003 | 2026-01-15 | 1200.00 | 1015 | 5002 |
```

```
| 3005 | 2026-02-01 | 3200.00 | 1006 | 5019 |
```

```
| 3008 | 2026-02-15 | 1500.50 | 1007 | 5022 |
```

```
| 3010 | 2026-03-01 | 2300.00 | 1001 | 5004 |
```

```
| 3012 | 2026-03-10 | 4300.25 | 1005 | 5013 |
```

```
| 3014 | 2026-03-20 | 2800.50 | 1018 | 5012 |
```

```
+-----+-----+-----+-----+-----+
```

7 rows in set (0.00 sec)

9) WAQ to print all details of sales people but sales name

should be indescending order.

```
sql> select *
```

```
→ from salespeople
```

```
→ order by sname desc;
```

snum	sname	city	comm	country
1005	sophia	NewYork	699353.11	NULL
1011	Simran	London	70474.21	NULL
1015	shilpa	Bengaluru	8494.21	NULL
1013	sherya	USA	7172.31	NULL
1018	Rixon	London	99345.21	NULL
1001	Raju	Delhi	46232.23	NULL
1020	Raghul	NULL	NULL	NULL
1014	Punit	Mumbai	25547.66	NULL
1012	Peel	London	6062.01	NULL
1004	Pankaj	Mumbai	645887.87	NULL
1017	monika	Barcelona	4254.21	NULL
1003	Manju	Bengaluru	66087.32	NULL
1030	mani	manchester	600.00	NULL
1010	Malu	TamilNadu	79545.21	NULL
1019	Kavya	Mysore	66073.21	NULL
10067	James	London	640.00	UK
1007	Chinju	Bengaluru	6247.12	NULL
1008	Bhavya	Delhi	11832.00	NULL
1006	Appu	Chennai	988164.00	NULL
1021	anju	manchester	600.00	NULL
1009	Angel	USA	99075.21	NULL
1016	alexander	London	99345.01	NULL
1002	Alex	London	5877553.21	NULL

23 rows in set (0.01 sec)

10) WAQ where you will print number of customers for each sales person and it should be printed in descending order

```
SELECT snum, COUNT(*) AS number_of_customers
```

```
→ FROM customers
```

```
→ GROUP BY snum
```

```
→ ORDER BY number_of_customers DESC;
```

```
+-----+-----+
```

```
| snum | number_of_customers |
```

```
+-----+-----+
```

```
| 1006 |          3 |
```

```
| 1003 |          3 |
```

```
| 1015 |          2 |
```

```
| 1016 |          2 |
```

```
| 1002 |          2 |
```

```
| 1005 |          2 |
```

```
| 1011 |          2 |
```

```
| 1014 |          2 |
```

```
| 1001 |          2 |
```

```
| 1004 |          1 |
```

```
| 1009 |          1 |
```

```
| 1013 |          1 |
```

```
| 1012 |          1 |
```

```
| 1018 |          1 |
```

```
| 1017 |          1 |
```

```
| 1021 |          1 |
```

```
| 1007 |          1 |
```

```
| 1010 |          1 |
```

```
| 1008 | 1 |
```

```
+-----+-----+
```

19 rows in set (0.00 sec)

11) WAQ where you will print number of orders for every
salesman ,his highest order amount,lowest order amount and average
order amount.Customer number should be printed in ascending order

```
mysql> SELECT snum,  
→ COUNT(*) AS number_of_orders,  
→ MAX(oamount) AS highest_order_amount,  
→ MIN(oamount) AS lowest_order_amount,  
→ AVG(oamount) AS average_order_amount  
→ FROM orders  
→ GROUP BY snum  
→ ORDER BY snum ASC;
```

```
+-----+-----+-----+-----+-----+  
-----+
```

```
| snum | number_of_orders | highest_order_amount | lowest_order_amount |  
average_order_amount |
```

```
+-----+-----+-----+-----+-----+  
-----+
```

1001	1	2300.00	2300.00
2300.000000			
1002	1	2500.50	2500.50
2500.500000			
1003	1	5600.80	5600.80
5600.800000			
1004	1	4500.75	4500.75
4500.750000			
1005	1	4300.25	4300.25
4300.250000			

1006 3200.000000	1	3200.00	3200.00
1007 1500.500000	1	1500.50	1500.50
1009 9900.000000	1	9900.00	9900.00
1011 8900.900000	1	8900.90	8900.90
1014 9100.000000	1	9100.00	9100.00
1015 1200.000000	1	1200.00	1200.00
1016 7800.250000	1	7800.25	7800.25
1017 7600.000000	1	7600.00	7600.00
1018 2800.500000	1	2800.50	2800.50
1021 6700.750000	1	6700.75	6700.75

-----+-----+-----+-----+

-----+

```
15 rows in set (0.00 sec)
```