

1 **PyAFBF: a Python library for sampling image textures**  
2 **from the anisotropic fractional Brownian field.**

3 **Frédéric J.P. Richard**<sup>1</sup>

4 **1** Aix Marseille University, CNRS, Centrale Marseille, I2M, UMR 7373, Marseille, France.

DOI: [10.21105/joss.03310](https://doi.org/10.21105/joss.03310)

**Software**

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

**Editor:** [Pending Editor](#) ↗

**Submitted:** 24 May 2021

**Published:** 24 May 2021

**License**

Authors of papers retain  
copyright and release the work  
under a Creative Commons  
Attribution 4.0 International  
License ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).

5 **Summary**

6 The Python library **PyAFBF** is devoted to the simulation of anisotropic textures of image.  
7 These textures are sampled from a mathematical model called the anisotropic fractional Brownian field (AFBF) ([Bonami & Estrade, 2003](#)); see [Figure 1](#) for an illustration. The library offers  
8 several features. It enables to set, either manually or randomly, the simulated model so as to  
9 generate a wide variety of textures. It also include tools to compute model features (regularity,  
10 anisotropy,...) which may serve as attributes to describe generated textures. The library further  
11 offers the possibility to sample heterogeneous textures from random field models related to  
12 the AFBF.  
13




Figure 1: A patchwork of simulated textures.

## Statement of need

For the simulation of random fields, the library **PyAFBF** relies upon the turning-band method developed in (Biermé et al., 2015). This method was historically designed to facilitate researches on the anisotropic fractional Brownian field (Bonami & Estrade, 2003) and related models (Benassi et al., 1997; Guyon & Perrin, 2000; Peltier & Levy Vehel, 1996; Polisano et al., 2014; Vu & Richard, 2020). Simulations it generates have been particularly useful to set experimental protocols aiming at assessing performances of estimation methods (Biermé & Richard, 2008; Richard, 2017, 2015, 2016b, 2016a; Richard & Biermé, 2010). The estimation issues tackled in these works concerned the functional parameters and features of the AFBF and related models. There are still largely open. The library **PyAFBF** is intended to support future experiments and help mathematicians to validate and compare their methods. In particular, it could be the basis for collaborative works aiming at the development of benchmarks and data challenges.

The simulation of random fields is a classical topic of spatial statistics (Chilès & Delfiner, 2012; Cressie, 2015; Lantuéjoul, 2013). As reviewed in (Liu et al., 2019), there are some R packages devoted to this topic, among which:

- 30 ■ [RandomFields](#) ([Schlather et al., 2015](#)) that enables the simulation of stationary fields  
31 and also some non-stationary Gaussian random fields such as max-stable fields,
- 32 ■ [FieldSim](#) ([Brouste et al., 2007](#)) that allows the simulation of manifold indexed Gaussian  
33 field,

34 None of these package deals directly with the anisotropic fractional Brownian fields. The pack-  
35 age [FieldSim](#) deals with mono- and multi- fractional Brownian fields but only in an isotropic  
36 setting. The package [RandomFields](#) offers a wide range of methods to simulate stationary  
37 and non-stationary, isotropic and anisotropic random fields. However, it only handles geo-  
38 metric and zonal anisotropies, which both differ from the one of an AFBF. Moreover, it is  
39 not specifically devoted to models derived from the fractional Brownian fields. Hence, the  
40 package **PyAFBF** is complementary to these R packages.

41 The implementation of random field simulation methods in Python are less manifest. It is  
42 the purpose of the package [python-randomfields](#) and [dune-randomfield](#). It is also a part of  
43 packages [spam](#) and [dorie](#). But, none of these package enables the simulation of AFBF. Hence,  
44 the package [AFBF](#) offers original simulation tools to a large community of Python developers.  
45 This is of interest for researchers in image processing where random fields can serve as texture  
46 or noise models for medical images ([Biermé et al., 2009](#); [Biermé & Richard, 2011](#); [Richard,](#)  
47 [2015, 2016a](#); [Richard & Biermé, 2010](#)) or photographic films ([Richard, 2017](#)). This is also  
48 of interest for researchers in machine learning where the random field simulation could be  
49 included in image generative models such as GAN.

## 50 Definition and simulation of an AFBF.

51 An AFBF  $Z$  is a Gaussian non-stationary random field with stationary increments whose  
52 semi-variograms are of a form

$$v(h) = \frac{1}{2} \mathbb{E}((Z(x+h) - Z(x))^2) = \frac{1}{2} \int_{-\frac{\pi}{2}}^{\frac{\pi}{2}} \tau(\theta) |h, u(\theta)|^{2\beta(\theta)} d\theta, \quad u(\theta) = (\cos \theta, \sin \theta),$$

53 which is characterized by two  $\pi$ -periodic functions  $\tau$  and  $\beta$  called the topothesy function and  
54 the Hurst function, respectively. These functions determined the properties of the AFBF and  
55 the aspect of the textures that are sampled from it.

56 The package **PyAFBF** proposes some convenient representations for these functions (Fourier,  
57 step functions,...) that enable to easily set an AFBF, either manually or at random, in a proper  
58 way.

59 Using the package **PyAFBF**, image textures are realizations of an AFBF on a discrete grid.  
60 This are simulated using a turning band fields ([Biermé et al., 2015](#)). These fields are defined,  
61 for some set of angles  $(\varphi_k, k = 1, \dots, K)$  in  $[-\frac{\pi}{2}, \frac{\pi}{2}]$  and of appropriate non-negative weights  
62  $(\lambda_k, k = 1, \dots, K)$ , as

$$Z_\varphi(x) = \sum_{k=1}^K \lambda_k X_k(\langle u(\varphi_k), x \rangle),$$

63 where  $X_k$  are independent Brownian motions with Hurst index  $h_k$ . The package includes a  
64 Python class to handle turning-band fields, simulate them and compute their properties.

## Availability and Community Guidelines

The package **PyAFBF** can be downloaded from the Github [repository](#). A documentation, which includes a quickstart guide, a gallery of examples and API, is available at the [PyAFBF](#) site. Users and contributors are welcome to contribute, request features, and report bugs via Github.

## References

- Benassi, A., Jaffard, S., & Roux, D. (1997). Elliptic Gaussian random processes. *Revista Matemática Iberoamericana*, 13(1), 19–89.
- Biermé, H., Moisan, M., & Richard, F. (2015). A turning-band method for the simulation of anisotropic fractional Brownian field. *Journal of Computational and Graphical Statistics*, 24(3), 885–904.
- Biermé, H., & Richard, F. (2011). Analysis of texture anisotropy based on some Gaussian fields with spectral density. In M. Bergounioux (Ed.), *Mathematical Image Processing* (pp. 59–73). Springer Proceedings.
- Biermé, H., & Richard, F. J. P. (2008). Estimation of anisotropic Gaussian fields through Radon transform. *ESAIM: Probability & Statistics*, 12(1), 30–50.
- Biermé, H., Richard, F., Rachidi, M., & Benhamou, C. L. (2009). Anisotropic texture modeling and applications to medical image analysis. In H. Ammari (Ed.), *Mathematical methods for imaging and inverse problems* (Vol. 26, pp. 100–122).
- Bonami, A., & Estrade, A. (2003). Anisotropic analysis of some Gaussian models. *Journal of Fourier Analysis and Applications*, 9, 215–236.
- Brouste, A., Istas, J., Lambert-Lacroix, S., & others. (2007). On fractional Gaussian random fields simulations. *Journal of Statistical Software*, 23(1), 1–23.
- Chilès, J. P., & Delfiner, P. (2012). *Geostatistics: Modeling spatial uncertainty* (2nd ed.). J. Wiley.
- Cressie, N. (2015). *Statistics for spatial data*. John Wiley & Sons.
- Guyon, X., & Perrin, O. (2000). Identification of space deformation using linear and superficial quadratic variations. *Statistics and Probability Letters*, 47(3), 307–316.
- Lantuéjoul, C. (2013). *Geostatistical simulation: Models and algorithms*. Springer Science & Business Media.
- Liu, Y., Li, J., Sun, S., & Yu, B. (2019). Advances in gaussian random field generation: A review. *Computational Geosciences*, 23(5), 1011–1047.
- Peltier, R. F., & Levy Vehel, J. (1996). *Multifractional Brownian motion: Definition and preliminary results* (No. 2645). INRIA.
- Polisano, K., Clausel, M., Perrier, V., & Condat, L. (2014). Texture modeling by Gaussian fields with prescribed local orientation. *International Conference on Image Processing (ICIP), 2014 IEEE*, 6091–6095.
- Richard, F. J. P. (2017). Anisotropy of Hölder Gaussian random fields: Characterization, estimation, and application to image textures. *Statistics and Computing*, 1–14.
- Richard, F. J. P. (2015). Analysis of anisotropic Brownian textures and application to lesion detection in mammograms. *Procedia Environmental Sciences*, 27, 16–20.

- 106 Richard, F. J. P. (2016a). Some anisotropy indices for the characterization of Brownian  
107 textures and their application to breast images. *Spatial Statistics*, 18, 147–162.
- 108 Richard, F. J. P. (2016b). Tests of isotropy for rough textures of trended images. *Statistica*  
109 *Sinica*, 26(3), 1279–1304.
- 110 Richard, F. J. P., & Biermé, H. (2010). Statistical tests of anisotropy for fractional Brownian  
111 textures. Application to full-field digital mammography. *Journal of Mathematical Imaging*  
112 *and Vision*, 36(3), 227–240.
- 113 Schlather, M., Malinowski, A., Menck, P., Oesting, M., & Storkorb, K. (2015). Analysis, sim-  
114 ulation and prediction of multivariate random fields with package RandomFields. *Journal*  
115 *of Statistical Software*, 63(8), 1–25.
- 116 Vu, H., & Richard, F. (2020). Statistical tests of heterogeneity for anisotropic multifractional  
117 Brownian fields. *Stochastic Processes and Their Applications*, 130(8), 4667–4692.

DRAFT