

Semi-Automatic Classification Plugin: A Python tool for the download and processing of remote sensing images in QGIS

Luca Congedo¹

¹ Independent Researcher

DOI: [10.21105/joss.03172](https://doi.org/10.21105/joss.03172)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Kristen Thyng](#) ↗

Reviewers:

- [@bstabler](#)
- [@joferkington](#)

Submitted: 08 March 2021

Published: 12 July 2021

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

The Semi-Automatic Classification Plugin is a Python plugin for the software QGIS ([QGIS Development Team, 2021](#)) developed with the overall objective to facilitate land cover monitoring by people whose main field is not strictly remote sensing, but that could benefit from remote sensing analysis. The Semi-Automatic Classification Plugin provides a set of intertwined tools and a user interface for easing and automating the phases of land cover classification, from the download of remote sensing images, to the preprocessing (i.e. tools for preparing the data to the analysis or other calculations), the processing (i.e. tools for performing the classification of land cover or perform analysis), and postprocessing (i.e. tools for assessing the classification accuracy, refining the classification, or integrating additional data). The processing of remote sensing data can be computationally intensive, therefore most of the developed tools use [Python multiprocessing](#) to exploit the system CPU and RAM by splitting the work among multiple threads. The aim of this paper is to describe the main characteristics of the Semi-Automatic Classification Plugin for the land cover classification of remote sensing images.

Statement of need

Land cover is defined as the material at the Earth's surface, such as soil, vegetation, water, asphalt, etc. ([Fisher & Unwin, 2005](#)); during the last decades, remote sensing has been widely used for land cover monitoring and assessing environmental changes ([Rogan & Chen, 2004](#)).

Remote sensing is the measurement, by a sensor, of the energy that is emanated from the Earth's surface. The source of the measured energy can be the Sun (i.e. passive remote sensing, when the sensors measure the energy reflected by the Earth's surface), or the sensor platform (i.e. active remote sensing, when the sensors emit the energy and measure the energy reflected by the Earth's surface) such as radar sensors which work in the microwave range ([Richards & Jia, 2006](#)).

Sensors can be installed on board of airplanes or satellites, measuring the electromagnetic radiation (i.e. radiance) at specific ranges of wavelength (also called bands). The result of the sensor measurements are converted into a digital image, having different characteristics (resolutions) depending on the sensor ([Richards & Jia, 2006](#)):

- Spatial resolution (also referred to as Instantaneous field of view), usually corresponding to pixel size measured in meters;

- 38 ▪ Spectral resolution, is the number of the spectral bands located in the electromagnetic
- 39 spectrum; usually, each band corresponds to an image raster;
- 40 ▪ Radiometric resolution, is the number of binary digits representing the range of bright-
- 41 ness values, usually measured as bit number.

42 During the last few years, the availability of satellite images has increased and become afford-
43 able, especially because of the free access to the Landsat data (a set of satellites developed by
44 the National Aeronautics and Space Administration of USA, since the early 1970's) ([United](#)
45 [States Geological Survey, 2019](#)), and the European satellites Sentinel-2 launched in 2015 ([Eu-](#)
46 [ropean Space Agency, 2018](#)). The free availability of these data extended their use in various
47 fields such as urban planning, agriculture, environmental monitoring, etc. ([Nink et al., 2019](#);
48 [Pesaresi et al., 2016](#); [Weiss et al., 2020](#)).

49 For land cover analysis, it useful to define the reflectance as the ratio of reflected versus
50 total incident energy ([Richards & Jia, 2006](#)); each material at the ground is characterized by
51 a spectral signature, which is the reflectance as a function of wavelength. Therefore, it is
52 possible to classify land cover using the spectral signatures of materials, through classification
53 algorithms that label image pixels, allowing for the creation of thematic maps.

54 A supervised classification (also known as semi-automatic classification) is an image processing
55 technique that aims at classifying land cover by training an algorithm with samples of material
56 spectral signatures. There are several semi-automatic classification algorithms that in general
57 require a priori knowledge of material spectral signatures, through the identification in the
58 image of training pixels and calculation of the corresponding spectral signatures ([Richards &](#)
59 [Jia, 2006](#)). Based on the training pixels (i.e. spectral signatures) the algorithm classifies the
60 whole remote sensing image through a mathematical model.

61 Remote sensing images are spatial data and require the use of a Geographic Information
62 System (GIS) for visualization and processing. The development of open source GIS and
63 processing software can foster environmental monitoring, which can be performed with no
64 cost for software and remote sensing images considering the free data availability. QGIS is an
65 open source GIS software which provides several tools for data visualization and analysis; it is
66 mainly written in C++ code, but it also allows to extend the functions thereof through API
67 and plugins written in Python ([QGIS Development Team, 2021](#)). QGIS has a large repository
68 of plugins that improve data analysis and also provide access to several image processing
69 tools included in other open source programs such as GRASS ([GRASS Development Team,](#)
70 2017), GDAL ([GDAL/OGR contributors, 2021](#)), and Orfeo Toolbox ([OTB Development Team,](#)
71 2020). These programs allow for the processing of satellite images, nevertheless their use can
72 be difficult for people interested in land cover classifications but specialized in fields other
73 than remote sensing, because of the several steps required for image processing.

74 The Semi-Automatic Classification Plugin aims to provide a complete suite of tools for
75 processing remote sensing data, easing the phases related to the download, the preprocessing
76 of images, and the postprocessing of classifications.

77 Several tutorials about the Semi-Automatic Classification Plugin are freely available
78 on the [official website](#), and the [user manual](#) is being translated into several languages by the
79 user community.

80 The Semi-Automatic Classification Plugin has been cited in several studies about
81 land cover, urban growth, and image processing ([Arekhi et al., 2019](#); [Damtew et al., 2021](#);
82 [Furukawa et al., 2020](#); [Garilli et al., 2021](#); [Huq et al., 2019](#); [Leroux et al., 2018](#); [Palafox-Juárez](#)
83 [et al., 2021](#); [Pelage et al., 2019](#); [Teodoro & Amaral, 2019](#); [Zhang et al., 2018](#)).

Overview of the Semi-Automatic Classification Plugin

The Semi-Automatic Classification Plugin interfaces is composed of several modules (as illustrated in Figure 1). A module allows for searching and downloading freely available images (in particular ASTER, GOES, Landsat, MODIS, Sentinel-1, Sentinel-2, and Sentinel-3). It is possible to perform the preprocessing and raster calculations automatically after the download, by setting a few parameters in the user interface.




Figure 1: User interface of the Semi-Automatic Classification Plugin for QGIS.

The interface allows to define an image input (named band set) which is the set of raster bands to be processed.

The following tools are available for preprocessing:

- Conversion to reflectance for ASTER, GOES, Landsat, MODIS, Sentinel-1, Sentinel-2, and Sentinel-3 images;
- Clip multiple rasters at once;
- Cloud masking based on the values of a raster mask;
- Mosaic band sets, merging the corresponding bands of two or more band sets;
- Statistic calculation for neighbor pixels;
- Reprojection of the coordinates of raster bands;
- Splitting or stacking raster bands in a unique file;
- Vector to raster conversion.

The following processing tools are available:

- Band combination to get a raster where each value corresponds to a combination of input values;
- Clustering for unsupervised classification (i.e. without training input);
- Principal Component Analysis of band set;
- Calculation of the spectral distance between every corresponding pixel of two band sets;
- Classification using one of the available algorithms, such as Minimum Distance (Richards & Jia, 2006), Maximum Likelihood (Richards & Jia, 2006), Spectral Angle Mapping (Kruse et al., 1993), and Random Forest (Breiman, 2001).

111 Considering that semi-automatic classification algorithms require training pixels (i.e. spectral
112 signatures), a specific dock interface for training input creation and spectral signature calcu-
113 lation is available, which allows to create polygons interactively (manually or through region
114 growing) and import spectral libraries such as the USGS Spectral Library (Kokaly et al., 2017).
115 The interface allows to create classification previews on small portion of the image to assess
116 the results before launching the classification process for the whole image. In addition, the
117 plot of spectral signatures can be visualized in order to assess the spectral separability of
118 signatures.

119 A band calculator is available for performing mathematical and conditional calculation using
120 input rasters, for instance for the calculation of spectral indices.

121 The following postprocessing tools are available for refining the classification output and
122 further analyses:

- 123 ▪ Accuracy assessment of the classification;
- 124 ▪ Classification dilation, erosion, and sieve for refining the patches of the classes;
- 125 ▪ Classification report for calculation of class statistics such as number of pixels, percent-
126 age and area;
- 127 ▪ Conversion of classification from raster to vector;
- 128 ▪ Manual editing of raster values;
- 129 ▪ Assessment of land cover change comparing two classifications;
- 130 ▪ Statistics related to an input raster for every unique value of a reference vector or raster;
- 131 ▪ Reclassification of raster values.

132 Finally, the tool Batch allows for performing a series of functions consecutively and automat-
133 ically through the definition of a script.

134 The Semi-Automatic Classification Plugin for QGIS is developed with Python 3 and
135 requires the installation of GDAL, NumPy, SciPy, and Matplotlib (as illustrated in Figure 2).
136 The user interface is developed using the Qt framework. The additional installation of SNAP
137 (European Space Agency, 2021) is required for the Sentinel-1 preprocessing and random forest
138 classification tools.




Figure 2: Framework of the Semi-Automatic Classification Plugin main dependencies.

139 A testing tool is available for verifying the correct installation of the required dependencies
140 and check the main functions of the Semi-Automatic Classification Plugin.

141 Acknowledgements

142 The first version of the Semi-Automatic Classification Plugin was developed by Luca Congedo
143 in 2012 for the [ACC Dar Project](#) in order to create a tool for the classification of land cover
144 in an affordable and automatic fashion; following versions 2, 3, 4, and 5 of Semi-Automatic
145 Classification Plugin were developed by Luca Congedo as personal commitment to the remote
146 sensing field and open source philosophy. Semi-Automatic Classification Plugin version 6 was
147 developed in the frame of Luca Congedo's PhD in Landscape and Environment at Sapienza
148 University of Rome. Semi-Automatic Classification Plugin version 7 was developed by
149 Luca Congedo as personal commitment to the remote sensing field and open source philosophy.

150 Special thanks to all the users for contributing to the Semi-Automatic Classification Plugin
151 and translating the interface and user manual to other languages.

152 References

- 153 Arekhi, M., Goksel, C., Balik Sanli, F., & Senel, G. (2019). Comparative Evaluation of the
154 Spectral and Spatial Consistency of Sentinel-2 and Landsat-8 OLI Data for Igneada Longos
155 Forest. *ISPRS International Journal of Geo-Information*, 8(2). <https://doi.org/10.3390/ijgi8020056>
156
157 Breiman, L. (2001). Random Forests. *Machine Learning*, 45(1), 5–32. <https://doi.org/10.1023/A:1010933404324>
158

- 159 Damtew, Y. T., Verbeiren, B., Awoke, A., & Triest, L. (2021). Satellite Imageries and Field
160 Data of Macrophytes Reveal a Regime Shift of a Tropical Lake (Lake Ziway, Ethiopia).
161 *Water*, 13. <https://doi.org/10.3390/w13040396>
- 162 European Space Agency. (2018). *Sentinel-2 Products Specification Document*. European
163 Space Agency. [https://sentinels.copernicus.eu/web/sentinel/user-guides/sentinel-2-msi/](https://sentinels.copernicus.eu/web/sentinel/user-guides/sentinel-2-msi/document-library)
164 [document-library](https://sentinels.copernicus.eu/web/sentinel/user-guides/sentinel-2-msi/document-library)
- 165 European Space Agency. (2021). *SNAP - ESA sentinel application platform* (Version 8.0.0)
166 [Computer software]. <http://step.esa.int>
- 167 Fisher, P. F., & Unwin, D. J. (2005). *Re-Presenting GIS* (J. W. & Sons, Ed.). John Wiley
168 & Sons. ISBN: 978-0-470-84847-0
- 169 Furukawa, F., Morimoto, J., Yoshimura, N., & Kaneko, M. (2020). Comparison of Con-
170 ventional Change Detection Methodologies Using High-Resolution Imagery to Find For-
171 est Damage Caused by Typhoons. *Remote Sensing*, 12(19). [https://doi.org/10.3390/](https://doi.org/10.3390/rs12193242)
172 [rs12193242](https://doi.org/10.3390/rs12193242)
- 173 Garilli, E., Bruno, N., Autelitano, F., Roncella, R., & Giuliani, F. (2021). Automatic detection
174 of stone pavement's pattern based on UAV photogrammetry. *Automation in Construction*,
175 122, 14. [https://doi.org/https://doi.org/10.1016/j.autcon.2020.103477](https://doi.org/10.1016/j.autcon.2020.103477)
- 176 GDAL/OGR contributors. (2021). *GDAL/OGR geospatial data abstraction software library*.
177 Open Source Geospatial Foundation. <https://gdal.org>
- 178 GRASS Development Team. (2017). *Geographic resources analysis support system (GRASS*
179 *GIS) software, version 7.2*. Open Source Geospatial Foundation. <http://grass.osgeo.org>
- 180 Huq, N., Bruns, A., & Ribbe, L. (2019). Interactions between freshwater ecosystem services
181 and land cover changes in southern Bangladesh: A perspective from short-term (seasonal)
182 and long-term (1973–2014) scale. *Science of The Total Environment*, 650, 132–143.
183 [https://doi.org/https://doi.org/10.1016/j.scitotenv.2018.08.430](https://doi.org/10.1016/j.scitotenv.2018.08.430)
- 184 Kokaly, R. F., Clark, R. N., Swayze, G. A., Livo, K. E., Hoefen, T. M., Pearson, N. C., Wise,
185 R. A., Benzel, W. M., Lowers, H. A., Driscoll, R. L., & Klein, A. J. (2017). USGS spectral
186 library version 7. In U. S. G. Survey (Ed.), *Data Series* (p. 68). [http://pubs.er.usgs.gov/](http://pubs.er.usgs.gov/publication/ds1035)
187 [publication/ds1035](http://pubs.er.usgs.gov/publication/ds1035)
- 188 Kruse, F. A., Lefkoff, A. B., Boardman, J. B., Heidebrecht, K. B., Shapiro, A. T., Barloon, P.
189 J., & Goetz, A. F. H. (1993). The Spectral Image Processing System (SIPS) - Interactive
190 Visualization and Analysis of Imaging spectrometer Data. *Remote Sensing of Environment*,
191 44(/), 145–163.
- 192 Leroux, L., Congedo, L., Bellón, B., Gaetano, R., & Bégué, A. (2018). Land Cover Mapping
193 Using Sentinel-2 Images and the Semi-Automatic Classification Plugin: A Northern Burk-
194 ina Faso Case Study. In *QGIS and Applications in Agriculture and Forest* (pp. 119–151).
195 John Wiley & Sons, Ltd. <https://doi.org/10.1002/9781119457107.ch4>
- 196 Nink, S., Hill, J., Stoffels, J., Buddenbaum, H., Frantz, D., & Langshausen, J. (2019). Using
197 Landsat and Sentinel-2 Data for the Generation of Continuously Updated Forest Type
198 Information Layers in a Cross-Border Region. *Remote Sensing*, 11(20). [https://doi.org/](https://doi.org/10.3390/rs11202337)
199 [10.3390/rs11202337](https://doi.org/10.3390/rs11202337)
- 200 OTB Development Team. (2020). *Orfeo ToolBox 7.2* (Version 7.2.0) [Computer software].
201 Zenodo. <https://doi.org/10.5281/zenodo.4066373>
- 202 Palafox-Juárez, E. B., López-Martínez, J. O., Hernández-Stefanoni, J. L., & Hernández-
203 Nuñez, H. (2021). Impact of Urban Land-Cover Changes on the Spatial-Temporal Land
204 Surface Temperature in a Tropical City of Mexico. *ISPRS International Journal of Geo-*
205 *Information*, 10(2). <https://doi.org/10.3390/ijgi10020076>

- 206 Pelage, L., Domalain, G., Lira, A. S., Travassos, P., & Frédou, T. (2019). Coastal Land
207 Use in Northeast Brazil: Mangrove Coverage Evolution Over Three Decades. *Tropical*
208 *Conservation Science*, 12, 15. <https://doi.org/10.1177/1940082918822411>
- 209 Pesaresi, M., Corbane, C., Julea, A., Florczyk, A. J., Syrris, V., & Soille, P. (2016). Assess-
210 ment of the Added-Value of Sentinel-2 for Detecting Built-up Areas. *Remote Sensing*,
211 8(4), 299. <https://doi.org/10.3390/rs8040299>
- 212 QGIS Development Team. (2021). *QGIS geographic information system*. QGIS Association.
213 <https://www.qgis.org>
- 214 Richards, J. A., & Jia, X. (2006). *Remote Sensing Digital Image Analysis: An Introduction*
215 (Springer, Ed.). Springer.
- 216 Rogan, J., & Chen, D. (2004). Remote sensing technology for mapping and monitoring land-
217 cover and land-use change. *Progress in Planning*, 61(4), 301–325. [https://doi.org/10.](https://doi.org/10.1016/S0305-9006(03)00066-7)
218 [1016/S0305-9006\(03\)00066-7](https://doi.org/10.1016/S0305-9006(03)00066-7)
- 219 Teodoro, A., & Amaral, A. (2019). A Statistical and Spatial Analysis of Portuguese Forest
220 Fires in Summer 2016 Considering Landsat 8 and Sentinel 2A Data. *Environments*, 6(3).
221 <https://doi.org/10.3390/environments6030036>
- 222 United States Geological Survey. (2019). *Landsat 8 (L8) Data Users Handbook*.
223 *Version 5.0*. Department of the Interior U.S. Geological Survey. [https://prd-](https://prd-wret.s3.us-west-2.amazonaws.com/assets/palladium/production/atoms/files/LSDS-1574_L8_Data_Users_Handbook-v5.0.pdf)
224 [wret.s3.us-west-2.amazonaws.com/assets/palladium/production/atoms/files/LSDS-](https://prd-wret.s3.us-west-2.amazonaws.com/assets/palladium/production/atoms/files/LSDS-1574_L8_Data_Users_Handbook-v5.0.pdf)
225 [1574_L8_Data_Users_Handbook-v5.0.pdf](https://prd-wret.s3.us-west-2.amazonaws.com/assets/palladium/production/atoms/files/LSDS-1574_L8_Data_Users_Handbook-v5.0.pdf)
- 226 Weiss, M., Jacob, F., & Duveiller, G. (2020). *Remote sensing for agricultural applications: A*
227 *meta-review*. 236, 111402. [https://doi.org/https://doi.org/10.1016/j.rse.2019.111402](https://doi.org/10.1016/j.rse.2019.111402)
- 228 Zhang, Y., Zhang, H., & Sun, Z. (2018). Effects of Urban Growth on Architectural Heritage:
229 The Case of Buddhist Monasteries in the Qinghai-Tibet Plateau. *Sustainability*, 10(5).
230 <https://doi.org/10.3390/su10051593>