

SiSyPHE: A Python package for the Simulation of Systems of Particles with High Efficiency

Antoine Diez¹

¹ Department of Mathematics, Imperial College London, South Kensington Campus, London, SW7 2AZ, UK

DOI: [10.21105/joss.03425](https://doi.org/10.21105/joss.03425)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Pending Editor](#) ↗

Submitted: 27 June 2021

Published: 28 June 2021

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Over the past decades, the study of systems of particles has become an important part of many research areas, from theoretical physics to applied biology and computational mathematics. One of the main motivations is the modelling of large animal societies and the emergence of complex patterns from simple behavioral rules, e.g. the flock of birds, fish schools, ant colonies etc. In the microscopic world, particle systems are used to model a wide range of phenomena, from the collective motion of spermatozoa to the anarchical development of cancer cells. Within this perspective, there are at least three important reasons to conduct large scale computer simulations of particle systems. First, numerical experiments are essential to calibrate the models and test the influence of each parameter in a controlled environment. For instance, the renowned Vicsek model ([Vicsek et al., 1995](#)) is a minimal model of *flocking* which exhibits a complex behavior, studied numerically in particular in ([Chaté et al., 2008](#)). Secondly, particle simulations are used to check the validity of *macroscopic* models which describe the statistical behavior of particle systems. These models are usually based on Partial Differential Equations (PDE) derived using phenomenological considerations which are often difficult to justify mathematically ([Degond et al., 2021](#); [Degond & Motsch, 2008](#); [Dimarco & Motsch, 2016](#)). Finally, inspired by models in Biology, there is an ever growing literature on the design of algorithms based on the simulation of *artificial* particle systems to solve tough optimization problems ([Grassi & Pareschi, 2020](#); [Kennedy & Eberhart, 1995](#); [Pinnau et al., 2017](#); [Totzeck, 2021](#)) and to construct new more efficient Markov Chain Monte Carlo methods ([Cappé et al., 2004](#); [Clarté et al., 2021](#); [Del Moral, 1998, 2013](#); [Doucet et al., 2001](#)).

Statement of need

The SiSyPHE library builds on recent advances in hardware and software for the efficient simulation of large scale interacting *mean-field* particle systems, both on the GPU and on the CPU. The implementation is based on recent libraries originally developed for machine learning purposes to significantly accelerate tensor (array) computations, namely the PyTorch package ([Paszke et al., 2019](#)) and the KeOps library ([Charlier et al., 2021](#)). The versatile object-oriented Python interface is well suited to the comparison of new and classical many-particle models, enabling ambitious numerical experiments and leading to novel conjectures. The SiSyPHE library speeds up both traditional Python and low-level implementations by one to three orders of magnitude for systems with up to several millions of particles.

A typical model which is implemented in the SiSyPHE library is the variant of the Vicsek model introduced by [Degond & Motsch \(2008\)](#) and defined by the system of $2N$ Stratonovich Stochastic Differential Equations

$$dX_t^i = c_0 V_t^i dt, \quad dV_t^i = \sigma P(V_t^i) \circ (J_t^i dt + dB_t^i), \quad (1)$$

where the position at time t of a particle indexed by $i \in \{1, \dots, N\}$ is a vector $X_t^i \in \mathbb{R}^d$ and its orientation (or velocity) is a unit vector $V_t^i \in \mathbb{R}^d$ with $|V_t^i| = 1$. The coefficient $c_0 > 0$ is the speed of the particles (assumed to be constant), the matrix $P(V_t^i) = I_d - V_t^i \otimes V_t^i$ is the orthogonal projection matrix on the plane orthogonal to V_t^i , $(B_t^i)_t$ is an independent Brownian motion and $\sigma > 0$ is a diffusion coefficient which models the level of noise. The quantity $J_t^i \in \mathbb{R}^d$ is called a *target*: it is the orientation that particle i is trying to adopt. In the Vicsek model introduced by [Degond & Motsch \(2008\)](#),

$$J_t^i = \frac{\sum_{j=1}^N K(|X_t^j - X_t^i|) V_t^j}{\left| \sum_{j=1}^N K(|X_t^j - X_t^i|) V_t^j \right|}, \quad (2)$$

where the *kernel* $K : [0, +\infty) \rightarrow [0, +\infty)$ is a smooth nonnegative function vanishing at infinity which models the visual perception of the particles: in the Vicsek model, the vision of the particles depends on the distance between them. With the target given by [Equation 2](#), each particle tries to adopt the average orientation of its neighbors, which is a typical *flocking* behavior.

On a computer, the time-continuous system given by [Equation 1](#) needs to be discretized first. Then, at each time step, the most expensive operation is the computation of the target given by [Equation 2](#), which requires $\mathcal{O}(N)$ operations for each of the N particles. The total simulation cost is thus $\mathcal{O}(N^2 T)$ where T is the total number of iterations. Within the framework of the KeOps library on which SiSyPHE is based, the computation of the target [Equation 2](#) is called a *kernel operation* which is efficiently carried out using a *symbolic* definition of the $N \times N$ interaction matrix whose (i, j) -entry is $K(|X_t^j - X_t^i|)$. The computation of the target is then understood as a symbolic matrix-vector product between the interaction matrix and the vector of orientations.

To the best of our knowledge only model-specific packages such as ([Motsch, 2016](#)) are available. The SiSyPHE library includes within a common framework the implementation of many classical models and their variants as well as recent models for which no implementation was previously available. All the models detailed in the Example gallery of the documentation are directly taken from the literature on collective dynamics in Mathematics and Active Matter Physics. Moreover, the SiSyPHE library is designed in such a way that new custom models can easily be added in order to facilitate the study and comparison of models from a research perspective.

The development of the SiSyPHE library was initially motivated by the study of *body-oriented particles* ([Degond et al., 2019](#)). The (formal) derivation of a macroscopic PDE model from the particle system has lead to a novel conjecture which postulates the existence of a class of so-called *bulk topological states* in ([Degond et al., 2021](#)). The quantitative comparison between this theoretical prediction and the numerical simulation of the particle system in a suitable regime (with more than 10^6 particles) has confirmed the existence of these new states of matter. The study of their physical properties which are observed in the numerical experiments but not readily explained by the PDE model is an ongoing work.

Acknowledgements

The development of this library would not have been possible without the help of Jean Feydy, his constant support and precious advice. This project was initiated by Pierre Degond and has grown out of many discussions with him.

References

- Cappé, O., Guillin, A., Marin, J. M., & Robert, C. P. (2004). Population Monte Carlo. *J. Comput. Graph. Statist.*, 13(4), 907–929. <https://doi.org/10.1198/106186004X12803>
- Charlier, B., Feydy, J., Glaunès, J. A., Collin, F.-D., & Durif, G. (2021). Kernel Operations on the GPU, with Autodiff, without Memory Overflows. *J. Mach. Learn. Res.*, 22(74), 1–6.
- Chaté, H., Ginelli, F., Grégoire, G., & Raynaud, F. (2008). Collective motion of self-propelled particles interacting without cohesion. *Phys. Rev. E*, 77(4), 046113. <https://doi.org/10.1103/PhysRevE.77.046113>
- Clarté, G., Diez, A., & Feydy, J. (2021). Collective Proposal Distributions for Nonlinear MCMC samplers: Mean-Field Theory and Fast Implementation. *arXiv Preprint: arXiv:1909.08988*. <http://arxiv.org/abs/1909.08988>
- Degond, P., Diez, A., & Na, M. (2021). Bulk topological states in a new collective dynamics model. *arXiv Preprint: arXiv:2101.10864*. <http://arxiv.org/abs/2101.10864>
- Degond, P., Frouvelle, A., Merino-Aceituno, S., & Trescases, A. (2019). Alignment of Self-propelled Rigid Bodies: From Particle Systems to Macroscopic Equations. In G. Giacomini, S. Olla, E. Saada, H. Spohn, & G. Stoltz (Eds.), *Stochastic Dynamics Out of Equilibrium, Institut Henri Poincaré, Paris, France, 2017* (pp. 28–66). Springer, Cham. https://doi.org/10.1007/978-3-030-15096-9_2
- Degond, P., & Motsch, S. (2008). Continuum limit of self-driven particles with orientation interaction. *Math. Models Methods Appl. Sci.*, 18(Suppl.), 1193–1215. <https://doi.org/10.1142/S0218202508003005>
- Del Moral, P. (1998). Measure-valued processes and interacting particle systems. Application to nonlinear filtering problems. *Ann. Appl. Probab.*, 8, 438–495. <https://doi.org/10.1214/aoap/1028903535>
- Del Moral, P. (2013). *Mean field simulation for Monte Carlo integration*. CRC Press, Taylor & Francis Group.
- Dimarco, G., & Motsch, S. (2016). Self-alignment driven by jump processes: Macroscopic limit and numerical investigation. *Math. Models Methods Appl. Sci.*, 26(07), 1385–1410. <https://doi.org/10.1142/S0218202516500330>
- Doucet, A., Freitas, N., & Gordon, N. (Eds.). (2001). *Sequential Monte Carlo Methods in Practice*. Springer-Verlag New York. <https://doi.org/10.1007/978-1-4757-3437-9>
- Grassi, S., & Pareschi, L. (2020). From particle swarm optimization to consensus based optimization: Stochastic modeling and mean-field limit. *arXiv Preprint: arXiv:2012.05613*. <http://arxiv.org/abs/2012.05613>
- Kennedy, J., & Eberhart, R. (1995). Particle swarm optimization. *Proceedings of ICNN'95 - International Conference on Neural Networks*, 4, 1942–1948. <https://doi.org/10.1109/ICNN.1995.488968>
- Motsch, S. (2016). Vicsek_microFlat. *GitHub Repository*. https://github.com/smotsch/Vicsek_microFlat
- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An Imperative Style, High-Performance Deep Learning Library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. Alché-Buc, E. Fox, & R. Garnett (Eds.), *Advances in Neural Information Processing Systems* (Vol. 32). Curran Associates, Inc. <https://proceedings.neurips.cc/paper/2019/file/bdbca288fee7f92f2bfa9f7012727740-Paper.pdf>

- 128 Pinnau, R., Totzeck, C., Tse, O., & Martin, S. (2017). A consensus-based model for global
129 optimization and its mean-field limit. *Math. Models Methods Appl. Sci.*, 27(01), 183–
130 204. <https://doi.org/10.1142/S0218202517400061>
- 131 Totzeck, C. (2021). Trends in Consensus-based optimization. *arXiv Preprint: arXiv:2104.01383*.
132 <http://arxiv.org/abs/2104.01383>
- 133 Vicsek, T., Czirók, A., Ben-Jacob, E., Cohen, I., & Shochet, O. (1995). Novel Type of Phase
134 Transition in a System of Self-Driven Particles. *Phys. Rev. Lett.*, 75(6), 1226–1229.
135 <https://doi.org/10.1103/PhysRevLett.75.1226>

DRAFT